
Digitalni naslovljivi vmesnik za razsvetljavo - 103. del: Splošne zahteve - Krmilne naprave (IEC 62386-103:2014)

Digital addressable lighting interface - Part 103: General requirements - Control devices

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 62386-103:2014

SIST EN 62386-103:2015
<https://standards.iteh.ai/catalog/standards/sist/9f4098f2-c923-4fec-a399-56d9a8c86696/sist-en-62386-103-2015>

ICS:

29.140.50	Instalacijski sistemi za razsvetljavo	Lighting installation systems
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

SIST EN 62386-103:2015

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62386-103:2015

<https://standards.iteh.ai/catalog/standards/sist/9f4098f2-c923-4fec-a399-56d9a8c86696/sist-en-62386-103-2015>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62386-103

December 2014

ICS 29.140; 29.140.50

English Version

**Digital addressable lighting interface -
Part 103: General requirements - Control devices
(IEC 62386-103:2014)**

Interface d'éclairage adressable numérique -
Partie 103: Exigences générales - Dispositifs de commande
(CEI 62386-103:2014)

Digital adressierbare Schnittstelle für die Beleuchtung -
Teil 103: Allgemeine Anforderungen - Steuergeräte
(IEC 62386-103:2014)

This European Standard was approved by CENELEC on 2014-12-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 34C/1100/FDIS, future edition 1 of IEC 62386-103, prepared by SC 34C "Auxiliaries for lamps" of IEC/TC 34 "Lamps and related equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62386-103:2014.

The following dates are fixed:

- latest date by which the document has to be (dop) 2015-09-12
implemented at national level by
publication of an identical national
standard or by endorsement
- latest date by which the national (dow) 2017-12-12
standards conflicting with the
document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62386-103:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 15	NOTE	Harmonized as EN 55015.
IEC 60598-1	NOTE	Harmonized as EN 60598-1.
IEC 60669-2-1	NOTE	Harmonized as EN 60669-2-1.
IEC 60921	NOTE	Harmonized as EN 60921.
IEC 60923	NOTE	Harmonized as EN 60923.
IEC 60929	NOTE	Harmonized as EN 60929.
IEC 61347-1	NOTE	Harmonized as EN 61347-1.
IEC 61347-2-3	NOTE	Harmonized as EN 61347-2-3.
IEC 61547	NOTE	Harmonized as EN 61547.
IEC 62034	NOTE	Harmonized as EN 62034.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 62386-101	2014	Digital addressable lighting interface - Part 101: General requirements - System Components	EN 62386-101	2014
IEC 62386-102	2014	Digital addressable lighting interface - Part 102: General requirements - Control gear	EN 62386-102	2014

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 62386-103:2015](https://standards.iteh.ai/catalog/standards/sist/9f4098f2-c923-4fec-a399-56d9a8c86696/sist-en-62386-103-2015)

<https://standards.iteh.ai/catalog/standards/sist/9f4098f2-c923-4fec-a399-56d9a8c86696/sist-en-62386-103-2015>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62386-103:2015

<https://standards.iteh.ai/catalog/standards/sist/9f4098f2-c923-4fec-a399-56d9a8c86696/sist-en-62386-103-2015>



IEC 62386-103

Edition 1.0 2014-11

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Digital addressable lighting interface –
Part 103: General requirements – Control devices

Interface d'éclairage adressable numérique –
Partie 103: Exigences générales – Dispositifs de commande

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XH

ICS 29.140, 29.140.50

ISBN 978-2-8322-1905-8

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	11
INTRODUCTION.....	13
1 Scope.....	15
2 Normative references	15
3 Terms and definitions	15
4 General	18
4.1 General.....	18
4.2 Version number	18
5 Electrical specification	18
6 Interface power supply	18
7 Transmission protocol structure.....	18
7.1 General.....	18
7.2 24 bit forward frame encoding.....	19
7.2.1 Frame format for instructions and queries.....	19
7.2.2 Frame format for event messages.....	20
8 Timing	21
9 Method of operation.....	21
9.1 General.....	21
9.2 Application controller.....	21
9.2.1 General	21
9.2.2 Single-master application controller.....	22
9.2.3 Multi-master application controller.....	22
9.3 Input device	22
9.4 Instances of input devices.....	23
9.4.1 General	23
9.4.2 Instance number.....	23
9.4.3 Instance type	23
9.4.4 Feature type	23
9.4.5 Instance groups.....	24
9.5 Commands	24
9.5.1 General	24
9.5.2 Device commands	24
9.5.3 Instance commands.....	25
9.5.4 Feature commands	25
9.6 Event messages	25
9.6.1 Response to event messages	25
9.6.2 Device power cycle event	25
9.6.3 Input notification event	25
9.6.4 Event message filter	26
9.7 Input signal and input value	27
9.7.1 General	27
9.7.2 Input resolution.....	27
9.7.3 Getting the input value.....	27
9.7.4 Notification of changes	28
9.8 System failure.....	28

9.9	Operating a control device	29
9.9.1	Enable/disable the application controller.....	29
9.9.2	Enable/disable event messages.....	29
9.9.3	Quiescent mode	29
9.9.4	Modes of operation	30
9.10	Memory banks	30
9.10.1	General	30
9.10.2	Memory map.....	31
9.10.3	Selecting a memory bank location	31
9.10.4	Memory bank reading	32
9.10.5	Memory bank writing.....	32
9.10.6	Memory bank 0.....	33
9.10.7	Memory bank 1.....	35
9.10.8	Manufacturer specific memory banks.....	37
9.10.9	Reserved memory banks	37
9.11	Reset.....	37
9.11.1	Reset operation	37
9.11.2	Reset memory bank operation	37
9.12	Power on behaviour.....	37
9.12.1	Power on	37
9.12.2	Power cycle notification.....	38
9.13	Priority use	38
9.13.1	General	38
9.13.2	Priority of input notifications	38
9.14	Assigning short addresses	39
9.14.1	General	39
9.14.2	Random address allocation.....	39
9.14.3	Identification of a device	39
9.15	Exception handling	40
9.16	Device capabilities and status information	40
9.16.1	Device capabilities.....	40
9.16.2	Device status.....	40
9.16.3	Instance status	41
9.17	Non-volatile memory	41
10	Declaration of variables	42
11	Definition of commands	43
11.1	General.....	43
11.2	Overview sheets	43
11.3	Event messages	48
11.3.1	INPUT NOTIFICATION (<i>device/instance, event</i>).....	48
11.3.2	POWER NOTIFICATION (<i>device</i>)	48
11.4	Device control instructions	48
11.4.1	General	48
11.4.2	IDENTIFY DEVICE	48
11.4.3	RESET POWER CYCLE SEEN	49
11.5	Device configuration instructions.....	49
11.5.1	General	49
11.5.2	RESET	49
11.5.3	RESET MEMORY BANK (<i>DTR0</i>)	49

11.5.4	SET SHORT ADDRESS (<i>DTR0</i>)	49
11.5.5	ENABLE WRITE MEMORY	49
11.5.6	ENABLE APPLICATION CONTROLLER	50
11.5.7	DISABLE APPLICATION CONTROLLER	50
11.5.8	SET OPERATING MODE (<i>DTR0</i>)	50
11.5.9	ADD TO DEVICE GROUPS 0-15 (<i>DTR2:DTR1</i>)	50
11.5.10	ADD TO DEVICE GROUPS 16-31 (<i>DTR2:DTR1</i>)	50
11.5.11	REMOVE FROM DEVICE GROUPS 0-15 (<i>DTR2:DTR1</i>).....	50
11.5.12	REMOVE FROM DEVICE GROUPS 16-31 (<i>DTR2:DTR1</i>).....	50
11.5.13	START QUIESCENT MODE	50
11.5.14	STOP QUIESCENT MODE	50
11.5.15	ENABLE POWER CYCLE NOTIFICATION	51
11.5.16	DISABLE POWER CYCLE NOTIFICATION	51
11.5.17	SAVE PERSISTENT VARIABLES	51
11.6	Device queries	51
11.6.1	General	51
11.6.2	QUERY DEVICE CAPABILITIES	51
11.6.3	QUERY DEVICE STATUS	51
11.6.4	QUERY APPLICATION CONTROLLER ERROR	52
11.6.5	QUERY INPUT DEVICE ERROR	52
11.6.6	QUERY MISSING SHORT ADDRESS	52
11.6.7	QUERY VERSION NUMBER	52
11.6.8	QUERY CONTENT <i>DTR0</i>	52
11.6.9	QUERY NUMBER OF INSTANCES	52
11.6.10	QUERY CONTENT <i>DTR1</i>	52
11.6.11	QUERY CONTENT <i>DTR2</i>	52
11.6.12	QUERY RANDOM ADDRESS (H)	53
11.6.13	QUERY RANDOM ADDRESS (M)	53
11.6.14	QUERY RANDOM ADDRESS (L)	53
11.6.15	READ MEMORY LOCATION (<i>DTR1</i> , <i>DTR0</i>)	53
11.6.16	QUERY APPLICATION CONTROL ENABLED	53
11.6.17	QUERY OPERATING MODE	53
11.6.18	QUERY MANUFACTURER SPECIFIC MODE	53
11.6.19	QUERY QUIESCENT MODE	53
11.6.20	QUERY DEVICE GROUPS 0-7	53
11.6.21	QUERY DEVICE GROUPS 8-15	54
11.6.22	QUERY DEVICE GROUPS 16-23	54
11.6.23	QUERY DEVICE GROUPS 24-31	54
11.6.24	QUERY POWER CYCLE NOTIFICATION	54
11.6.25	QUERY EXTENDED VERSION NUMBER(<i>DTR0</i>)	54
11.6.26	QUERY RESET STATE	54
11.7	Instance control instructions	54
11.8	Instance configuration instructions	54
11.8.1	General	54
11.8.2	ENABLE INSTANCE	55
11.8.3	DISABLE INSTANCE	55
11.8.4	SET PRIMARY INSTANCE GROUP (<i>DTR0</i>)	55
11.8.5	SET INSTANCE GROUP 1 (<i>DTR0</i>)	55
11.8.6	SET INSTANCE GROUP 2 (<i>DTR0</i>)	55

11.8.7	SET EVENT SCHEME (<i>DTR0</i>).....	55
11.8.8	SET EVENT PRIORITY (<i>DTR0</i>).....	56
11.8.9	SET EVENT FILTER (<i>DTR2</i> , <i>DTR1</i> , <i>DTR0</i>)	56
11.9	Instance queries	56
11.9.1	General	56
11.9.2	QUERY INSTANCE TYPE	56
11.9.3	QUERY RESOLUTION	56
11.9.4	QUERY INSTANCE ERROR	56
11.9.5	QUERY INSTANCE STATUS.....	56
11.9.6	QUERY INSTANCE ENABLED	57
11.9.7	QUERY PRIMARY INSTANCE GROUP	57
11.9.8	QUERY INSTANCE GROUP 1	57
11.9.9	QUERY INSTANCE GROUP 2	57
11.9.10	QUERY EVENT SCHEME.....	57
11.9.11	QUERY INPUT VALUE	57
11.9.12	QUERY INPUT VALUE LATCH.....	57
11.9.13	QUERY EVENT PRIORITY	57
11.9.14	QUERY FEATURE TYPE.....	58
11.9.15	QUERY NEXT FEATURE TYPE.....	58
11.9.16	QUERY EVENT FILTER 0-7	58
11.9.17	QUERY EVENT FILTER 8-15.....	58
11.9.18	QUERY EVENT FILTER 16-23.....	58
11.10	Special commands.....	58
11.10.1	General	58
11.10.2	TERMINATE	58
11.10.3	INITIALISE (<i>device</i>).....	59
11.10.4	RANDOMISE	59
11.10.5	COMPARE	59
11.10.6	WITHDRAW.....	59
11.10.7	SEARCHADDRH (<i>data</i>).....	60
11.10.8	SEARCHADDRM (<i>data</i>)	60
11.10.9	SEARCHADDRL (<i>data</i>)	60
11.10.10	PROGRAM SHORT ADDRESS (<i>data</i>)	60
11.10.11	VERIFY SHORT ADDRESS (<i>data</i>)	60
11.10.12	QUERY SHORT ADDRESS	61
11.10.13	WRITE MEMORY LOCATION (<i>DTR1</i> , <i>DTR0</i> , <i>data</i>)	61
11.10.14	WRITE MEMORY LOCATION – NO REPLY (<i>DTR1</i> , <i>DTR0</i> , <i>data</i>)	61
11.10.15	DTR0 (<i>data</i>)	61
11.10.16	DTR1 (<i>data</i>)	62
11.10.17	DTR2 (<i>data</i>)	62
11.10.18	DIRECT WRITE MEMORY (<i>DTR1</i> , <i>offset</i> , <i>data</i>)	62
11.10.19	DTR1:DTR0 (<i>data1</i> , <i>data0</i>).....	62
11.10.20	DTR2:DTR1 (<i>data2</i> , <i>data1</i>).....	62
11.10.21	SEND TESTFRAME (<i>data</i>)	62
12	Test procedures	63
12.1	General notes on test.....	63
12.1.1	General	63
12.1.2	Test execution	63
12.1.3	Data transmission.....	64

12.1.4	Test setup	64
12.1.5	Test output	64
12.1.6	Test notation	65
12.1.7	Test execution limitations	66
12.1.8	Test results	66
12.1.9	Exception handling	66
12.1.10	Unexpected answer	66
12.2	Preamble	68
12.2.1	Test preamble	68
12.3	Physical operational parameters	79
12.3.1	Polarity test	79
12.3.2	Maximum and minimum system voltage	80
12.3.3	Overvoltage protection test	80
12.3.4	Current rating test	81
12.3.5	Transmitter voltages	83
12.3.6	Transmitter rising and falling edges	84
12.3.7	Transmitter bit timing	86
12.3.8	Transmitter frame timing	88
12.3.9	Receiver start-up behavior	89
12.3.10	Receiver threshold	90
12.3.11	Receiver bit timing	91
12.3.12	Extended receiver bit timing	95
12.3.13	Receiver forward frame violation	97
12.3.14	Receiver settling timing	97
12.3.15	Receiver frame timing FF-FF send twice	98
12.3.16	Transmitter collision avoidance by priority	100
12.3.17	Transmitter collision detection for truncated idle phase	101
12.3.18	Transmitter collision detection for extended active phase	104
12.4	Device configuration instructions	107
12.4.1	RESET deviceGroups	107
12.4.2	RESET quiescentMode	108
12.4.3	RESET instance groups	109
12.4.4	RESET event filter	110
12.4.5	RESET event scheme	111
12.4.6	RESET: timeout / command in-between	112
12.4.7	Send twice timeout (device)	114
12.4.8	Send twice timeout (instance)	117
12.4.9	Commands in-between (device)	119
12.4.10	Commands in-between (instance)	122
12.4.11	SAVE PERSISTENT VARIABLES	125
12.4.12	SET OPERATING MODE	125
12.4.13	Device Disable/Enable Application Controller	126
12.4.14	Multi Master Control Device PING	127
12.4.15	Quiescent Mode	128
12.4.16	Device power cycle notification	129
12.4.17	SET SHORT ADDRESS	130
12.4.18	Reset/Power-on values (device)	131
12.4.19	Reset/Power-on values (instance)	133
12.4.20	DTR0 / DTR1 / DTR2	134

12.4.21	DTR1:DTR0 and DTR2:DTR1	135
12.4.22	Device Groups.....	136
12.5	Device queries.....	137
12.5.1	Device query capabilities	137
12.5.2	QUERY VERSION NUMBER.....	137
12.5.3	Device power cycle seen	138
12.5.4	Input device error	138
12.6	Device Memory banks.....	139
12.6.1	READ MEMORY LOCATION on Memory Bank 0.....	139
12.6.2	READ MEMORY LOCATION on Memory Bank 1.....	144
12.6.3	READ MEMORY LOCATION on other Memory Banks.....	146
12.6.4	Memory bank writing.....	148
12.6.5	ENABLE WRITE MEMORY: writeEnableState.....	153
12.6.6	ENABLE WRITE MEMORY: timeout / command in-between.....	155
12.6.7	RESET MEMORY BANK: timeout / command in-between	156
12.6.8	RESET MEMORY BANK.....	159
12.7	Device Special commands	160
12.7.1	INITIALISE – timer.....	160
12.7.2	TERMINATE.....	161
12.7.3	INITIALISE - device addressing	162
12.7.4	RANDOMISE.....	163
12.7.5	COMPARE	163
12.7.6	WITHDRAW.....	165
12.7.7	SEARCHADDRH / SEARCHADDRM / SEARCHADDRL	166
12.7.8	PROGRAM SHORT ADDRESS.....	167
12.7.9	VERIFY SHORT ADDRESS.....	169
12.7.10	QUERY SHORT ADDRESS	170
12.7.11	IDENTIFY DEVICE	172
12.8	Logical unit cross contamination	174
12.8.1	DTR0.....	174
12.8.2	NVM variables	174
12.8.3	Random address generation	175
12.8.4	Addressing 1	176
12.8.5	Addressing 2	177
12.8.6	Addressing 3	179
12.9	Instance addressing.....	180
12.9.1	Instance Type Addressing	180
12.9.2	Instance Primary Group	181
12.9.3	Instance Group 2	182
12.9.4	Instance Group 1	184
12.9.5	Instance Group Combinations.....	185
12.9.6	Multiple Instances Answer	187
12.10	Instance configuration instructions.....	188
12.10.1	Instance Enable/Disable	188
12.10.2	Event Scheme	190
12.10.3	Input Resolution & Input Value	195
12.10.4	Event Filter.....	195
12.11	Instance queries	196
12.11.1	Instance Number and Types	196

12.11.2	Instance Status.....	197
12.11.3	Instance Error.....	197
12.12	Instance cross contamination.....	198
12.12.1	Instance Event Priority.....	198
12.13	Reserved Commands.....	199
12.13.1	Reserved standard device commands.....	199
12.13.2	Reserved instance commands (instance type 0)	200
12.13.3	Reserved special commands	200
12.14	General subsequences	201
12.14.1	Reset Device	201
12.14.2	EnableApplicationControllerAndAllInstances.....	202
12.14.3	DisableApplicationControllerAndAllInstances	202
12.14.4	HasApplicationController	202
12.14.5	GetVersionNumber	203
12.14.6	AddDeviceGroups.....	203
12.14.7	RemoveDeviceGroups	203
12.14.8	ClearAllDeviceGroups.....	204
12.14.9	CheckDeviceGroups	204
12.14.10	GetDeviceGroups	205
12.14.11	PowerCycle	205
12.14.12	PowerCycleAndWaitForBusPower	205
12.14.13	PowerCycleAndWaitForDecoder.....	206
12.14.14	SetupTestFrame.....	206
12.14.15	GetNumberOfInstances	207
12.14.16	GetEventFilter	207
12.14.17	SetEventFilter.....	207
12.14.18	GetNumberOfLogicalUnits	207
12.14.19	GetIndexOfLogicalUnit.....	207
12.14.20	GetRandomAddress.....	208
12.14.21	GetLimitedRandomAddress	208
12.14.22	SetSearchAddress	208
12.14.23	SetShortAddress	209
12.14.24	ReadMemBankMultibyteLocation	209
12.14.25	FindImplementedMemoryBank.....	210
12.14.26	FindAllImplementedMemoryBanks	210
12.14.27	ShortAddress.....	211
12.14.28	GroupAddress	211
12.14.29	Broadcast	211
12.14.30	BroadcastUnaddressed.....	211
12.14.31	InstanceNumber	211
12.14.32	InstanceGroup.....	212
12.14.33	InstanceType	212
12.14.34	InstanceBroadcast.....	212
12.14.35	FeatureOfInstanceNumber.....	212
12.14.36	FeatureOfInstanceGroup	213
12.14.37	FeatureOfInstanceType	213
12.14.38	FeatureOfInstanceBroadcast	213
12.14.39	FeatureOfDevice	213
12.14.40	FeatureOfDeviceWithGroupAddress	214

12.14.41 FeatureOfDeviceWithBroadcast	214
Bibliography	215
Figure 1 - IEC 62386 graphical overview	13
Figure 2 – Current rating test	82
Table 1 – 24-bit command frame encoding	19
Table 2 – Instance byte in a command frame	19
Table 3 – 24-bit event message frame encoding	20
Table 4 – Instance types	23
Table 5 – Feature types	23
Table 6 – Instance group variables	24
Table 7 – Device address information in power cycle event	25
Table 8 – Event addressing schemes	26
Table 9 – Signal level (~50%) versus resolution and input value	27
Table 10 – Example querying sequence to read a 4-byte input value	28
Table 11 – Basic memory map of memory banks	31
Table 12 – Memory map of memory bank 0	34
Table 13 – Memory map of memory bank 1	36
Table 14 – Control device capabilities	40
Table 15 – Control device status	40
Table 16 – Instance status	41
Table 17 – Declaration of device variables	42
Table 18 – Declaration of instance variables	43
Table 19 – Instance event messages	43
Table 20 – Device event messages	43
Table 21 – Standard commands	44
Table 22 – Special commands (implemented by both application controller and input device)	47
Table 23 – Device addressing with “INITIALISE (<i>device</i>)”	59
Table 24 – Unexpected outcome	67
Table 25 – Parameters for test sequence Check Factory Default 103	74
Table 26 – Parameters for test sequence CheckFactoryDefault103PerLogicalUnit	77
Table 27 – Parameters for test sequence Transmitter bit timing	79
Table 28 – Parameters for test sequence Maximum and minimum system voltage	80
Table 29 – Parameters for test sequence Transmitter voltages	84
Table 30 – Parameters for test sequence Transmitter rising and falling edges	85
Table 31 – Parameters for test sequence Transmitter bit timing	88
Table 32 – Parameters for test sequence Receiver frame timing	89
Table 33 – Parameters for test sequence Receiver start-up behavior	90
Table 34 – Parameters for test sequence Receiver bit timing	92
Table 35 – Parameters for test sequence extended receiver bit timing	96
Table 36 – Parameters for test sequence Receiver frame violation and recovering after frame size violation	97