



SLOVENSKI STANDARD

SIST EN 302 480 V1.1.2:2008

01-september-2008

9`Y_Hfca U[bYtbUrnXfi ý`jj cgh]b'nUXYj Yj 'nj Yn]n'fUX]g_ ja 'gdY_Hfca 'fØFAŁ!
<Ufa cb]n]fUb]9B'nUg]ghYa Y; GA 'bU'YHJ] ž_j'nU^Ya UV]glj YbYnU hYj Y 'YbU' "&
X]fY_Hj YF/ HH9

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Harmonized EN for
the GSM onboard aircraft system covering essential requirements of Article 3.2 of the
R&TTE Directive

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 480 V1.1.2:2008](#)
<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beae/sist-en-302-480-v1-1-2-2008>

Ta slovenski standard je istoveten z: **EN 302 480 Version 1.1.2**

ICS:

| | | |
|-----------|---|--|
| 33.060.99 | Druga oprema za radijske komunikacije | Other equipment for radiocommunications |
| 33.070.50 | Globalni sistem za mobilno telekomunikacijo (GSM) | Global System for Mobile Communication (GSM) |
| 33.100.01 | Elektromagnetna združljivost na splošno | Electromagnetic compatibility in general |

SIST EN 302 480 V1.1.2:2008

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 480 V1.1.2:2008](https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beac/sist-en-302-480-v1-1-2-2008)
<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beac/sist-en-302-480-v1-1-2-2008>

ETSI EN 302 480 V1.1.2 (2008-04)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Harmonized EN for the GSM onboard aircraft system
covering the essential requirements
of Article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 480 V1.1.2:2008
<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beae/sist-en-302-480-v1-1-2-2008>



Reference

DEN/ERM-GSMOBA-001

Keywords

GSM

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 302 480 V1.1.2:2008](#)
<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4b24f>
Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
 All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

| | |
|---|----|
| Intellectual Property Rights | 6 |
| Foreword..... | 6 |
| Introduction | 6 |
| 1 Scope | 7 |
| 2 References | 8 |
| 2.1 Normative references | 8 |
| 2.2 Informative references..... | 9 |
| 3 Definitions and abbreviations..... | 9 |
| 3.1 Definitions..... | 9 |
| 3.2 Abbreviations | 9 |
| 4 Technical requirements specifications | 10 |
| 4.1 General | 10 |
| 4.1.1 Environmental profile | 10 |
| 4.1.2 GSMOBA system states | 11 |
| 4.2 Conformance requirements | 12 |
| 4.2.1 OBTS Transmitter Performance | 12 |
| 4.2.1.1 OBTS maximum output power | 12 |
| 4.2.1.1.1 Definition..... | 12 |
| 4.2.1.1.2 Limits | 12 |
| 4.2.1.2 OBTS Output RF spectrum | 12 |
| 4.2.1.2.1 Spectrum due to modulation and wideband noise..... | 12 |
| 4.2.1.2.2 Spectrum due to switching transients | 12 |
| 4.2.1.3 OBTS Radio Frequency Tolerance..... | 13 |
| 4.2.1.3.1 Definition..... | 13 |
| 4.2.1.3.2 Limits | 13 |
| 4.2.1.4 OBTS controlled MS RF power..... | 13 |
| 4.2.1.4.1 Definition..... | 13 |
| 4.2.1.4.2 Limits | 13 |
| 4.2.2 OBTS Receiver Performance..... | 13 |
| 4.2.2.1 OBTS Reference Sensitivity Level | 13 |
| 4.2.2.1.1 Definition..... | 13 |
| 4.2.2.1.2 Limits | 13 |
| 4.2.2.2 Unwanted emissions in the spurious domain | 14 |
| 4.2.2.2.1 Definition..... | 14 |
| 4.2.2.2.2 Limits | 14 |
| 4.2.3 NCU Transmitter Performance | 14 |
| 4.2.3.1 NCU maximum mean power spectral density..... | 14 |
| 4.2.3.1.1 Definition..... | 14 |
| 4.2.3.1.2 Limits | 14 |
| 4.2.3.2 NCU power flatness | 14 |
| 4.2.3.2.1 Definition..... | 14 |
| 4.2.3.2.2 Limits | 14 |
| 4.2.4 GSMOBA Transmitter Performance | 14 |
| 4.2.4.1 Unwanted emissions in the out-of-band domain | 14 |
| 4.2.4.1.1 Definition..... | 14 |
| 4.2.4.1.2 Limits | 15 |
| 4.2.4.2 Unwanted emissions in the spurious domain | 15 |
| 4.2.4.2.1 Definition..... | 15 |
| 4.2.4.2.2 Limits | 15 |
| 4.2.4.3 Cessation of emissions | 15 |
| 4.2.4.3.1 Definition..... | 15 |
| 4.2.4.3.2 Specification | 15 |
| 5 Testing for compliance with technical requirements..... | 16 |

| | | |
|-------------------------------|--|-----------|
| 5.1 | Interpretation of results and measurement uncertainty | 16 |
| 5.1.1 | Environmental conditions for testing | 16 |
| 5.1.2 | Interpretation of the measurement results | 16 |
| 5.1.3 | Measurement options | 17 |
| 5.2 | Essential radio test suites | 17 |
| 5.2.1 | OBTS Transmitter Performance | 17 |
| 5.2.1.1 | OBTS Output power | 17 |
| 5.2.1.1.1 | Test purpose | 17 |
| 5.2.1.1.2 | Test case | 17 |
| 5.2.1.2 | OBTS RF spectrum | 17 |
| 5.2.1.2.1 | Spectrum due to modulation and wideband noise | 17 |
| 5.2.1.2.2 | Spectrum due to switching transients | 18 |
| 5.2.1.3 | OBTS Radio Frequency Tolerance | 18 |
| 5.2.1.3.1 | Test purpose | 18 |
| 5.2.1.3.2 | Test case | 18 |
| 5.2.1.4 | OBTS controlled MS RF power | 18 |
| 5.2.1.4.1 | Test purpose | 18 |
| 5.2.1.4.2 | Methods of measurement | 18 |
| 5.2.2 | OBTS Receiver Performance | 19 |
| 5.2.2.1 | OBTS Reference Sensitivity Level | 19 |
| 5.2.2.1.1 | Test Purpose | 19 |
| 5.2.2.1.2 | Test Case | 20 |
| 5.2.2.2 | Unwanted emissions in the spurious domain | 20 |
| 5.2.2.2.1 | Test Purpose | 20 |
| 5.2.2.2.2 | Test Case | 20 |
| 5.2.3 | NCU Transmitter Performance | 20 |
| 5.2.3.1 | NCU maximum mean power spectral density | 20 |
| 5.2.3.1.1 | Test purpose | 20 |
| 5.2.3.1.2 | Methods of measurement | 20 |
| 5.2.3.2 | NCU power flatness | 21 |
| 5.2.3.2.1 | Test purpose | 21 |
| 5.2.3.2.2 | Methods of measurement | 21 |
| 5.2.4 | GSMOBA Transmitter Performance | 22 |
| 5.2.4.1 | Unwanted emissions in the out-of-band domain | 22 |
| 5.2.4.1.1 | Test purpose | 22 |
| 5.2.4.1.2 | Methods of measurement | 22 |
| 5.2.4.1.2.1 | Unwanted emissions in the out-of-band domain when OBTS is in standby state | 22 |
| 5.2.4.1.2.2 | Unwanted emissions in the out-of-band domain when OBTS is in active state | 23 |
| 5.2.4.2 | Unwanted emissions in the spurious domain | 23 |
| 5.2.4.2.1 | Test purpose | 23 |
| 5.2.4.2.2 | Methods of measurement | 23 |
| 5.2.4.2.2.1 | Unwanted emissions in the spurious domain when system is in standby state | 24 |
| 5.2.4.2.2.2 | Unwanted emissions in the spurious domain when system is in active state | 24 |
| 5.2.4.3 | Cessation of emissions | 24 |
| 5.2.4.3.1 | Test purpose | 24 |
| 5.2.4.3.2 | Methods of measurement | 25 |
| Annex A (normative): | HS Requirements and conformance Test specifications Table (HS-RTT) | 26 |
| Annex B (normative): | Environmental conditions | 28 |
| B.1 | General | 28 |
| B.2 | Environmental conformance requirements | 28 |
| B.3 | Environmental test conditions | 28 |
| Annex C (informative): | System Description | 29 |
| C.1 | High level System Description | 29 |
| C.2 | OBTS | 30 |

| | | |
|-------------------------------|---|-----------|
| C.3 | RF Screening | 30 |
| C.4 | Dedicated antenna system | 30 |
| C.5 | Dedicated antenna installation..... | 31 |
| Annex D (informative): | The EN title in the official languages | 32 |
| Annex E (informative): | Bibliography..... | 33 |
| History | | 34 |

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 302 480 V1.1.2:2008

<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beae/sist-en-302-480-v1-1-2-2008>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [12] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [11] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [11] are given in annex A.

SIST EN 302 480 V1.1.2:2008

https://standards.iteh.ai/standards/jist_en_302_480_v1_1_2_2008
National transposition dates

| | |
|--|-----------------|
| Date of adoption of this EN: | 11 April 2008 |
| Date of latest announcement of this EN (doa): | 31 July 2008 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 January 2009 |
| Date of withdrawal of any conflicting National Standard (dow): | 31 January 2010 |

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [13].

1 Scope

The present document applies to a system comprising the following radio equipment types:

- 1) an Onboard GSM Base Transceiver System (OBTS) supporting the GSM 1800 functions with specific protocols for power constraints;
- 2) a Network Control Unit (NCU) preventing direct connection of the onboard mobile terminals with mobile networks on the ground by raising the noise floor in the cabin.

These radio equipment types are capable of operating in all or any part of the frequency bands given below:

Table 1: Radiocommunications service frequency bands

| | Radiocommunications service frequency bands |
|-------------------|--|
| Transmit 1 (OBTS) | 1 805 MHz to 1 880 MHz |
| Receive 1 (OBTS) | 1 710 MHz to 1 785 MHz |
| Transmit 2 (NCU) | 460 MHz to 470 MHz |
| Transmit 2 (NCU) | 921 MHz to 960 MHz |
| Transmit 2 (NCU) | 1 805 MHz to 1 880 MHz |
| Transmit 2 (NCU) | 2 110 MHz to 2 170 MHz |

It applies to equipment for continuous and discontinuous transmission of data and digital speech.

The present document applies only to radio equipment using a dedicated transmitting antenna that is designed as an indispensable part of the system for usage on board an aircraft.

The system covered by the present document operates in accordance with the operational requirements as outlined in the Decision CEPT/ECC/DEC/(06)07 [14].

The present document covers the provisions of Directive 1999/5/EC (the R&TTE Directive), Article 3.2, which states "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of Article 3 of the R&TTE Directive may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

The present document does not cover equipment compliance with relevant civil aviation regulations. In this respect, a GSMOBA system, for its installation and operation on board an aircraft is subject to additional national or international civil aviation airworthiness certification requirements, for example to EUROCAE ED-14E [10].

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

iTeh STANDARD PREVIEW

2.1 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies. <https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4bea9/jst-en-302-480-v1-1-2-2008>

- [1] ETSI TS 145 005: "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception (3GPP TS 45.005 version 6.14.0 Release 6)".
- [2] ETSI TS 145 010: "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization (3GPP TS 45.010 version 6.6.0 Release 6)".
- [3] ETSI TS 145 008: "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control (3GPP TS 45.008 version 6.19.0 Release 6)".
- [4] 3GPP2 C.S0011-C (V2.0): "Recommended Minimum Performance Standards for cdma2000 Spread Spectrum Mobile Stations".

NOTE: http://www.3gpp2.org/Public_html/specs/C.S0011-C_v2.0_060315.pdf

- [5] ETSI TS 125 104: "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (FDD) (3GPP TS 25.104 version 6.16.0 Release 6)".
- [6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [7] ETSI TS 151 021: "Digital cellular telecommunications system (Phase 2+); Base Station System (BSS) equipment specification; Radio aspects (3GPP TS 51.021 version 6.3.0 Release 6)".
- [8] ETSI TS 145 004: "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 6.0.0 Release 6)".
- [9] CISPR 16-2-1 (2005): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-1: Methods of measurement of disturbances and immunity - Conducted disturbance measurements".

- [10] EUROCAE ED-14E (2005) (Equivalent to RTCA DO-160E): "Environmental Conditions and Test Procedures for Airborne Equipment".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [11] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [12] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [13] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [14] CEPT/ECC/DEC/(06)07: "ECC Decision of 1 December 2006 on the harmonized use of airborne GSM systems in the frequency bands 1710-1785 and 1805-1880 MHz".
- [15] CEPT/ERC/REC 74-01 (2005) (equivalent to ITU-R Recommendation SM.329-10): "Unwanted emissions in the spurious domain".

iTel STANDARD PREVIEW

3 Definitions and abbreviations (standards.iteh.ai)

3.1 Definitions

[SIST EN 302 480 V1.1.2:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-0f3a8e70a5a1>

For the purposes of the present document, the following terms and definitions apply:

Base Station System Test Equipment (BSSTE): functional tool for the purpose of acceptance testing of GSM Base Station Systems

NOTE: The BSSTE functionally carries out all tests described in the OBTS specification.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

GSM onboard aircraft system: system comprising the functions provided by the NCU and the OBTS

Network Control Unit (NCU): component of the GSM onboard aircraft system preventing direct connection of the onboard mobile terminals with mobile networks on the ground by raising the noise floor in the cabin

Onboard Base Transceiver Station (OBTS): component of the GSM onboard aircraft system responsible for radio transmission and reception to or from the onboard mobile terminals

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|------------------------------------|
| ACU | Antenna Coupler Unit |
| AGL | Above Ground Level |
| BER | Bit Error Rate |
| BCCCH | Broadcast Control CHannel |
| BLER | Block Error Rate |
| BSSTE | Base Station System Test Equipment |
| BTS | Base Transceiver Station |

| | |
|----------|---|
| dB | decibel |
| dBm | decibel relative to 1 mW |
| DTM | Dual Transfer Mode |
| e.i.r.p. | equivalent isotropically radiated power |
| ECC | Electronic Communications Committee |
| FER | Frame Error Rate |
| GGW | Ground GateWay |
| GPRS | General Packet Radio Service |
| GSM | Global System for Mobile communications |
| GSMOBA | GSM OnBoard Aircraft |
| MS | Mobile Station |
| MSC | Mobile Switching Centre |
| NCU | Network Control Unit |
| OBTS | Onboard Base Transceiver Station |
| PBCCH | Packet Broadcast Control CHannel |
| R&TTE | Radio and Telecommunications Terminal Equipment |
| RACH | Random Access CHannel |
| RBER | Residual BER |
| RBW | Resolution BandWidth |
| RF | Radio Frequency |
| rms | root mean square |
| SGSN | Serving GPRS Support Node |
| STE | Special Test Equipment |
| TCH | Traffic CHannel |
| VBW | Video BandWidth |

iTeh STANDARD PREVIEW**4 Technical requirements specifications
(standards.iteh.ai)****4.1 General**[SIST EN 302 480 V1.1.2:2008](#)<https://standards.iteh.ai/catalog/standards/sist/c9294b93-51ea-49ad-8db5-015d68e4beae/sist-en-302-480-v1-1-2-2008>**4.1.1 Environmental profile**

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile and for the environmental conditions (as specified in clause B.3).