



SLOVENSKI STANDARD

SIST EN 13081:2009

01-april-2009

Nadomešča:
SIST EN 13081:2002

Rezervoarji za prevoz nevarnega blaga - Oprema za oskrbovanje rezervoarjev - Spojka za zbiralnik pare

Tanks for transport of dangerous goods - Service equipment for tanks - Vapour collection adaptor and coupler

Tanks für die Beförderung gefährlicher Güter - Bedienungsausrüstung von Tanks - VKG- und MKG-Kupplungen für die Gassammelleitung

Citernes de transport de matières dangereuses - Equipement de service pour citernes - Adaptateur et coupleur pour la récupération des vapeurs

Ta slovenski standard je istoveten z: **EN 13081:2008**

ICS:

13.300	Varstvo pred nevarnimi izdelki	Protection against dangerous goods
23.020.20	Posode in vsebniki, montirani na vozila	Vessels and containers mounted on vehicles
23.040.60	Prirobnice, oglavki in spojni elementi	Flanges, couplings and joints

SIST EN 13081:2009

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 13081:2009

<https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009>

EUROPEAN STANDARD

EN 13081

NORME EUROPÉENNE

EUROPÄISCHE NORM

November 2008

ICS 13.300; 23.020.20; 23.040.60

Supersedes EN 13081:2001

English Version

Tanks for transport of dangerous goods - Service equipment for tanks - Vapour collection adaptor and coupler

Citernes de transport de matières dangereuses -
Équipement de service pour citernes - Adaptateur et
coupleur pour la récupération des vapeurs

Tanks für die Beförderung gefährlicher Güter -
Bedienungsausrüstung von Tanks - VKG- und MKG-
Kupplungen für die Gassammelleitung

This European Standard was approved by CEN on 13 September 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

[SIST EN 13081:2009](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009)

<https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Function	6
5 Design characteristics	6
5.1 General.....	6
5.2 Performance characteristics	6
5.3 Pressure ratings.....	6
5.4 Temperature range	6
5.5 Materials of construction	6
5.6 Dimensional characteristics	7
6 Tests.....	7
6.1 General.....	7
6.2 Production tests.....	7
6.2.1 General.....	7
6.2.2 Shell tightness test.....	8
6.2.3 Internal seat tightness test	8
6.2.4 Operability test.....	8
6.2.5 Test results.....	8
6.3 Type tests	8
6.3.1 General.....	8
6.3.2 Shell strength test.....	9
6.3.3 Shell tightness test.....	9
6.3.4 Internal seat tightness test	9
6.3.5 Mechanical endurance test.....	9
6.3.6 Mechanical strength test.....	9
6.3.7 Test results.....	10
7 Marking	10
8 Installation, operation and maintenance instructions	10
Annex A (normative) Vapour collection adaptor to be fitted on the transport tank	11
Annex B (normative) Vapour collection coupler to be fitted to the stationary loading and unloading facility	12
Annex C (normative) Interlock and other devices	13
C.1 Interlock	13
C.2 DTQM tank identifier.....	14
Annex D (informative) 4 hole fixing	15
Bibliography	16

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 13081:2009

<https://standards.itech.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6haf268/sist-en-13081-2009>

Foreword

This document (EN 13081:2008) has been prepared by Technical Committee CEN/TC 296 "Tanks for transport of dangerous goods", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2009, and conflicting national standards shall be withdrawn at the latest by May 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13081:2001.

This European standard forms part of a coherent standards programme comprising the following standards, under the general title "Tanks for transport of dangerous goods - Service equipment for tanks"

EN 13081, *Vapour collection adaptor and coupler*

EN 13082, *Vapour transfer valve*

EN 13083, *Adaptor for bottom loading and unloading*

EN 13308, *Non pressure balanced footvalve*

EN 13314, *Fill hole cover*

EN 13315, *Gravity discharge coupler*

EN 13316, *Pressure balanced footvalve*

EN 13317, *Manhole cover assembly*

EN 13922, *Overfill prevention systems for liquid fuels*

EN 14595, *Pressure and Vacuum Breather Vent*

EN 14596, *Emergency pressure relief valve*

EN 15208, *Sealed parcel delivery systems – Working principles and interface specifications*

The standards programme also includes the following Technical Report:

CEN/TR 15120, *Tanks for transport of dangerous goods - Guidance and recommendations for loading, transport and unloading.*

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Introduction

The vapour collection adaptor and coupler are part of the vapour collection system that is required to comply with the European Directive 94/63/EC on Volatile Organic Compounds (VOC) [1].

The vapour collection adaptor and coupler establish a vapour tight path between the transport tank and the stationary loading and unloading facilities.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 13081:2009](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009)

<https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009>

1 Scope

This European Standard covers the vapour collection adaptor and coupler used to achieve a vapour tight path between the transport tank and the stationary loading and unloading facilities.

This European Standard specifies the performance requirements and the critical dimensions of the vapour recovery adaptor fitted to the tank and the mating coupler fitted to a hose or to pipework connected to the stationary loading and unloading facilities. It also specifies the tests necessary to verify the compliance of the equipment with this standard. The equipment specified by this European Standard is suitable for use with liquid petroleum products and other dangerous substances of Class 3 of ADR [2] which have a vapour pressure not exceeding 110 kPa, at 50 °C and petrol, and which have no sub-classification as toxic or corrosive.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references only the edition cited applies. For undated references the latest edition of the referenced document (including amendments) applies.

EN 12266-1:2003, *Industrial valves — Testing of valves — Part 1: Pressure tests, test procedures and acceptance criteria — Mandatory requirements*

EN 12266-2:2002, *Industrial valves — Testing of valves — Part 2: Tests, test procedures and acceptance criteria — Supplementary requirements*

EN 15208:2007, *Tanks for transport of dangerous goods - Sealed parcel delivery systems – Working principles and interface specifications*

EN ISO 1302, *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation (ISO 1302:2002)*

EN ISO 4287, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters (ISO 4287:1997)*

ISO 2859-1, *Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

Maximum Working Pressure (MWP) gauge pressure

maximum pressure to which the equipment is designed to operate, being the highest of the following three pressures:

- a) highest effective pressure allowed in the tank during filling (maximum filling pressure allowed)
- b) highest effective pressure allowed in the tank during discharge (maximum discharge pressure allowed)
- c) effective gauge pressure to which the tank is subjected by its contents (including such extraneous gases as it may contain) at the maximum working temperature

EN 13081:2008 (E)**4 Function**

The vapour collection adaptor and coupler shall provide the following:

- a quick action vapour tight mechanical connection between the transport tank and the stationary loading and unloading facilities for the transfer of vapour;
- vapour tightness when not connected.

The vapour collection adaptor may be capable of accepting interlock actuators and similar devices, see Annex C.

The vapour collection adaptor may have provision for a sight glass to check for the presence of liquid.

The vapour collection adaptor may have provision for the drainage of liquid.

5 Design characteristics**5.1 General**

The vapour collection adaptor and coupler shall permit the transfer of vapour only after initiation of the mating action.

iTeh STANDARD PREVIEW

5.2 Performance characteristics (standards.iteh.ai)

The manufacturer shall provide the pressure drop curves for both the vapour collection adaptor and coupler at the following conditions:

[SIST EN 13081:2009](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-19412012081000-13081-2008)

[https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-19412012081000-13081-2008)

- flow rate up to 1 500 standard m³/h of air at 20 °C (1 500 standard m³/h of air corresponds to the bottom loading of 5 compartments simultaneously each at 150 m³/h flow of substances).

5.3 Pressure ratings

The vapour collection adaptor shall be capable of operating at the MWP of the transport tank to which it is attached.

The vapour collection coupler shall be capable of operating at the MWP of the stationary loading and unloading facility to which it is attached.

5.4 Temperature range

Unless otherwise specified, the design temperature range shall be – 20 °C to + 50 °C.

Where the vapour collection adaptor and coupler are subjected to more severe conditions, the design temperature range shall be extended to – 40 °C or + 70 °C as applicable.

5.5 Materials of construction

The manufacturer shall provide with the equipment a full material specification for those parts that may come into contact with the substances described by Clause 1.

5.6 Dimensional characteristics

The dimensions, tolerances and surface machined finish of the vapour collection adaptor and coupler shall be as given in Annexes A and B (see Figures A.1 and B.1).

The mounting dimensions of the flange connecting the vapour collection adaptor to the pipework of the tank shall be as follows:

- outside diameter (maximum) : 174 mm;
- inside diameter (minimum) : 100 mm;
- pitch circle diameter : 150 mm;
- number of holes : 8 equispaced;
- hole diameter : 14 mm.

NOTE 1 Tolerances ± 1 mm.

NOTE 2 Holes should straddle adaptor centre line.

NOTE 3 A 4 hole mounting, which can accommodate the specified 8 hole flange without loss of performance may be used as an option, see Annex D.

iTeh STANDARD PREVIEW (standards.iteh.ai)

6 Tests

6.1 General

[SIST EN 13081:2009](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009)

Two classes of tests are required: [production tests and type tests.](https://standards.iteh.ai/catalog/standards/sist/1cc0ec78-048b-423a-a722-b9dcd6baf268/sist-en-13081-2009)

Testing methods and procedures shall conform to EN 12266-1 and EN 12266-2 except as specified within this European Standard.

Unless otherwise specified, test fluids shall be air or other suitable gas. The choice of the fluid is the responsibility of the manufacturer.

NOTE Where the obturator forms part of the pressure containing shell, it may be closed during strength and tightness tests.

6.2 Production tests

6.2.1 General

The number, frequency and sampling methods of production test samples shall not be less than those specified within ISO 2859-1 (AQL of 2,5).

Production tests shall comprise the following:

- shell tightness test;
- internal seat tightness test; and
- operability test.