

# ETSI EN 301 489-33 V1.1.1 (2009-02)

---

*Harmonized European Standard (Telecommunications series)*

**Electromagnetic compatibility and  
Radio spectrum Matters (ERM);  
ElectroMagnetic Compatibility (EMC)  
standard for radio equipment and services;  
Part 33: Specific conditions for Ultra Wide Band (UWB)  
communications devices**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/5b159676-1a68-411b-926c-5d88691341bc/etsi-en-301-489-33-v1.1.1-2009-02>



## Reference

---

DEN/ERM-EMC-230-33

## Keywords

---

EMC, radio, UWB

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	6
2.1 Normative references .....	6
2.2 Informative references.....	6
3 Definitions and abbreviations.....	7
3.1 Definitions .....	7
3.2 Abbreviations .....	7
4 Test conditions .....	7
4.1 General .....	7
4.2 Arrangements for test signals .....	8
4.2.1 Arrangements for test signals at the input of transmitters.....	8
4.2.2 Arrangements for test signals at the output of transmitters.....	8
4.2.3 Arrangements for test signals at the input of receivers .....	8
4.2.4 Arrangements for test signals at the output of receivers .....	8
4.2.5 Arrangements for testing transmitter and receiver together (as a system) .....	8
4.3 Exclusion bands.....	9
4.4 Narrow band responses on receivers or receivers which are part of transceivers.....	9
4.5 Normal test modulation .....	9
5 Performance assessment.....	9
5.1 General .....	9
5.2 Arrangements for the assessment of host dependant equipment and plug-in cards.....	9
5.2.1 Alternative A: composite equipment .....	10
5.2.2 Alternative B: use of a test jig or host.....	10
5.3 Assessment procedures.....	10
5.4 Ancillary equipment.....	10
5.5 Equipment classification .....	10
6 Performance criteria .....	11
6.1 General performance criteria.....	11
6.2 Performance table.....	11
6.3 Performance criteria for Continuous phenomena applied to Transmitters (CT) .....	11
6.4 Performance criteria for Transient phenomena applied to Transmitters (TT).....	12
6.5 Performance criteria for Continuous phenomena applied to Receivers (CR).....	12
6.6 Performance criteria for Transient phenomena applied to Receivers (TR) .....	12
7 Applicability overview .....	12
7.1 Emission .....	12
7.1.1 General.....	12
7.1.2 Special conditions .....	12
7.2 Immunity .....	12
7.2.1 General.....	12
7.2.2 Special conditions .....	13
<b>Annex A (informative): The EN title in the official languages .....</b>	<b>14</b>
<b>Annex B (informative): Bibliography.....</b>	<b>15</b>
History .....	16

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.2] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The present document is part 33 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

### National transposition dates

Date of adoption of this EN:	2 February 2009
Date of latest announcement of this EN (doa):	31 May 2009
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2009
Date of withdrawal of any conflicting National Standard (dow):	30 November 2010

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.4].

# 1 Scope

The present document, together with EN 301 489-1 [1] covers EMC requirements of transceivers, transmitters and receivers utilizing Ultra Wide Band (UWB) technologies and used for short range communication purposes.

The present document applies to impulse, modified impulse and RF carrier based UWB communication technologies.

The present document applies to fixed (indoor only), mobile or portable applications, e.g.:

- stand-alone radio equipment with or without its own control provisions;
- plug-in radio devices intended for use with, or within, a variety of host systems, e.g. personal computers, hand-held terminals, etc.;
- plug-in radio devices intended for use within combined equipment, e.g. cable modems, set-top boxes, access points, etc.;
- combined equipment or a combination of a plug-in radio device and a specific type of host equipment;
- equipment for use in road and rail vehicles.

In case of differences (for instance concerning special conditions, definitions, abbreviations) between the present document and EN 301 489-1 [1], the provisions of the present document take precedence.

The environmental classification and the emission and immunity requirements used in the present document are as stated in EN 301 489-1 [1], except for any special conditions included in the present document.

The present document does not cover UWB transmitter equipment to be installed at a fixed outdoor location or for use in flying models, aircraft and other forms of aviation as per the ECC/DEC/(06)04 [i.5].

The present document applies to UWB equipment with an output connection used with a dedicated antenna or UWB equipment with an integral antenna.

These radio equipment types are capable of operating in all or part of the frequency bands given in table 1.

**Table 1: Radiocommunications frequency bands**

Radiocommunications frequency bands	
Transmit	3,4 GHz to 4,8 GHz
Receive	3,4 GHz to 4,8 GHz
Transmit	6,0 GHz to 8,5 GHz
Receive	6,0 GHz to 8,5 GHz

The present document is intended to cover the provisions of Directive 1999/5/EC [i.1] (R&TTE Directive), article 3.1(b).

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
  - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
  - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 301 489-1 (V1.8.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements".

### 2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on information society services.
- [i.3] Void.
- [i.4] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.5] ECC Decision ECC/DEC/(06)04 of 24 March 2006 amended 6 July 2007 at Constanta on the harmonised conditions for devices using UWB technology in bands below 10,6 GHz.

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 301 489-1 [1] and the following apply:

**Equipment Under Test (EUT):** equipment under test and subject to the performance requirements of the present document

**fixed station:** equipment intended for use in a fixed location and fitted with one or more antennas

NOTE: The equipment may be fitted with either antenna socket(s) or integral antenna(s) or both.

**host:** any equipment which has complete user functionality when not connected to the radio equipment part and to which the radio equipment part provides additional functionality and to which connection is necessary for the radio equipment part to offer functionality

**plug-in radio device:** equipment, including slide-in radio cards, intended to be used with or within a variety of host systems, using their control functions and power supply

**stand-alone radio equipment:** equipment that is intended primarily as communications equipment and that is normally used on a stand-alone basis

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	ACKnowledgement
ARQ	Automatic Retransmission reQuest
CR	Continuous phenomena applied to Receivers
CT	Continuous phenomena applied to Transmitters
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
NACK	Not ACKnowledgement
RF	Radio Frequency
TR	Transient phenomena applied to Receivers
TT	Transient phenomena applied to Transmitters
UWB	Ultra Wide Band

## 4 Test conditions

### 4.1 General

For the purposes of the present document, the test conditions of EN 301 489-1 [1], clause 4, shall apply as appropriate. Further product related test conditions for UWB communications systems are specified in clauses 4.2 to 4.5.

The radio equipment may take forms which may require special software and/or test fixtures. Equipment which requires connection to a host equipment to function shall use the test configuration as defined by the manufacturer. In all cases the EUT shall be exercised in a manner representative of normal intended use.

## 4.2 Arrangements for test signals

The provisions of EN 301 489-1 [1], clause 4.2 shall apply.

### 4.2.1 Arrangements for test signals at the input of transmitters

The provisions of EN 301 489-1 [1], clause 4.2.1 shall apply with the following modifications.

The wanted signals and/or controls required to establish a communications link shall be defined by the manufacturer. The transmitter shall be operated at maximum rated power.

### 4.2.2 Arrangements for test signals at the output of transmitters

The provisions of EN 301 489-1 [1], clause 4.2.2 shall apply with the following modifications.

The manufacturer may provide a suitable companion receiver that can be used to receive messages or to set up a communication link.

### 4.2.3 Arrangements for test signals at the input of receivers

The provisions of EN 301 489-1 [1], clause 4.2.3 shall apply with the following modifications.

The provider shall provide a suitable transmitter that can be used to set up the UWB communications link representing intended use of the equipment.

The wanted signals required to establish a communications link shall be defined by the manufacturer.

The distance between the transmitter and the receiver shall be one meter, except in cases where the intended communications range is shorter than 1,5 meter. In such cases, a shorter distance may be used and shall be defined by the manufacturer.

### 4.2.4 Arrangements for test signals at the output of receivers

The measuring equipment for the output signal from the receiver under test shall be located outside the test environment.

It shall be possible to assess the performance of the equipment by appropriately monitoring the receiver output.

If the receiver has an output connector or port providing the wanted output signal, then this port shall be used via a cable, consistent with the standard cable used in normal operation, connected to the external measuring equipment outside the test environment. The measuring equipment may be supplied by the manufacturer.

Precautions shall be taken to ensure that any effect on the test due to the coupling means is minimized.

The manufacturer may provide a suitable companion transmitter that can be used to transmit messages or to set up a communication link.

### 4.2.5 Arrangements for testing transmitter and receiver together (as a system)

The provisions of EN 301 489-1 [1], clause 4.2.5 shall apply.

The manufacturer may provide a suitable companion transceiver or transmitter and receiver that can be used to send and receive messages or to set up a communication link.

Both the EUT and the companion equipment shall transmit the normal test modulation. Further, the output of the radio equipment under test shall be monitored by the test system.



### 4.3 Exclusion bands

The frequencies on which the transmitter part of the EUT is intended to operate shall be excluded from conducted and radiated immunity measurements when performed in transmit mode of operation.

There shall be no frequency exclusion band applied to immunity measurements of the receiver part of transceivers or the stand alone receiver under test, and/or associated ancillary equipment.

The immunity test exclusions are referred to as "exclusion bands" and are defined in EN 301 489-1 [1], clause 4.3.

### 4.4 Narrow band responses on receivers or receivers which are part of transceivers

The provision of EN 301 489-1 [1], clause 4.4 shall apply.

### 4.5 Normal test modulation

The modulated test signal shall represent normal intended use, and may contain data formatting, error detection and correction information.

---

## 5 Performance assessment

### 5.1 General

The provision of EN 301 489-1 [1], clause 5.1 shall apply with the following modification.

The manufacturer shall supply at the time of submission of the equipment for test, the information required in EN 301 489-1 [1], clause 5.1 and the following which shall be recorded in the test report:

- the operating frequency range(s) of the equipment and, where applicable, band(s) of operation;
- the type of the equipment, for example: stand-alone or plug-in radio device;
- the host equipment to be combined with the radio equipment for testing;
- the minimum performance level under the application of EMC stress (see clause 6.2);
- the normal test modulation, the format, the type of error correction and any control signals e.g. ACKnowledgement (ACK)/Not ACKnowledgement (NACK) or Automatic Retransmission reQuest (ARQ).

### 5.2 Arrangements for the assessment of host dependant equipment and plug-in cards

For equipment parts for which integration with a host equipment is necessary in order to offer functionality, two alternative approaches defined in clauses 5.2.1 and 5.2.2 may be used. The manufacturer shall declare which alternative shall be used.