



SLOVENSKI STANDARD
SIST EN 300 392-2 V3.4.1:2010

01-oktober-2010

Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 2. del: Radijski vmesnik (AI)

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 300 392-2 Version 3.4.1

SIST EN 300 392-2 V3.4.1:2010
<https://standards.iteh.ai/catalog/standards/sist/ffab770c-bb69-4fa7-b4e2-85f63faa7881/sist-en-300-392-2-v3-4-1-2010>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-2 V3.4.1:2010 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V3.4.1:2010

<https://standards.iteh.ai/catalog/standards/sist/ffab770c-bb69-4fa7-b4e2-85f63faa7881/sist-en-300-392-2-v3-4-1-2010>

ETSI EN 300 392-2 V3.4.1 (2010-08)

European Standard (Telecommunications series)

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 392-2 V3.4.1:2010](https://standards.iteh.ai/catalog/standards/sist/ffab770c-bb69-4fa7-b4e2-85f63faa7881/sist-en-300-392-2-v3-4-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/ffab770c-bb69-4fa7-b4e2-85f63faa7881/sist-en-300-392-2-v3-4-1-2010>



Reference

REN/TETRA-03182

Keywords

air interface, radio, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-2 V3.4.1:2010

<https://standards.iteh.ai/catalog/standards/sist/f1ab770c-bb69-4fa7-b4e2-85f63faa78d1/ETSI-EN-300-392-v3-4-1-2010>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	40
Foreword.....	40
Introduction	41
1 Scope	42
2 References	42
2.1 Normative references	43
2.2 Informative references.....	45
3 Definitions and abbreviations.....	46
3.1 Definitions	46
3.2 Abbreviations	51
4 Radio aspects.....	57
4.1 Introduction	57
4.2 Set of logical channels.....	57
4.3 Reference configuration	57
4.4 Error control schemes.....	58
4.5 Multiple access and time slot structure.....	58
4.5.1 General.....	58
4.5.2 Hyperframes, multiframe and frames.....	59
4.5.3 Time slots and bursts.....	59
4.5.4 Mapping of logical channels onto physical channels.....	60
4.6 Coding, interleaving and scrambling.....	60
4.7 Modulation	60
4.8 Transmission and reception	60
4.9 Other radio-related functions.....	60
4.10 Performance	61
4.11 TETRA modes of operation	61
4.11.1 Transmission modes	61
4.11.1.1 D-CT mode	61
4.11.1.2 D-CTT mode.....	61
4.11.1.3 D-MCCTT mode.....	62
4.11.1.4 U-MST mode	62
4.11.2 Control modes.....	62
4.11.2.1 Normal Control Mode.....	62
4.11.2.2 Minimum Control Mode	62
5 Modulation	63
5.1 Introduction	63
5.2 Modulation type	63
5.3 Modulation rate	63
5.4 Modulation symbol definition	63
5.5 Modulated signal definition.....	65
5.6 Modulation filter definition	65
5.7 Modulation block diagram	66
5.8 Introduction to QAM channels.....	66
5.9 Modulation type	66
5.10 Use of sub-carriers in QAM carriers	66
5.11 Modulation rate	66
5.12 Modulation symbol definition	67
5.13 Bit to symbol mapping	67
5.14 Data, synchronization and pilot symbol multiplexing.....	70
5.15 Sub-carrier frequency domain multiplexing.....	71
5.16 Modulated signal definition.....	71
5.17 Modulation filter definition	72
5.18 Modulation block diagram	73

6	Radio transmission and reception.....	74
6.1	Introduction	74
6.2	Frequency bands and channel arrangement.....	74
6.3	Reference test planes	74
6.4	Transmitter characteristics.....	75
6.4.1	Output power for phase modulation	75
6.4.1.1	Base Station (BS).....	75
6.4.1.2	Mobile Station (MS)	76
6.4.2	Unwanted conducted emissions for phase modulation	76
6.4.2.1	Definitions.....	76
6.4.2.2	Unwanted emissions close to the carrier	77
6.4.2.2.1	Emission during the useful part of the burst.....	77
6.4.2.2.2	Emission during the switching transients	77
6.4.2.3	Unwanted emissions far from the carrier	78
6.4.2.4	Unwanted emissions during the CLCH and BLCH	78
6.4.2.5	Unwanted emissions in the non-transmit state	79
6.4.3	Unwanted radiated emissions for phase modulation.....	79
6.4.4	RF tolerance for phase modulation.....	79
6.4.5	RF Output power time mask for phase modulation	79
6.4.5.1	BS.....	80
6.4.5.2	MS.....	80
6.4.6	Transmitter intermodulation attenuation for phase modulation.....	80
6.4.6.1	Definition	80
6.4.6.2	BS.....	80
6.4.6.3	MS.....	81
6.4.7	Intra-BS intermodulation requirements	81
6.4.8	Output power for QAM.....	81
6.4.8.1	BS.....	81
6.4.8.2	MS.....	82
6.4.9	Unwanted conducted emissions for QAM.....	82
6.4.9.1	Definitions.....	82
6.4.9.2	Unwanted emissions close to the carrier.....	82
6.4.9.2.1	Emission during the useful part of the burst.....	83
6.4.9.2.2	Emission during the switching transients	83
6.4.9.3	Unwanted emissions far from the carrier	84
6.4.9.4	Unwanted emissions during the CLCH-Q and BLCH-Q.....	85
6.4.9.5	Unwanted emissions in the non-transmit state	85
6.4.10	RF Output power time mask for QAM.....	85
6.4.10.1	BS.....	86
6.4.10.2	MS.....	87
6.4.11	Transmitter intermodulation attenuation.....	87
6.4.12	Intra-BS intermodulation requirements	87
6.5	Receiver characteristics	87
6.5.1	Blocking characteristics	87
6.5.1.1	Definition	87
6.5.1.2	Specification for Phase Modulation	87
6.5.1.3	Specification for QAM.....	88
6.5.2	Spurious response rejection	88
6.5.2.1	Definition	88
6.5.2.2	Specification for phase modulation.....	89
6.5.2.3	Specification for QAM.....	89
6.5.3	Intermodulation response rejection.....	90
6.5.3.1	Definition	90
6.5.3.2	Specification for Phase Modulation	90
6.5.3.3	Specification for QAM.....	90
6.5.4	Unwanted conducted emissions.....	90
6.5.4.1	Definition	90
6.5.4.2	Specification.....	90
6.5.5	Unwanted radiated emissions	91
6.6	Transmitter/receiver performance for phase modulation.....	91
6.6.1	Transmitter performance for phase modulation.....	91
6.6.1.1	Modulation accuracy for phase modulation	91

6.6.1.2	Vector error magnitude requirement at symbol time for phase modulation.....	91
6.6.2	Receiver performance for phase modulation	92
6.6.2.1	Nominal error rates for phase modulation.....	93
6.6.2.1.1	Nominal error rates for $\pi/4$ -DQPSK modulation	93
6.6.2.1.2	Nominal error rates for $\pi/8$ -D8PSK modulation	93
6.6.2.2	Dynamic reference sensitivity performance for phase modulation	93
6.6.2.2.1	BS receiver performance	94
6.6.2.2.2	MS receiver performance	95
6.6.2.3	Receiver performance at reference interference ratios for Phase Modulation.....	96
6.6.2.3.1	BS receiver performance	97
6.6.2.3.2	MS receiver performance	98
6.6.2.4	Static reference sensitivity performance for phase modulation.....	98
6.6.2.4.1	BS receiver performance	99
6.6.2.4.2	MS receiver performance	99
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	100
6.7	Transmitter/receiver performance for QAM	100
6.7.1	Transmitter performance for QAM.....	100
6.7.1.1	Modulation accuracy for QAM.....	100
6.7.1.2	Vector error magnitude requirement at symbol time for QAM.....	101
6.7.2	Receiver performance for QAM	102
6.7.2.1	Nominal error rates for QAM.....	102
6.7.2.2	Dynamic reference sensitivity performance for QAM	102
6.7.2.3	Receiver performance at reference interference ratios for QAM	105
6.7.2.3.1	Adjacent channel interference	105
6.7.2.3.2	Co-channel interference.....	105
6.7.2.4	Static reference sensitivity performance for QAM	106
6.8	Propagation conditions	106
6.8.1	Propagation conditions - introduction.....	106
6.8.2	Tap-gain process types.....	107
6.8.3	Propagation models.....	108
7	Radio sub-system synchronization.....	109
7.1	Introduction	109
7.2	General description of synchronization system.....	109
7.3	Timebase counters for phase modulation	109
7.3.1	Timing counters for phase modulation	109
7.3.2	Values of the counters for phase modulation.....	109
7.4	Timing of transmitted signals for phase modulation	110
7.5	Timebase counters for QAM	110
7.5.1	Timing counters for QAM.....	110
7.5.2	Values of the counters for QAM.....	110
7.6	Timing of transmitted signals for QAM.....	111
7.7	BS requirements for synchronization	111
7.8	MS requirements for synchronization	111
8	Channel coding and scrambling	112
8.1	Introduction	112
8.2	General	112
8.2.1	Interfaces in the error control structure.....	112
8.2.1.1	Interfaces for phase modulation	112
8.2.1.2	Interfaces for QAM.....	114
8.2.2	Notation	115
8.2.3	Definition of error control codes.....	115
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	115
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4	115
8.2.3.1.2	Puncturing of the mother code.....	116
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	116
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3.....	116
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432.....	116
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432.....	116
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code	117
8.2.3.3	$(K_I + 16, K_I)$ block code	117

8.2.3.4	8-state Parallel Concatenated Convolutional Code (PCCC) for QAM	118
8.2.3.4.1	Encoding by the upper 8-state RSC encoder of rate 1/2.....	118
8.2.3.4.2	Interleaving by the quadratic-congruence interleaver.....	119
8.2.3.4.3	Encoding the interleaved bits by the lower 8-state RSC encoder of rate 1/2.....	120
8.2.3.4.4	Merging the systematic and parity bits for the PCCC encoder.....	120
8.2.3.4.5	Puncturing scheme for the PCCC encoder	121
8.2.3.4.6	Puncturing scheme for the PCCC encoder with coding rate 2/3.....	121
8.2.3.4.7	Puncturing scheme for the PCCC encoder with coding rate 1/2.....	121
8.2.3.5	(16,5) Reed-Muller (RM) code for QAM	121
8.2.4	Definition of interleaving schemes	121
8.2.4.1	Block interleaving for phase modulation	121
8.2.4.2	Interleaving over <i>N</i> blocks	122
8.2.4.3	Block interleaving for QAM	122
8.2.5	Definition of scrambling	123
8.2.5.1	Scrambling method	123
8.2.5.2	Scrambling sequence.....	123
8.3	Error control schemes.....	124
8.3.1	Error control schemes for phase modulation	124
8.3.1.1	Access Assignment Channel (AACH)	126
8.3.1.2	Broadcast Synchronization Channel (BSCH)	126
8.3.1.3	Traffic channels in circuit switched mode	127
8.3.1.3.1	Frame stealing and multi-slot transmission	127
8.3.1.3.2	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8)	127
8.3.1.3.3	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4)	128
8.3.1.3.4	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2)	128
8.3.1.3.5	Traffic Channel-P8, net rate = 10,8 kbit/s (TCH-P8/10,8)	129
8.3.1.3.6	Speech Channel, full slot (TCH/S)	129
8.3.1.3.7	Speech Traffic Channel, half slot (TCH/S)	129
8.3.1.4	Signalling channels for signalling and packet mode data	130
8.3.1.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STEaling CHannel (STCH)	130
8.3.1.4.2	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH-P8/HD).....	130
8.3.1.4.3	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU)	131
8.3.1.4.4	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH-P8/HU).....	131
8.3.1.4.5	Signalling CHannel for mapping onto Full bursts (SCH/F)	131
8.3.1.4.6	Signalling CHannel for mapping onto Full bursts (SCH-P8/F).....	132
8.3.2	Error control schemes for QAM	133
8.3.2.1	Slot Information Channel – QAM/Uplink (SICH-Q/U).....	133
8.3.2.2	Slot Information Channel – QAM/Downlink (SICH-Q/D).....	134
8.3.2.3	Access Assignment Channel – QAM (AACH-Q).....	134
8.3.2.4	Signalling Channel – QAM/Half slot Uplink (SCH-Q/HU)	134
8.3.2.5	Signalling Channel – QAM/Uplink (SCH-Q/U)	135
8.3.2.6	Signalling Channel – QAM/Downlink (SCH-Q/D) and Broadcast Network Channel – QAM (BNCH-Q).....	136
8.3.2.7	Signalling Channel – QAM/Random Access (SCH-Q/RA).....	137
9	Channel multiplexing	138
9.1	Introduction	138
9.2	Logical channels.....	138
9.2.1	Logical channels hierarchy	138
9.2.2	Traffic channels for $\pi/4$ -DQPSK	138
9.2.2a	Traffic channels for $\pi/8$ -D8PSK	138
9.2.3	Control CHannels (CCH) for phase modulation.....	139
9.2.3.1	General	139
9.2.3.2	BCCH.....	139
9.2.3.3	LCH.....	139
9.2.3.4	SCH for $\pi/4$ -DQPSK.....	139
9.2.3.4a	SCH for $\pi/8$ -D8PSK	140
9.2.3.5	AACH	140
9.2.3.6	STCH	140
9.2.4	QAM Control CHannels (CCH-Q)	140
9.2.4.1	General	140

9.2.4.2	BCCH-Q	140
9.2.4.3	LCH-Q	141
9.2.4.4	SCH-Q.....	141
9.2.4.5	AACH-Q.....	142
9.2.4.6	SICH-Q	142
9.3	The physical resource.....	142
9.3.1	General.....	142
9.3.2	RF channels for phase modulation.....	143
9.3.2a	RF channels for QAM.....	143
9.3.2b	Random access RF channels for QAM.....	144
9.3.3	Timeslots	144
9.3.4	TDMA frame	144
9.3.5	Timeslot numbering	144
9.3.6	Subslot	144
9.3.6a	Random access uplink RF channel subslots for QAM.....	144
9.3.7	Multiframe	145
9.3.8	Hyperframe	145
9.3.9	Frame alignment	145
9.4	Physical channels	145
9.4.1	General.....	145
9.4.2	Types of physical channels for phase modulation	145
9.4.2.1	CP channel	145
9.4.2.2	TP channel.....	145
9.4.2.3	UP channel	146
9.4.3	Bursts for phase modulation	146
9.4.3.1	General.....	146
9.4.3.2	Phase modulation symbol numbering	146
9.4.3.3	Phase modulation bit numbering.....	146
9.4.3.4	Burst timing.....	146
9.4.4	Type of bursts for phase modulation	147
9.4.4.1	General	147
9.4.4.2	Modulation bits allocation.....	149
9.4.4.2.1	Control uplink Burst (CB).....	149
9.4.4.2.2	Linearization uplink Burst (LB).....	150
9.4.4.2.3	Linearization downlink burst.....	150
9.4.4.2.4	Normal Uplink Burst (NUB)	150
9.4.4.2.5	Normal continuous downlink burst	151
9.4.4.2.6	Synchronization continuous downlink burst.....	151
9.4.4.2.7	Normal discontinuous downlink burst.....	152
9.4.4.2.8	Synchronization discontinuous downlink burst.....	153
9.4.4.3	Burst fields	153
9.4.4.3.1	Frequency correction field.....	153
9.4.4.3.2	Normal training sequence	153
9.4.4.3.3	Extended training sequence	154
9.4.4.3.4	Synchronization training sequence	154
9.4.4.3.5	Tail bits.....	155
9.4.4.3.6	Phase adjustment bits	155
9.4.5	Transmission modes for phase modulation.....	156
9.4.5.1	BS continuous transmission	156
9.4.5.2	BS timesharing transmission	156
9.4.5.3	MS multiple slot transmission.....	157
9.4.6	Types of physical channels for QAM	157
9.4.6.1	CP channel	157
9.4.6.2	UP channel	158
9.4.7	Bursts for QAM	158
9.4.7.1	General	158
9.4.7.2	Modulation symbol numbering.....	158
9.4.7.3	Modulation bit numbering.....	158
9.4.7.4	Burst timing.....	158
9.4.8	Type of bursts for QAM	159
9.4.8.1	General	159
9.4.8.2	Modulation symbols allocation	160

9.4.8.3	Burst sub-carrier symbol sets	160
9.4.8.3.1	General on burst sub-carrier symbol sets.....	160
9.4.8.3.2	Uplink sync sequence set.....	160
9.4.8.3.3	Downlink sync sequence set.....	161
9.4.8.3.4	Half-slot uplink pilots set	161
9.4.8.3.5	Full-slot uplink pilots set	161
9.4.8.3.6	Full-slot downlink pilots set	161
9.4.8.3.7	Filler sets	162
9.4.8.3.8	Linearization downlink zeroed set.....	162
9.4.9	Transmission modes for QAM.....	162
9.4.9.1	BS transmission.....	162
9.4.9.2	MS multiple slot transmission.....	162
9.5	Mapping of logical channels into physical channels	162
9.5.1	General mapping of logical channels into $\pi/4$ -DQPSK physical channels.....	163
9.5.1a	General mapping of logical channels into D8PSK physical channels	164
9.5.1b	General mapping of logical channels into unallocated physical channels for phase modulation	165
9.5.2	Mapping of BCCH and CLCH for phase modulation.....	165
9.5.3	Mapping of SCH for $\pi/4$ -DQPSK physical channels	166
9.5.3a	Mapping of SCH for $\pi/8$ -D8PSK physical channels.	166
9.5.4	Mapping of TCH and STCH for phase modulation	166
9.5.5	Mapping of AACH for phase modulation.....	167
9.5.6	General mapping of logical channels for QAM.....	167
9.5.7	General mapping of logical channels into unallocated physical channels for QAM	167
9.5.8	Mapping of CLCH-Q for QAM.....	168
9.5.9	Mapping of SCH-Q for QAM.....	168
9.5.10	Mapping of SICH-Q and AACH-Q for QAM	168
9.6	Monitoring pattern for transmitting MSs.....	169
9.7	BS timesharing transmission	169
9.7.1	Carrier sharing for Phase Modulation	169
9.7.2	MCCH sharing for Phase Modulation	169
9.7.3	BS timesharing transmission for QAM.....	170
9.8	Modes of control	170
9.8.1	Normal Control Mode.....	170
9.8.2	Minimum Control Mode.....	170
10	Radio subsystem link control	172
10.1	Introduction	172
10.2	RF power control.....	172
10.3	Radio link measurements	172
10.3.1	Received signal strength	172
10.3.1.1	Signal strength measurement	172
10.3.1.2	Sample duration for signal strength measurement	172
10.3.2	Signal quality.....	172
10.3.3	Round-trip MS-BS path delay	172
10.4	Link adaptation.....	173
11	Call Control (CC) service description	174
11.1	Introduction	174
11.2	Services offered.....	174
11.3	CC service	175
11.3.1	CC primitives exchanged through the TNCC-SAP	175
11.3.2	Service primitives at the TNCC-SAP	175
11.3.3	Primitive description.....	176
11.3.3.1	TNCC-ALERT primitive	176
11.3.3.2	TNCC-COMPLETE primitive	177
11.3.3.3	TNCC-DTMF primitive	177
11.3.3.4	TNCC-MODIFY primitive	178
11.3.3.5	TNCC-NOTIFY primitive	178
11.3.3.6	TNCC-PROCEED primitive.....	179
11.3.3.7	TNCC-RELEASE primitive.....	179
11.3.3.8	TNCC-SETUP primitive	179
11.3.3.9	TNCC-TX primitive.....	181

11.3.4	Parameter description	181
11.4	States for CC SAP	189
12	Supplementary Service (SS) service description.....	190
12.1	Introduction	190
12.2	Services offered.....	190
12.3	SS service	190
12.3.1	Primitives exchanged through TNSS-SAP	190
12.3.2	Parameter description	191
13	Short Data Service (SDS) service description.....	191
13.1	Introduction	191
13.2	Services offered.....	191
13.3	SDS	191
13.3.1	SDS primitives exchanged through the TNSDS-SAP	191
13.3.2	Service primitives at the TNSDS-SAP	192
13.3.2.1	TNSDS-STATUS primitive	192
13.3.2.2	TNSDS-REPORT primitive.....	193
13.3.2.3	TNSDS-UNITDATA primitive.....	193
13.3.2.4	TNSDS-CANCEL primitive	194
13.3.3	Parameter description	194
13.3.4	State description.....	197
13.3.4.1	NULL state.....	197
13.3.4.2	SHORT DATA INITIATED state	197
13.3.5	Service state diagram for the TNSDS-SAP	197
14	CMCE protocol	198
14.1	Introduction	198
14.2	Overview of CMCE.....	198
14.2.1	Communication routes of the CMCE model.....	199
14.2.2	Protocol structure and protocol stack.....	199
14.2.3	Addressing rules	201
14.2.4	CC, SS and SDS sub-entities	201
14.2.4.1	CC sub-entity.....	201
14.2.4.2	SS sub-entity	202
14.2.4.3	SDS sub-entity	202
14.2.5	PC sub-entity	202
14.2.6	Internal routes	203
14.2.7	Intra-CMCE primitive summary.....	205
14.2.7.1	Down link CC PDU parameters	205
14.2.7.2	Uplink CC PDU parameters	205
14.2.7.3	Downlink SS PDU parameters.....	206
14.2.7.4	Uplink SS PDU parameters.....	206
14.2.7.5	Down link SDS PDU parameters	206
14.2.7.6	Uplink SDS PDU parameters	206
14.2.7.7	CMCE management primitives.....	206
14.2.7.7.0	ACTIVITY request.....	206
14.2.7.7.1	BREAK indication.....	206
14.2.7.7.1a	BUSY indication	206
14.2.7.7.2	CANCEL request.....	207
14.2.7.7.3	CLOSE indication	207
14.2.7.7.4	CONFIGURE indication	207
14.2.7.7.5	CONFIGURE request.....	207
14.2.7.7.6	IDENTITIES request.....	207
14.2.7.7.6a	IDLE indication	207
14.2.7.7.6b	INFO indication.....	208
14.2.7.7.7	OPEN indication.....	208
14.2.7.7.8	REOPEN indication.....	208
14.2.7.7.9	REPORT indication.....	208
14.2.7.7.10	RESUME indication	208
14.3	Overview of services required by the CMCE.....	209
14.4	CMCE protocol states	209
14.4.1	States for PC	209

14.4.1.1	CLOSED	209
14.4.1.2	OPEN	209
14.4.2	States for CC	210
14.4.2.1	IDLE	212
14.4.2.2	MO-CALL-SETUP	212
14.4.2.3	MT-CALL-SETUP	212
14.4.2.4	CALL ACTIVE	213
14.4.2.5	CALL DISCONNECT	213
14.4.2.6	WAIT	213
14.4.3	States for SS	213
14.4.4	States for SDS	214
14.5	Procedures	214
14.5.1	Individual CC procedures	215
14.5.1.1	Call set-up procedures	215
14.5.1.1.1	Incoming call	216
14.5.1.1.2	Outgoing call	218
14.5.1.1.3	Colliding calls	219
14.5.1.1.4	Unsuccessful call set-up	219
14.5.1.1.5	Call rejection	220
14.5.1.2	Call maintenance procedures	220
14.5.1.2.1	Transmission control procedures	221
14.5.1.2.2	Call status information procedures	225
14.5.1.2.3	Call modification procedures	226
14.5.1.2.4	Call restoration procedures	227
14.5.1.2.5	DTMF procedures	229
14.5.1.2.6	Calls to and from external subscribers	230
14.5.1.3	Call disconnection procedures	231
14.5.1.3.1	User initiated disconnection	231
14.5.1.3.2	Network initiated disconnection	232
14.5.1.3.3	Reception of disconnection request	232
14.5.1.3.4	Expiry of timers	232
14.5.1.3.5	Colliding disconnection	233
14.5.1.4	U-Plane switching	233
14.5.1.4.1	End of call set-up phase	234
14.5.1.4.2	During call maintenance phase	234
14.5.1.4.3	Call disconnection phase	235
14.5.2	Group CC procedures	235
14.5.2.1	Call set-up procedures	235
14.5.2.1.1	Incoming call	236
14.5.2.1.2	Outgoing call	237
14.5.2.1.3	Colliding calls	238
14.5.2.1.4	Unsuccessful call set-up	238
14.5.2.1.5	Call rejection	238
14.5.2.2	Call maintenance procedures	239
14.5.2.2.1	Transmission control procedures	239
14.5.2.2.2	Call status information procedures	243
14.5.2.2.3	Call modification procedures	244
14.5.2.2.4	Call restoration procedures	245
14.5.2.2.5	DTMF procedures	247
14.5.2.2.6	Temporary address handling procedures	247
14.5.2.2.7	Calls to and from external subscribers	248
14.5.2.3	Call disconnection procedures	248
14.5.2.3.1	User initiated disconnection	249
14.5.2.3.2	Network initiated disconnection	250
14.5.2.3.3	Reception of disconnection request	250
14.5.2.3.4	Colliding disconnection	250
14.5.2.3.5	Expiry of timers	250
14.5.2.4	U-Plane switching	251
14.5.2.4.1	End of call set-up phase	251
14.5.2.4.2	During call maintenance phase	252
14.5.2.4.3	Call disconnection phase	253
14.5.2.5	Void	253

14.5.2.6	Acknowledged group call procedures	253
14.5.2.7	Call ownership	253
14.5.3	Traffic channel assignment procedures.....	254
14.5.3.1	SwMI related procedures	254
14.5.3.2	MS related procedures.....	255
14.5.3.2.1	General procedures	255
14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation.....	256
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	257
14.5.4	SS procedures	258
14.5.5	SDS procedures	258
14.5.5.1	Incoming short data message	258
14.5.5.2	Outgoing short data messages	258
14.5.6	PC procedures.....	259
14.5.6.1	Access to the communication resources.....	259
14.5.6.2	Access priority handling	259
14.5.6.2.1	Cancel.....	260
14.5.6.3	CMCE PDU exchange	260
14.5.6.3.1	Choice of layer 2 service	260
14.5.6.4	Control information exchange.....	260
14.5.6.5	PC protocol error conditions	261
14.5.6.5.1	PDU type error	261
14.5.6.5.2	Invalid call identifier	261
14.5.6.5.3	MS busy.....	261
14.5.6.6	Temporary Disablement.....	261
14.5.7	Subscriber class	262
14.5.8	Activity handling	262
14.6	Protocol timers	263
14.7	PDU descriptions.....	264
14.7.1	PDU description tables - downlink.....	265
14.7.1.1	D-ALERT.....	265
14.7.1.2	D-CALL PROCEEDING.....	265
14.7.1.3	D-CALL RESTORE	266
14.7.1.4	D-CONNECT.....	266
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	267
14.7.1.6	D-DISCONNECT	267
14.7.1.7	D-FACILITY	267
14.7.1.8	D-INFO	268
14.7.1.9	D-RELEASE.....	268
14.7.1.10	D-SDS-DATA.....	269
14.7.1.11	D-STATUS	269
14.7.1.12	D-SETUP	270
14.7.1.13	D-TX CEASED.....	270
14.7.1.14	D-TX CONTINUE.....	271
14.7.1.15	D-TX GRANTED	271
14.7.1.16	D-TX INTERRUPT	272
14.7.1.17	D-TX WAIT.....	272
14.7.2	PDU description tables - uplink.....	273
14.7.2.1	U-ALERT.....	273
14.7.2.2	U-CALL RESTORE	273
14.7.2.3	U-CONNECT.....	274
14.7.2.4	U-DISCONNECT	274
14.7.2.5	U-FACILITY	274
14.7.2.6	U-INFO	275
14.7.2.7	U-STATUS	275
14.7.2.8	U-SDS-DATA.....	276
14.7.2.9	U-RELEASE.....	277
14.7.2.10	U-SETUP	277
14.7.2.11	U-TX CEASED.....	278
14.7.2.12	U-TX DEMAND.....	278
14.7.3	PDU description tables - downlink and uplink	278
14.7.3.1	General rules for function not supported.....	278
14.7.3.2	CMCE FUNCTION NOT SUPPORTED	278

14.8	Information elements coding.....	279
14.8.1	Area Selection.....	279
14.8.2	Basic service information	280
14.8.3	Call identifier.....	280
14.8.3a	Call identifier present.....	280
14.8.4	Call ownership.....	280
14.8.5	Called party type identifier	281
14.8.6	Called party SNA.....	281
14.8.7	Called party extension	281
14.8.8	Called party SSI.....	281
14.8.9	Calling party type identifier.....	282
14.8.10	Calling party extension	282
14.8.11	Calling party SSI.....	282
14.8.12	Call priority.....	282
14.8.13	Call status	283
14.8.14	Call queued.....	283
14.8.15	Continue.....	283
14.8.16	Call time-out	284
14.8.17	Call time-out, set-up phase	284
14.8.17a	Circuit mode type	285
14.8.17b	CLIR control.....	285
14.8.17c	Communication type.....	285
14.8.18	Disconnect cause	286
14.8.18a	DM-MS address.....	286
14.8.19	DTMF	286
14.8.19a	DTMF digit.....	287
14.8.19b	DTMF type	287
14.8.20	External subscriber number	288
14.8.21	Encryption control	288
14.8.21a	Encryption flag	288
14.8.22	Facility	289
14.8.23	Hook method selection	289
14.8.24	Length indicator	289
14.8.25	New call identifier	289
14.8.26	Modify	289
14.8.27	Notification indicator.....	290
14.8.27a	Other party type identifier.....	290
14.8.27b	Other party SNA.....	290
14.8.27c	Other party extension.....	290
14.8.27d	Other party SSI	290
14.8.28	PDU type	291
14.8.29	Poll request	291
14.8.30	Poll response.....	291
14.8.31	Poll response addresses.....	292
14.8.32	Poll response number.....	292
14.8.33	Poll response percentage.....	292
14.8.34	Pre-coded status	293
14.8.35	Proprietary	293
14.8.36	Request to transmit/send data	293
14.8.37	Reset call time-out timer (T310).....	293
14.8.38	Short data type identifier.....	294
14.8.39	Simplex/duplex selection.....	294
14.8.39a	Slots per frame.....	294
14.8.40	Speech service	294
14.8.41	Temporary address.....	294
14.8.42	Transmission grant.....	295
14.8.43	Transmission request permission.....	295
14.8.44	Transmitting party type identifier	295
14.8.45	Transmitting party extension	295
14.8.46	Transmitting party SSI.....	296
14.8.47	TX demand priority	296
14.8.48	Type 3 element identifier.....	296

14.8.49	User defined data-1	296
14.8.50	User defined data-2	297
14.8.51	User defined data-3	297
14.8.52	User defined data-4	297
15	Mobility Management (MM) service description	298
15.1	Introduction	298
15.2	Services offered	298
15.3	Primitive description	299
15.3.1	Service state model for the MS	299
15.3.2	Service primitives at the TNMM-SAP, MS/LS side	299
15.3.3	Primitive description	300
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive	300
15.3.3.2	TNMM-DEREGISTRATION primitive	300
15.3.3.3	TNMM-DISABLING primitive	300
15.3.3.4	TNMM-ENABLING primitive	300
15.3.3.5	TNMM-ENERGY SAVING primitive	301
15.3.3.6	TNMM-REPORT primitive	301
15.3.3.7	TNMM-REGISTRATION primitive	301
15.3.3.8	TNMM-SERVICE primitive	302
15.3.3.9	TNMM-STATUS primitive	302
15.3.4	Parameters description	303
15.3.5	State description for the MS	307
15.3.5.1	Not updated	307
15.3.5.2	Wait updating	307
15.3.5.3	Updated	307
15.3.5.4	Temporary disabled	307
15.3.5.5	Permanently disabled	307
15.3.6	Service state diagram for the TNMM-SAP	308
16	MM protocol	312
16.1	Introduction	312
16.2	MM procedures	312
16.2.1	General	312
16.2.2	Services provided by the protocol	313
16.2.3	Underlying services assumed by the protocol	313
16.2.4	Services assumed from the local environment	313
16.3	Protocol functions	313
16.3.1	Activation and control of underlying MLE Service	315
16.3.1.1	Activation procedure	315
16.3.1.2	Deactivation procedure	316
16.3.1.3	Maintenance procedures	316
16.3.1.3.1	Report and cancel handling	316
16.3.1.3.2	Stealing permission and stealing repeats flag handling	316
16.3.1.3.3	Busy handling	317
16.3.1.3.4	Activity handling	317
16.4	Registration procedure	317
16.4.1	MLE initiated registration procedure	317
16.4.1.1	Normal registration	318
16.4.1.2	Forward registration	323
16.4.2	User application initiated registration procedure	325
16.4.3	Infrastructure initiated registration procedure	330
16.4.4	Colliding registrations	333
16.4.5	Expiry of timer T351	333
16.4.6	Expiry of LA timers	333
16.4.7	Lifetime of ASSI/(V)ASSI	333
16.4.7.1	ASSI/(V)ASSI validity at migration	333
16.4.7.2	ASSI/(V)ASSI validity by MS initiative	333
16.4.7.3	ASSI/(V)ASSI validity at registration rejection	334
16.4.8	Temporary registration	334
16.4.9	Subscriber class procedures	334
16.4.10	Frequency band capability procedures	335