

**Terrestrial Trunked Radio (TETRA);  
Voice plus Data (V+D);  
Part 2: Air Interface (AI)**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/696bd93d-29f1-449b-944c-b7165173ec5b/etsi-en-300-392-2-v3.4.1-2010-08>



---

Reference

REN/TETRA-03182

---

Keywords

air interface, radio, TETRA, V+D

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	40
Foreword.....	40
Introduction .....	41
1 Scope .....	42
2 References .....	42
2.1 Normative references .....	43
2.2 Informative references .....	45
3 Definitions and abbreviations.....	46
3.1 Definitions .....	46
3.2 Abbreviations .....	51
4 Radio aspects.....	57
4.1 Introduction .....	57
4.2 Set of logical channels.....	57
4.3 Reference configuration .....	57
4.4 Error control schemes.....	58
4.5 Multiple access and time slot structure.....	58
4.5.1 General.....	58
4.5.2 Hyperframes, multiframe and frames.....	59
4.5.3 Time slots and bursts .....	59
4.5.4 Mapping of logical channels onto physical channels.....	60
4.6 Coding, interleaving and scrambling.....	60
4.7 Modulation .....	60
4.8 Transmission and reception .....	60
4.9 Other radio-related functions.....	60
4.10 Performance .....	61
4.11 TETRA modes of operation .....	61
4.11.1 Transmission modes .....	61
4.11.1.1 D-CT mode .....	61
4.11.1.2 D-CTT mode.....	61
4.11.1.3 D-MCCTT mode.....	62
4.11.1.4 U-MST mode .....	62
4.11.2 Control modes.....	62
4.11.2.1 Normal Control Mode.....	62
4.11.2.2 Minimum Control Mode .....	62
5 Modulation .....	63
5.1 Introduction .....	63
5.2 Modulation type .....	63
5.3 Modulation rate .....	63
5.4 Modulation symbol definition .....	63
5.5 Modulated signal definition.....	65
5.6 Modulation filter definition .....	65
5.7 Modulation block diagram .....	66
5.8 Introduction to QAM channels.....	66
5.9 Modulation type .....	66
5.10 Use of sub-carriers in QAM carriers .....	66
5.11 Modulation rate .....	66
5.12 Modulation symbol definition.....	67
5.13 Bit to symbol mapping .....	67
5.14 Data, synchronization and pilot symbol multiplexing.....	70
5.15 Sub-carrier frequency domain multiplexing.....	71
5.16 Modulated signal definition.....	71
5.17 Modulation filter definition .....	72
5.18 Modulation block diagram .....	73

6	Radio transmission and reception.....	74
6.1	Introduction .....	74
6.2	Frequency bands and channel arrangement.....	74
6.3	Reference test planes .....	74
6.4	Transmitter characteristics.....	75
6.4.1	Output power for phase modulation .....	75
6.4.1.1	Base Station (BS).....	75
6.4.1.2	Mobile Station (MS) .....	76
6.4.2	Unwanted conducted emissions for phase modulation .....	76
6.4.2.1	Definitions.....	76
6.4.2.2	Unwanted emissions close to the carrier .....	77
6.4.2.2.1	Emission during the useful part of the burst.....	77
6.4.2.2.2	Emission during the switching transients .....	77
6.4.2.3	Unwanted emissions far from the carrier .....	78
6.4.2.4	Unwanted emissions during the CLCH and BLCH .....	78
6.4.2.5	Unwanted emissions in the non-transmit state .....	79
6.4.3	Unwanted radiated emissions for phase modulation.....	79
6.4.4	RF tolerance for phase modulation.....	79
6.4.5	RF Output power time mask for phase modulation .....	79
6.4.5.1	BS.....	80
6.4.5.2	MS.....	80
6.4.6	Transmitter intermodulation attenuation for phase modulation .....	80
6.4.6.1	Definition .....	80
6.4.6.2	BS.....	80
6.4.6.3	MS.....	81
6.4.7	Intra-BS intermodulation requirements .....	81
6.4.8	Output power for QAM .....	81
6.4.8.1	BS.....	81
6.4.8.2	MS.....	82
6.4.9	Unwanted conducted emissions for QAM.....	82
6.4.9.1	Definitions.....	82
6.4.9.2	Unwanted emissions close to the carrier.....	82
6.4.9.2.1	Emission during the useful part of the burst.....	83
6.4.9.2.2	Emission during the switching transients .....	83
6.4.9.3	Unwanted emissions far from the carrier .....	84
6.4.9.4	Unwanted emissions during the CLCH-Q and BLCH-Q.....	85
6.4.9.5	Unwanted emissions in the non-transmit state .....	85
6.4.10	RF Output power time mask for QAM .....	85
6.4.10.1	BS.....	86
6.4.10.2	MS.....	87
6.4.11	Transmitter intermodulation attenuation.....	87
6.4.12	Intra-BS intermodulation requirements .....	87
6.5	Receiver characteristics .....	87
6.5.1	Blocking characteristics .....	87
6.5.1.1	Definition .....	87
6.5.1.2	Specification for Phase Modulation .....	87
6.5.1.3	Specification for QAM.....	88
6.5.2	Spurious response rejection .....	88
6.5.2.1	Definition .....	88
6.5.2.2	Specification for phase modulation.....	89
6.5.2.3	Specification for QAM.....	89
6.5.3	Intermodulation response rejection.....	90
6.5.3.1	Definition .....	90
6.5.3.2	Specification for Phase Modulation .....	90
6.5.3.3	Specification for QAM.....	90
6.5.4	Unwanted conducted emissions.....	90
6.5.4.1	Definition .....	90
6.5.4.2	Specification.....	90
6.5.5	Unwanted radiated emissions .....	91
6.6	Transmitter/receiver performance for phase modulation.....	91
6.6.1	Transmitter performance for phase modulation.....	91
6.6.1.1	Modulation accuracy for phase modulation .....	91

6.6.1.2	Vector error magnitude requirement at symbol time for phase modulation.....	91
6.6.2	Receiver performance for phase modulation .....	92
6.6.2.1	Nominal error rates for phase modulation.....	93
6.6.2.1.1	Nominal error rates for $\pi/4$ -DQPSK modulation .....	93
6.6.2.1.2	Nominal error rates for $\pi/8$ -D8PSK modulation .....	93
6.6.2.2	Dynamic reference sensitivity performance for phase modulation .....	93
6.6.2.2.1	BS receiver performance .....	94
6.6.2.2.2	MS receiver performance .....	95
6.6.2.3	Receiver performance at reference interference ratios for Phase Modulation.....	96
6.6.2.3.1	BS receiver performance .....	97
6.6.2.3.2	MS receiver performance .....	98
6.6.2.4	Static reference sensitivity performance for phase modulation.....	98
6.6.2.4.1	BS receiver performance .....	99
6.6.2.4.2	MS receiver performance .....	99
6.6.2.5	MS receiver performance for synchronization burst acquisition.....	100
6.7	Transmitter/receiver performance for QAM .....	100
6.7.1	Transmitter performance for QAM.....	100
6.7.1.1	Modulation accuracy for QAM.....	100
6.7.1.2	Vector error magnitude requirement at symbol time for QAM.....	101
6.7.2	Receiver performance for QAM .....	102
6.7.2.1	Nominal error rates for QAM.....	102
6.7.2.2	Dynamic reference sensitivity performance for QAM.....	102
6.7.2.3	Receiver performance at reference interference ratios for QAM .....	105
6.7.2.3.1	Adjacent channel interference .....	105
6.7.2.3.2	Co-channel interference.....	105
6.7.2.4	Static reference sensitivity performance for QAM .....	106
6.8	Propagation conditions .....	106
6.8.1	Propagation conditions - introduction.....	106
6.8.2	Tap-gain process types.....	107
6.8.3	Propagation models.....	108
7	Radio sub-system synchronization.....	109
7.1	Introduction .....	109
7.2	General description of synchronization system.....	109
7.3	Timebase counters for phase modulation .....	109
7.3.1	Timing counters for phase modulation .....	109
7.3.2	Values of the counters for phase modulation.....	109
7.4	Timing of transmitted signals for phase modulation .....	110
7.5	Timebase counters for QAM .....	110
7.5.1	Timing counters for QAM .....	110
7.5.2	Values of the counters for QAM.....	110
7.6	Timing of transmitted signals for QAM.....	111
7.7	BS requirements for synchronization .....	111
7.8	MS requirements for synchronization .....	111
8	Channel coding and scrambling .....	112
8.1	Introduction .....	112
8.2	General .....	112
8.2.1	Interfaces in the error control structure.....	112
8.2.1.1	Interfaces for phase modulation .....	112
8.2.1.2	Interfaces for QAM.....	114
8.2.2	Notation .....	115
8.2.3	Definition of error control codes.....	115
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes .....	115
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4 .....	115
8.2.3.1.2	Puncturing of the mother code.....	116
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	116
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3.....	116
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432.....	116
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432.....	116
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code .....	117
8.2.3.3	$(K_I + 16, K_I)$ block code .....	117

8.2.3.4	8-state Parallel Concatenated Convolutional Code (PCCC) for QAM .....	118
8.2.3.4.1	Encoding by the upper 8-state RSC encoder of rate 1/2.....	118
8.2.3.4.2	Interleaving by the quadratic-congruence interleaver.....	119
8.2.3.4.3	Encoding the interleaved bits by the lower 8-state RSC encoder of rate 1/2.....	120
8.2.3.4.4	Merging the systematic and parity bits for the PCCC encoder.....	120
8.2.3.4.5	Puncturing scheme for the PCCC encoder .....	121
8.2.3.4.6	Puncturing scheme for the PCCC encoder with coding rate 2/3.....	121
8.2.3.4.7	Puncturing scheme for the PCCC encoder with coding rate 1/2.....	121
8.2.3.5	(16,5) Reed-Muller (RM) code for QAM .....	121
8.2.4	Definition of interleaving schemes .....	121
8.2.4.1	Block interleaving for phase modulation .....	121
8.2.4.2	Interleaving over $N$ blocks .....	122
8.2.4.3	Block interleaving for QAM .....	122
8.2.5	Definition of scrambling .....	123
8.2.5.1	Scrambling method .....	123
8.2.5.2	Scrambling sequence.....	123
8.3	Error control schemes.....	124
8.3.1	Error control schemes for phase modulation .....	124
8.3.1.1	Access Assignment Channel (AACH) .....	126
8.3.1.2	Broadcast Synchronization Channel (BSCH) .....	126
8.3.1.3	Traffic channels in circuit switched mode .....	127
8.3.1.3.1	Frame stealing and multi-slot transmission .....	127
8.3.1.3.2	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8) .....	127
8.3.1.3.3	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4) .....	128
8.3.1.3.4	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2) .....	128
8.3.1.3.5	Traffic Channel-P8, net rate = 10,8 kbit/s (TCH-P8/10,8).....	129
8.3.1.3.6	Speech Traffic Channel, full slot (TCH/S) .....	129
8.3.1.3.7	Speech Traffic Channel, half slot (TCH/S) .....	129
8.3.1.4	Signalling channels for signalling and packet mode data.....	130
8.3.1.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STealing CHannel (STCH) .....	130
8.3.1.4.2	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH-P8/HD).....	130
8.3.1.4.3	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU) .....	131
8.3.1.4.4	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH-P8/HU).....	131
8.3.1.4.5	Signalling CHannel for mapping onto Full bursts (SCH/F) .....	131
8.3.1.4.6	Signalling CHannel for mapping onto Full bursts (SCH-P8/F).....	132
8.3.2	Error control schemes for QAM.....	133
8.3.2.1	Slot Information Channel – QAM/Uplink (SICH-Q/U).....	133
8.3.2.2	Slot Information Channel – QAM/Downlink (SICH-Q/D).....	134
8.3.2.3	Access Assignment Channel – QAM (AACH-Q).....	134
8.3.2.4	Signalling Channel – QAM/Half slot Uplink (SCH-Q/HU) .....	134
8.3.2.5	Signalling Channel – QAM/Uplink (SCH-Q/U) .....	135
8.3.2.6	Signalling Channel – QAM/Downlink (SCH-Q/D) and Broadcast Network Channel – QAM (BNCH-Q).....	136
8.3.2.7	Signalling Channel – QAM/Random Access (SCH-Q/RA).....	137
9	Channel multiplexing .....	138
9.1	Introduction .....	138
9.2	Logical channels.....	138
9.2.1	Logical channels hierarchy .....	138
9.2.2	Traffic channels for $\pi/4$ -DQPSK .....	138
9.2.2a	Traffic channels for $\pi/8$ -D8PSK .....	138
9.2.3	Control CHannels (CCH) for phase modulation.....	139
9.2.3.1	General .....	139
9.2.3.2	BCCH.....	139
9.2.3.3	LCH.....	139
9.2.3.4	SCH for $\pi/4$ -DQPSK.....	139
9.2.3.4a	SCH for $\pi/8$ -D8PSK .....	140
9.2.3.5	AACH .....	140
9.2.3.6	STCH .....	140
9.2.4	QAM Control CHannels (CCH-Q) .....	140
9.2.4.1	General .....	140

9.2.4.2	BCCH-Q .....	140
9.2.4.3	LCH-Q .....	141
9.2.4.4	SCH-Q.....	141
9.2.4.5	AACH-Q.....	142
9.2.4.6	SICH-Q .....	142
9.3	The physical resource.....	142
9.3.1	General.....	142
9.3.2	RF channels for phase modulation.....	143
9.3.2a	RF channels for QAM.....	143
9.3.2b	Random access RF channels for QAM.....	144
9.3.3	Timeslots .....	144
9.3.4	TDMA frame .....	144
9.3.5	Timeslot numbering .....	144
9.3.6	Subslot .....	144
9.3.6a	Random access uplink RF channel subslots for QAM.....	144
9.3.7	Multiframe .....	145
9.3.8	Hyperframe .....	145
9.3.9	Frame alignment .....	145
9.4	Physical channels .....	145
9.4.1	General.....	145
9.4.2	Types of physical channels for phase modulation .....	145
9.4.2.1	CP channel .....	145
9.4.2.2	TP channel.....	145
9.4.2.3	UP channel .....	146
9.4.3	Bursts for phase modulation .....	146
9.4.3.1	General.....	146
9.4.3.2	Phase modulation symbol numbering .....	146
9.4.3.3	Phase modulation bit numbering .....	146
9.4.3.4	Burst timing.....	146
9.4.4	Type of bursts for phase modulation .....	147
9.4.4.1	General .....	147
9.4.4.2	Modulation bits allocation .....	149
9.4.4.2.1	Control uplink Burst (CB).....	149
9.4.4.2.2	Linearization uplink Burst (LB) .....	150
9.4.4.2.3	Linearization downlink burst.....	150
9.4.4.2.4	Normal Uplink Burst (NUB).....	150
9.4.4.2.5	Normal continuous downlink burst .....	151
9.4.4.2.6	Synchronization continuous downlink burst.....	151
9.4.4.2.7	Normal discontinuous downlink burst.....	152
9.4.4.2.8	Synchronization discontinuous downlink burst.....	153
9.4.4.3	Burst fields .....	153
9.4.4.3.1	Frequency correction field.....	153
9.4.4.3.2	Normal training sequence .....	153
9.4.4.3.3	Extended training sequence .....	154
9.4.4.3.4	Synchronization training sequence .....	154
9.4.4.3.5	Tail bits.....	155
9.4.4.3.6	Phase adjustment bits .....	155
9.4.5	Transmission modes for phase modulation.....	156
9.4.5.1	BS continuous transmission .....	156
9.4.5.2	BS timesharing transmission .....	156
9.4.5.3	MS multiple slot transmission.....	157
9.4.6	Types of physical channels for QAM .....	157
9.4.6.1	CP channel .....	157
9.4.6.2	UP channel .....	158
9.4.7	Bursts for QAM .....	158
9.4.7.1	General .....	158
9.4.7.2	Modulation symbol numbering.....	158
9.4.7.3	Modulation bit numbering.....	158
9.4.7.4	Burst timing.....	158
9.4.8	Type of bursts for QAM .....	159
9.4.8.1	General .....	159
9.4.8.2	Modulation symbols allocation .....	160



9.4.8.3	Burst sub-carrier symbol sets .....	160
9.4.8.3.1	General on burst sub-carrier symbol sets.....	160
9.4.8.3.2	Uplink sync sequence set.....	160
9.4.8.3.3	Downlink sync sequence set.....	161
9.4.8.3.4	Half-slot uplink pilots set .....	161
9.4.8.3.5	Full-slot uplink pilots set .....	161
9.4.8.3.6	Full-slot downlink pilots set .....	161
9.4.8.3.7	Filler sets .....	162
9.4.8.3.8	Linearization downlink zeroed set.....	162
9.4.9	Transmission modes for QAM.....	162
9.4.9.1	BS transmission.....	162
9.4.9.2	MS multiple slot transmission.....	162
9.5	Mapping of logical channels into physical channels .....	162
9.5.1	General mapping of logical channels into $\pi/4$ -DQPSK physical channels.....	163
9.5.1a	General mapping of logical channels into D8PSK physical channels .....	164
9.5.1b	General mapping of logical channels into unallocated physical channels for phase modulation .....	165
9.5.2	Mapping of BCCH and CLCH for phase modulation.....	165
9.5.3	Mapping of SCH for $\pi/4$ -DQPSK physical channels .....	166
9.5.3a	Mapping of SCH for $\pi/8$ -D8PSK physical channels. ....	166
9.5.4	Mapping of TCH and STCH for phase modulation .....	166
9.5.5	Mapping of AACH for phase modulation.....	167
9.5.6	General mapping of logical channels for QAM.....	167
9.5.7	General mapping of logical channels into unallocated physical channels for QAM .....	167
9.5.8	Mapping of CLCH-Q for QAM.....	168
9.5.9	Mapping of SCH-Q for QAM.....	168
9.5.10	Mapping of SICH-Q and AACH-Q for QAM.....	168
9.6	Monitoring pattern for transmitting MSs.....	169
9.7	BS timesharing transmission .....	169
9.7.1	Carrier sharing for Phase Modulation .....	169
9.7.2	MCCH sharing for Phase Modulation .....	169
9.7.3	BS timesharing transmission for QAM.....	170
9.8	Modes of control .....	170
9.8.1	Normal Control Mode.....	170
9.8.2	Minimum Control Mode.....	170
10	Radio subsystem link control .....	172
10.1	Introduction .....	172
10.2	RF power control.....	172
10.3	Radio link measurements .....	172
10.3.1	Received signal strength .....	172
10.3.1.1	Signal strength measurement .....	172
10.3.1.2	Sample duration for signal strength measurement .....	172
10.3.2	Signal quality .....	172
10.3.3	Round-trip MS-BS path delay .....	172
10.4	Link adaptation.....	173
11	Call Control (CC) service description .....	174
11.1	Introduction .....	174
11.2	Services offered.....	174
11.3	CC service .....	175
11.3.1	CC primitives exchanged through the TNCC-SAP .....	175
11.3.2	Service primitives at the TNCC-SAP .....	175
11.3.3	Primitive description.....	176
11.3.3.1	TNCC-ALERT primitive .....	176
11.3.3.2	TNCC-COMPLETE primitive .....	177
11.3.3.3	TNCC-DTMF primitive .....	177
11.3.3.4	TNCC-MODIFY primitive .....	178
11.3.3.5	TNCC-NOTIFY primitive .....	178
11.3.3.6	TNCC-PROCEED primitive.....	179
11.3.3.7	TNCC-RELEASE primitive.....	179
11.3.3.8	TNCC-SETUP primitive .....	179
11.3.3.9	TNCC-TX primitive.....	181



11.3.4	Parameter description .....	181
11.4	States for CC SAP .....	189
12	Supplementary Service (SS) service description.....	190
12.1	Introduction .....	190
12.2	Services offered.....	190
12.3	SS service .....	190
12.3.1	Primitives exchanged through TNSS-SAP .....	190
12.3.2	Parameter description .....	191
13	Short Data Service (SDS) service description.....	191
13.1	Introduction .....	191
13.2	Services offered.....	191
13.3	SDS .....	191
13.3.1	SDS primitives exchanged through the TNSDS-SAP .....	191
13.3.2	Service primitives at the TNSDS-SAP .....	192
13.3.2.1	TNSDS-STATUS primitive .....	192
13.3.2.2	TNSDS-REPORT primitive.....	193
13.3.2.3	TNSDS-UNITDATA primitive.....	193
13.3.2.4	TNSDS-CANCEL primitive .....	194
13.3.3	Parameter description .....	194
13.3.4	State description.....	197
13.3.4.1	NULL state.....	197
13.3.4.2	SHORT DATA INITIATED state .....	197
13.3.5	Service state diagram for the TNSDS-SAP .....	197
14	CMCE protocol .....	198
14.1	Introduction .....	198
14.2	Overview of CMCE.....	198
14.2.1	Communication routes of the CMCE model.....	199
14.2.2	Protocol structure and protocol stack .....	199
14.2.3	Addressing rules .....	201
14.2.4	CC, SS and SDS sub-entities .....	201
14.2.4.1	CC sub-entity .....	201
14.2.4.2	SS sub-entity .....	202
14.2.4.3	SDS sub-entity .....	202
14.2.5	PC sub-entity .....	202
14.2.6	Internal routes .....	203
14.2.7	Intra-CMCE primitive summary .....	205
14.2.7.1	Down link CC PDU parameters .....	205
14.2.7.2	Uplink CC PDU parameters .....	205
14.2.7.3	Downlink SS PDU parameters .....	206
14.2.7.4	Uplink SS PDU parameters .....	206
14.2.7.5	Down link SDS PDU parameters .....	206
14.2.7.6	Uplink SDS PDU parameters .....	206
14.2.7.7	CMCE management primitives.....	206
14.2.7.7.0	ACTIVITY request.....	206
14.2.7.7.1	BREAK indication.....	206
14.2.7.7.1a	BUSY indication .....	206
14.2.7.7.2	CANCEL request.....	207
14.2.7.7.3	CLOSE indication .....	207
14.2.7.7.4	CONFIGURE indication .....	207
14.2.7.7.5	CONFIGURE request.....	207
14.2.7.7.6	IDENTITIES request.....	207
14.2.7.7.6a	IDLE indication .....	207
14.2.7.7.6b	INFO indication.....	208
14.2.7.7.7	OPEN indication.....	208
14.2.7.7.8	REOPEN indication.....	208
14.2.7.7.9	REPORT indication.....	208
14.2.7.7.10	RESUME indication .....	208
14.3	Overview of services required by the CMCE.....	209
14.4	CMCE protocol states .....	209
14.4.1	States for PC .....	209

14.4.1.1	CLOSED .....	209
14.4.1.2	OPEN .....	209
14.4.2	States for CC .....	210
14.4.2.1	IDLE .....	212
14.4.2.2	MO-CALL-SETUP .....	212
14.4.2.3	MT-CALL-SETUP .....	212
14.4.2.4	CALL ACTIVE.....	213
14.4.2.5	CALL DISCONNECT .....	213
14.4.2.6	WAIT .....	213
14.4.3	States for SS.....	213
14.4.4	States for SDS .....	214
14.5	Procedures .....	214
14.5.1	Individual CC procedures .....	215
14.5.1.1	Call set-up procedures.....	215
14.5.1.1.1	Incoming call .....	216
14.5.1.1.2	Outgoing call .....	218
14.5.1.1.3	Colliding calls.....	219
14.5.1.1.4	Unsuccessful call set-up .....	219
14.5.1.1.5	Call rejection .....	220
14.5.1.2	Call maintenance procedures .....	220
14.5.1.2.1	Transmission control procedures .....	221
14.5.1.2.2	Call status information procedures .....	225
14.5.1.2.3	Call modification procedures.....	226
14.5.1.2.4	Call restoration procedures .....	227
14.5.1.2.5	DTMF procedures .....	229
14.5.1.2.6	Calls to and from external subscribers.....	230
14.5.1.3	Call disconnection procedures .....	231
14.5.1.3.1	User initiated disconnection .....	231
14.5.1.3.2	Network initiated disconnection.....	232
14.5.1.3.3	Reception of disconnection request .....	232
14.5.1.3.4	Expiry of timers .....	232
14.5.1.3.5	Colliding disconnection.....	233
14.5.1.4	U-Plane switching .....	233
14.5.1.4.1	End of call set-up phase.....	234
14.5.1.4.2	During call maintenance phase.....	234
14.5.1.4.3	Call disconnection phase .....	235
14.5.2	Group CC procedures .....	235
14.5.2.1	Call set-up procedures.....	235
14.5.2.1.1	Incoming call .....	236
14.5.2.1.2	Outgoing call .....	237
14.5.2.1.3	Colliding calls.....	238
14.5.2.1.4	Unsuccessful call set-up .....	238
14.5.2.1.5	Call rejection .....	238
14.5.2.2	Call maintenance procedures .....	239
14.5.2.2.1	Transmission control procedures .....	239
14.5.2.2.2	Call status information procedures .....	243
14.5.2.2.3	Call modification procedures.....	244
14.5.2.2.4	Call restoration procedures .....	245
14.5.2.2.5	DTMF procedures .....	247
14.5.2.2.6	Temporary address handling procedures .....	247
14.5.2.2.7	Calls to and from external subscribers.....	248
14.5.2.3	Call disconnection procedures .....	248
14.5.2.3.1	User initiated disconnection .....	249
14.5.2.3.2	Network initiated disconnection.....	250
14.5.2.3.3	Reception of disconnection request .....	250
14.5.2.3.4	Colliding disconnection.....	250
14.5.2.3.5	Expiry of timers .....	250
14.5.2.4	U-Plane switching .....	251
14.5.2.4.1	End of call set-up phase.....	251
14.5.2.4.2	During call maintenance phase.....	252
14.5.2.4.3	Call disconnection phase .....	253
14.5.2.5	Void.....	253

14.5.2.6	Acknowledged group call procedures .....	253
14.5.2.7	Call ownership .....	253
14.5.3	Traffic channel assignment procedures.....	254
14.5.3.1	SwMI related procedures .....	254
14.5.3.2	MS related procedures.....	255
14.5.3.2.1	General procedures .....	255
14.5.3.2.2	Procedures for acceptance of individually-addressed channel allocation.....	256
14.5.3.2.3	Procedures for acceptance of group-addressed channel allocation.....	257
14.5.4	SS procedures .....	258
14.5.5	SDS procedures .....	258
14.5.5.1	Incoming short data message .....	258
14.5.5.2	Outgoing short data messages .....	258
14.5.6	PC procedures.....	259
14.5.6.1	Access to the communication resources.....	259
14.5.6.2	Access priority handling .....	259
14.5.6.2.1	Cancel.....	260
14.5.6.3	CMCE PDU exchange .....	260
14.5.6.3.1	Choice of layer 2 service .....	260
14.5.6.4	Control information exchange.....	260
14.5.6.5	PC protocol error conditions .....	261
14.5.6.5.1	PDU type error .....	261
14.5.6.5.2	Invalid call identifier .....	261
14.5.6.5.3	MS busy.....	261
14.5.6.6	Temporary Disablement.....	261
14.5.7	Subscriber class .....	262
14.5.8	Activity handling .....	262
14.6	Protocol timers .....	263
14.7	PDU descriptions.....	264
14.7.1	PDU description tables - downlink .....	265
14.7.1.1	D-ALERT.....	265
14.7.1.2	D-CALL PROCEEDING.....	265
14.7.1.3	D-CALL RESTORE .....	266
14.7.1.4	D-CONNECT.....	266
14.7.1.5	D-CONNECT ACKNOWLEDGE.....	267
14.7.1.6	D-DISCONNECT .....	267
14.7.1.7	D-FACILITY .....	267
14.7.1.8	D-INFO .....	268
14.7.1.9	D-RELEASE.....	268
14.7.1.10	D-SDS-DATA.....	269
14.7.1.11	D-STATUS .....	269
14.7.1.12	D-SETUP .....	270
14.7.1.13	D-TX CEASED.....	270
14.7.1.14	D-TX CONTINUE.....	271
14.7.1.15	D-TX GRANTED .....	271
14.7.1.16	D-TX INTERRUPT .....	272
14.7.1.17	D-TX WAIT.....	272
14.7.2	PDU description tables - uplink.....	273
14.7.2.1	U-ALERT.....	273
14.7.2.2	U-CALL RESTORE .....	273
14.7.2.3	U-CONNECT.....	274
14.7.2.4	U-DISCONNECT .....	274
14.7.2.5	U-FACILITY .....	274
14.7.2.6	U-INFO .....	275
14.7.2.7	U-STATUS .....	275
14.7.2.8	U-SDS-DATA.....	276
14.7.2.9	U-RELEASE.....	277
14.7.2.10	U-SETUP .....	277
14.7.2.11	U-TX CEASED.....	278
14.7.2.12	U-TX DEMAND.....	278
14.7.3	PDU description tables - downlink and uplink .....	278
14.7.3.1	General rules for function not supported.....	278
14.7.3.2	CMCE FUNCTION NOT SUPPORTED .....	278

14.8	Information elements coding .....	279
14.8.1	Area Selection .....	279
14.8.2	Basic service information .....	280
14.8.3	Call identifier .....	280
14.8.3a	Call identifier present .....	280
14.8.4	Call ownership .....	280
14.8.5	Called party type identifier .....	281
14.8.6	Called party SNA .....	281
14.8.7	Called party extension .....	281
14.8.8	Called party SSI .....	281
14.8.9	Calling party type identifier .....	282
14.8.10	Calling party extension .....	282
14.8.11	Calling party SSI .....	282
14.8.12	Call priority .....	282
14.8.13	Call status .....	283
14.8.14	Call queued .....	283
14.8.15	Continue .....	283
14.8.16	Call time-out .....	284
14.8.17	Call time-out, set-up phase .....	284
14.8.17a	Circuit mode type .....	285
14.8.17b	CLIR control .....	285
14.8.17c	Communication type .....	285
14.8.18	Disconnect cause .....	286
14.8.18a	DM-MS address .....	286
14.8.19	DTMF .....	286
14.8.19a	DTMF digit .....	287
14.8.19b	DTMF type .....	287
14.8.20	External subscriber number .....	288
14.8.21	Encryption control .....	288
14.8.21a	Encryption flag .....	288
14.8.22	Facility .....	289
14.8.23	Hook method selection .....	289
14.8.24	Length indicator .....	289
14.8.25	New call identifier .....	289
14.8.26	Modify .....	289
14.8.27	Notification indicator .....	290
14.8.27a	Other party type identifier .....	290
14.8.27b	Other party SNA .....	290
14.8.27c	Other party extension .....	290
14.8.27d	Other party SSI .....	290
14.8.28	PDU type .....	291
14.8.29	Poll request .....	291
14.8.30	Poll response .....	291
14.8.31	Poll response addresses .....	292
14.8.32	Poll response number .....	292
14.8.33	Poll response percentage .....	292
14.8.34	Pre-coded status .....	293
14.8.35	Proprietary .....	293
14.8.36	Request to transmit/send data .....	293
14.8.37	Reset call time-out timer (T310) .....	293
14.8.38	Short data type identifier .....	294
14.8.39	Simplex/duplex selection .....	294
14.8.39a	Slots per frame .....	294
14.8.40	Speech service .....	294
14.8.41	Temporary address .....	294
14.8.42	Transmission grant .....	295
14.8.43	Transmission request permission .....	295
14.8.44	Transmitting party type identifier .....	295
14.8.45	Transmitting party extension .....	295
14.8.46	Transmitting party SSI .....	296
14.8.47	TX demand priority .....	296
14.8.48	Type 3 element identifier .....	296

14.8.49	User defined data-1 .....	296
14.8.50	User defined data-2 .....	297
14.8.51	User defined data-3 .....	297
14.8.52	User defined data-4 .....	297
15	Mobility Management (MM) service description .....	298
15.1	Introduction .....	298
15.2	Services offered .....	298
15.3	Primitive description .....	299
15.3.1	Service state model for the MS .....	299
15.3.2	Service primitives at the TNMM-SAP, MS/LS side .....	299
15.3.3	Primitive description .....	300
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive .....	300
15.3.3.2	TNMM-DEREGISTRATION primitive .....	300
15.3.3.3	TNMM-DISABLING primitive .....	300
15.3.3.4	TNMM-ENABLING primitive .....	300
15.3.3.5	TNMM-ENERGY SAVING primitive .....	301
15.3.3.6	TNMM-REPORT primitive .....	301
15.3.3.7	TNMM-REGISTRATION primitive .....	301
15.3.3.8	TNMM-SERVICE primitive .....	302
15.3.3.9	TNMM-STATUS primitive .....	302
15.3.4	Parameters description .....	303
15.3.5	State description for the MS .....	307
15.3.5.1	Not updated .....	307
15.3.5.2	Wait updating .....	307
15.3.5.3	Updated .....	307
15.3.5.4	Temporary disabled .....	307
15.3.5.5	Permanently disabled .....	307
15.3.6	Service state diagram for the TNMM-SAP .....	308
16	MM protocol .....	312
16.1	Introduction .....	312
16.2	MM procedures .....	312
16.2.1	General .....	312
16.2.2	Services provided by the protocol .....	313
16.2.3	Underlying services assumed by the protocol .....	313
16.2.4	Services assumed from the local environment .....	313
16.3	Protocol functions .....	313
16.3.1	Activation and control of underlying MLE Service .....	315
16.3.1.1	Activation procedure .....	315
16.3.1.2	Deactivation procedure .....	316
16.3.1.3	Maintenance procedures .....	316
16.3.1.3.1	Report and cancel handling .....	316
16.3.1.3.2	Stealing permission and stealing repeats flag handling .....	316
16.3.1.3.3	Busy handling .....	317
16.3.1.3.4	Activity handling .....	317
16.4	Registration procedure .....	317
16.4.1	MLE initiated registration procedure .....	317
16.4.1.1	Normal registration .....	318
16.4.1.2	Forward registration .....	323
16.4.2	User application initiated registration procedure .....	325
16.4.3	Infrastructure initiated registration procedure .....	330
16.4.4	Colliding registrations .....	333
16.4.5	Expiry of timer T351 .....	333
16.4.6	Expiry of LA timers .....	333
16.4.7	Lifetime of ASSI/(V)ASSI .....	333
16.4.7.1	ASSI/(V)ASSI validity at migration .....	333
16.4.7.2	ASSI/(V)ASSI validity by MS initiative .....	333
16.4.7.3	ASSI/(V)ASSI validity at registration rejection .....	334
16.4.8	Temporary registration .....	334
16.4.9	Subscriber class procedures .....	334
16.4.10	Frequency band capability procedures .....	335