

9`Y_fca U[bYfbUnXfi y`^j cgh]b`nUXYj Yj `nj Yn]`n`fUX]`g_`ja `gdY_fca `fØFAŁ!
?cdYbg_Ua cV]bUgłcf]hYj `!`FUX]`g_UcdfYa Un`bcłfUb`^a `U]`ni bUb`^a `F:!
_cbY_łcf`Ya žbUa Yb`YbUdfYXj gYa `nUUbUc[b]`[c] cf`!`%`XY. `HM b] bY
_UfU_hYf]gh_Y]b`a Yf]bY`a YłcXY

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Land Mobile Service
- Radio equipment with an internal or external RF connector intended primarily for
analogue speech - Part 1: Technical characteristics and methods of measurement

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 086-1 V1.3.1:2008](https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b994/sist-en-300-086-1-v1-3-1-2008)

[https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-
ed4f4979b994/sist-en-300-086-1-v1-3-1-2008](https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b994/sist-en-300-086-1-v1-3-1-2008)

Ta slovenski standard je istoveten z: EN 300 086-1 Version 1.3.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.070.01	Mobilni servisi na splošno	Mobile services in general
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 300 086-1 V1.3.1:2008 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 086-1 V1.3.1:2008

<https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b994/sist-en-300-086-1-v1-3-1-2008>

ETSI EN 300 086-1 V1.3.1 (2008-09)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Land Mobile Service;
Radio equipment with an internal or external RF
connector intended primarily for analogue speech;
Part 1: Technical characteristics and
methods of measurement**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 086-1 V1.3.1:2008](https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b994/sist-en-300-086-1-v1-3-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b994/sist-en-300-086-1-v1-3-1-2008>



Reference

REN/ERM-TGDMR-258-1

Keywords

analogue, antenna, mobile, PMR, radio, speech

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 086-1 V1.3.1:2008

<https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54-ed4f4979b974/ETSI-EN-300-086-1-v1-3-1-2008>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations	10
4 General	10
4.1 Selection of equipment for testing purposes	10
4.1.1 Choice of model for testing	10
4.1.1.1 Auxiliary test equipment	11
4.1.1.2 Declarations by the provider	11
4.2 Mechanical and electrical design.....	11
4.2.1 General.....	11
4.2.2 Controls	11
4.2.3 Transmitter shut-off facility.....	11
4.3 Marking.....	11
5 Test conditions, power sources and ambient temperatures	11
5.1 Normal and extreme test conditions	11
5.2 Test power source.....	12
5.3 Normal test conditions.....	12
5.3.1 Normal temperature and humidity.....	12
5.3.2 Normal test power source.....	12
5.3.2.1 Mains voltage.....	12
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	12
5.3.2.3 Other power sources.....	12
5.4 Extreme test conditions	13
5.4.1 Extreme temperatures	13
5.4.2 Extreme test source voltages.....	13
5.4.2.1 Mains voltage.....	13
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	13
5.4.2.3 Power sources using other types of batteries.....	13
5.4.2.4 Other power sources.....	13
5.5 Procedure for tests at extreme temperatures.....	14
5.5.1 Procedure for equipment designed for continuous transmission.....	14
5.5.2 Procedure for equipment designed for intermittent transmission	14
5.5.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment).....	14
6 General test conditions	15
6.1 Arrangements for test signals applied to the receiver input.....	15
6.2 Receiver mute or squelch facility	15
6.3 Artificial antenna.....	15
6.4 Test sites and general arrangements for radiated measurements.....	15
6.5 Arrangement for test signals at the input of the transmitter	15
6.6 Receiver rated audio output power.....	15
6.7 Tests of equipment with a duplex filter	15
7 Technical characteristics of the transmitter.....	16
7.1 Frequency error	16
7.1.1 Definition.....	16

7.1.2	Method of measurement	16
7.1.3	Limits.....	16
7.2	Transmitter power (conducted)	17
7.2.1	Definitions	17
7.2.2	Method of measurement	17
7.2.3	Limits.....	17
7.3	Maximum effective radiated power.....	17
7.3.1	Definition.....	17
7.3.2	Methods of measurement.....	18
7.3.3	Limits.....	20
7.4	Frequency deviation	21
7.4.1	Definition.....	21
7.4.2	Method of measurement	21
7.4.2.1	Maximum permissible frequency deviation.....	21
7.4.2.2	Response of the transmitter to modulation frequencies above 3 kHz	21
7.4.3	Limits.....	21
7.4.3.1	Maximum permissible frequency deviation.....	21
7.4.3.2	Response of the transmitter to modulation frequencies above 3 kHz	22
7.5	Adjacent and alternate channel power.....	22
7.5.1	Definition.....	22
7.5.2	Method of measurement	23
7.5.3	Limits.....	24
7.6	Unwanted emissions in the spurious domain.....	24
7.6.1	Definition.....	24
7.6.2	Method of measuring the power level	25
7.6.3	Method of measuring the effective radiated power.....	26
7.6.4	Limits.....	28
7.7	Intermodulation attenuation.....	29
7.7.1	Definition.....	29
7.7.2	Method of measurement	30
7.7.3	Limits.....	31
7.8	Void.....	31
8	Technical characteristics of the receiver.....	31
8.1	Maximum usable sensitivity (conducted).....	31
8.1.1	Definition.....	31
8.1.2	Method of measurement	31
8.1.3	Limits.....	31
8.2	Maximum usable sensitivity (field strength)	32
8.2.1	Definition.....	32
8.2.2	Method of measurement	32
8.2.3	Limits.....	33
8.3	Co-channel rejection.....	33
8.3.1	Definition.....	33
8.3.2	Method of measurement	33
8.3.3	Limits.....	33
8.4	Adjacent channel selectivity.....	34
8.4.1	Definition.....	34
8.4.2	Method of measurement	34
8.4.3	Limits.....	34
8.5	Spurious response rejection.....	34
8.5.1	Definition.....	34
8.5.2	Introduction to the method of measurement	35
8.5.3	Method of measurement	35
8.5.3.1	Method of search over the "limited frequency range".....	35
8.5.3.2	Method of measurement - Step 2	36
8.5.4	Limits.....	36
8.6	Intermodulation response rejection	36
8.6.1	Definition.....	36
8.6.2	Method of measurement	36
8.6.3	Limits.....	37

SIST EN 300 086-1 V1.3.1:2008

<https://standards.iteh.ai/catalog/standards/sist/aeb00d2f-3498-4796-9e54->[en-300-086-1-v1-3-1-2008](https://standards.iteh.ai/catalog/standards/sist/en-300-086-1-v1-3-1-2008)iTech STANDARD PREVIEW
(standards.iteh.ai)

8.7	Blocking or desensitization	37
8.7.1	Definition	37
8.7.2	Method of measurement	37
8.7.3	Limits	37
8.8	Spurious radiations	38
8.8.1	Definition	38
8.8.2	Method of measuring the power level	38
8.8.3	Method of measuring the effective radiated power	39
8.8.4	Limits	40
9	Duplex operation	41
9.1	Receiver desensitization (with simultaneous transmission and reception)	41
9.1.1	Definition	41
9.1.2	Method of measurement when the equipment operates with a duplex filter	41
9.1.3	Measuring method when the equipment operates with two antennas	41
9.1.4	Limits	42
9.2	Receiver spurious response rejection (with simultaneous transmission and reception)	42
9.2.1	Definition	42
9.2.2	Method of measurement	42
9.2.3	Limits	43
10	Measurement uncertainty	43
Annex A (normative): Radiated measurement		45
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	45
A.1.1	Anechoic chamber	45
A.1.2	Anechoic chamber with a conductive ground plane	46
A.1.3	Open Area Test Site (OATS)	47
A.1.4	Test antenna	48
A.1.5	Substitution antenna	48
A.1.6	Measuring antenna	49
A.2	Guidance on the use of radiation test sites	49
A.2.1	Verification of the test site	49
A.2.2	Preparation of the EUT	49
A.2.3	Power supplies to the EUT	49
A.2.4	Volume control setting for analogue speech tests	49
A.2.5	Range length	50
A.2.6	Site preparation	50
A.3	Coupling of signals	51
A.3.1	General	51
A.3.2	Data signals	51
A.3.3	Speech and analogue signals	51
A.3.3.1	Acoustic coupler description	51
A.3.3.2	Calibration	52
Annex B (normative): Specification for some particular measurement arrangements		53
B.1	Power measuring receiver specification	53
B.1.1	IF filter	53
B.1.2	Attenuation indicator	54
B.1.3	RMS value indicator	54
B.1.4	Oscillator and amplifier	54
B.2	Spectrum analyser specification	55
B.2.1	Adjacent and alternate channel power measurement	55
B.2.2	Unwanted emissions measurement	55
B.3	Integrating and power summing device	55
Annex C (informative): Bibliography		56
History	57

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering the Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	23 September 2008
Date of latest announcement of this EN (doa):	31 December 2008
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2009
Date of withdrawal of any conflicting National Standard (dow):	30 June 2009

1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, primarily intended for analogue speech.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

The equipment comprises a transmitter and associated modulator and/or a receiver and associated demodulator. The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable);
- and those hand portable stations:
 - a) fitted with an antenna connector; or
 - b) without an external antenna connector, but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

NOTE: Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document (integral antenna equipment is covered by EN 300 296 [i.1]).

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [2] ITU-T Recommendation O.41: " Psophometer for use on telephone-type circuits".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI EN 300 296 (all parts): "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech".
- [i.2] ETSI EN 300 793 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.3] ETSI TR 102 273 (V1.2.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.4] ANSI C63.5 (2004): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [i.5] IEC 60489-3 (1988): "Methods of measurement for radio equipment used in the mobile services. Part 3: Receivers for A3E or F3E emissions".
- [i.6] CEPT/ERC/REC 74-01E: "Unwanted emissions in the spurious domain". (Hradec Kralove 2005).

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

50 Ω : 50 ohm non-reactive impedance

adjacent channel: channel offset from the wanted channel by the channel spacing, see figure 1

alternate channels: two channels offset from the wanted channel by double the channel spacing, see figure 1




Figure 1: Adjacent and alternate channel definitions

SIST EN 300 086-1 V1.3.1:2008

angle modulation: either phase modulation or frequency modulation

base station: equipment fitted with an antenna connector, for use with an external antenna, and intended for use in a fixed location

conducted measurements: measurements which are made using a direct 50 Ω connection to the equipment under test

hand portable station: equipment either fitted with an antenna connector or an integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

Listen Before Transmit mode (LBT): monitoring mode in which the RF channel is checked for activity before transmitting and equipment is designed to automatically prevent transmission for interference reduction purposes if a signal is detected on the channel

mobile station: mobile equipment fitted with an antenna connector, for use with an external antenna, normally used in a vehicle or as a transportable station

radiated measurements: measurements which involve the absolute measurement of a radiated field

SINAD metre: measurement instrument used to measure SND/ND

3.2 Symbols

For the purposes of the present document, the following symbols apply:

E_o reference field strength

NOTE: See annex A.

F_{cs} frequency equal to channel separation
 f_{I1} 1st intermediate frequency
 f_{I2} 2nd intermediate frequency
 f_{In} nth intermediate frequency
 f_l frequency of the limited frequency range
 f_{LO} Local oscillator frequency
 R_o reference distance

NOTE: See annex A.

T_{max} Maximum extreme test temperature
 T_{min} Minimum extreme test temperature
 V_{max} Maximum extreme test voltage
 V_{min} Minimum extreme test voltage
 Ω ohm

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CSP Channel SeParation
 CW Continuous Wave
 dB decibel
 dBm dB relative to 1 mW
 DC Direct Current
 emf electromotive force
 EUT Equipment Under Test
 IF Intermediate Frequency
 LBT Listen Before Transmit mode
 MPFD Maximum Permissible Frequency Deviation
 OATS Open Area Test Site
 PMR Private Mobile Radio
 RF Radio Frequency
 rms root mean squared
 SINAD received signal quality based on (Signal + Noise + Distortion)/(Noise + Distortion)
 SND/ND (Signal + Noise + Distortion)/(Noise + Distortion)
 sr switching range
 Tx Transmitter
 VSWR Voltage Standing Wave Ratio

4 General

4.1 Selection of equipment for testing purposes

Each equipment to be tested shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

The provider or manufacturer shall declare the frequency ranges, the range of operating conditions and power requirements as applicable, to establish the appropriate test conditions.

Additionally, technical documentation and operating manuals, sufficient to make the test, shall be supplied.

Guidance on the presentation of equipment is also given in EN 300 793 [i.2].

4.1.1 Choice of model for testing

The provider or manufacturer shall provide one or more samples of the equipment, as appropriate for testing.

Stand-alone equipment shall be complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters then the tests need only to be performed on the equipment configured with the combination of features considered to be the most complex.

Where practicable, equipment to be tested shall provide a 50 Ω connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have a internal permanent 50 Ω connector then it is permissible to supply a second sample of the equipment with a temporary antenna connector fitted to facilitate testing.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model.

4.1.1.1 Auxiliary test equipment

All necessary auxiliary test equipment, setting up instructions and other product information shall accompany the equipment to be tested.

4.1.1.2 Declarations by the provider

The provider or manufacturer shall declare the necessary information of the equipment with respect to all technical requirements set by the present document.

4.2 Mechanical and electrical design

4.2.1 General

The equipment shall be designed, constructed and manufactured in accordance with good engineering practice, and with the aim of minimizing harmful interference to other equipment and services.

4.2.2 Controls

Those controls, which if maladjusted, might increase the interfering potentialities of the equipment shall not be accessible for adjustment by the user.

4.2.3 Transmitter shut-off facility

When a timer for an automatic shut-off facility is operative, at the moment of the time-out the transmitter shall automatically be switched off (the re-activation of the transmitter shall reset the timer).

A shut-off facility shall be inoperative for the duration of the measurements unless it has to remain operative to protect the equipment. If the shut-off facility is left operative the status of the equipment shall be indicated.

4.3 Marking

The equipment shall be marked in a visible place. This marking shall be legible, tamperproof and durable.

The marking shall be in accordance with EC Directives and/or CEPT decisions or recommendations as appropriate.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Testing shall be performed under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in clauses 5.2 to 5.5.

5.2 Test power source

During testing the power source of the equipment shall be replaced by a test power source capable of producing normal and extreme test voltages as specified in clauses 5.3.2 and 5.4.2. The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of tests, the voltage of the power source shall be measured at the input terminals of the equipment.

For battery operated equipment the battery shall be removed and the test power source shall be applied as close to the battery terminals as practicable.

During tests of DC powered equipment the power source voltages shall be maintained within a tolerance of $< \pm 1$ % relative to the voltage at the beginning of each test. The value of this tolerance is critical for power measurements. Using a smaller tolerance will provide better measurement uncertainty values.

5.3 Normal test conditions

5.3.1 Normal temperature and humidity

The normal temperature and humidity conditions for tests shall be any convenient combination of temperature and humidity within the following ranges:

- temperature: +15 °C to +35 °C;
- relative humidity: 20 % to 75 %.

When it is impracticable to carry out the tests under these conditions, a note to this effect, stating the ambient temperature and relative humidity during the tests, shall be added to the test report.

5.3.2 Normal test power source

5.3.2.1 Mains voltage

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage or any of the declared voltages for which the equipment was designed.

The frequency of the test power source corresponding to the ac mains shall be between 49 Hz and 51 Hz.

5.3.2.2 Regulated lead-acid battery power sources used on vehicles

When the radio equipment is intended for operation from the usual types of regulated lead-acid battery power source used on vehicles the normal test voltage shall be 1,1 times the nominal voltage of the battery (for nominal voltages of 6 V and 12 V, these are 6,6 V and 13,2 V respectively).

5.3.2.3 Other power sources

For operation from other power sources or types of battery (primary or secondary), the normal test voltage shall be that declared by the equipment manufacturer.

5.4 Extreme test conditions

5.4.1 Extreme temperatures

For tests at extreme temperatures, measurements shall be made in accordance with the procedures specified in clause 5.5, at the upper and lower temperatures of one of the following two ranges:

- -20 °C to +55 °C;
All mobile and handportable equipment.
Base stations for outdoor/uncontrolled climate conditions.
- 0 °C to +40 °C;
Base stations for indoor/controlled climate conditions.

In the case of base station equipment, the manufacturer shall declare which conditions the equipment is intended to be installed in.

5.4.2 Extreme test source voltages

5.4.2.1 Mains voltage

The extreme test voltage for equipment to be connected to an ac mains source shall be the nominal mains voltage $\pm 10\%$.

5.4.2.2 Regulated lead-acid battery power sources used on vehicles

When the equipment is intended for operation from the usual types of regulated lead-acid battery power sources used on vehicles the extreme test voltages shall be 1,3 and 0,9 times the nominal voltage of the battery (for a nominal voltage of 6 V, these are 7,8 V and 5,4 V respectively and for a nominal voltage of 12 V, these are 15,6 V and 10,8 V respectively).