



Industrial automation systems — Manufacturing Message Specification —

Part 2: Protocol specification

TECHNICAL CORRIGENDUM 2

Systèmes d'automatisation industrielle — Spécification de messagerie industrielle —

Partie 2: Spécification de protocole

RECTIFICATIF TECHNIQUE 2

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Technical corrigendum 2 to International Standard ISO/IEC 9506-2:1990 was prepared by Technical Committee ISO/TC 184, *Industrial automation systems and integration*, Subcommittee SC 5, *Architecture and communications*.

NOTE — Proper application of this corrigendum requires that amendment 1, technical corrigendum 1, and amendment 2 have been applied (in that order) to the base document. Page numbers in this technical corrigendum refer to the base standard as published in 1990; subclause and paragraph references are to the base standard as modified by the prior two amendments and the prior corrigendum.

Page 18

Subclause 6.4

Add to the end of the first paragraph:

If the invalid PDU is determined to be an invalid RejectPDU, a RejectPDU shall not be sent.

Page 79

Subclause 15.6

Between

```
evaluationInterval[4] IMPLICIT Unsigned32 OPTIONAL  
and  
}
```

ICS 25.040.40

Ref. No. ISO/IEC 9506-2:1990/Cor.2:1995(E)

Descriptors: automation, automation engineering, manufacturing, messages, computer applications, data processing, information interchange, network interconnection, open systems interconnection, communication procedure, protocols.

© ISO/IEC 1995

Printed in Switzerland

Add the following lines:

```
-- At least one of enabled, priority, alarmSummaryReports, or
-- evaluationInterval shall be present.
```

Subclause 15.6.1

Delete:

At least one of enable, priority, of alarmSummaryReports, or evaluationInterval shall be present.

Page 86

Subclause 15.16

Change

```
current state [0] CHOICE {
    state          [0] IMPLICIT EE-State,
    undefined      [1] IMPLICIT NULL
}
```

to

```
current state [0] CHOICE {
    state          [0] IMPLICIT EE-State
}
```

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Page 91

Subclause 15.22.3

[ISO/IEC 9506-2:1990/Cor 2:1995](https://standards.iteh.ai/catalog/standards/sist/6d946b0e-9856-42a7-9174-4adb31df39/iso-iec-9506-2-1990-cor-2-1995)

Change <https://standards.iteh.ai/catalog/standards/sist/6d946b0e-9856-42a7-9174-4adb31df39/iso-iec-9506-2-1990-cor-2-1995>
(7) -- ACTIVE-ACKED

to

```
(7), -- ACTIVE-ACKED
undefined(8) -- UNDEFINED
```

Page 115

Subclause A.1

Change the first word of the first sentence to the following:

For those Companion Standards that define extensions to the MMS protocol, this