



**SLOVENSKI STANDARD**  
**SIST ES 202 391-1 V1.3.1:2008**  
**01-september-2008**

---

**Odpri dostop do storitve (OSA) - Spletne storitve Parlay X - 1. del: Splošno (Parlay X 2)**

Open Service Access (OSA) - Parlay X Web Services - Part 1: Common (Parlay X 2)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ES 202 391-1 V1.3.1:2008](#)

**Ta slovenski standard je istoveten z:** [ES 202 391-1 Version 1.3.1](https://standards.iteh.ai/catalog/standards/sist/2dec7c66-4d58-4fc2-95f4-ccc781a827ae/sist-es-202-391-1-v1-3-1-2008)

---

**ICS:**

35.100.01      Medsebojno povezovanje      Open systems  
                      odprtih sistemov na splošno      interconnection in general

**SIST ES 202 391-1 V1.3.1:2008**      **en**

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ES 202 391-1 V1.3.1:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008>

# ETSI ES 202 391-1 V1.3.1 (2008-05)

ETSI Standard

**Open Service Access (OSA);  
Parlay X Web Services;  
Part 1: Common  
(Parlay X 2)**



**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

SIST ES 202 391-1 V1.3.1:2008

<https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008>



---

Reference

RES/TISPAN-01056-01-OSA

---

Keywords

API, OSA, service

***ETSI***

650 Route des Lucioles  
 F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
 Association à but non lucratif enregistrée à la  
 Sous-Préfecture de Grasse 06 N° 7303/88

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ES 202 391-1 V1.3.1:2008](#)  
<https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a8270000000000000000000000>  
***Important notice***

---

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
 Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.  
 © The Parlay Group 2008.  
 All rights reserved.

**DECT™, PLUGTESTS™, UMTS™, TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

---

## Contents

Intellectual Property Rights .....	5
Foreword.....	5
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations .....	8
4 Use of Web Services technologies .....	9
4.1 Web Service message content .....	9
4.1.1 SOAP .....	9
4.1.2 XML .....	9
4.1.3 HTTP .....	9
4.2 Web Service interface definitions .....	9
4.2.1 WSDL.....	9
4.3 Security for Parlay X 2 Web Services .....	9
4.4 XML data types.....	9
5 Detailed service description .....	10
5.1 Address data items.....	10
5.2 Charging .....	10
5.2.1 Charging data type .....	10
5.3 Exception definition .....	11
5.4 Service exception .....	11
5.5 Policy exception .....	11
	<a href="https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008">https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008</a>
6 Namespaces .....	12
7 Sequence diagrams .....	12
8 XML Schema data type definition .....	12
8.1 TimeMetrics enumeration .....	12
8.2 TimeMetric structure .....	12
8.3 ChargingInformation structure .....	12
8.4 ServiceError structure.....	13
8.5 SimpleReference structure.....	13
9 Web Service interface definition .....	13
10 Fault definitions.....	13
10.1 ServiceException.....	13
10.1.1 SVC0001: Service error .....	13
10.1.2 SVC0002: Invalid input value .....	14
10.1.3 SVC0003: Invalid input value with list of valid values .....	14
10.1.4 SVC0004: No valid addresses .....	14
10.1.5 SVC0005: Duplicate correlator.....	14
10.1.6 SVC0006: Invalid group.....	14
10.1.7 SVC0007: Invalid charging information.....	14
10.1.8 SVC0008: Overlapping Criteria .....	14
10.2 PolicyException .....	15
10.2.1 POL0001: Policy error.....	15
10.2.2 POL0002: Privacy error.....	15
10.2.3 POL0003: Too many addresses .....	15
10.2.4 POL0004: Unlimited notifications not supported .....	15
10.2.5 POL0005: Too many notifications requested .....	15
10.2.6 POL0006: Groups not allowed .....	16

10.2.7	POL0007: Nested groups not allowed .....	16
10.2.8	POL0008: Charging not supported .....	16
10.2.9	POL0009: Invalid frequency requested .....	16
10.2.10	POL0010: Retention time interval expired .....	16
10.3	Fault number ranges by service .....	16
11	Service policies .....	17
12	WSDL usage and style .....	17
12.1	Service definition and documents .....	17
12.1.1	Interface sets .....	17
12.1.2	Preparing for document definition .....	17
12.1.3	Documents .....	18
12.1.3.1	Types definition document .....	18
12.1.3.2	Shared faults document .....	18
12.1.3.3	Service interface document .....	19
12.1.3.4	Service bindings document .....	19
12.1.4	Document separation rationale .....	19
12.1.5	Document version identifier .....	19
12.1.6	Document naming example .....	20
12.1.7	Service definitions for notification patterns .....	20
12.2	Namespaces .....	20
12.2.1	Namespaces for Parlay X 2 Web Services .....	21
12.2.2	Use of namespaces .....	21
12.2.3	Namespace elements .....	21
12.2.4	Namespace usage .....	21
12.2.4.1	Why namespace versions are used .....	21
12.2.4.2	When namespace versions are changed .....	22
12.2.4.3	Benefit of managing namespace versions .....	22
12.2.5	Common namespaces .....	22
12.2.6	Target namespace .....	22
12.2.7	WSDL and Schema namespaces .....	23
12.2.8	Local namespace use .....	23
12.2.9	Examples .....	23
12.3	Authoring style - Document content and names .....	24
12.3.1	General WSDL document information .....	24
12.3.2	Names .....	24
12.3.3	Case usage for names .....	24
12.3.4	Naming conventions for special names .....	25
12.3.5	Document layout .....	25
12.4	Data type definitions .....	25
12.4.1	Types section declaration .....	25
12.4.1.1	Optional elements .....	26
12.4.1.2	Nillable elements .....	26
12.4.1.3	User defined simple data types .....	26
12.4.1.4	Data structures .....	26
12.4.1.5	Enumerations .....	26
12.4.1.6	Unions .....	27
12.4.1.7	Web Service references .....	27
12.5	Messages and interfaces (PortTypes) .....	27
12.5.1	Messages .....	27
12.5.1.1	Document style Web Services .....	28
12.5.2	Interfaces (PortTypes) .....	28
12.5.3	Faults (Exceptions) .....	28
12.6	Bindings and service definitions .....	29
12.6.1	Binding .....	29
12.6.2	Service definition .....	29
<b>Annex A (normative):</b>	<b>WSDL for common data definitions .....</b>	<b>30</b>
History .....	31	

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This ETSI Standard (ES) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN).

The present document is part 1 of a multi-part deliverable covering Open Service Access (OSA); Parlay X Web Services, as identified below:

**Part 1: "Common";**

Part 2: "Third Party Call";

Part 3: "Call Notification";

Part 4: "Short Messaging";

**jTeh STANDARD PREVIEW  
(standards.iteh.ai)**

Part 5: "Multimedia Messaging"; [SIST ES 202 391-1 V1.3.1:2008](#)

Part 6: "Payment"; <https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008>

Part 7: "Account Management";

Part 8: "Terminal Status";

Part 9: "Terminal Location";

Part 10: "Call Handling";

Part 11: "Audio Call";

Part 12: "Multimedia Conference";

Part 13: "Address List Management";

Part 14: "Presence".

The present document has been defined jointly between ETSI, The Parlay Group (<http://www.parlay.org>) and the 3GPP.

**The present document forms part of the Parlay X 2.2 set of specifications.**

**The present document is equivalent to 3GPP TS 29.199-01 V6.6.0 (Release 6).**

The Mapping specification of the Parlay X 2 Web Services (ES 202 391) to the Parlay/OSA APIs (ES 203 915 [11]) and, where applicable, to IMS, is also structured as above. A mapping of the Parlay X 2 Web Services is however not applicable for all parts (e.g. part 13), but the numbering of parts is kept.

**Table 1: Overview of the Parlay X 2 Web Services and OSA APIs mappings**

<b>Parlay X 2 Web Services (ES 202 391 series)</b>		<b>OSA APIs (and IMS) mappings (TR 102 397 series)</b>	
ES 202 391-01	Common	TR 102 397-01	Common mapping
ES 202 391-02	Third party call	TR 102 397-02-1	Generic Call Control mapping
		TR 102 397-02-2	Multi-Party Call Control mapping
ES 202 391-03	Call notification	TR 102 397-03-1	Generic Call Control mapping
		TR 102 397-03-2	Multi-Party Call Control mapping
ES 202 391-04	Short messaging	TR 102 397-04-1	User Interaction mapping
		TR 102 397-04-2	Multi-Media Messaging mapping
ES 202 391-05	Multimedia messaging	TR 102 397-05-1	User Interaction mapping
		TR 102 397-05-2	Multi-Media Messaging mapping
ES 202 391-06	Payment	TR 102 397-06	Charging mapping
ES 202 391-07	Account management	TR 102 397-07	Account Management mapping
ES 202 391-08	Terminal status	TR 102 397-08	Mobility User Status mapping
ES 202 391-09	Terminal location	TR 102 397-09-1	Mobility User Location mapping
		TR 102 397-09-2	Mobility User Location CAMEL mapping
ES 202 391-10	Call handling	TR 102 397-10-1	Generic Call Control & User Interaction mapping
		TR 102 397-10-2	Multi-Party Call Control & User Interaction mapping
		TR 102 397-10-3	Policy Management mapping
ES 202 391-11	Audio call	TR 102 397-11-1	Generic Call Control & User Interaction mapping
		TR 102 397-11-2	Multi-Party Call Control & User Interaction mapping
ES 202 391-12	Multimedia conference	TR 102 397-12	Multi-Media Call Control mapping
ES 202 391-13	<i>Address list management</i>	TR 102 397-13	<i>Not Applicable</i>
ES 202 391-14	Presence	TR 102 397-14-1	Presence & Availability Management mapping
		TR 102 397-14-2	SIP/IMS Networks mapping

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ES 202 391-1 V1.3.1:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ae/sist-es-202-391-1-v1-3-1-2008>

# 1 Scope

The present document is part 1 of the Stage 3 Parlay X 2 Web Services specification for Open Service Access (OSA).

The OSA specifications define an architecture that enables application developers to make use of network functionality through an open standardized interface, i.e. the OSA APIs.

The present document specifies the Common aspects of the Parlay X 2 Web Services. The following are defined here:

- Name spaces.
- Data definitions.
- Fault definitions.
- WSDL Description of the interfaces.

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 

**iTel STANDARD PREVIEW**  
**(standards.iteh.ai)**

  - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document: [SIST ES 202 391-1 V1.3.1:2008](#)
  - for informative references: <https://references.iteh.ai/catalog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ac/sist-es-202-391-1-v1-3-1-2008>

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI TR 121 905: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Vocabulary for 3GPP Specifications (3GPP TR 21.905 version 7.2.0 Release 7)".
- [2] W3C Recommendation (2 May 2001): "XML Schema Part 2: Datatypes".

NOTE: Available at: <http://www.w3.org/TR/2001/REC-xmleschema-2-20010502/>.

- [3] IETF RFC 3966: "The tel URI for Telephone Numbers".  
 NOTE: Available at: <http://www.ietf.org/rfc/rfc3966.txt>.
- [4] IETF RFC 3261: "SIP: Session Initiation Protocol".  
 NOTE: Available at: <http://www.ietf.org/rfc/rfc3261.txt>.
- [5] WS-I Basic Profile Version 1.0: "Final Material".  
 NOTE: Available at: <http://www.ws-i.org/Profiles/BasicProfile-1.0-2004-04-16.html>.
- [6] W3C Note (15 March 2001): "Web Services Description Language (WSDL) 1.1".  
 NOTE: Available at: <http://www.w3.org/TR/2001/NOTE-wsdl-20010315>.
- [7] OASIS Standard 200401 (March 2004): "Web Services Security: SOAP Message Security 1.0 (WS-Security 2004)".  
 NOTE: Available at: <http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0.pdf>.
- [8] W3C Recommendation (12 February 2002): "XML-Signature Syntax and Processing".  
 NOTE: Available at: <http://www.w3.org/TR/2002/REC-xmldsig-core-20020212/>.
- [9] ISO 4217: "Codes for the representation of currencies and funds".
- [10] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".  
 NOTE: Available at: <http://www.ietf.org/rfc/rfc3986.txt>
- [11] ETSI ES 203 915 (series): "Open Service Access (OSA); Application Programming Interface (API)".

SIST ES 202 391-1 V1.3.1:2008

<https://standards.iteh.ai/batchlog/standards/sist/2dec7e66-4d58-4fc2-95f4-eee781a827ac/sist-es-202-391-1-v1-3-1-2008>

### 3 Definitions and abbreviations

For the purposes of the present document, the following terms and definitions apply:

**application:** computer program that accesses a Web Service

**SOAP:** not an acronym, protocol used for XML messaging

**Web Service:** software system designed to support interoperable machine-to-machine interaction over a network

**Web Service Provider:** entity which provides Web Services interfaces to capabilities offered

**Web Service Requester:** entity which operates Applications that access Web Services

### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 121 905 [1] and the following apply:

3GPP	Third Generation Partnership Project
ETSI	European Telecommunications Standards Institute
IT	Information Technology
OASIS	Organization for the Advancement of Structured Information Standards
OSA	Open Service Access
RFC	Request For Comment
SIP	Session Initiation Protocol
UDDI	Universal Description Discovery and Integration

URI	Uniform Resource Identifier
W3C	World Wide Web Consortium
WSDL	Web Service Definition Language
WS-I	Web Services-Interoperability Organization
XML	Extensible Markup Language

## 4 Use of Web Services technologies

### 4.1 Web Service message content

#### 4.1.1 SOAP

All Web Service messages SHALL send and accept messages that conform to the SOAP use defined in the WS-I Basic Profile [5], using the document/literal encoding style.

#### 4.1.2 XML

All Web Service messages SHALL send and accept messages that conform to the XML use defined in the WS-I Basic Profile [5].

#### 4.1.3 HTTP

All Web Service messages SHALL send and accept messages that conform to the HTTP use defined in the WS-I Basic Profile [5].

### 4.2 Web Service interface definitions

All Parlay X 2 Web Services are defined according to the following:

#### 4.2.1 WSDL

All Web Service interfaces SHALL be defined using WSDL 1.1 as defined in the WSDL specification [6] and be conformant to the WSDL use defined in WS-I Basic Profile [5].

See clause 12 for detailed information on the WSDL style to be followed by Parlay X 2 Web Services.

### 4.3 Security for Parlay X 2 Web Services

If a message contains an identifier and/or credentials representing the sender of the message then these SHALL be provided in a manner prescribed by WS-Security [7].

Encryption of message content MAY be required by the Web Service Provider. If this is required, then this SHALL be accomplished in one of the following manners:

- Use of a Virtual Private Network, to be administered independent of the Web Service implementation.
- Use of Transport Level Security using HTTP over TLS as specified in the WS-I Basic Profile [5].

Integrity of the message content MAY be required by the Web Service Provider. If this is required, then this SHALL be accomplished using XML Digital Signature [8].

### 4.4 XML data types

Where possible standard XML Schema data types are used, as defined in clause 3 (Built-in datatypes) in XML Schema [2].

## 5 Detailed service description

### 5.1 Address data items

Addresses, unless the specification provides specific additional instruction, MUST conform to the address portion of the URI definition provided in RFC 3966 [3] for 'tel:' addresses, RFC 3261 [4] for 'sip:' addresses or the definition given below for shortcodes or aliased addresses. Optional additions to the address portion of these URI definitions MUST NOT be considered part of the address accepted by the Parlay X 2 Web Services interfaces, and an implementation MAY choose to reject an address as invalid if it contains any content other than the address portion.

When processing a 'tel:' URI, as specified in RFC 3966 [3], Parlay X 2 Web Services MUST accept national addresses (those not starting with '+' and a country code) and MUST accept international addresses (those starting with '+' and a country code). When specified in the definition of a service operation, the URI may contain wildcard characters in accordance with the appropriate specification (i.e. RFC 3966 [3] or RFC 3261 [4]).

Shortcodes are short telephone numbers, usually 4 to 6 digits in length reserved for telecom service providers' own functionality. They shall be differentiated from national addresses by the use of a 'short:' rather than 'tel:' URI scheme. The short code defined in the URI consists of a string of digits with no non-digit characters.

Support for aliases in addresses is provided by use of the URI defined in RFC 3986 [10]. This allows for arbitrary data to be submitted to the Parlay X Web Service interface. The following is an example of how this could be applied:

<uri scheme>:<generic syntax>

An alias is generally a relatively short character string that holds a scrambled address such that only the application identified in the URI can expand it.

### 5.2 Charging

**ITEH STANDARD PREVIEW**

(standards.iteh.ai)

Web Services may use a Web Service Provider to deliver content or function. In some cases, the producer of the content or capability will wish to use a bill-on-behalf-of capability offered by the Web Service Provider to charge for the content/function provided. For those services where the charge is part of a single activity, providing the charging related information as part of the message is very efficient.

An example is a messaging service, where a sports business collects information and distributes short messages with sports scores to its subscribers. The sports business has an agreement with a Web Service Provider where the charges for the messages are included in the bill provided by the Web Service Provider (thus the Web Service Provider is billing on behalf of the sports business).

To enable this capability to be provided across a variety of services in a consistent manner, thus making implementation easy and efficient, the information to be provided in the Web Service message for charging information is defined as a common charging data type.

#### 5.2.1 Charging data type

The charging information is provided in an XML data type, using the following schema:

```

<xsd:complexType name="ChargingInformation">
  <xsd:sequence>
    <xsd:element name="description" type="xsd:string"/>
    <xsd:element name="currency" type="xsd:string" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="amount" type="xsd:decimal" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="code" type="xsd:string" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>

```