



SLOVENSKI STANDARD

SIST EN 302 066-1 V1.2.1:2008

01-september-2008

9`Y_Ifca U[bYfbUnXfi y`^j cgh]b`nUXYj Y`j `nj Yn]`n`fUX]`g_`ja `gdY_Ifca `fØFAŁ!
I dcfUVUg]ghYa cj `nUg`_`Ub`Y`df]`fUXUf`^` `nUgcbX]`fUb`Y`U` `]b`n]Xcj `f! DF#K DFŁ!`%
XY.`HM b] bY`_UfU`hf]gh`_Y`]b`dfYg_i gbY`a YtcXY

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Ground- and Wall-
Probing Radar applications (GPR/WPR) imaging systems - Part 1: Technical
characteristics and test methods

ITh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 066-1 V1.2.1:2008](https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008>

Ta slovenski standard je istoveten z: EN 302 066-1 Version 1.2.1

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 302 066-1 V1.2.1:2008 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 066-1 V1.2.1:2008

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008>

ETSI EN 302 066-1 V1.2.1 (2008-02)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Ground- and Wall- Probing Radar applications (GPR/WPR)
imaging systems;
Part 1: Technical characteristics and
test methods**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 066-1 V1.2.1:2008](https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008)

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008>



Reference

REN/ERM-TG31A-0113-1

Keywords

radar, radio, SRD, testing, UWB**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 066-1 V1.2.1:2008

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c040/sist-en-302-066-1-v1-2-1-2008>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Technical requirements specifications	8
4.1 Presentation of equipment for testing purposes.....	8
4.1.1 Choice of model for testing	9
4.2 Mechanical and electrical design.....	9
4.3 Auxiliary test equipment	9
4.4 General requirements for RF cables	9
5 Test conditions, power sources and ambient temperatures	9
5.1 Normal and extreme test conditions	9
5.2 External test power source.....	9
5.3 Normal test conditions.....	10
5.3.1 Normal temperature and humidity.....	10
5.3.2 Normal test power source	10
5.3.2.1 Regulated lead-acid battery power source.....	10
5.3.2.2 Other power sources.....	10
5.4 Extreme test conditions	10
5.4.1 Extreme temperatures	10
5.4.1.1 Procedure for tests at extreme temperatures.....	10
5.4.1.2 Extreme temperature ranges.....	11
5.4.2 Extreme test source voltages.....	11
5.4.2.1 Regulated lead-acid battery power source.....	11
5.4.2.2 Other power sources.....	11
5.5 Combined equipment	11
6 General conditions.....	11
6.1 Radiated measurement arrangements	11
6.2 Measuring receiver	11
7 Measurement uncertainty	12
8 Methods of measurement and limits.....	12
8.1 Frequency band of operation	12
8.1.1 Definition.....	12
8.1.2 Method of measurement	13
8.1.3 Limits.....	13
8.2 Undesired Emissions	13
8.2.1 Definition.....	13
8.2.2 Method of measurement	13
8.2.3 Limits.....	15
Annex A (normative): Radiated measurements	16
A.1 Test sites and general arrangements for measurements involving the use of radiated fields	16
A.1.1 Test antenna.....	16
A.1.2 Measuring antenna	17

A.2	Guidance on the use of radiation test sites	17
A.2.1	Verification of the test site	17
A.2.2	Preparation of the EUT.....	17
A.2.3	Power supplies to the EUT	17
A.2.4	Range length.....	17
A.2.5	Site preparation	18
A.2.6	Conversion of field strength to power limits	18
Annex B (normative):	Deactivation mechanism.....	19
Annex C (informative):	Measurement antenna and preamplifier specifications	20
Annex D (normative):	Calculation of the Mean Power Density.....	21
Annex E (informative):	Bibliography.....	24
History		25

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 302 066-1 V1.2.1:2008

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering the Electromagnetic compatibility and Radio spectrum Matters (ERM); Ground- and Wall- Probing Radar applications, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

iTeh STANDARD PREVIEW

(standards.itih.ai)

Date of adoption of this EN:	22 February 2008
Date of latest announcement of this EN (doa):	31 May 2008
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2008
Date of withdrawal of any conflicting National Standard (dow):	30 November 2008

1 Scope

The present document specifies the requirements for Ground- and Wall- Probing Radar imaging systems applications. Ground Probing Radars (GPR) and Wall Probing Radars (WPR) are used in survey and detection applications.

The scope is limited to GPR and WPR radars, in which the system is in close proximity to the materials being investigated. It does not include radars operated from aircraft or spacecraft.

The GPR/WPR applications in the present document are not intended for communications purposes, and the intended signal is not radiated into free space.

NOTE: Equipment covered by the present document is intended to be used by competent professional personnel.

The present document applies to:

- 1) Ground Probing Radars (GPR) operating over approximately one decade in the frequency range 30 MHz to 12,4 GHz radiating directly downwards into the ground. Any horizontal radiation from this equipment is caused by leakage and is considered as undesired emission.
- 2) Wall Probing Radars (WPR) operating in the frequency range 30 MHz to 12,4 GHz radiating directly into a "wall". The "wall" is a building material structure, the side of a bridge, the wall of a mine or another physical structure that absorbs a significant part of the signal transmitted by the radar.
- 3) Equipment fitted with integral antennas and without antenna connector.
- 4) Equipment which uses different imaging heads (antennas) with an antenna connector, to allow operation at different frequencies.

The present document does not necessarily include all the characteristics which may be required by a user, nor does it necessarily represent the optimum performance achievable.

SIST EN 302 066-1 V1.2.1:2008

<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-51bddde9c00c/sist-en-302-066-1-v1-2-1-2008>

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] CISPR 16-1: "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1: Radio disturbance and immunity measuring apparatus".
- [2] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] ETSI EN 302 066-2 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Ground- and Wall- Probing Radar applications (GPR/WPR) imaging systems; Part 2: Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

2.2 Informative references

- [4] ETSI TR 102 070-2 (V1.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Guide to the application of harmonized standards to multi-radio and combined radio and non-radio equipment; Part 2: Effective use of the radio frequency spectrum".
- [5] CENELEC EN 55022: "Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement".
- [6] ANSI C63.5-2004: "American National Standard for Electromagnetic Compatibility-Radiated Emission Measurements in Electromagnetic Interference (EMI) Control-Calibration of Antennas (9 kHz to 40 GHz)".
- [7] ETSI TR 102 273-2 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
<https://standards.iteh.ai/catalog/standards/sist/eb6f9352-6cac-4494-9c2c-3180dc90c/sist-en-302-066-1-v1-2-1-2008>
- [8] ETSI TR 102 273-4 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

Pulse Repetition Frequency (PRF): inverse of the Pulse Repetition Interval (PRI), averaged over a sufficiently long time to cover all PRI variations

radiated measurements: measurements which involve the absolute measurement of a radiated field

3.2 Symbols

For the purposes of the present document, the following symbols apply:

E	Electrical field strength
f	Frequency
f_c	Frequency at which the emission is the peak power at maximum
f_H	Highest frequency of the frequency band of operation
f_L	Lowest frequency of the frequency band of operation
P	Power
R	Distance
t	Time
λ	wavelength

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

dB	decibel
dBi	gain in decibels relative to an isotropic antenna
DT	DwellTime
e.i.r.p.	equivalent isotropically radiated power
e.r.p.	effective radiated power
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
GPR	Ground Probing Radar, Ground Penetrating Radar
IF	Input Frequency
LNA	Low Noise Amplifier
OATS	Open Area Test Site
PRF	Pulse Repetition Frequency
PRI	Pulse Repetition Interval
PSD	Power Spectral Density
R&TTE	Radio and Telecommunications Terminal Equipment
RBW	Resolution BandWidth
RF	Radio Frequency
RMS	Root Mean Square
RNSS	Radio Navigation Satellite Service
SA	Spectrum Analyser
ST	ScanTime
UWB	Ultra WideBand
VBW	Video BandWidth
VSWR	Voltage Standing Wave Ratio
WPR	Wall Probing Radar

4 Technical requirements specifications

4.1 Presentation of equipment for testing purposes

Each equipment to be tested, where applicable, shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

The provider shall provide one or more samples of the equipment, as appropriate for testing.

Additionally, technical documentation and operating manuals, sufficient to allow testing to be performed, shall be supplied.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model. In order to avoid any ambiguity in that assessment, the present document contains instructions for the presentation of equipment for testing purposes (clause 5), conditions of testing (clause 6) and the measurement methods (clause 8).

Equipment shall be offered by the provider complete with any ancillary equipment needed for testing. The provider shall declare the frequency range(s), the range of operation conditions and power requirements, as applicable, in order to establish the appropriate test conditions.

4.1.1 Choice of model for testing

If an equipment has several optional features, considered not to affect the RF parameters then the tests need only to be performed on the equipment configured with that combination of features considered to be the most complex, as proposed by the provider and agreed by the test laboratory.

In addition, when a device has the capability of using different imaging heads, each one shall be tested independently.

4.2 Mechanical and electrical design

The equipment submitted by the provider shall be designed, constructed and manufactured in accordance with good engineering practice and with the aim of minimizing harmful interference to other equipment and services.

Transmitters and receivers may be individual or combination units.

4.3 Auxiliary test equipment

All necessary test signal sources and set-up information shall accompany the equipment when it is submitted for testing.

4.4 General requirements for RF cables

Due to the low power levels involved in the measurements, all RF cables including their connectors at both ends used within the measurement arrangements and set-ups shall be of coaxial type featuring within the frequency range they are used:

- a nominal characteristic impedance of 50 Ω ;
- a VSWR of less than 1,2 at either end;
- a shielding loss in excess of 60 dB.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Testing shall be made under normal test conditions, and also, where stated, under extreme test conditions.

The test conditions and procedures shall be as specified in clauses 5.2 to 5.4.

5.2 External test power source

During tests the power source of the equipment shall be an external test power source, capable of producing normal and extreme test voltages. The internal impedance of the external test power source shall be low enough for its effect on the test results to be negligible.