

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Technical characteristics and methods of measurement
for equipment for generation, transmission
and reception of Digital Selective Calling (DSC)
in the maritime MF, MF/HF and/or VHF mobile service;
Part 2: Class A/B DSC**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/362e9139-69b6-4b2a-9585-4bf1156940f9/etsi-en-300-338-2-v1.3.1-2010-02>



Reference

REN/ERM-TG26-066-2

Keywords

maritime, radio, GMDSS, DSC

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	6
Foreword.....	6
1 Scope	7
2 References	7
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations	10
4 Controls and Indicators in Class A/B DSC Equipment.....	11
4.1 Visual indication	11
5 Technical requirements	11
5.1 Facilities for DSC transmission and reception	11
5.1.1 Multi-frequency distress alert attempts and watch receiver capabilities (MF/HF)	11
5.1.2 Watch receiver capabilities (VHF)	11
5.2 Remote alarms.....	11
5.3 Galvanic isolation.....	11
5.4 Manuals	11
6 Automated and Non-Automated Procedure Requirements in Class A/B DSC Equipment.....	12
6.1 Introduction	12
6.2 Non-automated features	12
6.2.1 DSC Message Composition	12
6.2.2 Transmission of DSC messages and prioritized wait	13
6.2.3 Alarms	14
6.3 Standby.....	14
6.4 Sending distress automated procedure	15
6.4.1 Procedure.....	15
6.4.2 Tasks.....	17
6.4.3 Display.....	17
6.4.3.1 Examples of sending distress procedure displays on VHF equipment.....	18
6.4.4 Dedicated distress button sub procedure.....	19
6.4.5 Transmission of the alert attempt.....	19
6.4.6 Updating position.....	20
6.4.7 Handling received DSC Messages.....	20
6.4.8 Alarms	20
6.4.9 Determining Subsequent communications.....	20
6.4.10 Automated tuning	20
6.4.11 Cancelling the Distress Alert	21
6.4.11.1 Examples of cancel-distress displays on VHF equipment.....	22
6.4.12 Acknowledgments	22
6.4.13 Termination.....	22
6.4.14 Warnings.....	22
6.5 Receiving distress automated procedure	23
6.5.1 Procedure.....	23
6.5.2 Tasks.....	25
6.5.3 Display.....	25
6.5.3.1 Examples of received distress procedure displays on VHF equipment.....	26
6.5.4 Handling received DSC Messages.....	27
6.5.5 Alarms	27
6.5.6 Determining Subsequent communications.....	27
6.5.7 Automated tuning	27
6.5.8 Acknowledgments	27
6.5.9 Sending Relays and Acknowledgments.....	28

6.5.10	Termination.....	28
6.5.11	Warnings.....	28
6.6	Sending non distress automated procedure	28
6.6.1	Procedure	28
6.6.2	Tasks	29
6.6.3	Display	30
6.6.3.1	Examples of sending non distress procedures displays on VHF equipment	31
6.6.4	Handling received DSC Messages	31
6.6.5	Alarms	31
6.6.6	Automated tuning	31
6.6.7	Delayed Acknowledgements	32
6.6.8	Termination.....	32
6.6.9	Warnings.....	32
6.7	Receiving non distress automated procedure	32
6.7.1	Procedure	32
6.7.2	Tasks	33
6.7.3	Display	34
6.7.3.1	Examples of receiving non distress procedures displays on VHF equipment	35
6.7.4	Handling received DSC messages	35
6.7.5	Alarms	35
6.7.6	Automated tuning	36
6.7.7	Acknowledgments	36
6.7.8	Termination.....	36
6.7.9	Warnings.....	37
6.8	Communications automated procedure	37
6.8.1	Procedure	37
6.8.2	Tasks	37
6.8.3	Display	37
6.8.4	Handling received DSC Messages	37
6.8.5	Tuning of the general receiver and transmitter	38
6.8.6	Termination.....	38
6.9	Multiple automated procedures and parallel event handling	38
6.9.1	Procedure	38
6.9.2	Tasks	38
6.9.3	Examples of multiple procedure screens	39
Annex A (normative): DSC Message Composition		41
A.1	Default values.....	41
A.2	The default DROBOSE.....	42
A.3	Allowable non distress DSC message parameters.....	42
Annex B (normative): Radius-Centre point conversion and rounding algorithm		43
B.1	Radius-centre point conversion	43
B.2	Rounding	44
B.3	Special cases for either form of area data entry	44
Annex C (normative): Automated Non Distress Channel/Frequency Selection Algorithm		45
C.1	VHF.....	45
C.2	HF.....	45
Annex D (normative): Alarms.....		46
D.1	Alarm specifications.....	46
D.2	Alarming with critical errors	47
D.3	Default alarm sounds.....	48
D.4	Other alarm sounds.....	48

Annex E (informative):	Bibliography.....	49
History		50

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/362e9139-69b6-4b2a-9585-4bf115694099/etsi-en-300-338-2-v1.3.1-2010-02>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.2].

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document states the minimum requirements for equipment to be used for generation, transmission and reception of Class A or B Digital Selective Calling (DSC) for use on board ships.

DSC may be used in the Medium Frequency (MF), High Frequency (HF) and Very High Frequency (VHF) Maritime Mobile Service (MMS), for both distress, safety and general communications.

The present document is part 2 of a multi-part standard that covers the requirements to be fulfilled by equipment that is either integrated with a transmitter and/or a receiver or equipment that is a stand-alone DSC terminal and has the following class of DSC:

- Class A - includes all the facilities defined in annex 1 of ITU-R Recommendation M.493-12 [3] and complies with the IMO Global Maritime Distress and Safety System (GMDSS) carriage requirements for MF/HF installations and/or VHF installations;
- Class B - provides minimum facilities for equipment on ships not required to use class A equipment and complies with the minimum IMO GMDSS carriage requirements for MF and/or VHF installations. This equipment should provide for:
 - alerting, acknowledgement and relay facilities for distress purposes;
 - calling and acknowledgement for general communication purposes; and
 - calling in connection with semi-automatic/automatic services, as defined in ITU-R Recommendation M.493-12 [3], annex 2, clause 3.

These requirements include the relevant provisions of the ITU Radio Regulations [2] and ITU-R Recommendations, the International Convention for the Safety Of Life At Sea (SOLAS) [1], and the relevant resolutions of the International Maritime Organization (IMO).

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] International Convention for the Safety of Life at Sea (1974) as amended.
- [2] ITU Radio Regulations (2008).
- [3] ITU-R Recommendation M.493-12: "Digital selective-calling system for use in the maritime mobile service".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] IMO Regulation IV/14, regulation X/3, IV/6.6, IMO resolution MSC.97 (73) 14.6.4.
- [i.2] ETSI EN 300 338-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 1: Common requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

acknowledged: automated procedure it indicates that the objective of the initial DSC message has been achieved

active: automated procedure which has control of the general receiver and transmitter and is thus able to engage in subsequent communications and receive DSC messages on both the watch receiver and general receiver

automated procedure: set of actions necessary to complete the objective of an initiating DSC message or non DSC communication event

NOTE 1: Four DSC automated procedures are designed to process these. They are the receiving of distress DSC messages, the receiving of non distress DSC messages, the sending of distress DSC alert attempts and the sending of non distress DSC messages. In addition a fifth procedure is designed to handle non DSC communication events.

NOTE 2: These automated procedures are called:

- Received distress automated procedure.
- Sending distress automated procedure.
- Received non-distress automated procedure.
- Sending non-distress automated procedure.
- Communications automated procedure.

critical errors: set of information characters obtained from one or more received DSC messages is considered to have critical errors if the automated procedure needs information characters from that set in order to proceed or perform any task, but the required information characters are in error

EXAMPLE: An acknowledgement cannot be composed to an individual DSC message that has errors in the senders MMSI).

default: value selected or an action taken by the equipment software in the absence of any operator input

distress alert: name given to the single distress DSC message with the format symbol 112

distress alert attempt: set of distress alerts sent by a vessel when in distress

NOTE: A distress alert DSC message by itself is never intentionally sent by a vessel in distress. For example, the single frequency distress alert attempt consists of five consecutive distress alerts with no break in between each distress alert.

distress DSC message: DSC message or acknowledgement containing the distress information

distress event: unique distress situation identified by two (VHF) or three (MF/HF) parameters of the distress information; the MMSI of the vessel in distress and the nature of distress and on MF/HF the mode of subsequent communication

distress information: symbols within a DSC message describing a distress situation consisting of the MMSI of the vessel in distress, the nature of distress, the position of the vessel in distress, the UTC time of that position, and the mode of subsequent communication

engaged: used to indicate that the equipment is busy handling an automated procedure

factory default: default value that is set by the manufacturer such that the field or behaviour is defined prior to any operator intervention

general receiver: receiver part of the transceiver used for the reception of all subsequent communications and on HF the reception of DSC acknowledgements on the duplex DSC channels

NOTE: It is important to distinguish this unit from the watch receiver.

Information characters: set of symbols in a DSC message that contains the items of interest for the recipient and is used to compute the ECC symbol that terminates the message

NOTE: These symbols are repeated in the DX/RX time diversity pattern.

initial DSC message: DSC message that starts an automated procedure

non distress DSC message: DSC messages or acknowledgments that do not have the format specifier or category of "distress"

objective: when in reference to a DSC message or automated procedure, the goal or intent of the item

NOTE: Usually this goal or intent is to establish subsequent communications or request information.

on hold: automated procedure which does not have access to the transmitter and general receiver and therefore cannot engage in subsequent communications and is only able to receive DSC messages on the watch receiver

operator options: any choices the operator can make while the automated procedure is engaged

parallel event handling: background process of handling a received DSC message that is not pertinent to the active automated procedure

pertinent to the automated procedure: expression used primarily with reference to DSC messages to indicate that the message has something to do with the procedure and is therefore "handled" by the procedure

NOTE: A DSC message is pertinent to an automated procedure if the set of information characters in the DSC message has the correct values.

pertinent to the station: any DSC message that would start an automated procedure if the transceiver were in standby

self-terminating alarm: short alarm that stops by itself without operator intervention

NOTE: The purpose of this alarm is to inform the operator that a DSC message is received but it does not require his immediate attention.

standby: the equipment is not handling an automated procedure, either active or on hold, but is able to receive DSC messages

symbol (as part of the DSC sentence): the term "symbol" used to describe the 7 binary bits of a 10 bit DSC word that have the information content

toggle (between automated procedures): ability to make one automated procedure active assuring that all other procedures go on hold

top level: top level means that items, buttons, or functions are present and visible without requiring any action by the operator (such as scrolling, opening up menus, or removing any obscuring covers, etc.)

two-tone alarm: alarm consisting of a repetition of the 2 200 Hz frequency for 250 ms followed by a 1 300 Hz frequency for 250 ms

NOTE: This alarm is used for the initiation of the received distress DSC automated procedure. The characteristics of this alarm on the equipment shall not be able to be altered.

urgency alarm: alarm consisting of a repetition of the 2 200 Hz frequency for 250 ms followed by 250 ms period of silence

NOTE: This alarm is used for the initiation of the received non distress DSC automated procedure when the category of the initiating DSC message is "urgency". The characteristics of this alarm on the equipment shall not be able to be altered.

watch receiver: this unit is the separate receiver in DSC radios that continuously monitors the DSC distress frequencies on MF/HF, 2 187,5 kHz on MF, and channel 70 on VHF

NOTE: On MF/HF it is sometimes referred to as the scanning receiver.

word (as part of the DSC sentence): term "word" used to describe the 10 binary bits that make up the coded entities of a transmitted DSC message

NOTE: The 10 bits consist of a 7 bit "symbol" that gives the information content and 3 bit error check that gives the number of 0 binary bits in the 7 bit symbol.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AIS	universal shipborne Automatic Identification System
ALE	Automatic Linking Exchange
DROBOSE	Distress Relay On Behalf Of Someone Else
DSC	Digital Selective Calling
ECC	Error Check Character
EUT	Equipment Under Test
GMDSS	Global Maritime Distress and Safety System
HF	High Frequency
IEC	International Electrotechnical Commission
ISO	International Standardization Organization
ITU	International Telecommunications Union
ITU-R	ITU - Radiocommunications Sector
ITU-T	ITU - Telecommunications Sector
MF	Medium Frequency
MMSI	Maritime Mobile Service Identity
NBDP	Narrow Band Direct Printing
UTC	Universal Time Co-ordinated
VHF	Very High Frequency

4 Controls and Indicators in Class A/B DSC Equipment

4.1 Visual indication

Any visual display of the information content shall be clearly legible under all ambient light conditions.

The display shall be large enough to hold enough information from the active procedure to safely guide the operator through operator options in any engaged DSC procedure (distress or non-distress). It shall at any time hold information on how to instantly recall any waiting procedure, or put any active procedure on hold.

The amount of information to display simultaneously on the display shall correspond to the information that can be written in plain text with a minimum of 160 characters, each character having a minimum height of 3,5 mm, and a nominal character width/height ratio of 0,7.

Where logic flows and procedural guidance, expressed by graphical symbols, have an advantage over text, this shall be allowed. Any graphical symbols shall be clearly defined in the operation manual.

All DSC displays at all operating positions shall comply with these requirements.

5 Technical requirements

5.1 Facilities for DSC transmission and reception

5.1.1 Multi-frequency distress alert attempts and watch receiver capabilities (MF/HF)

The equipment shall either:

- be capable of receiving DSC messages on all distress frequencies (except for the transmit frequency in use) whilst the distress alert is being transmitted; or
- be able to complete the multi-frequency distress alert attempt within one minute.

5.1.2 Watch receiver capabilities (VHF)

The watchkeeping receiver part of the DSC equipment shall be designed for continuous operation on channel 70 but the receiver need not operate when the transmitter is in use on that channel.

5.2 Remote alarms

The equipment shall be provided with facilities for connecting remote alarms as recommended in IMO Regulation IV/14, regulation X/3, IV/6.6, IMO resolution MSC.97 (73) 14.6.4 [i.1].

5.3 Galvanic isolation

No exposed metallic part of the equipment shall cause any terminal of the source of electrical energy to be earthed.

5.4 Manuals

Maintenance or service manuals shall be available and shall contain:

- If the equipment is so constructed that fault diagnosis and repair is practicable down to component level, the maintenance instructions shall include full circuit diagrams, component layouts and components parts lists.

- If the equipment contains modules in which fault diagnosis and repair down to component level is not practicable, the maintenance instructions shall contain sufficient information to enable localization and replacement of the defective module.

6 Automated and Non-Automated Procedure Requirements in Class A/B DSC Equipment

6.1 Introduction

This clause covers the minimum level of software automation, operational simplicity, and interface consistency requirements for shipborne fixed installations using class A/B Digital Selective Calling equipment as specified in ITU-R Recommendation M.493-12 [3] annexes 1, 3 and 4.

Perhaps the most important issue concerns an implied expectation for the use of the terminology "automated procedure" as used in the present document to appear in the user interface. The terminology "automated procedure" describes the set of algorithms that are used to encapsulate all the activities necessary to perform multitasking, DSC, and non DSC communication events. The operator does not need to know anything about the existence of automated procedures in order to operate a radio that makes use of these algorithms. Though the present document refers to items such as the "Sending Distress Automated Procedure" such language shall not appear on the user interface of the equipment.

The primary purpose of DSC signalling is to provide the means to set-up subsequent communications between vessels and/or coast stations. A call may be considered as being the total duration from the start of the DSC signalling until the end of the subsequent communications, and the automated procedure is terminated.

The operational functionality described in this part has the objective of not disturbing any ongoing call. Furthermore, the equipment shall assist the operator by providing simple audible indication of a received DSC call whilst the equipment is engaged, and provide a facility to manage activation amongst initiated automated procedures.

6.2 Non-automated features

This clause describes the features of the equipment that are necessary to assure compliance to the ITU-R DSC functionality standards and support a smoother operation of the automation algorithms, but are not directly related to the automation algorithms.

6.2.1 DSC Message Composition

The equipment shall provide factory default values for all non distress DSC messages as specified in ITU-R Recommendation M.493-12 [3] annex 3 and summarized in figure A.1 for all parameters where the operator has the option to select or enter more than one value and has not already done so.

The default values for the Distress Relay On Behalf Of Someone Else (DROBOSE) shall be as given in table A.1.

The default values for the operator-composed distress alert shall be the default distress alert as specified in the sent distress automated procedure.

A destination MMSI that does not have at least 9 digits entered is invalid.

The MMSI "unknown" indicator shall only be able to be used for the MMSI of the vessel in distress when composing a DROBOSE.

No DSC message shall be able to be sent that has an invalid parameter.

For simplicity of the user interface:

- a) the DSC message composition interface shall be such that the operator needs no user manual to initiate the desired DSC message;
- b) it shall require a maximum of two keystrokes, button pushes or menu actions plus the entry or selection of a destination MMSI for the operator to send the default (routine individual) DSC message from standby;

- c) parameter descriptions and terms shall be provided in plain language;
- d) all parameters of the DSC message that do not require an operator choice shall be entered automatically;
- e) guidance and/or prompting shall be provided for the entry of any necessary parameters of the DSC message if these parameters and/or their values are not plainly visible from context or on the display.

For data entry:

- a) the equipment shall only allow the operator to compose and send DSC messages that are compliant with the latest version of ITU-R recommendation M.493-12 [3];
- b) acknowledgements shall be automatically composed by the equipment and user options for these acknowledgements are provided by the automated procedures;
- c) the equipment shall provide the operator with the choice of specifying the geographic area parameters as either a circle of radius "r" about a centre point or the traditional latitude-longitude Mercator box and northwest corner point or about a centre point;
- d) the equipment shall convert and round the radius-centre point entry according to the algorithm given in annex B;
- e) the equipment shall provide an automatic determination of the channel and or frequencies of subsequent communication according to the algorithm given in ITU-R Recommendation M.493-12 [3] annex 3 and summarized in annex C.

The automated channel selection shall be able to be overridden.

It shall not be possible to select a distress channel for subsequent communications for DSC messages of priority routine.

The equipment shall automatically set the dot pattern length to 20 bits for all transmitted DSC messages on VHF, and on MF/HF all DSC messages addressed to a coast station and all individual acknowledgements with format specifiers 120 and 123.

Furthermore MF/HF equipment shall automatically set the dot pattern length to 200 bits for all transmitted DSC messages for:

- distress alerts;
- distress acknowledgements;
- distress relays addressed to a geographic area;
- distress relay acknowledgements addressed to all ships;
- all calls addressed to a ship station other than messages addressed to a coast station or all individual acknowledgements with format specifiers 120 and 123.

6.2.2 Transmission of DSC messages and prioritized wait

If the channel is free after the transmitter has powered up, the transmission shall begin immediately. If the channel is not free, and the DSC message is a distress alert, the alert shall be transmitted as soon as the channel becomes free or after 10 s on MF or HF or 1 s on VHF, whichever ever occurs first. (The 10 s and 1 s values are approximate average times for HF and VHF DSC messages, respectively.) For all other DSC messages, the equipment shall wait for the channel to become free and then the equipment shall delay transmission of the DSC message for a specified wait time.

The specified wait time shall depend upon the message type and priority. Distress DSC messages (except for alerts), urgency, safety, routine and test DSC messages shall wait one, two, three, and four "fixed" units of time plus a random addition described below, respectively, before attempting to transmit. Transmission occurs if and only if the channel is still free after this wait time has elapsed, otherwise the process is repeated.

The fixed "unit" of time shall be 100 ms on MF and HF and 50 ms on VHF. The randomly generated component shall be some positive integer with resolution in milliseconds between zero and the fixed interval. The random component serves as a tie breaker when multiple DSC messages of the same priority and type are waiting to be transmitted. The randomly generated part of the wait time shall be recomputed for every transmission attempt.