

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Ground-based UHF radio transmitters, receivers
and transceivers for the UHF aeronautical mobile service
using amplitude modulation;
Part 1: Technical characteristics and
methods of measurement**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/61b0d475-80b2-46d-ad9e-ac958e9efcc0/etsi-en-302-617-1-v1.1.1-2009-01>



ReferenceDEN/ERM-TG25-262-1

Keywordsaeronautical, AM, DSB, radio, testing, UHF

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions and abbreviations.....	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 General requirements	9
4.1 Controls and indicators.....	9
4.2 Class of emission and modulation characteristics	10
4.3 Warm up.....	10
5 Test conditions, power sources and ambient temperatures	10
5.1 Normal and extreme test conditions	10
5.2 Test power source.....	10
5.3 Normal test conditions.....	10
5.3.1 Normal temperature and humidity	10
5.3.2 Normal power sources	11
5.3.2.1 Mains voltage and frequency	11
5.3.2.2 Other power sources.....	11
5.4 Extreme test conditions	11
5.4.1 Extreme temperatures	11
5.4.2 Extreme values of test power sources.....	11
5.4.2.1 Mains voltage.....	11
5.4.2.2 Other power sources.....	11
5.5 Performance test.....	11
5.6 Environmental tests	12
5.6.1 General.....	12
5.6.2 Procedure for tests at extreme temperatures	12
5.6.3 Temperature tests.....	12
5.6.3.1 High temperature.....	12
5.6.3.2 Low temperature	12
6 General conditions of measurement	13
6.1 Receiver test signal arrangement.....	13
6.1.1 Test signal sources	13
6.1.2 Nominal frequency	13
6.1.3 Normal test signal	13
6.1.4 Squelch	13
6.1.5 Normal audio output power	13
6.1.6 Audio AGC.....	13
6.2 Transmitter test signal arrangement	13
6.2.1 Coaxial termination.....	13
6.2.2 Signal sources	13
6.2.3 Normal test signal	13
6.3 Test channels	14
7 Transmitter	14
7.1 Protection of the transmitter	14
7.1.1 Definition.....	14
7.1.2 Method of measurement	14
7.1.3 Requirement.....	14
7.2 Frequency error	14

7.2.1	Definition.....	14
7.2.2	Method of measurement	14
7.2.3	Limits.....	15
7.3	Carrier power.....	15
7.3.1	Definitions	15
7.3.2	Method of measurement	15
7.3.3	Tolerances.....	15
7.3.3.1	Normal test conditions	15
7.3.3.2	Extreme test conditions	15
7.4	Amplitude modulation characteristic.....	16
7.4.1	Modulation depth.....	16
7.4.1.1	Definitions.....	16
7.4.1.2	Method of measurement.....	16
7.4.1.3	Limits	16
7.4.2	Modulation compression.....	16
7.4.2.1	Definition	16
7.4.2.2	Method of measurement.....	16
7.4.2.3	Limits	17
7.4.3	Amplitude modulation distortion	17
7.4.3.1	Definition	17
7.4.3.2	Method of measurement.....	17
7.4.3.3	Limits	17
7.4.4	Audio frequency response	17
7.4.4.1	Definition	17
7.4.4.2	Method of measurement.....	17
7.4.4.3	Limits	17
7.5	Adjacent channel power	18
7.5.1	Definition.....	18
7.5.2	Measurement.....	18
7.5.3	Limits.....	18
7.6	Broadband noise measurement.....	18
7.6.1	Definition.....	18
7.6.2	Method of measurement	19
7.6.3	Limit	19
7.7	Conducted spurious emissions	20
7.7.1	Definition.....	20
7.7.2	Method of measurement	20
7.7.3	Limits.....	20
7.8	Intermodulation attenuation.....	20
7.8.1	Definition.....	20
7.8.2	Method of measurement	21
7.8.3	Limits.....	21
7.9	RF power attack time and release time.....	22
7.9.1	Definitions	22
7.9.2	Method of measurement	22
7.9.2.1	Attack time	22
7.9.2.2	Release time	22
7.9.3	Limits.....	23
7.10	Keying Transient frequency behaviour of the transmitter	23
7.10.1	Definitions	23
7.10.2	Method of measurement	23
7.10.3	Limits.....	24
7.11	Sidetone.....	24
7.11.1	Limits.....	24
8	Receiver.....	24
8.1	Sensitivity.....	24
8.1.1	Definition.....	24
8.1.2	Method of measurement	24
8.1.3	Limits.....	25
8.2	Harmonic distortion.....	25
8.2.1	Definition.....	25

8.2.2	Method of measurement	25
8.2.3	Limits.....	25
8.3	Audio frequency response	25
8.3.1	Definition.....	25
8.3.2	Method of measurement	25
8.3.3	Limits.....	25
8.4	Audio noise	26
8.4.1	Definition.....	26
8.4.2	Method of measurement	26
8.4.3	Limits.....	26
8.5	Effective acceptance bandwidth	26
8.5.1	Definition.....	26
8.5.2	Method of measurement	26
8.5.3	Limits.....	26
8.6	Adjacent channel rejection	27
8.6.1	Definition.....	27
8.6.2	Method of measurement	27
8.6.3	Limits.....	27
8.7	Spurious response rejection	28
8.7.1	Definition.....	28
8.7.2	Introduction to the method of measurement	28
8.7.3	Method of search of the limited frequency range	28
8.7.4	Method of measurement	29
8.7.5	Limit	29
8.8	Intermodulation response rejection	29
8.8.1	Definition.....	29
8.8.2	Method of measurement	29
8.8.3	Limit	30
8.9	Blocking or desensitization	30
8.9.1	Definition.....	30
8.9.2	Method of measurement	30
8.9.3	Limit	31
8.10	Conducted spurious emissions	31
8.10.1	Definition.....	31
8.10.2	Method of measuring the power level	31
8.10.3	Limits.....	32
8.11	Squelch operation	32
8.11.1	Definition.....	32
8.11.2	Method of measurement	32
8.11.3	Limits.....	32
8.12	Cross modulation rejection	33
8.12.1	Definition.....	33
8.12.2	Method of measurement	33
8.12.3	Limits.....	33
8.13	Receiver dynamic range	33
8.13.1	Definition.....	33
8.13.2	Method of measurement	33
8.13.3	Limit	34
8.14	AGC attack time and release time	34
8.14.1	Definitions	34
8.14.2	Method of measurement	34
8.14.2.1	Attack time.....	34
8.14.2.2	AGC Decay time	34
8.14.3	Limits.....	34
8.15	AF AGC	35
8.15.1	Definition.....	35
8.15.2	Method of measurement	35
8.15.3	Limit	35
8.16	Cabinet Radiation	35
9	Measurement uncertainty and interpretation of the measured results	35
9.1	Maximum measurement uncertainties	36

9.2	Interpretation of the measurement results	37
Annex A (normative):	Auxiliary cables.....	38
Annex B (informative):	Specification for adjacent channel power measurement arrangements.....	39
B.1	Power measuring receiver specification.....	39
B.1.1	IF filter	39
B.1.2	Attenuation indicator.....	40
B.1.3	RMS value indicator.....	40
B.1.4	Oscillator and amplifier.....	40
Annex C (informative):	Bibliography.....	41
History		42

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/61b0d475-80b2-4f6d-ad9e-ac958c9efcc0/etsi-en-302-617-1-v1.1.1-2009-01>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Vote phase of the ETSI standards Two-step Approval Procedure.

The present document is part 1 of a multi-part deliverable covering the Electromagnetic compatibility and Radio Spectrum Matters (ERM): Ground-based UHF radio transmitters, receivers and transceivers for the UHF aeronautical mobile service using amplitude modulation as identified below:

- Part 1: "Technical characteristics and methods of measurement";**
- Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document states the minimum performance requirements for radio transmitters receivers and transceivers at ground-based aeronautical stations operating in the UHF band (225 MHz to 399,975 MHz) allocated to the aeronautical mobile service.

The present document applies to DSB AM systems, with channel separations of 25 kHz intended for analogue speech.

The scope of the present document is limited to ground base stations.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.2] NATO STANAG 4205: "Technical Standards for Single Channel UHF Radio Equipment".

- [i.3] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

aeronautical mobile service: mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

conducted measurements: measurements which are made using a direct RF connection to the equipment under test

ground base station: aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

radiated measurements: measurements which involve the measurement of a radiated field

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AF	Audio Frequency
AGC	Automatic Gain Control
AM	Amplitude Modulation
dBc	dB relative to the carrier power
DSB	Double Side Band
IF	Intermediate Frequency
ppm	parts per million
RF	Radio Frequency
rms	root mean square
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion)
UHF	Ultra High Frequency
VSWR	Voltage Standing Wave Ratio

4 General requirements

25 kHz equipment shall be able to operate on the frequencies 225,000 MHz to 399,975 MHz.

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

It shall not be possible to transmit during channel switching operations.

4.1 Controls and indicators

The equipment shall have the following controls and indicators as a minimum:

- a visual indication that the device is switched on;
- a facility to disable the squelch for test purposes (by local or remote control);
- a visual indication that the carrier is being produced.

The equipment shall also meet the following requirements:

- the user shall not have access to any control which, if unintentionally set, might impair the operating parameters of the equipment.

4.2 Class of emission and modulation characteristics

The equipment shall use Double Side Band (DSB) Amplitude Modulation (AM) full carrier, 6K80A3EJN with 25 kHz channel spacing.

4.3 Warm up

After being switched on the equipment shall meet the requirements of the present document within one minute under normal test conditions (see clause 5.3).

If the equipment includes parts which require to be heated in order to operate correctly (e.g. crystal ovens) a warming-up period of 10 minutes of those parts shall be allowed.

5 Test conditions, power sources and ambient temperatures

5.1 Normal and extreme test conditions

Measurements shall be made under normal test conditions (see clause 5.3) and also, where stated, under extreme test conditions (see clauses 5.4.1 and 5.4.2).

5.2 Test power source

During testing, the equipment shall be supplied from a test power source capable of producing normal and extreme test voltages.

The internal impedance of the test power source shall be low enough for its effect on the test results to be negligible. For the purpose of testing the power source voltage shall be measured at the input terminals of the equipment.

During testing, the power source voltages shall be maintained within a tolerance of ± 3 % relative to the voltage level at the beginning of each test.

5.3 Normal test conditions

5.3.1 Normal temperature and humidity

The normal temperature and humidity conditions for tests shall be a combination of temperature and humidity within the following ranges:

- temperature: +15 °C to +35 °C;
- relative humidity: 20 % to 75 %.

When it is impracticable to carry out the tests under these conditions, a note to this effect, stating the ambient temperature and relative humidity during the tests, shall be added to the test report.

5.3.2 Normal power sources

5.3.2.1 Mains voltage and frequency

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage.

For the purpose of the present document, the nominal voltage shall be the declared voltage or any of the declared voltages for which the equipment was designed.

The frequency of the test power source corresponding to the AC mains shall be between 49 Hz and 51 Hz.

5.3.2.2 Other power sources

For operation from other power sources or types of battery (primary or secondary), the normal test voltage shall be that declared by the equipment manufacturer.

5.4 Extreme test conditions

5.4.1 Extreme temperatures

For tests at extreme temperatures, measurements shall be made in accordance with clause 5.5, at a lower temperature of -20 °C and an upper temperature of +55 °C. This test shall be performed at the nominal supply voltage as defined in clause 5.3.2.

5.4.2 Extreme values of test power sources

5.4.2.1 Mains voltage

The extreme test voltages shall be between 207 V and 253 V. This test shall be performed at the normal temperature and humidity as defined in clause 5.3.1.

The frequency of the test voltage shall be between 49 Hz and 51 Hz.

5.4.2.2 Other power sources

For equipment using other power sources, or capable of being operated from a variety of power sources, the extreme test voltages shall be those agreed between the equipment manufacturer and the testing laboratory and shall be recorded in the test report.

5.5 Performance test

For the purposes of the present document, the term "performance test" shall be taken to mean the following measurements and limits:

- for the transmitter:
 - frequency error:
with the transmitter connected to a coaxial termination (see clause 6.2.1), the frequency error shall be as in clause 7.2;
 - carrier power:
with the transmitter connected to a coaxial termination (see clause 6.2.1), the transmitter shall be keyed without modulation and the output power shall be as defined in clause 7.3;
 - modulation:
with the transmitter connected to a coaxial termination (see clause 6.2.1), the transmitter shall be keyed. The modulation distortion shall be as in clause 7.4.3.

- for the receiver:
 - sensitivity:
 - with the AGC operative, a normal test signal (see clause 6.1.3) shall be applied to the receiver. The sensitivity shall be as defined in clause 8.1.

5.6 Environmental tests

5.6.1 General

Environmental tests shall follow checking the protection of the transmitter (see clause 7.1) which follows the first application of the Performance test (see clause 5.5).

5.6.2 Procedure for tests at extreme temperatures

Before tests at the upper extreme temperature ($55\text{ °C} \pm 3\text{ °C}$), the equipment shall be placed in the test chamber and left until thermal balance is attained. The equipment shall then be switched on for 30 minutes. The transmitter shall then be keyed for 1 minute in the transmit condition, after which the equipment shall meet the specified requirements. Transmitters shall be operated in the highest rated power transmit condition.

For tests at the lower extreme temperature ($-20\text{ °C} \pm 3\text{ °C}$), the equipment shall be left in the test chamber until thermal balance is attained, then switched to the standby or receive condition for 1 minute after which the equipment shall meet the specified requirements.

NOTE: It is assumed that equipment intended for off-set carrier operation will be installed in a building with facilities suitable to provide protection from temperature extremes, therefore extreme temperature tests need not be applied to such equipment.

5.6.3 Temperature tests

The chamber must be able to maintain the required temperature value during the measurement.

5.6.3.1 High temperature

- Place the equipment in a chamber and heat to the required temperature value and allow to stabilize for 1 hour.
- Switch on the equipment.
- After 30 minutes carry out the performance test as detailed in clause 5.5.
- Switch off the equipment and allow the chamber to cool to room temperature over a 1 hour period.
- Allow time for the equipment to stabilize to normal room temperature and humidity before carrying out the next test.

5.6.3.2 Low temperature

- Place the equipment in a chamber and cool to the required temperature value for 2 hours.
- Switch on the equipment and maintain the chamber at the required operating temperature.
- After 10 minutes carry out the performance test as detailed in clause 5.5.
- Switch off the equipment and allow the chamber to rise to room temperature over a 1 hour period.
- Allow time for the equipment to stabilize to normal room temperature and for moisture to disperse before carrying out the next test.