# Standard Specification for Dry Bleached Lac<sup>1</sup>

This standard is issued under the fixed designation D 207; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\epsilon)$  indicates an editorial change since the last revision or reapproval.

ϵ¹ Note—Keywords were added editorially in May 1995.

#### 1. Scope

1.1 This specification covers two grades of dry bleached lac, namely, regular and refined.

Note 1—Dry bleached lac is also known as "bone-dry," "bac-dry," or "kiln-dry" bleached lac. The refined grade is bleached lac from which practically all the wax and insoluble matter has been removed during the process of manufacture.

#### 2. Referenced Documents

2.1 ASTM Standards:

D 29 Test Methods for Sampling and Testing Lac Resins<sup>2</sup>

# 3. Properties

3.1 Dry bleached lac shall conform to the following requirements:

	Regular	Refined
Matter insoluble in specified hot	1.0	0.2
solvents, max, %		
Moisture, max,%	6.0	6.0
Wax, max, %	5.5	0.2
Matter soluble in water, max, %	1.0	0.3
Ash, max, %	1.0	0.5
Rosin	none	none
Copals	none	none

### 4. Test Methods

4.1 The material shall be sampled and the properties enumerated in this specification shall be determined in accordance with Test Methods D 29.

## 5. Keywords

5.1 lac; lac; bleached; lac; bone dry; lac; refined

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, 100 Barr Harbor Drive, West Conshohocken, PA 19428.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (http://www.astm.org).

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D-1 on Paint and Related Coatings, Materials, and Applications, and is the direct responsibility of Subcommittee D01.33 on Polymers and Resins.

Current edition approved Sept. 12, 1955. Published November 1955. Originally published as D 207-25. Last previous edition D 207-49.

<sup>&</sup>lt;sup>2</sup> Annual Book of ASTM Standards, Vol 06.03.