INTERNATIONAL STANDARD

ISO 4036

Second edition 1999-08-15

Corrected and reprinted 2000-12-01

Hexagon thin nuts (unchamfered) — Product grade B

Écrous bas hexagonaux (sans chanfrein) — Grade B

iTeh STANDARD PREVIEW (standards.iteh.ai)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 4036:1999 https://standards.iteh.ai/catalog/standards/sist/e3bebf09-1444-436a-9ed5-0cff96d26219/iso-4036-1999

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 4036 was prepared by Technical Committee ISO/TC 2, Fasteners.

This second edition cancels and replaces the first edition (ISO 4036:1979) which has been technically revised.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 4036:1999(E) © ISO

Introduction

This International Standard is part of the complete ISO product standard series on external hexagon drive fasteners. The series comprises:

- a) hexagon head bolts (ISO 4014 to ISO 4016 and ISO 8765);
- b) hexagon head screws (ISO 4017, ISO 4018 and ISO 8676);
- c) hexagon nuts (ISO 4032 to ISO 4036, ISO 8673 to ISO 8675);
- d) hexagon bolts with flange (ISO 4162 and ISO 15071);
- e) hexagon nuts with flange (ISO 4161 and ISO 10663);
- f) structural bolts and nuts (ISO 4775, ISO 7411 to ISO 7414 and ISO 7417).

iTeh STANDARD PREVIEW (standards.iteh.ai)

Hexagon thin nuts (unchamfered) — Product grade B

1 Scope

This International Standard specifies the characteristics of unchamfered hexagon thin nuts, with threads from M1,6 up to and including M10 and product grade B.

If, in special cases, specifications other than those listed in this International Standard are required, they should be selected from existing International Standards, for example ISO 724, ISO 965-1 and ISO 4759-1.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards: sist/e3bebf09-1444-436a-9ed5-0cf96d26219/iso-4036-1999

ISO 225:1983, Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions.

ISO 724:1993, ISO general-purpose metric screw threads — Basic dimensions.

ISO 965-1:1998, ISO general purpose metric screw threads — Tolerances — Part 1: Principles and basic data.

ISO 3269:—1), Fasteners — Acceptance inspection.

ISO 4042:1999, Fasteners — Electroplated coatings.

ISO 4759-1:—2), Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C.

ISO 6157-2:1988, Fasteners — Surface discontinuities — Part 2: Nuts.

ISO 8839:1986, Mechanical properties of fasteners — Bolts, screws, studs and nuts made of non-ferrous metals.

ISO 8992:1986, Fasteners — General requirements for bolts, screws, studs and nuts.

ISO 10683:—3), Fasteners — Non-electrolytically applied zinc flake coatings.

¹⁾ To be published. (Revision of ISO 3269:1988)


²⁾ To be published. (Revision of ISO 4759-1:1978)

³⁾ To be published.

ISO 4036:1999(E) © ISO

3 Dimensions

See Figure 1 and Table 1. Symbols and descriptions of dimensions are defined in ISO 225.






Figure 1

Table 1 — Dimensions

Dimensions in millimetres

Thread (d)			M1,6	M2	M2,5	М3	(M3,5) ^a	M4	M5	М6	М8	M10
Ppp			0,35	0,4	0,45	0,5	0,6	0,7	0,8	1	1,25	1,5
e		min.	3,28 _e	4,18	5,31	5,88	06, 44 F	7,5	8,63	10,89	14,2	17,59
m		max.	1,00	1,20 _{S1}	a ^{1,60}	arus.	iten.	2.20	2,70	3,2	4,0	5,0
		min.	0,75	0,95	1,35	1,55	1,75	1,95	2,45	2,9	3,7	4,7
S	nom. =	max. 1	ttps3/,2tano	larc 4,0 eh.	0.40(42)	stan 5 ;5ds/	sist 6,0 beb	f0 7 , 00 44	43 8,00 ed	5-10,00	13,00	16,00
		min.	2,9	3,7	4,7	5,2	5,7	6,64	7,64	9,64	12,57	15,57

^a If possible, the size in parentheses should be avoided.

b P is the pitch of the thread.

4 Specifications and reference standards

See Table 2.

Table 2 — Specifications and reference standards

Material		Steel (St)	Non-ferrous metal				
General International requirements Standard		ISO 8992					
Thread	Tolerance	6H					
International Standards		ISO 724, ISO 965-1					
Mechanical	Hardness min.	110 HV30					
	International Standard	-	Materials as specified in ISO 8839				
Tolerances	Product grade	В					
	International Standard	ISO 4759-1					
	i	Teh STANDARD PRI	EVIEW Plain				
Finish and/or coating https://		Requirements for electroplating are covered in ISO 4042. Requirements for non-electrolytically applied zinc flake coatings are covered standards itch ain 1SO 10683 ds/sist/e3bebf0 -1444-436a-9ed5- If different electroplating requirements are desired or if requirements are needed for other finishes, they should be agreed between customer and supplier.					
		Limits for surface discontinuities are covered in ISO 6157-2.					
Acceptability		For acceptance procedure, see ISO 32	269.				

5 Designation

EXAMPLE

An unchamfered hexagon thin nut with thread M6 made from steel with a minimum hardness of 110 HV30 (St) is designated as follows:

Hexagon nut ISO 4036 - M6 - St

ISO 4036:1999(E) © ISO

Bibliography

- [1] ISO 4014:1999, Hexagon head bolts Product grades A and B.
- [2] ISO 4015:1979, Hexagon head bolts Product grade B Reduced shank (shank diameter approximately equal to pitch diameter).
- [3] ISO 4016:1999, Hexagon head bolts Product grade C.
- [4] ISO 4017:1999, Hexagon head screws Product grades A and B.
- [5] ISO 4018:1999, Hexagon head screws Product grade C.
- [6] ISO 4032:1999, Hexagon nuts, style 1 Product grades A and B.
- [7] ISO 4033:1999, Hexagon nuts, style 2 Product grades A and B.
- [8] ISO 4034:1999, Hexagon nuts Product grade C.
- [9] ISO 4035:1999, Hexagon thin nuts (chamfered) Product grades A and B.
- [10] ISO 4161:1999, Hexagon nuts with flange Coarse thread.
- [11] ISO 4162:—4), Hexagon bolts with flange Small series Product grade combination A/B.
- [12] ISO 4775:1984, Hexagon nuts for high-strength structural bolting with large width across flats Product grade B Property classes 8 and 10.

 ISO 4036:1999
- [13] ISO 7411:1984, Hexagon bolts for high-strength/structural bolting With large width across flats (thread lengths according to ISO 888) Product grade O Property classes 8.8 and 10.9.
- [14] ISO 7412:1984, Hexagon bolts for high-strength structural bolting with large width across flats (short thread length) Product grade C Property classes 8.8 and 10.9.
- [15] ISO 7413:1984, Hexagon nuts for structural bolting, style 1, hot-dip galvanized (oversize tapped) Product grades A and B Property classes 5, 6 and 8.
- [16] ISO 7414:1984, Hexagon nuts for structural bolting with large width across flats, style 1 Product grade B Property class 10.
- [17] ISO 7417:1984, Hexagon nuts for structural bolting, style 2, hot-dip galvanized (oversize tapped) Product grade A Property class 9.
- [18] ISO 8673:1999, Hexagon nuts, style 1, with metric fine pitch thread Product grades A and B.
- [19] ISO 8674:1999, Hexagon nuts, style 2, with metric fine pitch thread Product grades A and B.
- [20] ISO 8675:1999, Hexagon thin nuts (chamfered) with metric fine pitch thread Product grades A and B.
- [21] ISO 8676:1999, Hexagon head screws with metric fine pitch thread Product grades A and B.

4

⁴⁾ To be published. (Revision of ISO 4162:1990)

- [22] ISO 8765:1999, Hexagon head bolts with metric fine pitch thread Product grades A and B.
- [23] ISO 10663:1999, Hexagon nuts with flange Fine pitch thread.
- [24] ISO 15071:1999, Hexagon bolts with flange Small series Product grade A.

iTeh STANDARD PREVIEW (standards.iteh.ai)