

Hydraulic fluid power -- Determination of the fluid-borne noise characteristics of components and systems -- Part 2: Measurement of the speed of sound in a fluid in a pipe

Hydraulic fluid power -- Determination of the fluid-borne noise characteristics of components and systems -- Part 2: Measurement of the speed of sound in a fluid in a pipe

iteh STANDARD PREVIEW
(standards.iteh.ai)

Transmissions hydrauliques -- Évaluation des caractéristiques du bruit liquidien des composants et systèmes -- Partie 2: Mesurage de la vitesse du son émis dans un fluide dans une tuyauterie

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

Ta slovenski standard je istoveten z: ISO 15086-2:2000

ICS:

| | | |
|-----------|--------------------------------|---|
| 17.140.20 | Emisija hrupa naprav in opreme | Noise emitted by machines and equipment |
| 23.100.01 | Fluid power systems in general | Fluid power systems in general |

SIST ISO 15086-2:2001

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15086-2:2001

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

INTERNATIONAL
STANDARD

ISO
15086-2

First edition
2000-02-01

**Hydraulic fluid power — Determination of
fluid-borne noise characteristics of
components and systems —**

Part 2:

**Measurement of speed of sound in a fluid in
a pipe**

iTeh STANDARD PREVIEW

(standards.iteh.ai)

*Transmissions hydrauliques — Évaluation des caractéristiques du bruit
liquidien des composants et systèmes —*

*Partie 2: Mesurage de la vitesse du son émis dans un fluide dans une
tuyauterie*



Reference number
ISO 15086-2:2000(E)

© ISO 2000

ISO 15086-2:2000(E)**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 15086-2:2001](https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001)

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

| | Page |
|---|-----------|
| Foreword..... | iv |
| Introduction..... | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and subscripts | 2 |
| 5 Instrumentation..... | 3 |
| 6 Hydraulic noise generator..... | 4 |
| 7 Test conditions | 5 |
| 8 Test rig..... | 5 |
| 9 Test procedure for Method 1 | 9 |
| 10 Test procedure for Method 2..... | 10 |
| 11 Test report | 11 |
| 12 Identification statement (Reference to this part of ISO 15086)..... | 12 |
| Annex A (normative) Errors and classes of measurement of mean value | 13 |
| Annex B (normative) Errors and classes of dynamic measurement..... | 14 |
| Annex C (normative) Data reduction algorithms..... | 15 |
| Annex D (informative) Example of speed of sound calculation in MATLAB® language using three pressure transducers in a pipe (Method 1) | 21 |
| Annex E (informative) Example of speed of sound calculation in MATLAB® language using two pressure transducers in a closed-end pipe (Method 2) | 25 |
| Bibliography | 27 |

ISO 15086-2:2000(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 15086 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 15086-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 8, *Product testing*.

ISO 15086 consists of the following parts, under the general title *Hydraulic fluid power — Determination of fluid borne noise characteristics of components and systems*:

— Part 1: Introduction

— Part 2: Measurement of the speed of sound in a fluid in a pipe

Annexes A, B and C form a normative part of this part of ISO 15086. Annexes D and E are for information only

Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. During the process of converting mechanical power into hydraulic fluid power, flow and pressure fluctuations and structure-borne vibrations are generated.

Hydro-acoustical characteristics of hydraulic components can be measured with acceptable accuracy if the speed of sound in the fluid is precisely known.

The measurement technique for determining the speed of sound in a pipe, as described in this part of ISO 15086, is based upon the application of plane wave transmission line theory to the analysis of pressure fluctuations in rigid pipes [1].

Two different measurement approaches are presented, namely the use of:

- three pressure transducers in a pipe,
- acoustic antiresonance in a closed-end pipe system.

The three-pressure-transducer method should be used at any time when the speed of sound is to be measured under the effective working conditions in a system.

The antiresonance method should be used to produce a table of speed-of-sound data as a function of mean pressure and temperature for a particular fluid.

[SIST ISO 15086-2:2001](https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001)

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 15086-2:2001

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

Hydraulic fluid power — Determination of fluid borne noise characteristics of components and systems —

Part 2: Measurement of the speed of sound in a fluid in a pipe

1 Scope

This part of ISO 15086 describes the procedure for the determination of the speed of sound in a fluid enclosed in a pipe, by measurements from pressure transducers mounted in the pipe.

This part of ISO 15086 is applicable to all types of hydraulic circuit operating under steady state conditions, irrespective of size, for pressure pulsations over a frequency range from 25 Hz to 2 500 Hz.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 15086. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 15086 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 1000:1992, *SI units and recommendations for the use of their multiples and of certain other units*.

ISO 1219-1:1991, *Fluid power systems and components — Graphic symbols and circuit diagrams — Part 1: Graphic symbols*.

ISO 5598:1985, *Fluid power systems and components — Vocabulary*.

3 Terms and definitions

For the purposes of this part of ISO 15086, the terms and definitions given in ISO 5598 and the following apply.

3.1

flow ripple

fluctuating component of flowrate in a hydraulic fluid, caused by interaction with a flow ripple source within the system

3.2

pressure ripple

fluctuating component of pressure in a hydraulic fluid, caused by interaction with a flow ripple source within the system

3.3

fundamental frequency

lowest frequency of pressure ripple measured by the frequency-analysis instrument

ISO 15086-2:2000(E)

3.4

harmonic

sinusoidal component of the pressure ripple or flow ripple occurring at an integer multiple of the fundamental frequency

NOTE A harmonic may be represented by its amplitude and phase, or alternatively by its real and imaginary parts.

3.5

hydraulic noise generator

hydraulic component generating flow ripple and consequently pressure ripple in the circuit

3.6

measurement pipe

pipe in which the pressure transducers are mounted

3.7

impedance

complex ratio of the pressure ripple to the flow ripple occurring at a given point in a hydraulic system and at a given frequency

3.8

entry impedance.

impedance at the entry of a pipe or piping system

3.9

first acoustic antiresonance frequency

lowest frequency at which the magnitude of the entry impedance of the measurement pipe is at a minimum

iTech STANDARD PREVIEW
(standards.iteh.ai)

4 Symbols and subscripts

[SIST ISO 15086-2:2001](https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001)

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

4.1 Symbols

| | |
|----------------------|---|
| A, A', a, B, B', b | Frequency-dependent wave propagation coefficients (complex numbers) |
| c | Acoustic velocity in the fluid |
| d | Internal diameter of pipe |
| f | Frequency of the wave pulsation harmonic |
| f_i | Vector of frequencies at which measurements are conducted |
| f_0 | First acoustic antiresonance frequency (in hertz) |
| H | Transfer function (complex number) between two pressure transducer signals after calibration correction |
| H' | Transfer function (complex number) between two pressure transducer signals under calibration |
| H^* | Transfer function (complex number) between two pressure transducer signals |
| j | $\sqrt{-1}$ |
| L | Distance between transducers 1 and 2 (Method 1) |
| L' | Distance between transducers 2 and 3 (Method 1) |

| | |
|-----------------------|--|
| l | Distance between pressure transducers (Method 2) |
| P_1 | Pressure ripple of transducer PT1 (complex number) |
| P_2 | Pressure ripple of transducer PT2 (complex number) |
| P_3 | Pressure ripple of transducer PT3 (complex number) |
| $Q_{1 \rightarrow 2}$ | Flow ripple at location 1, from 1 to 2 (complex number) |
| $Q_{2 \rightarrow 1}$ | Flow ripple at location 2, from 2 to 1 (complex number) |
| $Q_{2 \rightarrow 3}$ | Flow ripple at location 3, from 2 to 3 (complex number) |
| S_i | Coherence function corresponding to measurement frequencies, f_i |
| ε | Error (complex number) |
| $\bar{\varepsilon}$ | Conjugate of complex number ε (complex number) |
| ε_x | Real part of ε |
| ε_y | Imaginary part of ε |
| ρ | Density of fluid |
| ν | Kinematic viscosity of fluid |
| ω | $2\pi f$ |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-ec270228b293/sist-iso-15086-2-2001>

NOTE $H, H', H^*, P_1, P_2, P_3, Q_{1 \rightarrow 2}, Q_{2 \rightarrow 1}, Q_{2 \rightarrow 3}$ are all frequency-dependent terms and hence are designated by upper-case letters.

Units used in this part of ISO 15086 are in accordance with ISO 1000.

Graphical symbols are in accordance with ISO 1219-1 unless otherwise stated.

4.2 Subscripts

| | |
|---|---------------------|
| O | Index for old value |
| N | Index for new value |

5 Instrumentation

5.1 Static measurements

The instruments used to measure

- mean flow (Method 1 only);
- mean fluid pressure;
- fluid temperature;

shall meet the requirements for "industrial class" accuracy of measurement, i.e. class C as given in annex B.

ISO 15086-2:2000(E)**5.2 Dynamic measurements**

The instruments used to measure pressure ripple shall have the following characteristics:

- a) resonant frequency ≥ 30 kHz;
- b) linearity $\geq \pm 1$ %;
- c) preferably include acceleration compensation.

The instruments need not respond to steady-state pressure. It may be advantageous to filter out any steady-state signal component using a high-pass filter. This filter shall not introduce an additional amplitude or phase error exceeding 0,5 % or 0,5° respectively of the current measurement.

5.3 Frequency analysis of pressure ripple

A suitable instrument shall be used to measure the amplitude and phase of the pressure ripple.

The instrument shall be capable of measuring the pressure ripple from the pressure transducers such that, for a particular harmonic, the measurements from each transducer are performed simultaneously and synchronised in time with respect to each other.

The instrument shall have an accuracy and resolution for harmonic measurements of

- a) amplitude within $\pm 0,5$ %;
 - b) phase within $\pm 0,5^\circ$;
 - c) frequency within $\pm 0,5$ %;
- over the frequency range from 25 Hz to 2 500 Hz

STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 15086-2:2001](https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-c0270228b293/sist-iso-15086-2-2001)

<https://standards.iteh.ai/catalog/standards/sist/07b1c2ec-e912-46b4-a30b-c0270228b293/sist-iso-15086-2-2001>

5.4 Uncertainty

Compliance with the above specification will result in an uncertainty in measurement of speed of sound of less than ± 3 %.

6 Hydraulic noise generator**6.1 General**

Any type of hydraulic noise generator may be used, provided that sufficient pressure ripple is created at the pressure transducers to allow accurate measurements to be taken.

EXAMPLE Pumps and motors create a pressure ripple consisting essentially of many harmonics of the fundamental frequency. In these cases, the fundamental frequency is equal to the product of the shaft rotational frequency and the number of gear teeth, vanes or pistons, etc. (as appropriate to the machine employed).

Suitable alternatives include:

- an auxiliary valve with a rotating spool allowing flow to pass to the return line over part of its rotation;
- an electrohydraulic servo-valve driven by a frequency generator.
- The servo-valve may be operated with a white noise signal in order to obtain significant pressure ripple measurements at each frequency of interest.