



# SLOVENSKI STANDARD

## SIST ISO 15242-1:2005

01-januar-2005

---

### Kotalni ležaji – Metode za merjenje vibracij – 1. del: Osnove

Rolling bearings -- Measuring methods for vibration -- Part 1: Fundamentals

Roulements -- Méthodes de mesurage des vibrations -- Partie 1: Principes fondamentaux

**(standards.iteh.ai)**

Ta slovenski standard je istoveten z: **ISO 15242-1:2004**

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

#### **ICS:**

21.100.20      Kotalni ležaji                      Rolling bearings

**SIST ISO 15242-1:2005**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 15242-1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

# INTERNATIONAL STANDARD

# ISO 15242-1

First edition  
2004-05-01

---

---

## Rolling bearings — Measuring methods for vibration —

### Part 1: Fundamentals

*Roulements — Méthodes de mesure des vibrations —  
Partie 1: Principes fondamentaux*  
**(standards.iteh.ai)**

[SIST ISO 15242-1:2005](https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>



Reference number  
ISO 15242-1:2004(E)

© ISO 2004

**ISO 15242-1:2004(E)****PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 15242-1:2005](https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword.....	iv
Introduction .....	v
1 Scope.....	1
2 Normative references .....	1
3 Terms and definitions.....	1
4 Fundamental concepts.....	3
4.1 Bearing vibration measurement.....	3
4.2 Characteristics of an axis of rotation.....	3
4.3 Bearing error motion .....	4
4.4 Bearing vibration.....	5
5 Measurement process .....	6
5.1 Basis of measurement.....	6
5.2 Speed of rotation.....	6
5.3 Orientation of bearing rotational axis .....	6
5.4 Bearing load .....	6
5.5 Transducers.....	6
6 Measurement and evaluation methods.....	7
6.1 Physical quantity measured.....	7
6.2 Frequency domain .....	7
6.3 Time domain .....	7
6.4 Transducer response and filter characteristics.....	8
6.5 Method of time-averaging .....	9
6.6 Testing sequence .....	10
7 Conditions for measurement .....	10
7.1 Bearing conditions for measurement .....	10
7.2 Conditions of the test environment .....	10
7.3 Conditions for the test device.....	11
7.4 Requirements for the operator .....	11
8 Calibration and reference evaluation of measuring system.....	11
8.1 General .....	11
8.2 Calibration of system components.....	11
8.3 System performance evaluation.....	12
Annex A (informative) Contact resonance considerations .....	13
Bibliography .....	14

## ISO 15242-1:2004(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15242-1 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*.

ISO 15242 consists of the following parts, under the general title *Rolling bearings — Measuring methods for vibration*:

- *Part 1: Fundamentals*
- *Part 2: Radial ball bearings with cylindrical bore and outside surface*
- *Part 3: Radial double-row spherical and tapered roller bearings with cylindrical bore and outside surface*

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

SIST ISO 15242-1:2005  
<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

## Introduction

Vibration in rotating rolling bearings can be of importance as an operating characteristic of such bearings. The vibration can affect the performance of the mechanical system incorporating the bearing and can result in audible noise when the vibration is transmitted to the environment in which the mechanical system operates.

Vibration of rotating rolling bearings is a complex physical phenomenon dependent on the conditions of operation. Measuring the vibration output of an individual bearing under a certain set of conditions does not necessarily characterize the vibration output under a different set of conditions or when the bearing becomes part of a larger assembly. Assessment of the audible sound generated by the mechanical system incorporating the bearing is complicated further by the influence of the interface conditions, the location and orientation of the sensing device, and the acoustical environment in which the system operates. Assessment of airborne noise, which for the purpose of this document can be defined as any disagreeable and undesired sound, is further complicated by the subjective nature of the terms *disagreeable* and *undesired*. Structure-borne vibration can be considered the driving mechanism that ultimately results in the generation of airborne noise. Only selected methods for the measurement of the structure-borne vibration of rotating rolling bearings are addressed in the current edition of ISO 15242.

This part of ISO 15242 serves to define and specify the physical quantities measured and the general test conditions and environment utilized in the measurement of vibration generated by rolling bearings on a test rig. Based on this part of ISO 15242, parties to the acceptance inspection of rolling bearings may, by agreement, establish acceptance criteria with which to control bearing vibration.

Vibration of rotating rolling bearings can be assessed by any of a number of means using various types of transducers and test conditions. No simple set of values characterizing the vibration of a bearing is adequate for the evaluation of the vibratory performance in all possible applications. Ultimately, a knowledge of the type of bearing, its application and the purpose of the vibration testing (e.g., as a manufacturing process diagnostic or an assessment of product quality) is required to select the most suitable method for testing. The field of application for standards on bearing vibration is, therefore, not universal. However, certain methods have established a wide enough level of application to be considered as standard methods for the purposes of this part of ISO 15242.

This part of ISO 15242 serves to define the general principles involved in vibration measurement. It is intended that further parts will specify in more detail the methods for assessing vibration of different types of bearings with cylindrical bore and outside surface.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 15242-1:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>



# Rolling bearings — Measuring methods for vibration —

## Part 1: Fundamentals

### 1 Scope

This part of ISO 15242 specifies measuring methods for vibration of rotating rolling bearings under established test conditions, together with calibration of the related measuring systems.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-2, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 558, *Conditioning and testing — Standard atmospheres — Definitions*

ISO 1132-1, *Rolling bearings — Tolerances — Part 1: Terms and definitions*

ISO 2041, *Vibration and shock — Vocabulary*

ISO 3205, *Preferred test temperatures*

ISO 3448, *Industrial liquid lubricants — ISO viscosity classification*

ISO 5593, *Rolling bearings — Vocabulary*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1132-1, ISO 2041, ISO 5593 and the following apply.

#### 3.1

##### **error motion**

undesired radial or axial (translational) motion or tilt (angular) motion of an axis of rotation, excluding motions due to changes of temperature or externally applied load

#### 3.2

##### **stiffness**

ratio of change of force (or torque) to the corresponding change in translational (or rotational) displacement of an elastic element

**ISO 15242-1:2004(E)**

**3.3**  
**vibration**  
variation with time of the magnitude of a quantity which is descriptive of the motion or position of a mechanical system, when the magnitude is alternately greater and smaller than some average value or reference

**3.4**  
**transducer**  
device designed to receive energy from one system and supply energy, of either the same or of a different kind, to another system in such a manner that the desired characteristics of the input energy appear at the output

**3.5**  
**electromechanical pickup**  
transducer which is actuated by energy from a mechanical system (strain, force, motion, etc.), and supplies energy to an electrical system, or vice versa

NOTE The principal types of transducers used in vibration and shock measurement are

- a) piezoelectric accelerometer;
- b) piezoresistive accelerometer;
- c) strain-gauge type accelerometer;
- d) variable-resistance transducer;
- e) electrostatic (capacitor/condenser) transducer;
- f) bonded-wire (foil) strain-gauge;
- g) variable-reluctance transducer;
- h) magnetostriction transducer;
- i) moving-conductor transducer;
- j) moving-coil transducer;
- k) induction transducer.

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 15242-1:2005](https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

**3.6**  
**displacement**  
vector quantity that specifies the change of position of a body, or particle, with respect to a reference frame

**3.7**  
**velocity**  
vector quantity that specifies the time-derivative of displacement

**3.8**  
**acceleration**  
vector quantity that specifies the time-derivative of velocity

**3.9**  
**filter**  
**wave filter**  
device for separating oscillations on the basis of their frequency. It introduces relatively small attenuation to wave oscillations in one or more frequency bands and relatively large attenuation to oscillations of other frequencies

**3.10**  
**band-pass filter**  
filter which has a single transmission band extending from a lower cut-off frequency greater than zero to a finite upper cut-off frequency

**3.11****pass-band**

⟨band-pass filter⟩ frequency band between the upper and lower cut-off frequencies

**3.12****nominal upper and lower cut-off frequencies****cut-off frequency**

⟨band-pass filter⟩ frequencies above and below the frequency of maximum response of a filter at which the response to a sinusoidal signal is 3 dB below the maximum response

**3.13****root mean square (r.m.s.) velocity**

$v_{r.m.s.}(t)$

square root, over a time interval  $T$ , of the average of squared values of the velocity' over the time interval

NOTE Root mean square value can also be used for displacement and acceleration.

**3.14****exponential mean effective (e.m.e.) velocity**

$v_{e.m.e.}(t)$

parameter for obtaining a time-average velocity, which is similar to root mean square velocity, but considers exponential decay

NOTE 1 Exponential mean effective value can also be used for displacement and acceleration.

NOTE 2 Exponential mean effective value is also known as exponential average value or time relaxation value.

**3.15****period**

smallest increment of the independent variable of a periodic quantity for which the function repeats itself

<https://standards.iteh.ai/catalog/standards/sist/1b6b6d64-f494-427f-9aa4-47fe00113d2f/sist-iso-15242-1-2005>

**4 Fundamental concepts****4.1 Bearing vibration measurement**

The diagram in Figure 1 shows the fundamental elements of bearing vibration measurement and the factors that influence the measurement. The numbers in Figure 1 correspond to clauses of this part of ISO 15242.

**4.2 Characteristics of an axis of rotation**

A rotating rolling bearing is designed to provide an axis of rotation for rotational motion of one machine element relative to another while supporting radial and/or axial loads. An axis of rotation may exhibit motion in six basic degrees of freedom. These are shown in Figure 2, and are listed below:

- rotational motion, see Figure 2 b);
- translational motion in a radial direction, i.e. in one or both orthogonal planes passing through the axis of rotation, see Figures 2 c) and 2 d);
- translational motion in an axial direction, i.e. in a direction parallel to the axis of rotation, see Figure 2 e);
- tilt motion in an angular direction, i.e. in one or both orthogonal planes passing through the axis of rotation, see Figures 2 f) and 2 g).