



SLOVENSKI STANDARD
kSIST-TS FprCEN/TS 16196:2011
01-januar-2011

Gnojila - Manganometrijsko določevanje ekstrahiranega kalcija po obarjanju v obliki oksalata

Fertilizers - Manganimetric determination of extracted calcium following precipitation in the form of oxalate

Düngemittel - Manganometrische Bestimmung von Calcium nach Oxalatfällung

Engrais - Dosage manganométrique du calcium extrait après précipitation sous forme d'oxalate

Ta slovenski standard je istoveten z: FprCEN/TS 16196

ICS:

65.080 Gnojila Fertilizers

kSIST-TS FprCEN/TS 16196:2011 en,fr,de

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

FINAL DRAFT
FprCEN/TS 16196

November 2010

ICS

English Version

Fertilizers - Manganometric determination of extracted calcium following precipitation in the form of oxalate

Engrais - Dosage manganométrique du calcium extrait
après précipitation sous forme d'oxalate

Düngemittel - Manganometrische Bestimmung von Calcium
nach Oxalatfällung

This draft Technical Specification is submitted to CEN members for formal vote. It has been drawn up by the Technical Committee CEN/TC 260.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Warning : This document is not a Technical Specification. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a Technical Specification.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Sampling	4
5 Principle	4
6 Reagents	5
7 Apparatus	5
8 Preparation of the test portion	5
9 Procedure	5
10 Calculation and expression of the result	6
11 Precision	6
12 Test report	7
Annex A (informative) Statistical results of the inter-laboratory tests	8
Bibliography	10

Foreword

This document (FprCEN/TS 16196:2010) has been prepared by Technical Committee CEN/TC 260 "Fertilizers and liming materials", the secretariat of which is held by DIN.

This document is currently submitted to the Formal Vote.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

FprCEN/TS 16196:2010 (E)

1 Scope

This Technical Specification specifies a manganometric method for the determination of the calcium content in fertilizer extracts.

This method is applicable to EC fertilizers for which a declaration of the total and/or water-soluble calcium content is provided for in Regulation (EC) 2003/2003, Annex I [1].

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1482-2, *Fertilizers and liming materials — Sampling and sample preparation — Part 2: Sample preparation*

EN 12944-1:1999, *Fertilizers and liming materials and soil improvers — Vocabulary— Part 1: General terms*

EN 12944-2:1999, *Fertilizers and liming materials and soil improvers — Vocabulary— Part 2: Terms relating to fertilizers*

CEN/TS 15960, *Fertilizers — Extraction of total calcium, total magnesium, total sodium and total sulfur in the forms of sulfates*

CEN/TS 15961, *Fertilizers — Extraction of water soluble calcium, magnesium, sodium and sulfur in the form of sulfates*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 12944-1:1999 and EN 12944-2:1999 apply.

4 Sampling

Sampling is not part of the method specified in this document. A recommended sampling method is given in EN 1482-1.

Sample preparation shall be carried out in accordance with EN 1482-2. Grinding of the laboratory sample is recommended for homogeneity reasons.

5 Principle

Precipitation of the calcium contained in an aliquot of the extraction solution in the form of an oxalate, which is determined by titration using potassium permanganate.

6 Reagents

- 6.1 **Diluted hydrochloric acid**, one volume of hydrochloric acid, $\rho = 1,18\text{g/ml}$, and one volume of water.
- 6.2 **Sulfuric acid**, 1:10 diluted, one volume of sulfuric acid, $\rho = 1,84\text{ g/ml}$, in ten volumes of water.
- 6.3 **Ammonia solution**, 1:1 diluted, one volume of ammonia, $\rho = 0,88\text{ g/ml}$, and one volume of water.
- 6.4 **Ammonia oxalate**, $[(\text{NH}_4)_2\text{C}_2\text{O}_4 \cdot \text{H}_2\text{O}]$, saturated solution at ambient temperature, approximately $\rho = 40\text{ g/l}$.
- 6.5 **Citric acid solution**, 30 % (mass concentration).
- 6.6 **Ammonium chloride solution**, 5 % (mass concentration).
- 6.7 **Solution of bromothymol blue in ethanol**, at 95 %, 0,1 % (mass concentration).
- 6.8 **Solution of bromocresol green in ethanol**, at 95 %, 0,04 % (mass concentration).
- 6.9 **Standard solution of potassium permanganate**, $c = 0,02\text{ mol/l}$.

7 Apparatus

- 7.1 **Filter crucible**, with 5 μm to 20 μm porosity sintered glass.
- 7.2 **Hot water bath**.
- 7.3 **400 ml beaker**.

8 Preparation of the test portion

Using a pipette, take an aliquot portion of the extraction solution obtained according to CEN/TS 15960 or CEN/TS 15961, containing between 15 mg and 50 mg of Ca (= 21 mg to 70 mg of CaO). The volume of this aliquot is v_2 . Pour into a beaker (7.3). If necessary, neutralize, turning of indicator (6.7) from green to blue, with a few drops of the ammonia solution (6.3).

Add 1 ml of the citric acid solution (6.5) and 5 ml of ammonium chloride solution (6.6).

9 Procedure

9.1 Preparation of the calcium oxalate

Add approximately 100 ml of water. Bring to the boil, add eight to ten drops of indicator solution (6.8) and, slowly, 50 ml of a hot ammonium oxalate solution (6.4). If a precipitate forms, dissolve by adding a few drops of hydrochloric acid (6.1). Neutralize very slowly with ammonia solution (6.3) while stirring continuously to a pH of 4,4 to 4,6, turning of indicator (6.8) from green to blue. Place the beaker in a boiling hot water bath (7.2) for approximately 30 min.

Remove the beaker from the bath, leave standing for 1 h and filter into the crucible (7.1).

FprCEN/TS 16196:2010 (E)**9.2 Titration of the oxalate precipitate**

Wash the beaker and crucible until the excess ammonium oxalate has been completely removed (this can be checked by the absence of chloride in the washing water). Place the crucible in the beaker (7.3) and dissolve the precipitate with 50 ml of hot sulfuric acid (6.2). Add water to the beaker in order to obtain a volume of approximately 100 ml. Bring to a temperature of 70 °C to 80 °C and titrate drop by drop with a permanganate solution (6.9) until the pink colour lasts for a minute. This volume is n .

10 Calculation and expression of the result

Calculate the calcium (Ca) content, w_{Ca} , in percent of the fertilizer analyzed according to Equation (1).

$$w_{Ca} = n \times 0,2004 \times \frac{t}{0,02} \times \frac{v_1}{v_2 \times m} \quad (1)$$

where

- n is the amount of permanganate used, in millilitres;
- m is the mass of the test portion, in grams;
- v_2 is the aliquot volume, in millilitres;
- v_1 is the volume of the extraction solution, in millilitres;
- t is the mass concentration of the permanganate solution in moles per litre.

$$\text{CaO (\%)} = \text{Ca (\%)} \times 1,400$$

11 Precision**11.1 Inter-laboratory test**

Repeated inter-laboratory tests have been carried out in 2007 and 2009 with different numbers of participating laboratories and several different samples (see Table A.1 to Table A.4). Repeatability and reproducibility were calculated according to ISO 5725-2.

The values derived from these inter-laboratory tests may not be applicable to concentration ranges and matrices other than those given in Annex A.

11.2 Repeatability

The absolute difference between two independent single test results, obtained with the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will in not more than 5 % of the cases exceed the values of r given in Table 1 and Table 2.

11.3 Reproducibility

The absolute difference between two single test results, obtained with the same method on identical test material in different laboratories by different operators using different equipment, will in not more than 5 % of the cases exceed values of R given in Table 1 and Table 2.

Table 1 — Results ring test 2007

Sample	Extraction method	\bar{x} %	r %	R %
CAN	CEN/TS 15960	6,39	0,19	1,13
	CEN/TS 15961	2,49	0,38	1,85
NPK1:23-4-13+7SO3	CEN/TS 15960	0,51	0,08	0,43
	CEN/TS 15961	0,36	0,07	0,31
NPK2:12-11-18+2+8	CEN/TS 15960	3,49	0,15	1,20
	CEN/TS 15961	0,53	0,10	0,49

Table 2 — Results ring test 2009

Sample	Extraction method	\bar{x} %	r %	R %
CAN	CEN/TS 15960	6,20	0,25	1,2
	CEN/TS 15961	2,61	0,19	4,05
NPK:12-12-17S+2	CEN/TS 15960	5,80	0,13	0,74
	CEN/TS 15961	3,52	0,27	3,93

12 Test report

The test report shall contain at least the following information:

- all information necessary for the complete identification of the sample;
- the test method used with reference to this document;
- the method of preparation of the extraction solution (CEN/TS 15960 or CEN/TS 15961);
- the test results obtained;
- date of sampling and sampling procedure (if known);
- date when the analysis was finished;
- whether the requirement of the repeatability limit has been fulfilled;
- all operating details not specified in this document, or regarded as optional, together with details of any incidents occurred when performing the method, which might have influenced the test result(s).