



SLOVENSKI STANDARD
SIST EN ISO 19123:2007

01-junij-2007

Geografske informacije – Shema za geometrijo podatkovnega sloja in funkcije (ISO 19123:2005)

Geographic information - Schema for coverage geometry and functions (ISO 19123:2005)

Geoinformation - Coverage Geometrie- und Funktionsschema (ISO 19123:2005)

Information géographique - Schéma de la géométrie et des fonctions de couverture (ISO 19123:2005)

iTeh STANDARD PREVIEW
(standards.itih.ai)

[SIST EN ISO 19123:2007](https://standards.itih.ai/catalog/standards/sist/sa1fb566-0dad-4704-8087-e0d1cccd17cc5/sist-en-iso-19123-2007)

Ta slovenski standard je istoveten z: EN ISO 19123:2007

<https://standards.itih.ai/catalog/standards/sist/sa1fb566-0dad-4704-8087-e0d1cccd17cc5/sist-en-iso-19123-2007>

ICS:

35.240.70	Uporabniške rešitve IT v znanosti	IT applications in science
-----------	-----------------------------------	----------------------------

SIST EN ISO 19123:2007

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 19123:2007

<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfcd17cc5/sist-en-iso-19123-2007>

ICS 35.240.70

English Version

Geographic information - Schema for coverage geometry and
functions (ISO 19123:2005)

Information géographique - Schéma de la géométrie et des
fonctions de couverture (ISO 19123:2005)

Geoinformation - Coverage Geometrie- und
Funktionsschema (ISO 19123:2005)

This European Standard was approved by CEN on 25 February 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

[SIST EN ISO 19123:2007](https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfcd17cc5/sist-en-iso-19123-2007)

<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfcd17cc5/sist-en-iso-19123-2007>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of ISO 19123:2005 has been prepared by Technical Committee ISO/TC 211 "Geographic information/Geomatics" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 19123:2007 by Technical Committee CEN/TC 287 "Geographic Information", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2007, and conflicting national standards shall be withdrawn at the latest by September 2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Endorsement notice

The text of ISO 19123:2005 has been approved by CEN as EN ISO 19123:2007 without any modifications.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 19123:2007
<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007>

**Geographic information — Schema for
coverage geometry and functions**

*Information géographique — Schéma de la géométrie et des fonctions
de couverture*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 19123:2007](https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007)

[https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-
e0dfccd17cc5/sist-en-iso-19123-2007](https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 19123:2007](https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007)

<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007>

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	v
Introduction	vi
1 Scope	1
2 Conformance	1
3 Normative references	2
4 Terms, definitions, abbreviated terms and notation	2
4.1 Terms and definitions.....	2
4.2 Abbreviated terms	7
4.3 Notation	7
5 Fundamental characteristics of coverages.....	8
5.1 The context for coverages	8
5.2 The coverage schema	9
5.3 CV_Coverage.....	10
5.4 CV_DomainObject.....	13
5.5 CV_AttributeValues	13
5.6 CV_CommonPointRule.....	14
5.7 CV_DiscreteCoverage	14
5.8 CV_GeometryValuePair.....	15
5.9 CV_ContinuousCoverage	16
5.10 CV_ValueObject	17
5.11 CV_InterpolationMethod	18
5.12 Subclasses of CV_ContinuousCoverage.....	18
6 Discrete coverages	18
6.1 Discrete coverage types	18
6.2 CV_DiscretePointCoverage	19
6.3 CV_PointValuePair.....	20
6.4 CV_DiscreteGridPointCoverage	20
6.5 CV_GridPointValuePair	21
6.6 CV_DiscreteCurveCoverage	21
6.7 CV_CurveValuePair	22
6.8 CV_DiscreteSurfaceCoverage	22
6.9 CV_SurfaceValuePair	24
6.10 CV_DiscreteSolidCoverage	24
6.11 CV_SolidValuePair.....	24
7 Thiessen polygon coverage	25
7.1 Thiessen polygon networks	25
7.2 CV_ThiessenPolygonCoverage.....	25
7.3 CV_ThiessenValuePolygon	27
8 Quadrilateral grid coverages	27
8.1 General.....	27
8.2 Quadrilateral grid geometry.....	27
8.3 CV_Grid.....	30
8.4 CV_GridEnvelope.....	31
8.5 CV_GridPoint.....	31
8.6 CV_GridCoordinate.....	32
8.7 CV_GridCell	32
8.8 CV_Footprint	33
8.9 CV_RectifiedGrid	33

8.10	CV_ReferenceableGrid	34
8.11	CV_ContinuousQuadrilateralGridCoverage	35
8.12	CV_GridValueCell.....	36
8.13	CV_GridPointValuePair	36
8.14	CV_GridValuesMatrix.....	37
8.15	CV_SequenceRule	38
8.16	CV_SequenceType.....	38
9	Hexagonal Grid Coverages	39
9.1	General	39
9.2	CV_HexagonalGridCoverage	39
9.3	CV_GridValuesMatrix.....	41
9.4	CV_ValueHexagon	41
10	Triangulated irregular network (TIN) coverages	41
10.1	General	41
10.2	CV_TINCoverage	43
10.3	CV_ValueTriangle.....	43
11	Segmented curve coverages	44
11.1	General	44
11.2	CV_SegmentedCurveCoverage	45
11.3	CV_ValueCurve	45
11.4	CV_ValueSegment	46
11.5	Evaluation	46
Annex A	(normative) Abstract test suite.....	47
Annex B	(informative) UML Notation.....	51
Annex C	(informative) Interpolation methods.....	56
Annex D	(informative) Sequential enumeration.....	60
Bibliography	65

iTech STANDARD PREVIEW
 (standards.itech.ai)
 SIST EN ISO 19123:2007
<https://standards.itech.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19123 was prepared by Technical Committee ISO/TC 211, *Geographic information/Geomatics*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN ISO 19123:2007](https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007)

<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007>

Introduction

Geographic phenomena fall into two broad categories — discrete and continuous. Discrete phenomena are recognizable objects that have relatively well-defined boundaries or spatial extent. Examples include buildings, streams and measurement stations. Continuous phenomena vary over space and have no specific extent. Examples include temperature, soil composition and elevation. A value or description of a continuous phenomenon is only meaningful at a particular position in space (and possibly time). Temperature, for example, takes on specific values only at defined locations, whether measured or interpolated from other locations.

These concepts are not mutually exclusive. In fact, many components of the landscape may be viewed alternatively as discrete or continuous. For example, a stream is a discrete entity, but its flow rate and water quality index vary from one position to another. Similarly, a highway can be thought of as a feature or as a collection of observations measuring accidents or traffic flow, and an agricultural field is both a spatial object and a set of measurements of crop yield through time.

Historically, geographic information has been treated in terms of two fundamental types called vector data and raster data.

“Vector data” deals with discrete phenomena, each of which is conceived of as a feature. The spatial characteristics of a discrete real-world phenomenon are represented by a set of one or more geometric primitives (points, curves, surfaces or solids). Other characteristics of the phenomenon are recorded as feature attributes. Usually, a single feature is associated with a single set of attribute values. ISO 19107:2003 provides a schema for describing features in terms of geometric and topological primitives.

“Raster data”, on the other hand, deals with real-world phenomena that vary continuously over space. It contains a set of values, each associated with one of the elements in a regular array of points or cells. It is usually associated with a method for interpolating values at spatial positions between the points or within the cells. Since this data structure is not the only one that can be used to represent phenomena that vary continuously over space, this International Standard uses the term “coverage,” adopted from the Abstract Specification of the Open GIS Consortium [1], to refer to any data representation that assigns values directly to spatial position. A coverage is a function from a spatial, temporal or spatiotemporal domain to an attribute range. A coverage associates a position within its domain to a record of values of defined data types.

In this International Standard, coverage is a subtype of feature. A coverage is a feature that has multiple values for each attribute type, where each direct position within the geometric representation of the feature has a single value for each attribute type.

Just as the concepts of discrete and continuous phenomena are not mutually exclusive, their representations as discrete features or coverages are not mutually exclusive. The same phenomenon may be represented as either a discrete feature or a coverage. A city may be viewed as a discrete feature that returns a single value for each attribute, such as its name, area and total population. The city feature may also be represented as a coverage that returns values such as population density, land value or air quality index for each position in the city.

A coverage, moreover, can be derived from a collection of discrete features with common attributes, the values of the coverage at each position being the values of the attributes of the feature located at that position. Conversely, a collection of discrete features can be derived from a coverage, each discrete feature being composed of a set of positions associated with specified attribute values.

Geographic information — Schema for coverage geometry and functions

1 Scope

This International Standard defines a conceptual schema for the spatial characteristics of coverages. Coverages support mapping from a spatial, temporal or spatiotemporal domain to feature attribute values where feature attribute types are common to all geographic positions within the domain. A coverage domain consists of a collection of direct positions in a coordinate space that may be defined in terms of up to three spatial dimensions as well as a temporal dimension. Examples of coverages include rasters, triangulated irregular networks, point coverages and polygon coverages. Coverages are the prevailing data structures in a number of application areas, such as remote sensing, meteorology and mapping of bathymetry, elevation, soil and vegetation. This International Standard defines the relationship between the domain of a coverage and an associated attribute range. The characteristics of the spatial domain are defined whereas the characteristics of the attribute range are not part of this standard.

2 Conformance

This International Standard specifies interfaces for several types of coverage objects. In addition, it supports the interchange of coverage data independently of those interfaces. Thus, it specifies two sets of conformance classes: one for implementation of the interfaces, the other for the exchange of coverage data. Each set includes one conformance class for each type of coverage specified in this International Standard (Table 1).

Table 1 — Conformance classes

Conformance class	Subclause
Simple coverage interface	A.1.1
Discrete coverage interface	A.1.2
Thiessen polygon coverage interface	A.1.3
Quadrilateral grid coverage interface	A.1.4
Hexagonal grid coverage interface	A.1.5
TIN coverage interface	A.1.6
Segmented curve coverage interface	A.1.7
Discrete coverage interchange	A.2.1
Thiessen polygon coverage interchange	A.2.2
Quadrilateral grid coverage interchange	A.2.3
Hexagonal grid coverage interchange	A.2.4
TIN coverage interchange	A.2.5
Segmented curve coverage interchange	A.2.6

In general, the interface conformance classes require implementation of all attributes, associations and operations of relevant classes. This set includes a single conformance class (A.2.1) that supports a simple interface for evaluation of any coverage type, but exposes none of the internal structure of the coverage. The remainder of the set are conformance classes that support interfaces to specific coverage types that expose additional information about the internal structure of the coverage.

The interchange conformance classes require only implementation of the attributes and associations of the relevant classes.

The Abstract Test Suite in Annex A shows the implementation requirements necessary to conform to this International Standard. Table 1 lists the subclauses of the Abstract Test Suite that apply for each conformance class.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 19103:2005, *Geographic information — Conceptual schema language*

ISO 19107:2003, *Geographic information — Spatial schema*

ISO 19108:2002, *Geographic information — Temporal schema*

ISO 19109:2005, *Geographic information — Rules for application schema*

ISO 19111:2003, *Geographic information — Spatial referencing by coordinates*

ISO 19115:2003, *Geographic information — Metadata*

<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfcd17cc5/sist-en-iso-19123-2007>

4 Terms, definitions, abbreviated terms and notation

4.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1.1

continuous coverage

coverage that returns different values for the same feature attribute at different **direct positions** within a single **spatial object**, **temporal object** or **spatiotemporal object** in its **domain**

NOTE Although the domain of a continuous coverage is ordinarily bounded in terms of its spatial and/or temporal extent, it can be subdivided into an infinite number of direct positions.

4.1.2

convex hull

smallest **convex set** containing a given **geometric object**

[adapted from *Dictionary of Computing*:1996 [2]]

4.1.3

convex set

geometric set in which any **direct position** on the straight-line segment joining any two **direct positions** in the **geometric set** is also contained in the **geometric set**

[*Dictionary of Computing*:1996 [2]]

4.1.4**coordinate**

one of a sequence of n numbers designating the position of a **point** in n -dimensional space

[ISO 19111:2003]

4.1.5**coordinate dimension**

number of measurements or axes needed to describe a position in a coordinate system

[ISO 19107:2003]

4.1.6**coordinate reference system**

coordinate system that is related to the real world by a datum

[ISO 19111:2003]

4.1.7**coverage**

feature that acts as a **function** to return values from its **range** for any **direct position** within its spatial, temporal or **spatiotemporal domain**

EXAMPLE Examples include a raster image, polygon overlay or digital elevation matrix.

NOTE In other words, a coverage is a feature that has multiple values for each attribute type, where each direct position within the geometric representation of the feature has a single value for each attribute type.

4.1.8**coverage geometry**

configuration of the **domain** of a **coverage** described in terms of **coordinates**

4.1.9**curve**

1-dimensional **geometric primitive**, representing the continuous image of a line

[ISO 19107:2003]

NOTE The boundary of a curve is the set of points at either end of the curve.

4.1.10**Delaunay triangulation**

network of triangles such that the circle passing through the vertices of any triangle does not contain, in its interior, the vertex of any other triangle

4.1.11**direct position**

position described by a single set of **coordinates** within a **coordinate reference system**

[ISO 19107:2003]

4.1.12**discrete coverage**

coverage that returns the same **feature attribute** values for every **direct position** within any single **spatial object**, **temporal object** or **spatiotemporal object** in its **domain**

NOTE The domain of a discrete coverage consists of a finite set of spatial, temporal, or spatiotemporal objects.

4.1.13

domain

well-defined set

[ISO/TS 19103]

NOTE Domains are used to define the domain and range of operators and functions.

4.1.14

evaluation

〈**coverage**〉 determination of the values of a **coverage** at a **direct position** within the **domain** of the coverage

4.1.15

feature

0 abstraction of real world phenomena

[ISO 19101]

4.1.16

feature attribute

characteristic of a **feature**

[ISO 19101]

4.1.17

function

rule that associates each element from a **domain** (source or domain of the function) to a unique element in another **domain** (target, co-domain or **range**)

[ISO 19107:2003]

iTeh STANDARD PREVIEW
(standards.iteh.ai)
SIST EN ISO 19123:2007
<https://standards.iteh.ai/catalog/standards/sist/ea1fb566-0dad-4704-8087-e0dfccd17cc5/sist-en-iso-19123-2007>

4.1.18

geometric object

spatial object representing a **geometric set**

[ISO 19107:2003]

4.1.19

geometric primitive

geometric object representing a single, connected, homogeneous element of space

[ISO 19107:2003]

4.1.20

geometric set

set of **direct positions**

[ISO 19107:2003]

4.1.21

geometry value object

object composed of a set of **geometry value pairs**

4.1.22

geometry value pair

ordered pair composed of a **spatial object**, a temporal object or a **spatiotemporal object** and a **record of feature attribute values**

4.1.23**grid**

network composed of two or more sets of **curves** in which the members of each set intersect the members of the other sets in an algorithmic way

NOTE The curves partition a space into grid cells.

4.1.24**grid point**

point located at the intersection of two or more **curves** in a **grid**

4.1.25**inverse evaluation**

<coverage> selection of a set of objects from the **domain** of a **coverage** based on the **feature attribute** values associated with the objects

4.1.26**point**

0-dimensional **geometric primitive**, representing a position

[ISO 19107:2003]

NOTE The boundary of a point is the empty set.

4.1.27**point coverage**

coverage that has a **domain** composed of **points**

4.1.28**polygon coverage**

coverage that has a **domain** composed of **polygons**

4.1.29**range**

<coverage> set of **feature attribute** values associated by a **function** with the elements of the **domain** of a **coverage**

4.1.30**raster**

usually rectangular pattern of parallel scanning lines forming or corresponding to the display on a cathode ray tube

NOTE A raster is a type of grid.

4.1.31**record**

finite, named collection of related items (objects or values)

[ISO 19107:2003]

NOTE Logically, a record is a set of pairs <name, item>.

4.1.32**rectified grid**

grid for which there is an affine transformation between the grid **coordinates** and the coordinates of an external **coordinate reference system**

NOTE If the coordinate reference system is related to the earth by a datum, the grid is a georectified grid.