



SLOVENSKI STANDARD
SIST EN 1380:2009

01-september-2009

BUXca Yý U
SIST EN 1380:2000

Lesene konstrukcije - Metode preskušanja - Nosilni žebljani spoji

Timber structures - Test methods - Load bearing nails, screws, dowels and bolts

Holzbauwerke - Prüfverfahren - Tragende Nagelverbindungen

Structures en bois - Méthode d'essai - Pointes, tire-fonds, broches et boulons porteurs
iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: SIST EN 1380:2009

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6fdeb0383e/sist-en-1380-2009>

ICS:

91.080.20 Lesene konstrukcije Timber structures

SIST EN 1380:2009

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1380:2009

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 1380

April 2009

ICS 91.080.20

Supersedes EN 1380:1999

English Version

Timber structures - Test methods - Load bearing nails, screws, dowels and bolts

Structures en bois - Méthode d'essai - Pointes, tire-fonds,
broches et boulons porteurs

Holzbauwerke - Prüfverfahren - Tragende
Nagelverbindungen

This European Standard was approved by CEN on 2 November 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW
(standardsite.com)
<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 Symbols and abbreviations	5
5 Requirements	5
5.1 Timber	5
5.2 Wood-based products	5
5.3 Metal plates and dowel type fasteners	5
6 Test methods.....	6
6.1 General.....	6
6.2 Conditioning.....	6
6.3 Fabrication of the test pieces	6
6.4 Preparation of the test pieces	6
6.4.1 Load parallel to grain	6
6.4.2 Load perpendicular to grain	9
6.4.3 Determination of relative displacements	14
6.5 Test procedure	14
6.6 Test results	14
6.7 Test report	14

SIST EN 1380:2009

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>

Foreword

This document (EN 1380:2009) has been prepared by Technical Committee CEN/TC 124 "Timber structures", the secretariat of which is held by SFS.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2009, and conflicting national standards shall be withdrawn at the latest by October 2009.

This document supersedes EN 1380:1999.

The first version of this European Standard was published in September 1999 and considered only connections with nails. When the product standard for dowel type fasteners EN 14592 became available the scope of EN 1380 was expanded. Therefore, this revised version covers dowel type fasteners as nails, screws, dowels and bolts.

Connections with load bearing staples are considered in EN 1381:1999.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

(standards.iteh.ai)

SIST EN 1380:2009

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>

EN 1380:2009 (E)**1 Scope**

This European Standard specifies test methods for determining the strength and deformation characteristics of laterally loaded connections with nail, screws, dowels and bolts in load-bearing timber structures.

The methods assess connections with members of timber (solid timber or glued laminated timber) or wood-based products or metal plates (but not punched metal plate fasteners) in the combination proposed for use in service.

The methods are used to determine load-slip characteristics and maximum load of connections where various angles between the applied force and the timber grain direction, or the main direction of the wood-based products, respectively, are possible.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 322, *Wood-based panels — Determination of moisture content*

EN 323, *Wood-based panels — Determination of density*

EN 13183-2, *Moisture content of a piece of sawn timber — Part 2: Estimation by electrical resistance method*

EN 14080, *Timber structures — Glued laminated timber — Requirements*

EN 14081-1, *Timber structures — Strength graded structural timber with rectangular cross section — Part 1: General requirements*

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>

EN 14358, *Timber structures — Calculation of characteristic 5-percentile values and acceptance criteria for a sample*

EN 14592, *Timber structures — Dowel-type fasteners — Requirements*

EN 26891:1991, *Timber structures — Joints made with mechanical fasteners — General principles for the determination of strength and deformation characteristics (ISO 6891:1983)*

EN 28970, *Timber structures — Testing of joints made with mechanical fasteners — Requirements for wood density (ISO 8970:1989)*

ISO 3131, *Wood — Determination of density for physical and mechanical tests*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

deformation of the connection

mean value of the measurements of the relative displacements of the members

3.2

dowel type fasteners

elements such as nails, screws, dowels and bolts as defined by EN 14592

4 Symbols and abbreviations

For the purposes of this document, the following symbols and abbreviations apply.

b width of member cross-section, in millimetres

F load, in newtons

t member thickness, in millimetres

ITEH STANDARD PREVIEW
(standards.iteh.ai)

5 Requirements

5.1 Timber

[SIST EN 1380:2009
https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009](https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009)

The timber (solid timber or glued laminated timber) shall satisfy the requirements of EN 14080, EN 14081-1 and shall be selected in accordance with either of the methods given in EN 28970.

For each test piece, the individual members to be joined shall be selected to ensure a test piece of balanced density. For a group of similar test pieces, separate planks shall be used for each test piece.

NOTE The members should be free from major defects, which could lead to premature failure in the area away from the fasteners.

5.2 Wood-based products

The specification of the wood based products shall be established. The products used for the individual members of the test pieces shall be representative of the class or range of product to which they belong and the relevant properties shall be declared.

One unique grade shall be used to make the test pieces. For each test piece, the individual members in the connection shall be selected from separate pieces of material.

5.3 Metal plates and dowel type fasteners

The specification of the metal plates shall be established.

The requirements for dowel type fasteners as given in EN 14592 apply.

EN 1380:2009 (E)**6 Test methods****6.1 General**

The moisture content and density of the timber or wood-based products members at test shall be determined as specified in EN 13183-2, ISO 3131, EN 322 and EN 323 as appropriate.

6.2 Conditioning

The test pieces shall be manufactured with the timber or wood-based products at an equilibrium moisture content corresponding to $(20 \pm 2) ^\circ\text{C}$ and $(85 \pm 5) \%$ relative humidity. The material is conditioned when it attains constant mass. Constant mass is considered to be attained when the results of two successive weightings, carried out at an interval of 6 h, do not differ by more than 0,1 % of the mass of the material.

After manufacture but prior to testing the test pieces shall be stored for at least one week at $(20 \pm 2) ^\circ\text{C}$ and $(65 \pm 5) \%$ relative humidity.

For certain investigations other moisture conditioning can be appropriate, and shall be reported.

NOTE For some hardwoods a much longer storing period can be necessary or the test pieces should be made with appropriate gaps between the members.

6.3 Fabrication of the test pieces

If there are no special requirements, timber members shall be planed. Test pieces shall be fabricated with the fasteners perpendicular to the member surface. The insertion of the dowel type fasteners shall follow normal preparation (e.g. pre-boring) and practice, which shall be reported. The number of fasteners shall reflect the actual use in practice.

In principle the connection is symmetrical with respect to the direction of the load comprising the geometry of the timber members and number and penetration depth of the fasteners.

For nails and screws the depth of the fastener head indentation will have an influence on the test result, particularly for connections loaded in double shear. Therefore, if the fabrication technique permits the fastener heads shall protrude above the surface.

6.4 Preparation of the test pieces**6.4.1 Load parallel to grain**

For connections with fasteners that do not pass fully through all members:

- consisting solely of timber or wood-based products (or combinations thereof) the test pieces shall be fabricated either as

- a) three-member connections with dowel type fasteners from each side, loaded in single shear, see Figure 1, or
- b) three-member connections with dowel type fasteners from each side, loaded in double shear, see Figure 2.

The minimum end length l is 50 mm as shown in Figures 1 and 2 may not be appropriate to thin timber or wood-based products subjected to compression loads.

- with metal plates connected with dowel type fasteners to timber or wood-based products members, the test pieces shall be fabricated either as

- a) single shear test pieces with dowel type fasteners from each side and with the side members of metal plates, or
- b) double shear test pieces with dowel type fasteners from each side and with the metal plate as central member.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 1380:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/ad9c2d6f-1d7a-4067-ab51-1d6f9cb0383e/sist-en-1380-2009>