



SLOVENSKI STANDARD
SIST ISO 199:2001

01-julij-2001

Kotalni ležaji - Aksialni ležaji - Tolerance

Rolling bearings -- Thrust bearings -- Tolerances

Roulements -- Butées -- Tolérances

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ISO 199:1997

[SIST ISO 199:2001](https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001)

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

ICS:

21.100.20 Kotalni ležaji Rolling bearings

SIST ISO 199:2001

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 199:2001

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

INTERNATIONAL STANDARD

ISO
199

Second edition
1997-12-01

Rolling bearings — Thrust bearings — Tolerances

Roulements — Butées — Tolérances

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 199:2001

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>



Reference number
ISO 199:1997(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 199 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 4, *Tolerances*.

This second edition cancels and replaces the first edition (ISO 199:1979), which has been technically revised.

[SIST ISO 199:2001](https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001)

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

© ISO 1997

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet central@iso.ch
X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Rolling bearings — Thrust bearings — Tolerances

1 Scope

This International Standard specifies tolerances for boundary dimensions (except chamfer dimensions) and for running accuracy of thrust rolling bearings with flat back faces specified in ISO 104.

This International Standard does not apply to certain thrust bearings, e.g. needle roller bearings, or for particular fields of application, e.g. special precision bearings.

Chamfer dimension limits are given in ISO 582. [SIST ISO 199:2001](https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001)

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 104:1994, *Rolling bearings — Thrust bearings — Boundary dimensions, general plan.*

ISO 582:1995, *Rolling bearings — Chamfer dimensions — Maximum values.*

ISO 1132:1980, *Rolling bearings — Tolerances — Definitions.*

ISO 5593:1997, *Rolling bearings — Vocabulary.*

3 Definitions

For the purposes of this International Standard the definitions given in ISO 1132 and ISO 5593 apply.

4 Symbols

The symbols (except those for tolerances) and the values given in the tables denote nominal dimensions unless specified otherwise.

d bore diameter of shaft washer, single-direction bearing

d_2 bore diameter of shaft washer, double-direction bearing

Δ_{dmp} deviation of mean bore diameter in a single plane of shaft washer, single-direction bearing

Δ_{d2mp} deviation of mean bore diameter in a single plane of shaft washer, double-direction bearing

D outside diameter of housing washer

Δ_{Dmp} deviation of mean outside diameter in a single plane of housing washer

S_e variation in thickness between housing washer raceway and back face

NOTE — Applies only to ball thrust bearings and cylindrical roller thrust bearings with 90° contact angle.

S_i variation in thickness between shaft washer raceway and back face

NOTE — Applies only to ball thrust bearings and cylindrical roller thrust bearings with 90° contact angle.

T bearing height, single-direction bearing

T_1 bearing height, double direction bearing

Δ_{Ts} deviation of the actual bearing height, single-direction bearing

Δ_{T1s} deviation of the actual bearing height, double-direction bearing

V_{dp} variation of bore diameter in a single plane of shaft washer, single-direction bearing

V_{d2p} variation of bore diameter in a single plane of shaft washer, double-direction bearing

V_{Dp} variation of outside diameter in a single radial plane of housing washer

5 Tolerances

Tables 1 to 8 give the tolerances for single-direction and double-direction thrust bearings.

5.1 Normal tolerance class

See tables 1 and 2.

Table 1 — Shaft washer and bearing height

Tolerance values in micrometres

d and d_2 mm		$\Delta_{d_{mp}}, \Delta_{d_{2mp}}$		$V_{d_p}, V_{d_{2p}}$	S_i	Δ_{T_s}		$\Delta_{T_{1s}}$	
>	\leq	high	low	max.	max.	high	low	high	low
—	18	0	-8	6	10	+20	-250	+150	-400
18	30	0	-10	8	10	+20	-250	+150	-400
30	50	0	-12	9	10	+20	-250	+150	-400
50	80	0	-15	11	10	+20	-300	+150	-500
80	120	0	-20	15	15	+25	-300	+200	-500
120	180	0	-25	19	15	+25	-400	+200	-600
180	250	0	-30	23	20	+30	-400	+250	-600
250	315	0	-35	26	25	+40	-400	—	—
315	400	0	-40	30	30	+40	-500	—	—
400	500	0	-45	34	30	+50	-500	—	—
500	630	0	-50	38	35	+60	-600	—	—
630	800	0	-75	55	40	+70	-750	—	—
800	1 000	0	-100	75	45	+80	-1 000	—	—
1 000	1 250	0	-125	95	50	+100	-1 400	—	—
1 250	1 600	0	-160	120	60	+120	-1 600	—	—
1 600	2 000	0	-200	150	75	+140	-1 900	—	—
2 000	2 500	0	-250	190	90	+160	-2 300	—	—

NOTE — For double-direction bearings the values apply only up to and including $d_2 = 190$ mm.

SIST ISO 199:2001

<https://standards.iteh.org/standards/sist/199-2001/537-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

Table 2 — Housing washer

Tolerance values in micrometres

D mm		$\Delta_{D_{mp}}$		V_{D_p}	S_e
>	\leq	high	low	max.	max.
10	18	0	-11	8	Identical to S_i of shaft washer of same bearing
18	30	0	-13	10	
30	50	0	-16	12	
50	80	0	-19	14	
80	120	0	-22	17	
120	180	0	-25	19	
180	250	0	-30	23	
250	315	0	-35	26	
315	400	0	-40	30	
400	500	0	-45	34	
500	630	0	-50	38	
630	800	0	-75	55	
800	1 000	0	-100	75	
1 000	1 250	0	-125	95	
1 250	1 600	0	-160	120	
1 600	2 000	0	-200	150	
2 000	2 500	0	-250	190	
2 500	2 850	0	-300	225	

NOTE — For double-direction bearings the values apply only up to and including $D = 360$ mm.

5.2 Tolerance class 6

See tables 3 and 4.

Table 3 — Shaft washer and bearing height

Tolerance values in micrometres

d and d_2 mm		$\Delta_{d_{mp}}, \Delta_{d_{2mp}}$		$V_{d_p}, V_{d_{2p}}$	S_i	Δ_{T_s}		$\Delta_{T_{1s}}$	
>	\leq	high	low	max.	max.	high	low	high	low
—	18	0	-8	6	5	+20	-250	+150	-400
18	30	0	-10	8	5	+20	-250	+150	-400
30	50	0	-12	9	6	+20	-250	+150	-400
50	80	0	-15	11	7	+20	-300	+150	-500
80	120	0	-20	15	8	+25	-300	+200	-500
120	180	0	-25	19	9	+25	-400	+200	-600
180	250	0	-30	23	10	+30	-400	+250	-600
250	315	0	-35	26	13	+40	-400	—	—
315	400	0	-40	30	15	+40	-500	—	—
400	500	0	-45	34	18	+50	-500	—	—
500	630	0	-50	38	21	+60	-600	—	—
630	800	0	-75	55	25	+70	-750	—	—
800	1 000	0	-100	75	30	+80	-1 000	—	—
1 000	1 250	0	-125	95	35	+100	-1 400	—	—
1 250	1 600	0	-160	120	40	+120	-1 600	—	—
1 600	2 000	0	-200	150	45	+140	-1 900	—	—
2 000	2 500	0	-250	190	50	+160	-2 300	—	—

NOTE — For double-direction bearings the values apply only up to and including $d_2 = 190$ mm.

SIST ISO 199:2001

<https://standards.iteh.ai/catalog/standards/sist/01af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>
Table 4 — Housing washer

Tolerance values in micrometres

D mm		$\Delta_{D_{mp}}$		V_{D_p}	S_e
>	\leq	high	low	max.	max.
10	18	0	-11	8	Identical to S_i of shaft washer of same bearing
18	30	0	-13	10	
30	50	0	-16	12	
50	80	0	-19	14	
80	120	0	-22	17	
120	180	0	-25	19	
180	250	0	-30	23	
250	315	0	-35	26	
315	400	0	-40	30	
400	500	0	-45	34	
500	630	0	-50	38	
630	800	0	-75	55	
800	1 000	0	-100	75	
1 000	1 250	0	-125	95	
1 250	1 600	0	-160	120	
1 600	2 000	0	-200	150	
2 000	2 500	0	-250	190	
2 500	2 850	0	-300	225	

NOTE — For double-direction bearings the values apply only up to and including $D = 360$ mm.

5.3 Tolerance class 5

See tables 5 and 6.

Table 5 — Shaft washer and bearing height

Tolerance values in micrometres

d and d_2 mm		$\Delta_{d_{mp}}, \Delta_{d_{2mp}}$		$V_{d_p}, V_{d_{2p}}$	S_i	Δ_{T_s}		$\Delta_{T_{1s}}$	
>	≤	high	low	max.	max.	high	low	high	low
—	18	0	-8	6	3	+20	-250	+150	-400
18	30	0	-10	8	3	+20	-250	+150	-400
30	50	0	-12	9	3	+20	-250	+150	-400
50	80	0	-15	11	4	+20	-300	+150	-500
80	120	0	-20	15	4	+25	-300	+200	-500
120	180	0	-25	19	5	+25	-400	+200	-600
180	250	0	-30	23	5	+30	-400	+250	-600
250	315	0	-35	26	7	+40	-400	—	—
315	400	0	-40	30	7	+40	-500	—	—
400	500	0	-45	34	9	+50	-500	—	—
500	630	0	-50	38	11	+60	-600	—	—
630	800	0	-75	55	13	+70	-750	—	—
800	1 000	0	-100	75	15	+80	-1 000	—	—
1 000	1 250	0	-125	95	18	+100	-1 400	—	—
1 250	1 600	0	-160	120	25	+120	-1 600	—	—
1 600	2 000	0	-200	150	30	+140	-1 900	—	—
2 000	2 500	0	-250	190	40	+160	-2 300	—	—

NOTE — For double-direction bearings the values apply only up to and including $d_2 = 190$ mm.

SIST ISO 199:2001

<https://standards.iteh.ai/catalog/standards/sist/91af53c7-d379-42fb-9e7c-f5bf810dad48/sist-iso-199-2001>

Table 6 — Housing washer

Tolerance values in micrometres

D mm		$\Delta_{D_{mp}}$		V_{D_p}	S_e
>	≤	high	low	max.	max.
10	18	0	-11	8	Identical to S_i of shaft washer of same bearing
18	30	0	-13	10	
30	50	0	-16	12	
50	80	0	-19	14	
80	120	0	-22	17	
120	180	0	-25	19	
180	250	0	-30	23	
250	315	0	-35	26	
315	400	0	-40	30	
400	500	0	-45	34	
500	630	0	-50	38	
630	800	0	-75	55	
800	1 000	0	-100	75	
1 000	1 250	0	-125	95	
1 250	1 600	0	-160	120	
1 600	2 000	0	-200	150	
2 000	2 500	0	-250	190	
2 500	2 850	0	-300	225	

NOTE — For double-direction bearings the values apply only up to and including $D = 360$ mm.