
**Agricultural wheeled tractors —
Operator's seat — Laboratory
measurement of transmitted vibration**

*Tracteurs agricoles à roues — Siège du conducteur — Mesurage en
laboratoire des vibrations transmises*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 5007:2003](https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003)

<https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 5007:2003](https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003)

<https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003>

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 General	3
5.1 Evaluation criteria	3
5.2 Instrumentation and frequency analysis	3
5.3 Safety	3
6 Test conditions and procedure	3
6.1 General	3
6.2 Simulation of vibration (see ISO 10326-1:1992, Clause 5)	3
6.3 Test seat	4
6.4 Test person and posture	4
6.5 Input vibration	5
6.6 Tolerances on input vibration (see ISO 10326-1:1992, 8.1)	6
7 Acceptance criteria	7
7.1 SEAT factor	7
7.2 Damping performance	7
7.3 Damper adjustment	7
8 Seat identification	8
9 Test report	8
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 5007 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 2, *Common tests*.

This second edition cancels and replaces the first edition (ISO 5007:1990), which has been technically revised.

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 5007:2003](https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003)

<https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003>

Introduction

The operators of agricultural tractors are often exposed to a low frequency vibration environment, partly caused by the movement of the vehicles over uneven ground and the tasks carried out. The seat constitutes the last stage of suspension before the driver. In order for it to be efficient at attenuating the vibration, the suspension seat should be chosen in accordance with the dynamic characteristics of the vehicle. The design of the seat and its suspension is a compromise between the requirements of reducing the effects of vibration and shock on the operator, and of providing stable support so that the operator can control the machine effectively.

Thus, because seat vibration attenuation is a compromise of a number of factors, the selection of seat vibration parameters needs to be taken in context with the other requirements for the seat.

The performance criteria provided in this International Standard have been set in accordance with that which is attainable using what is at present the best design practice. They do not necessarily ensure the complete protection of the operator against the effects of vibration and shock, and could be revised in the light of future developments and improvements in suspension design.

The test inputs included in this International Standard are based on a very large number of measurements taken *in situ* on agricultural tractors operating on the 100 m OECD standard track defined in ISO 5008, as well as on tractors operating under severe but typical field conditions. The test methods are based on ISO 10326-1, a general method applicable to seats for different types of vehicles.

(<https://standards.iteh.ai>)
Document Preview

[ISO 5007:2003](https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003)

<https://standards.iteh.ai/catalog/standards/iso/8ab5cf2c-af26-40fa-8133-e813ce4b93e9/iso-5007-2003>

Agricultural wheeled tractors — Operator's seat — Laboratory measurement of transmitted vibration

1 Scope

This International Standard specifies, in accordance with ISO 10326-1, a laboratory method for measuring and evaluating the effectiveness of the suspension of operator seats on agricultural wheeled tractors. It also specifies acceptance criteria based on the test results, while defining the input spectral classes relating to three classes of agricultural tractor with rubber tyres, unsprung rear axles and no low-frequency cab isolation — those of up to 3 600 kg (class 1), those of from 3 600 kg to 6 500 kg (class 2), and those of over 6 500 kg (class 3) — each of which defines a group of machines having similar vibration characteristics.

The method tests the effectiveness of the seat suspension in reducing the vertical whole-body vibration transmitted to the operator at frequencies of from 1 Hz to 20 Hz. It is not applicable to vibration reaching the operator other than through the seat (e.g. that sensed by the operator's feet on the platform or control pedals or hands on the steering wheel).

NOTE The tests and criteria defined in this International Standard are intended for operator seats used in agricultural tractors of conventional design. Tractors with design features such as isolated front or rear axles or both and low-frequency cab suspensions, which result in significantly different vibration characteristics, can be tested in accordance with ISO 5008 to determine a whole body vibration emission value or using other standards developed for measuring and evaluating the effectiveness of the seat suspension on such vehicles.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Vibration and shock — Vocabulary*

ISO 2631-1:1997, *Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 1: General requirements*

ISO 8041, *Human response to vibration — Measuring instrumentation*

ISO 10326-1:1992, *Mechanical vibration — Laboratory method for evaluating vehicle seat vibration — Part 1: Basic requirements*

ISO 13090-1:1998, *Mechanical vibration and shock — Guidance on safety aspects of tests and experiments with people — Part 1: Exposure to whole-body mechanical vibration and repeated shock*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041 and the following apply.

3.1

whole-body vibration

vibration transmitted to the body as a whole through the buttocks of a seated operator

**3.2
input spectral class**

tractors having similar ride vibration characteristics at the seat attachment point, grouped by virtue of various mechanical characteristics

**3.3
unballasted mass**

mass of tractor in working order with full tanks and radiators, and including, where relevant, the mass of protective structures, but less the mass of the operator and without removable ballast weights, special equipment or other loads

**3.4
operator seat**

portion of the machine provided for the purpose of supporting the buttocks and back of the seated operator, including any suspension system and other mechanisms provided (for example, for adjusting the seat position)

**3.5
frequency analysis**

process of arriving at a quantitative description of vibration amplitude as a function of frequency

**3.6
measuring period**

time duration in which vibration data for analysis is obtained

4 Symbols and abbreviated terms

See Table 1.

Table 1 — Symbols and abbreviated terms

Symbol/abbreviation	Description
$a_P(f_r)$	Unweighted rms value of the measured vertical acceleration at the platform under the seat (see Figure 1) <i>measured</i> at the resonance frequency when the seat is excited at the resonance frequency
a_{P12}^*, a_{P34}^*	Unweighted rms value of the target vertical acceleration at the platform under the seat (see Figure 1) between frequencies f_1 and f_2 , or f_3 and f_4
a_{P12}, a_{P34}	Unweighted rms value of the measured vertical acceleration at the platform under the seat (see Figure 1) between frequencies f_1 and f_2 , or f_3 and f_4
$a_S(f_r)$	Unweighted rms value of the measured vertical acceleration at the seat disc <i>measured</i> at the resonance frequency when the seat is excited at the resonance frequency
a_{WP12}^*, a_{WP34}^*	Weighted rms value of the target vertical acceleration at the platform under the seat (see Figure 1) platform between frequencies f_1 and f_2 , or f_3 and f_4
a_{WP12}	Weighted rms value of the measured vertical acceleration at the platform under the seat (see Figure 1) between frequencies f_1 and f_2
a_{WS12}	Weighted rms value of the measured vertical acceleration at the seat disc (see Figure 1) between frequencies f_1 and f_2
B_e	Resolution bandwidth, expressed in Hertz
f	Frequency, expressed in Hertz
f_r	Frequency at resonance, expressed in Hertz
$G_P(f)$	Measured PSD of the vertical vibration at the platform (seat base)
$G_P^*(f)$	Target PSD of the vertical vibration at the platform (seat base)
$G_{PL}^*(f)$	Lower limit for the measured PSD of the vertical vibration at the platform (seat base)

Table 1 (continued)

Symbol/abbreviation	Description
$G_{PU}^*(f)$	Upper limit for the measured PSD of the vertical vibration at the platform (seat base)
$H(f_r)$	Transmissibility at the resonance frequency
PSD	Power spectral density, expressed as acceleration squared per unit bandwidth, $(m/s^2)^2/Hz$
rms	Root mean square
SEAT	Seat effective amplitude transmissibility
F_{SEAT}	Seat effective amplitude transmissibility factor (see Table 2)
T_s	Sampling time, expressed in seconds

5 General

5.1 Evaluation criteria

The laboratory simulated machine vertical vibration, specified as input spectral class, is based on representative measured data from tractors driven on a standardized test track and on data obtained from field tests under various conditions of use. The test input for a particular tractor class is a representative envelope for the machines within that class.

Two criteria are used for the evaluation of seat vibration:

- the SEAT (seat effective amplitude transmissibility) factor in accordance with ISO 10326-1:1992, 9.1, but with frequency weighting in accordance with ISO 2631-1;
- the maximum transmissibility ratio in the damping test in accordance with ISO 10326-1:1992, 9.2.

5.2 Instrumentation and frequency analysis

The measuring equipment shall be in accordance with ISO 8041 (type 1 instrument) and ISO 10326-1:1992, Clause 4. The frequency weighting shall include the effects of the band limiting filters and shall be in accordance with ISO 2631-1.

5.3 Safety

Safety precautions shall be in accordance with ISO 13090-1.

Any compliant end-stops or devices normally fitted to production versions of the seat to be tested to minimize the effect of suspension over travel shall be in place for the dynamic tests.

6 Test conditions and procedure

6.1 General

The test conditions and test procedure shall be in accordance with ISO 10326-1:1992, Clauses 7 and 8.

6.2 Simulation of vibration (see ISO 10326-1:1992, Clause 5)

A platform whose dimensions correspond approximately to those of the operator's platform on an agricultural tractor shall be mounted on a vibrator capable of generating vibration along the vertical axis (see Figure 1).

The vibrator should be capable of simulating sinusoidal vibration having a peak-to-peak displacement of at least $\pm 7,5$ cm at a frequency of 2 Hz (see 6.5.1).

6.3 Test seat

6.3.1 General

The operator seat for the test shall be representative of series-produced models, with regard to construction, static and vibration characteristics and other features which may affect the vibration test result.

6.3.2 Run-in

Before the test, the suspension seats shall be run in under conditions stipulated by the manufacturer. If the manufacturer does not state such conditions, then the seat shall be run in for a minimum of 5 000 cycles, with measurements at 1 000-cycle intervals.

For this purpose, the seat shall be loaded with an inert mass of 75 kg ($\pm 1\%$) and adjusted to the mass in accordance with the manufacturer's instructions. If the manufacturer's instructions for seat adjustment are not available, then the seat shall be adjusted to the centre of the stroke. The seat and suspension shall be mounted on the platform of a vibrator, and a sinusoidal input vibration shall be applied to the platform at approximately the natural frequency of the suspension and inert mass. This input vibration shall have a peak-to-peak displacement sufficient to cause movement of the seat suspension over approximately 75 % of its stroke. A platform peak-to-peak displacement of approximately 40 % of the seat suspension stroke is likely to achieve this. Care should be taken to ensure against overheating of the suspension damper during the running-in, for which forced cooling is acceptable.

The seat shall be considered to have been run in if the value for the vertical transmissibility remains within a tolerance of $\pm 5\%$ when three successive measurements are performed under these run-in conditions. The time interval between two measurements shall be half an hour or 1 000 cycles, whichever is the lesser, with the seat being constantly run in.

6.3.3 Seat adjustment

The seat shall be adjusted to the weight of the test person in accordance with the manufacturer's instructions.

The seat fore-aft adjustment shall be set to the centre of its adjustment range.

For seats where the suspension stroke available is unaffected by the adjustment for seat height or test-person weight, testing shall be performed with the seat adjusted to the centre of the stroke.

For seats where the suspension stroke available is affected by the adjustment of the seat height or by test-person weight, testing shall be performed in the lowest position that provides the full working suspension stroke as specified by the seat manufacturer.

When the inclination of the backrest is adjustable, it shall be set approximately upright, inclined slightly backwards (approximately $10^\circ \pm 5^\circ$).

6.4 Test person and posture

The simulated input vibration test shall be performed with two persons, one lighter than the other. The lighter person shall have a total mass of 52 kg to 55 kg, of which not more than 5 kg may be carried in a belt around the waist. The heavier person shall have a total mass of 98 kg to 103 kg, of which not more than 8 kg may be carried in a belt around the waist.

Each person shall adopt a natural upright position on the seat and maintain this position throughout the test (see Figure 1). For this reason, the position of the arms and angles of knees and ankles have been specified in Figure 1.

The use of a seat belt may affect the test results. If a seat belt is used during the test, the belt should be adjusted by tightening it to a comfortable level, while noting that particular belt length, then loosening it by increasing the noted belt length by an additional 50 mm.