



SLOVENSKI STANDARD
SIST EN ISO 3171:1999
01-november-1999

BUZBYHY_c jbyE5 j hca Uh] bc'j ncf Yb^Y]n^Wj cj cXUfIGC'' %&%% , , Ł

Petroleum liquids - Automatic pipeline sampling (ISO 3171:1988)

Produits pétroliers liquides - Echantillonnage automatique en oléoduc (ISO 3171:1988)

Ta slovenski standard je istoveten z: **EN ISO 3171:1999**

[SIST EN ISO 3171:1999](https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999)

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>

ICS:

75.080	Naftni proizvodi na splošno	Petroleum products in general
--------	-----------------------------	-------------------------------

SIST EN ISO 3171:1999

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 3171:1999

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN ISO 3171

March 1999

ICS 75.080

English version

Petroleum liquids - Automatic pipeline sampling (ISO
3171:1988)

Produits pétroliers liquides - Echantillonnage automatique
en oléoduc (ISO 3171:1988)

This European Standard was approved by CEN on 18 February 1999.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Page 2
EN ISO 3171:1999

Foreword

The text of the International Standard from Technical Committee ISO/TC 28 "Petroleum products and lubricants" of the International Organization for Standardization (ISO) has been taken over as an European Standard by Technical Committee CEN/TC 19 "Petroleum products, lubricants and related products", the secretariat of which is held by NNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 1999, and conflicting national standards shall be withdrawn at the latest by September 1999.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of the International Standard ISO 3171:1988 has been approved by CEN as a European Standard without any modification.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 3171:1999

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>



REPUBLIKA ČESKÁ
MĚŠTŮ A OBČÍ
MĚŠTŮ A OBČÍ
MĚŠTŮ A OBČÍ
MĚŠTŮ A OBČÍ

.....
MĚŠTŮ A OBČÍ



INTERNATIONAL STANDARD

ISO
3171

Second edition
1988-12-01



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Petroleum liquids — Automatic pipeline sampling

Produits pétroliers liquides — Échantillonnage automatique en oléoduc

ITeH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 3171:1999

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>

ISO 3171 : 1988 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 3171 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*.

This second edition cancels and replaces the first edition (ISO 3171 : 1975) of which it constitutes a technical revision.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

Contents

	Page
0 Introduction	1
1 Scope and field of application	1
2 References	2
3 Definitions	2
4 Principles	4
5 Selection of sampling point (including stream conditioning)	6
6 Profile testing	7
7 Sampling probe design	9
8 Sampler design and installation	9
9 Control equipment	10
10 Flow measurement	11
11 Sample receivers and containers	12
12 Sample handling	13
13 Safety precautions	15
14 Operating procedures	15
15 Proving the sampling system	17
16 Estimation of overall sampling system uncertainty	20
17 Bibliography	23
Annexes	
A Estimating water-in-oil dispersion	32
B Example of water concentration profile tests at a crude oil terminal	51
C Guide for initial screening of potential sampling locations	54

ISO 3171 : 1988 (E)

Tables

1	Recommended sampler characteristics for crude oil and refined products	11
2	Typical operating parameters for intermittent fixed-grab-volume samplers . . .	16
3	Typical sampler maintenance and performance report for an intermittent grab sampler	18
4	Sampling test ratings for injected water concentrations of 1 % and above . . .	20
5	Symbols	34
6	Suggested resistance coefficients	36
7	Values of β for bends	37
8	Expected concentration ratio	37
9	Acceptability of profile	38
10a	Water concentration profile test at a crude oil terminal (set 1)	52
10b	Water concentration profile test at a crude oil terminal (set 2)	53
11	Suggested minimum flow rates versus mixing elements	54

Figures

1	Initial or periodic validation of a sampling system	24
2	Graphical representation of concentration profiles in a horizontal pipe	25
3	Location of sampling point	25
4	Multipoint probe for profile sampling	26
5	Arrangement of multipoint probe in horizontal pipeline for 300 mm diameter pipelines or larger	27
6	Typical timing diagram for sampler system testing	28
7	Bar graph presentation of automatic profile test at three locations	29
8	Results from profile tests (typical profiles)	30
9	Typical sampling systems	31
10	Energy rate and drop size	45
11	Settling rate	47
12	Turbulence (diffusivity)	49
13a	Water concentration profile test at a crude oil terminal (example 1)	52
13b	Water concentration profile test at a crude oil terminal (example 2)	53

iTeh STANDARD PREVIEW

(standards.iteh.ai)

SIST EN ISO 3171:1999

<https://standards.iteh.ai/catalog/standards/sist/07c28177-67ac-4d7e-b12e-0131a3e2c383/sist-en-iso-3171-1999>

Petroleum liquids – Automatic pipeline sampling

0 Introduction

The purpose of collecting a sample of the material flowing through a pipeline is to determine the mean composition and quality of the bulk quantity. Samples of the bulk quantity in the line may be analysed to determine composition, water and sediment content, or any other important attributes such as density, viscosity or, with special precautions, vapour pressure.

Manual methods of pipeline sampling are adequate for homogeneous liquids whose composition and quality do not significantly vary with time. If this is not the case, automatic sampling is the recommended procedure since the continuous or repetitive extraction of small samples from a pipeline ensures that any changes in the bulk contents are reflected in the collected sample. In order that the sample shall be as representative as possible it is essential to ensure that the recommendations of this International Standard with respect to the required homogeneity of the liquid at the sampling location and to the required frequency of extraction of the small samples are met.

Consideration should be given to having standby samples provided by manual methods that may be referred to if the automatic sampler fails to perform satisfactorily; however, manual sampling will be subject to uncertainty if pipeline conditions are varying. (See ISO 3170.)

The equipment and techniques described have generally been used for sampling stabilized crude oil, but may also be applied to unstabilized crude oil and refined products provided consideration is given to the relevant safety precautions and the difficulties of sample handling.

Representative sampling of crude oil for density and water and sediment content is a critical process. Extensive studies have shown that, in crude oil transfers, four distinct steps are required for determining representative values:

- a) adequate stream conditioning of the pipeline contents;
- b) reliable and effective sampling, ensuring proportionality between sampling ratio and flow rate in the line;
- c) adequate conservation and transporting of the sample;
- d) adequate conditioning and dividing into parts for accurate laboratory analysis.

This International Standard refers to existing methods of sampling and the type of equipment presently in use. It is, however, not intended that it should exclude new equipment not yet developed for commercial use, provided that such equipment enables samples to be obtained that are representative, and is in accordance with the general requirements and procedures of this International Standard.

The annexes to this International Standard contain calculation procedures about pipeline mixing theory and profile testing and also give basic guidelines for sampler location.

It is realized that in many countries some or all of the items covered by this International Standard are subject to mandatory regulations imposed by the laws of those countries; such regulations must be rigorously observed. In cases of conflict between such mandatory regulations and this International Standard, the former should prevail.

1 Scope and field of application

1.1 This International Standard recommends procedures to be used for obtaining, by automatic means, representative samples of crude oil and liquid petroleum products being conveyed by pipeline.

NOTE — Although throughout this International Standard the term crude oil is used, this should be taken to include other petroleum liquids where the technique and equipment are also applicable.

1.2 This International Standard does not apply to the sampling of liquefied petroleum gases and liquefied natural gases.

1.3 The principal purpose of this International Standard is to give guidelines for specifying, testing, operating, maintaining and monitoring crude oil samplers.

1.4 The sampling procedures for crude oil are intended to provide representative samples for the determination of

- a) the oil composition and quality;
- b) the total water content;
- c) other contaminants that are not considered to be part of the crude oil transferred.

ISO 3171 : 1988 (E)

If the sampling procedures for a), b) and c) are in conflict, separate samples may be required.

NOTE — The results of the laboratory analysis may be used for calculating adjustments to the declared quantity of crude oil transferred. The procedure for carrying out the adjustments does not form part of this International Standard.

1.5 Sample handling is included, covering all aspects following collection to the transfer of the sample to laboratory apparatus.

1.6 This International Standard describes the practices and procedures believed at the present time to be the most likely to lead to representative sampling and hence to accurate water determination. However, the accuracy of the water determination on pipeline samples obtained using automatic samplers will depend upon the arrangement and characteristics of all the various elements making up the sampling system, and on the accuracy of the subsequent analytical procedures.

A theoretical technique for evaluating the combined accuracy of the automatic sampling system and the analytical test is given in clause 16. A practical test procedure for field use is described in clause 15.

Normally, the acceptable accuracy limits for a particular automatic sampling system will be specified in agreement between the interested parties.

Table 4 of clause 15 classifies the performance of automatic sampling systems by ratings based on the accuracy of practical test results. These ratings may be used as a guide to possible performance and as a basis for individual agreement.

2 References

ISO 3165, *Sampling of chemical products for industrial use — Safety in sampling.*

ISO 3170, *Petroleum products — Liquid hydrocarbons — Manual sampling.*

NOTE — See also clause 17, Bibliography.

3 Definitions

For the purpose of this International Standard, the following definitions apply.

3.1 acceptable (accuracy) limits: The limits within which the determined concentration of water in a sample is acceptable relative to the true value or other specified value, at the 95 % probability level.

3.2 automatic sampler: A system capable of extracting a representative sample from the liquid flowing in a pipe. The system consists of a sampling probe and/or a separating device, an associated controller and a sample receiver.

3.2.1 intermittent sampler: A system for extracting liquid from a flowing stream, a sample receiver to contain the sample grabs taken from the stream, and a means for controlling the amount of sample taken by varying the sampling frequency or grab volume in relation to flow rate.

3.2.2 continuous sampler: A system for extracting liquid from a flowing stream which has a separating device which continuously withdraws liquid from the main pipeline in relation to flow rate, an intermediate sample receiver, and a means for controlling secondary withdrawal to a final sample receiver.

3.3 calculated sample volume: The theoretical sample volume obtained by multiplying the sample grab volume by the number of actually collected grabs.

3.4 competent person: A person who by reason of his or her training, experience, and theoretical and practical knowledge is able to detect any defects or weaknesses in the plant or equipment and to make an authoritative judgement as to its suitability for further use.

NOTE — This person should have sufficient authority to ensure that the necessary action is taken following his or her recommendation.

3.5 controller: A device which governs the operation of the automatic sampler in order to provide a representative sample.

3.6 fixed-rate sample; time-proportional sample: A sample taken from a pipeline during the whole period of transfer of a batch, composed of equal increments at uniform time intervals.

3.7 flow-proportional sample: A sample taken from a pipeline during the whole period of transfer of a batch, at a rate which is proportional to the rate of flow of the liquid through the pipeline at any instant.

3.8 grab: The portion of liquid extracted from the pipe by a single actuation of the separating device. The sum of all the portions results in a sample.

3.9 homogeneous mixture: A liquid is homogeneous if the composition is the same at all points. For the purposes of this International Standard a liquid is homogeneous if the variation in composition does not exceed the limits provided in 4.4.

3.10 integrity of the sample: The condition of being complete and unaltered, i.e. the sample being preserved with the same composition as when it was taken from the bulk of the liquid.

3.11 isokinetic sampling: Sampling in such a manner that the linear velocity of the liquid through the opening of the sampling probe is equal to the linear velocity of the liquid in the pipeline at the sampling location and is in the same direction as that of the bulk of the liquid in the pipeline approaching the sampling probe.

3.12 mixer: A device which provides a homogeneous mixture of the liquid within a pipeline or container in order to obtain a representative sample.

3.12.1 powered mixer: A mixing device which depends on an external source of power for the energy required to mix the liquid.

3.12.2 static mixer: A mixing device having no moving parts and located within a pipe or tube. It depends on the kinetic energy of the moving liquid for the energy required to mix the liquid.

3.12.3 variable-geometry static mixer: A mixing device with parts inside the pipe or tube which can be adjusted to modify its characteristics at different flow rates.

3.13 pipeline: Any section of pipe used for the transfer of liquid. An unobstructed pipe does not have any internal fittings such as a static mixer or orifice plate.

3.14 profile testing: A technique for simultaneous sampling at several points across the diameter of a pipe. Terms used in connection with profile testing are as follows:

3.14.1 overall mean: The average of either the point averages or the profile averages. (Note that the result is the same.)

3.14.2 point: A single sampling orifice in the profile.

3.14.3 point average: The average of the water concentration at the same point in all profiles (neglect points with less than 1 % water).

3.14.4 profile: A set of samples taken simultaneously at several points across a diameter of the pipe.

NOTE — The term is also used to denote the series of sampling points themselves and the set of results obtained by analysis of the samples taken at these points.

3.14.5 profile average: The average of the water concentration at each point in the same profile (neglect the profile if it has less than 1 % water).

3.15 representative sample: A sample having its physical or chemical characteristics identical to the average characteristics of the total volume being sampled.

NOTE — Since errors cannot be quantified exactly, compliance with this ideal can only be expressed as an uncertainty that can be obtained either from practical tests or by theoretical calculation.

3.16 sample: The portion of liquid extracted from the pipeline that is subsequently transferred to the laboratory for analysis.

3.17 sample conditioning: Homogenization necessary to stabilize the sample during sample handling in preparation for analysis.

3.18 sample container: A vessel used for the storage, transportation and preconditioning of the total quantity, or a proportion of the total quantity, of the sample for analytical work or for division into identical small sub-samples to be analysed.

3.19 sample handling: The conditioning, transferring, dividing and transporting of the sample. It includes transferring the sample from the receiver to the container and from the container to the laboratory apparatus in which it is analysed.

3.20 sample loop: A by-pass to the main pipeline being sampled through which a representative portion of the total flow is circulated.

3.21 sample receiver; receptacle: A vessel connected to the automatic sampler in which the sample is collected during the sampling operation. A receiver may be permanently attached to the sampler or it may be portable. In either case, it should be designed to maintain the integrity of the sample.

NOTE — In certain circumstances, it is possible to collect the total sample in more than one sample receiver. In such circumstances, the sample integrity has to be maintained for each individual sample volume.

3.22 sampler performance factor (PF): The ratio between the accumulated sample volume and the calculated sample volume (see 14.6).

3.23 sampling frequency: The number of grabs taken in unit time.

3.24 sampling interval: The time between successive grabs.

3.25 sampling location: The cross-section of the pipe where the sampling probe is, or is proposed to be, located.

3.26 sampling probe: The sampler element that extends into the pipeline.

3.27 sampling ratio: The quantity of pipeline contents represented by one grab.

NOTE — It can be expressed as either the volume, in cubic metres per grab, or the equivalent length of pipeline, in metres per grab.

3.28 separating device: A device that separates a small volume of liquid from the batch of liquid that the small volume represents.

3.29 stream conditioning: The distribution and dispersion of the pipeline contents, upstream of the sampling location.

ISO 3171 : 1988 (E)

3.30 time-proportional sample: See 3.6.

3.31 water.

3.31.1 dissolved water: The water contained within the oil forming a solution at the prevailing temperature.

3.31.2 suspended water: The water within the oil that is finely dispersed as small droplets.

NOTE — It may, over a period of time, either collect as free water or become dissolved water, depending on the conditions of temperature and pressure prevailing.

3.31.3 free water: The water that exists as a separate layer from the oil, and typically lies beneath the oil.

3.31.4 total water: The sum of all the dissolved, suspended and free water in a cargo or parcel of oil.

3.32 worst-case conditions: The operating conditions for the sampler that present the most uneven and unstable concentration profile at the sampling location.

NOTE — This will usually be at minimum flow rate, minimum oil density and minimum oil viscosity but may also be influenced by other factors such as emulsifiers and surfactants.

4 Principles

4.1 Purpose

This clause defines the principles which it is essential to observe during sampling operations in order that the representativity of the sample taken corresponds to the specifications of this International Standard, and meets the acceptability criteria given in 4.4.

4.2 Principles to be observed

In order to determine the oil composition, quality and total water content of a batch of crude oil, samples that are representative of the batch are taken and analysed. The batch may be either a discrete pipeline transfer over a given period of time, or the whole or part of the cargo of a tanker, either loading or unloading.

Representativity depends on four conditions, all of which should be observed, since failure to comply with any one of them could affect the quality of the final result.

4.2.1 The first condition is that the samples that are taken from the pipeline should have the same composition as the average composition of the crude oil over the whole cross-section of the pipeline at the location and time of sampling. It is not easy to comply with this condition, because of the possibility of a variable concentration gradient existing across the section.

This condition requires that at the sampling location:

- a) the distribution or concentration of the water in the crude oil should be uniform across the section of the pipeline within the acceptance limits given in 4.4;
- b) the diameter of the entry port of the sampling probe should be large in relation to the maximum water droplet size. The port opening should not be smaller than 6 mm (see 7.3).

4.2.2 The second condition is that representativity should persist throughout the period of transfer of the batch, the composition of which may change between the start and finish of sampling. The rate of sampling, whether it is continuous or intermittent, should be in proportion to the flow rate in the pipe. When an intermittent sampler is used the sampling frequency and grab size should both be sufficient to guarantee acceptable representativity.

Furthermore, the representativity of the sample should be maintained in the automatic sampler from the sampling probe up to the final receiver. Samples should be taken with an appliance that complies with the recommendations in clauses 7, 8, 9 and 10.

4.2.3 The third condition is that the sample should be maintained in the same condition as at the point of extraction, without loss from it of liquid, solids or gases and without contamination.

Storage and transfer of samples should comply with the recommendations in clause 11.

4.2.4 The fourth condition concerns division of a sample into a number of sub-samples in such a way as to ensure that each of them has exactly the same composition as the original sample.

The procedure for dividing each sample into sub-samples, and for transferring them to laboratory appliances, is given in clause 12.

NOTE — It should be emphasized that this fourth condition concerns a critical activity and any error introduced is capable of destroying the representativity achieved by the first three.

4.3 Sampling tolerances and validation

In order to ensure that each sample sent to the laboratory for analysis is representative of the whole batch, the composition of the sample should not differ from the composition of the batch by more than the tolerances given in table 4 and as applied in 15.5.

In order to ensure that any departure from the conditions given above (see 4.2) does not result in a sample representativity which exceeds the tolerances given in table 4, each step of the sampling operation should be validated as shown in figure 1.

4.4 General principles for sampling

Hydraulic laws governing the behaviour of heterogeneous liquids which will mix or will not mix in the pipe show that for stream conditioning a sufficiently high energy dissipation rate should be provided to keep drops of water and heavier solid particles suspended in the crude oil. Such an energy dissipation rate may be provided either from the velocity in an unobstructed pipe, or from a mixing device immediately upstream of the sampling location.

In considering the distribution of water over the cross-section, the acceptable limits of the values found in the profile test (clause 6) should be relative to the mean concentration of water in that plane and should be within $\pm 0,05$ g/100 g for samples having a water content up to 1 g/100 g and should be ± 5 % of the mean concentration (relative) for samples having a water content greater than 1 g/100 g [but see also case 2 (4.4.2)].

NOTE — Although the concentrations above are quoted in mass units, they also apply to volume units.

In a horizontal pipe, three cases may be used to describe the ways in which the concentration of the different phases may vary over the cross-section of the pipe depending on hydraulic conditions (flow rate, product density and viscosity, dispersed phase composition, interfacial tension modifiers, etc.).

4.4.1 Case 1 (see figure 2, profile type 1)

In this case, the concentration is the same, within the acceptable limits as defined above, across the entire cross-section of the pipeline for all concentrations of water. The existing conditions are acceptable for sampling, since water is evenly distributed over the pipe cross-section. A representative sample consequently exists at the inlet of the sampling probe, which can be placed at any point on the diameter although it is essential that care should be taken not to place the sampling probe too near the wall in order to minimize wall effects.

4.4.2 Case 2 (see figure 2, profile type 2)

In this case, the concentration varies from one point to another in the cross-section, but with a uniform gradient such that there is at least one point where the concentration is equal to the mean concentration across the entire section. Based on a theoretical analysis, this point is generally found between 0,4 and 0,5 of the vertical diameter from the bottom of a horizontal pipeline.

Sampling at this location will only be acceptable if the water concentration found at the sampling point under worst-case conditions is equal to the mean concentration within the acceptable limits as defined above.

4.4.3 Case 3 (see figure 2, profile types 3a and 3b)

In this case, the concentration across the cross-section of the pipe is non-linear, indicating the presence of segregation (type 3a). Some erratic profiles may also be encountered (type 3b).

As there is a range of concentrations at different points in the cross-section, sampling at a predetermined point is unacceptable, and it will be necessary to install a mixing device (see 5.3).

NOTE — If there is any free water, or an emulsion having a high concentration of water, at the bottom of the pipe, representative sampling is not possible.

4.5 Dispersed phase — variations with time

It is unlikely that the concentration of a dispersed phase component in the bulk liquid will be constant with time. For example in the discharge of crude oil from a marine tanker, in addition to more gradual changes in the base water content, there may also be periods when peaks of relatively high concentrations of water travel down the pipeline. Experimental observations indicate that these "transients" may contain over 50 % water and may be shorter than a minute in duration. Depending on the unloading procedures, the significance of the water discharged in the form of transients may vary relative to the base level carried with the bulk of the discharged cargo.

It is apparent that the representativity of samples taken in such applications will be dependent upon the ability of the automatic sampler system to reflect, both accurately and proportionally, the integrated water content of these peaks in the total collected sample volume.

With intermittent-type samplers, accuracy will depend on the type of equipment and its frequency of operation in relation to the frequency and duration of the transients. With continuous-type samplers, accuracy will depend on the external collection and mixing arrangements and on the rate of secondary sampling if applied. For both types of sampler, the overall duration of the oil transfer, the duration of any water transients and the sampling frequency have statistical significance in the determination of sampling accuracy.

Theoretical analysis of the effect of dispersed phase transients on the performance of the different types of samplers leads to the following general conclusions:

- a) in short-term transfers in which there is a possibility of frequent, short-duration transients, the accuracy of the continuous type of automatic sampler is least affected by the transients;
- b) in short-term transfers in which there may be relatively few long-duration transients, the accuracy of the intermittent-type sampler approaches that of the continuous type of automatic sampler;
- c) for long-term transfers, the mean error introduced by transients of any duration, using either type of sampler, is within the limits of acceptability defined in this International Standard.

4.6 Low water content

Attention is drawn to the fact that, if the concentration of water is about 0,1 % (*m/m*), i.e. near the level at which water is soluble in crude oil, the concentration profiles will show a good uniformity of water distribution under all hydraulic conditions.

ISO 3171 : 1988 (E)

5 Selection of sampling point (including stream conditioning)

5.1 General

As has been emphasized in clause 4, it is essential that the sampling probe is presented with a portion of the liquid flowing in the pipeline which is representative of the whole. This depends on the extent of mixing within the pipeline, which in turn depends on a number of factors including flow rate and pipe configuration upstream of the sampling location.

The guidance given in this clause for the selection of the sampling point assumes that the pipeline remains full at all times.

5.2 Initial selection of sampling probe location

5.2.1 The force of gravity tends to promote stratification in horizontal pipelines whereas distribution tends to be more uniform in vertical lines. For this reason, given the choice between vertical and horizontal, and assuming identical operating conditions, the preferred location is in a length of vertical pipe, provided that the pumping rate is significantly higher than the water and sediment settling rate (see annex A, A.2.2).

Reference should be made to annex C for a useful guide to the initial screening of potential sampling locations but annex A is preferred as it provides a more detailed treatment.

5.2.2 The turbulence which exists naturally in a long horizontal pipeline can be, but frequently is not, sufficient to provide adequate mixing. The minimum natural turbulence for adequate mixing depends on flow rate, pipe diameter, viscosity, density and interfacial tension. If the natural turbulence is not sufficient for representative sampling, then the additional mixing offered by specific pipeline components should be introduced (see 5.3 and annex A).

5.2.3 The minimum acceptable flow rate and/or the minimum energy to be provided by a mixing device should be determined. Suitable procedures using formulae or nomographs described in annex A may be used.

5.3 Mixing devices

5.3.1 General

Mixing devices produce homogeneity by the addition of kinetic energy from outside or the conversion of pressure energy from within the pipeline.

In situations where there is an insufficient rate of energy dissipation for pipeline fittings or static mixers to be effective, consideration should be given to the use of powered mixers.

Reference should be made to annex C for a useful guide to the initial screening of potential sampling locations.

5.3.2 Pipeline fittings

Pipeline fittings may be used as in-line mixing devices. The fittings which may be suitable in this respect are valves, orifices, pipe reducers and expanders, manifolds, T-junctions and metering stations. These, however, vary in their effectiveness as mixers and may create concentration zones, leading to zigzag concentration profiles over a downstream distance equivalent to about 20 pipe diameters.

5.3.3 Reduced pipe diameter

If the velocity is too low for sufficient mixing, a length of pipe of reduced diameter can often be installed to advantage but not to the extent that the obstruction caused by the sampling probe will distort the water distribution (see 7.2).

5.3.4 Vertical loops

The improved distribution afforded by a vertical length of pipeline (see 5.2.1) can be obtained by inserting a vertical loop into a horizontal line. If sufficient line pressure is available the flow rate may be increased by reducing the diameter in the vertical loop to below that of the main line. In a vertical loop, the sampling probe should be preferably installed in the downstream leg, at a minimum distance of three, but preferably greater than five, pipe diameters from the upstream bend and a minimum distance of 0,5 pipe diameters from the downstream bend.

It should be noted that water can accumulate at the bottom of vertical piping until these accumulations reach such a size that they are carried forward in the form of slugs. As a result of this phenomenon, water transients occur and this should be taken into account.

5.3.5 Static mixers

Static mixers are commercially available devices specially designed in one or more stages to provide adequate distribution and dispersion of the pipeline constituents prior to sampling. Reference should be made to the manufacturer for advice on the minimum flow rate at which the mixer is still effective.

The maximum flow rate will be limited by the acceptable pressure drop across the mixer, but a wide flow range can be accommodated using a variable geometry mixer.

5.3.6 Powered mixers

Powered mixers can be dynamic versions of the static mixer in which the mixer elements are driven from an external power source to introduce a high shearing action which effects the maximum dispersion of the contacting media. Alternatively, mixing may be achieved when a portion of the flow is re-introduced into the pipeline via a pump and high-velocity injector(s), upstream of the sampling probe.

5.4 Position of the sampling probe

5.4.1 If the contents of the pipeline have been adequately mixed the position of the sampling probe relative to the pipe wall is relatively unimportant. However, to avoid wall effects, which could influence the flow rate as well as the water concentration, the sample should be drawn from the centre of the pipe. In horizontal or vertical pipes the sampling probe should be positioned to withdraw from the shaded areas shown in figure 3.

5.4.2 Under some conditions, centrifugal forces occurring at bends may act to separate the dispersed phase from the bulk liquid. Therefore the exclusive use of single bends to provide mixing upstream of the sampling location is not recommended.

5.4.3 The distance between the mixing device and the sampling probe should be sufficient to avoid the effects of swirl and asymmetry generated by the device but not so great as to lose the mixing effect provided by the device. Recommended distances are between one-half of a pipe diameter and 8 pipe diameters, depending on the type of mixing device being used.

5.5 Checking the location of the sampling probe

Whatever location is chosen for the sampling probe, or whatever additional form of mixing is employed, it is recommended that the concentration profile at the sampling location be checked. The test procedure for this check is described in clause 6. Other methods of checking may be used if they provide equal assurance that the sample taken will be representative.

6 Profile testing

6.1 Introduction

This clause describes methods which may be used to test the uniformity of water distribution across the pipeline at the chosen sampling location.

6.2 Principle

Profile testing can verify that a representative sample is available at the proposed or existing sampling location. The extent of stratification or non-uniformity of water concentration can be determined by taking samples simultaneously at several points across the diameter of the pipe and analysing these for water content. A multipoint probe, as opposed to a traversing probe, is required to eliminate uncertainties due to non-simultaneous sampling.

In order to make a valid judgement regarding uniform dispersion, a minimum of five profile tests should be made, although only three profile tests are required to demonstrate stratification. For acceptable results when using manual methods of test, the mean water concentration should be between 1 and 5 %.

NOTE — If centrifuge tubes are being used for the water determination and the water concentration is above 20 % extreme care should be taken when taking the readings because of the larger volumes between graduations.

If an automatic continuous method of determining water content is employed, then the water content should be within the working range of the instrument. To cope with conditions of complete water separation, the instrument should tolerate 100 % water without failure.

6.3 Methods

The choice is between three methods of test, depending upon the level of water concentration that can be assured throughout the period of testing and the ability to achieve reliable and stable conditions. Generally, a level of at least 1 % water is necessary for a valid test.

— Method 1 employs the injection of additional water into the pipeline. It is the preferred procedure and should be used whenever there is doubt that the natural level of water concentration in the crude oil will be consistently more than 1 % during the test period.

— Method 2 relies upon the natural level of water concentration. To be valid, this method should only be used when there is certainty that the natural water concentration in the crude oil during the period of test will be at least 1 %.

— Method 3 is an alternative method for use with ships. Under some circumstances additional water may be introduced into the ship's compartments or storage tanks to increase the level of water concentration to at least 1 %.

NOTE — A water concentration of 1 % is enough to determine whether the dynamics of the system can provide adequate mixing while minimizing the effects of the inherent measurement error.

6.4 Determining the water concentration profile in a pipeline and validation of the sampling location

6.4.1 Equipment

6.4.1.1 Multipoint sampling probe

The test is performed using the multipoint probe illustrated in figure 4. The probe openings should face upstream into the direction of flow and are internally reamed to minimize entry flow disturbances. The probe should be fitted horizontally into a vertical pipe, or vertically into a horizontal pipe. When the probe is fitted vertically, the recommended direction of flow in the probes is vertically downward where possible. In horizontal pipes, an extra straight-tube without bend is positioned vertically with the entry opening as near as practicable to the bottom wall of the pipeline (see figure 5). This point is used to check that no free water is running along the bottom of the pipe.