# INTERNATIONAL STANDARD

ISO 8036-1

> Second edition 1998-03-01

### Optics and optical instruments — Microscopes —

Part 1:

Immersion oil for general use in light microscopy

microscopy
iTeh STANDARD PREVIEW

Optique et instruments d'optique — Microscopes — (Standards.iten.al)

Partie 1: Huile d'immersion pour usage général en microscopie optique

ISO 8036-1:1998

https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998



#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and nongovernmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote. TIEN STANDARD PRE

International Standard ISO 8036-1 was prepared by Technical Committee ISO/TC 172, Optics and optical instruments, Subcommittee SC 5, Microscopes and endoscopes. ISO 8036-1:1998

https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4second edition cancels and replaces 7 the first 1 edition (ISO 8036-1:1986), which has been technically revised.

ISO 8036 consists of the following parts, under the general title Optics and optical instruments — Microscopes:

- Part 1: Immersion oil for general use in light microscopy
- Part 2: Immersion oil for use in fluorescence microscopy

Annex A of this part of ISO 8036 is for information only.

@ ISO 1998

This

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland central@iso.ch Internet c=ch; a=400net; p=iso; o=isocs; s=central X.400

Printed in Switzerland

#### Introduction

The image quality of microscopes with oil-immersion objectives is dependent on the optical properties of the immersion oil used. In order to guarantee a certain minimum quality, this part of ISO 8036 specifies the relevant properties of immersion oil for general use, with the purpose of making immersion oil with the specified properties available throughout the world.

The optical and physical requirements for immersion oil have been specified taking into account the optical properties of objectives which are in general use and which are made by different manufacturers.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8036-1:1998 https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8036-1:1998 https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998

### Optics and optical instruments — Microscopes —

#### Part 1:

Immersion oil for general use in light microscopy

#### 1 Scope

This part of ISO 8036 specifies requirements for immersion oil for general use in light microscopy in the visible spectral range.

NOTE 1 Visible spectral range is defined as being the wavelength range from 400 nm to 760 nm.

Owing to its optical effect, immersion oil forms part of the optical system of a microscope; this part of ISO 8036 specifies the requirements which shall be met to ensure image quality.

NOTE 2 This part of ISO 8036 does not cover requirements for suitability for fluorescence microscopy; immersion oil suitable for fluorescence microscopy will be dealt with in ISO 8036-2036-1:1998

https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998

#### 2 Requirements

#### 2.1 Optical properties

Immersion oil shall have the following optical properties, measured at a temperature of 23 °C and at a pressure of 101 325 Pa:

- Principal refractive index:  $n_e = 1,518.0 \pm 0,000.5$
- Abbe number:  $v_{e}$ = 44 ± 3

The Abbe number  $v_e$  is calculated using the following formula:

$$v_{\rm e} = \frac{n_{\rm e} - 1}{n_{\rm F'} - n_{\rm C'}}$$

where

 $n_a$  is the principal refractive index;

 $n_{\rm F}$  is the refractive index of light at the blue cadmium F'-line ( $\lambda_{\rm F}$  =479,99 nm);

 $n_{\rm C}$  is the refractive index of light at the red cadmium C'-line ( $\lambda_{\rm C}$  = 643,85 nm).

NOTE 1 Highest optical quality, particularly with large objective aperture will be obtained at a temperature of use of 23 °C.

ISO 8036-1:1998(E) © ISO

NOTE 2 The principal refractive index,  $n_{\rm e}$ , is the refractive index of light at the green mercury e-line ( $\lambda_{\rm e}$  = 546,07 nm; see ISO 7944). This wavelength is close to the maximum sensitivity of the eye and has been used as the principal wavelength of optical computation for some time.

#### 2.2 Light transmittance

Immersion oil shall have no regions of selective absorption between 400 nm and 760 nm. The minimum percentage transmittance measured through a 10 mm cell path shall be as given in table 1.

Table 1 — Light transmittance

<b>Wavelength</b>	Transmittance
nm	%
400	60
500	95
600	95
760	95 95

#### 2.3 Viscosity

Immersion oil shall range in viscosity from 0,000 15 m²/s to 0,0015 m²/s ± 10 % measured at a temperature of 23°C.

(standards.iteh.ai)

#### 2.4 Toxicity

ISO 8036-1:1998

https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-

The data sheet on material safety shall be available from the manufacturer.

#### 3 Marking

The packaging and container label of immersion oil conforming to this part of ISO 8036 shall be marked with the indication "ISO 8036-1". Toxic, harmful or suspect components shall be indicated on the packaging and on the container label.

In addition, the following information may be included on the container label:

- a) the principal refractive index and its tolerance at 23 °C;
- b) the Abbe number and its tolerance at 23 °C;
- c) the refractive index temperature coefficient;
- d) the viscosity, in metres squared per second, and tolerance;
- e) the date of expiry for unopened containers;
- f) the manufacturer's or supplier's name or mark, and the country of origin.

### Annex A

(informative)

### **Bibliography**

[1] ISO 7944:1998, Optics and optical instruments — Reference wavelengths.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8036-1:1998 https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998 ISO 8036-1:1998(E) © ISO

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8036-1:1998 https://standards.iteh.ai/catalog/standards/sist/dd2e43df-7f9c-4a8d-81f4-14fc28317b4d/iso-8036-1-1998

#### ICS 37.020

**Descriptors:** optics, optical equipment, microscopes, immersion oils, specifications, optical properties, physical properties, marking. Price based on 3 pages