



SLOVENSKI STANDARD
SIST EN 300 175-3 V2.2.1:2009
01-januar-2009

8 [[]HbY]nVc`yUbYvfYnj fj] bYhY_ca i b]_UWY'fB97HL!'G_i db]j a Ygb]_f7 4!' " XY.'D`Ugh_fa]^b^UXcghcdUXc`dfYbcgbY[Ua YX]UfA57Ł

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part 3: Medium Access Control (MAC) layer

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST EN 300 175-3 V2.2.1:2009} **EN 300 175-3 Version 2.2.1**
<https://standards.iteh.ai/catalog/standards/sist/561572bc-1ecc-4449-b41a-f4577ea4a0b9/sist-en-300-175-3-v2-2-1-2009>

ICS:

33.070.30 Öä åæ ^/á à| |zæ ^ Digital Enhanced Cordless
à!^: ç|çã } ^/á |^ \ [{ ~ } å æ åæ Telecommunications (DECT)
ÇÖÓÓVD

SIST EN 300 175-3 V2.2.1:2009 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-3 V2.2.1:2009

<https://standards.iteh.ai/catalog/standards/sist/56f372be-fec5-4449-b4fa-f4577ea4a0b9/sist-en-300-175-3-v2-2-1-2009>

ETSI EN 300 175-3 V2.2.1 (2008-11)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-3 V2.2.1:2009](https://standards.iteh.ai/catalog/standards/sist/56f372be-fec5-4449-b4fa-f4577ea4a0b9/sist-en-300-175-3-v2-2-1-2009)

<https://standards.iteh.ai/catalog/standards/sist/56f372be-fec5-4449-b4fa-f4577ea4a0b9/sist-en-300-175-3-v2-2-1-2009>



Reference

REN/DECT-000248-3

KeywordsDECT, IMT-2000, MAC, mobility, radio, TDD,
TDMA**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-3 V2.2.1:2009<https://standards.iteh.ai/catalog/standards/sist/56f372be-fec5-4449-b4fa-f4577ea4a0f2/sist-en-300-175-3-v2-2-1-2009>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	13
Foreword.....	13
1 Scope	14
2 References	14
2.1 Normative references	15
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	16
4 Description of the MAC layer	18
4.1 MAC layer reference model	18
4.1.1 General.....	19
4.1.2 Cluster Control Function (CCF)	19
4.1.3 Cell Site Functions (CSF).....	19
4.1.4 Relationship to physical layer elements.....	19
4.2 Frame and multiframe structures.....	20
4.2.1 General.....	20
4.2.2 Frame structure	20
4.2.3 Multiframe structure	22
4.3 State definitions.....	22
4.3.1 PP states	22
4.3.2 RFP states	23
5 Overview of MAC layer services.....	24
5.1 General	24
5.1.1 Broadcast Message Control (BMC).....	24
5.1.2 Connectionless Message Control (CMC).....	24
5.1.3 Multi-Bearer Control	24
5.2 Service descriptions.....	24
5.2.1 Common functions.....	24
5.2.2 BMC service	25
5.2.3 CMC service	25
5.2.4 MBC services.....	25
5.3 Logical channels.....	26
5.3.1 MBC connection endpoints (MC-SAP logical channels)	26
5.3.1.1 The higher layer C-plane channels, C	26
5.3.1.2 The higher layer U-Plane channels, I	26
5.3.1.3 The higher layer U-Plane control channel, G _F	27
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I _{PF}	27
5.3.2 CMC endpoints (MB-SAP logical channels).....	27
5.3.2.1 The connectionless C-Plane channels, CL	27
5.3.2.2 The connectionless U-Plane channels, SI _N and SI _P	28
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI _{PF}	28
5.3.3 BMC endpoint (MA-SAP logical channel).....	28
5.3.3.1 The slow broadcast channel, B _S	28
5.3.4 Internal MAC control channels.....	28
5.3.4.1 The system information channel, Q	28
5.3.4.2 Identities channel, N.....	29
5.3.4.3 The MAC control channel, M	29
5.3.4.4 MAC paging channel, P	29
5.4 SAP definitions	29
5.4.1 MA SAP	29
5.4.2 MB SAP.....	30
5.4.3 MC SAP.....	30

5.4.4	ME SAP	31
5.4.5	Order of transmission.....	31
5.5	Bearers.....	31
5.5.1	Bearer types	31
5.5.2	Bearer operation.....	32
5.6	Connection oriented services.....	32
5.6.1	Connection types	32
5.6.1.1	Basic connections.....	32
5.6.1.2	Advanced connections	33
5.6.1.2.1	Rules for ECN selection in advanced connections	33
5.6.1.3	Connection identifiers	33
5.6.1.4	Complementary connections	34
5.6.2	Symmetric and asymmetric connections.....	34
5.6.2.1	Symmetric connections	34
5.6.2.2	Asymmetric connections	39
5.7	Broadcast and connectionless services	47
5.7.1	The broadcast services	48
5.7.1.1	The continuous broadcast service	48
5.7.1.2	The non-continuous broadcast service	48
5.7.2	The connectionless services	49
5.7.2.1	Connectionless downlink services	49
5.7.2.2	Connectionless uplink services	49
6	Multiplexing	50
6.1	CCF multiplexing functions	50
6.2	CSF multiplexing functions.....	50
6.2.1	Bit Mappings (MAP)	55
6.2.1.1	D-field mapping (D-MAP)	55
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80)	56
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	56
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00)	57
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j)	57
6.2.1.2	A-field Mapping (A-MAP)	58
6.2.1.3	B-field Mapping (B-MAP)	59
6.2.1.3.1	Unprotected format	59
6.2.1.3.2	Encoded protected format	61
6.2.1.3.3	Multisubfield protected format	61
6.2.1.3.4	Singlesubfield protected format.....	63
6.2.2	Time multiplexers	65
6.2.2.1	Tail MUltipleXer (T-MUX)	65
6.2.2.1.1	T-MUX algorithm for RFP transmissions	65
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	66
6.2.2.2	B-field control multiplexer (E/U-MUX)	67
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes	69
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield	69
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation	82
6.2.2.4	Priority scheme in E or E+U mode	82
6.2.3	Encryption.....	83
6.2.4	Scrambling	84
6.2.5	Error control.....	85
6.2.5.1	R-CRC overview	85
6.2.5.2	R-CRC generation and checking.....	86
6.2.5.3	X-CRC overview.....	87
6.2.5.4	X-CRC generation and checking.....	87
6.2.5.5	B-CRC generation and checking	89
6.2.6	Broadcast controller	89
7	Medium access layer messages	90
7.1	Header field	90
7.1.1	Overview/formatting.....	90
7.1.2	Tail identification, TA, bits a_0 to a_2	91
7.1.3	The "Q1/BCK" bit, bit a_3	91

7.1.4	B-field identification, BA, bits a_4 to a_6	92
7.1.5	The "Q2" bit, bit a_7	93
7.2	Messages in the tail field	93
7.2.1	Overview	93
7.2.2	Identities information (N_T).....	93
7.2.3	System information and multiframe marker (Q_T)	94
7.2.3.1	General	94
7.2.3.2	Static system information.....	95
7.2.3.2.1	General, $Q_H = 0, 1$ (hex)	95
7.2.3.2.2	Q_H and Normal-Reverse (NR)	95
7.2.3.2.3	Slot Number (SN).....	95
7.2.3.2.4	Start Position (SP)	96
7.2.3.2.5	ESCAPE bit (ESC)	96
7.2.3.2.6	Number of transceivers.....	96
7.2.3.2.7	Extended RF carrier information available (M_c).....	96
7.2.3.2.8	RF carriers available (RF-cars).....	97
7.2.3.2.9	Spare bits (SPR)	97
7.2.3.2.10	Carrier number.....	97
7.2.3.2.11	Spare bits (SPR)	97
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	98
7.2.3.3	Extended RF carrier information part 1	98
7.2.3.3.1	General, $Q_H = 2$ (hex)	98
7.2.3.3.2	Further RF carrier extensions	99
7.2.3.3.3	Number of RF carriers.....	99
7.2.3.4	Fixed part capabilities	99
7.2.3.4.1	General, $Q_H = 3$ (hex)	99
7.2.3.4.2	Standard capabilities.....	99
7.2.3.5	Extended fixed part capabilities	100
7.2.3.5.1	General, $Q_H = 4$ (hex)	100
7.2.3.5.2	Extended Physical and MAC layer capabilities.....	101
7.2.3.5.3	Extended higher layer capabilities.....	102
7.2.3.6	Secondary access rights identities	102
7.2.3.6.1	General, $Q_H = 5$ (hex)	102
7.2.3.6.2	SARI message	102
7.2.3.7	Multiframe number	102
7.2.3.7.1	General, $Q_H = 6$ (hex)	102
7.2.3.7.2	Multiframe number.....	102
7.2.3.8	Escape	103
7.2.3.8.1	General, $Q_H = 7$ (hex)	103
7.2.3.8.2	Escape information	103
7.2.3.9	Extended RF carrier information part 2	103
7.2.3.9.1	General, $Q_H = 9$ (hex)	103
7.2.3.10	Transmit information	103
7.2.3.10.1	General, $Q_H = B$ (hex)	103
7.2.3.11	Extended fixed part capabilities (part 2)	104
7.2.3.11.1	General, $Q_H = C$ (hex)	104
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2).....	104
7.2.3.11.3	Extended higher layer capabilities (part 2).....	105
7.2.4	Paging Tail (P_T)	105
7.2.4.1	General format	105
7.2.4.1.1	P_T format for full and long page messages	105
7.2.4.1.2	P_T format for short page messages	106
7.2.4.1.3	P_T format for zero length page messages.....	106
7.2.4.1.4	P_T format for MAC_Resume_and_Control_page message	106
7.2.4.2	P_T header format.....	107
7.2.4.2.1	General format.....	107
7.2.4.2.2	Bit a_8 is the extend flag.....	107
7.2.4.2.3	B_S SDU length indication	107
7.2.4.3	MAC layer information for PT.....	108
7.2.4.3.1	Information type	108
7.2.4.3.2	Fill bits / Blind long slot ($j=640$ / $j=672$) information	108
7.2.4.3.3	Blind full slot information	109

7.2.4.3.4	Bearer description.....	109
7.2.4.3.5	Escape.....	110
7.2.4.3.6	Dummy or connectionless downlink bearer marker	110
7.2.4.3.7	Bearer handover/replacement information	110
7.2.4.3.8	RFP status and modulation types.....	111
7.2.4.3.9	Active carriers	112
7.2.4.3.10	RFP power level	112
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	113
7.2.4.3.12	Extended modulation types	113
7.2.5	MAC control (M_T)	114
7.2.5.1	General format and contents	114
7.2.5.2	Basic connection control	114
7.2.5.2.1	General	114
7.2.5.2.2	Format for most messages	115
7.2.5.2.3	WAIT	115
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm}	115
7.2.5.3	Advanced connection control.....	116
7.2.5.3.1	General	116
7.2.5.3.2	ACCESS_REQUEST	116
7.2.5.3.3	BEARER_HANDOVER_REQUEST	116
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST	116
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST	117
7.2.5.3.6	BEARER_CONFIRM	117
7.2.5.3.7	WAIT	117
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm}	117
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm}	120
7.2.5.3.10	Channel list	120
7.2.5.3.11	Unconfirmed_dummy	121
7.2.5.3.12	Unconfirmed_handover	121
7.2.5.3.13	RELEASE	121
7.2.5.4	MAC layer test messages	122
7.2.5.4.1	Basic format	122
7.2.5.4.2	FORCE_TRANSMIT	123
7.2.5.4.3	LOOPBACK_DATA	123
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY	124
7.2.5.4.5	ESCAPE	125
7.2.5.4.6	NETWORK_TEST	125
7.2.5.4.7	CLEAR_TEST_MODES	125
7.2.5.4.8	CHANGE_MODULATION_SCHEME	125
7.2.5.5	Quality control	126
7.2.5.5.1	Prolonged preamble diversity	127
7.2.5.6	Broadcast and connectionless services	128
7.2.5.7	Encryption control.....	128
7.2.5.8	B-field setup, first PT transmission.....	129
7.2.5.9	Escape	129
7.2.5.10	TARI message.....	129
7.2.5.11	REP connection control.....	129
7.2.5.11.1	General	129
7.2.5.11.2	Format for most messages	130
7.2.5.11.3	REP CHANNEL MAP REQUEST	130
7.2.5.11.4	REP CHANNEL MAP CONFIRM	130
7.3	Messages in the B-field	130
7.3.1	Overview	130
7.3.2	Advanced connection control	132
7.3.2.1	General format	132
7.3.2.2	BEARER_REQUEST	132
7.3.2.3	BEARER_CONFIRM	133
7.3.2.4	WAIT	133
7.3.2.5	ATTRIBUTES_B_{Req;Cfm}	133
7.3.2.6	BANDWIDTH_B_{Req;Cfm}	134
7.3.2.7	CHANNEL_LIST	135
7.3.2.8	UNCONFIRMED_DUMMY	135

7.3.2.9	UNCONFIRMED_HANDOVER	135
7.3.2.10	RELEASE	135
7.3.3	Null or I _{PF} segmentation info	137
7.3.3.1	Spare or I _{PF} segmentation info	138
7.3.3.2	Extended NCF bits	138
7.3.4	Quality control	139
7.3.4.1	General format	139
7.3.4.2	Bearer and connection control.....	139
7.3.4.3	RESET	141
7.3.4.4	Bearer quality in an asymmetric connection	141
7.3.5	Extended system information	142
7.3.5.1	General format	142
7.3.5.2	TARI messages	142
7.3.5.3	"no-emission" mode sync information	142
7.3.6	G _F channel data packet.....	143
7.3.7	Escape.....	143
8	Medium access layer primitives	143
8.1	Connection oriented service primitives	144
8.1.1	Connection setup: MAC_CON {req;ind;cfm}	144
8.1.2	Connection modification: MAC_MOD {req;ind;cfm}	145
8.1.3	CO data transmit ready: MAC_CO_DTR {ind}	146
8.1.4	CO data transfer: MAC_CO_DATA {req;ind}	147
8.1.5	Restart DLC: MAC_RES_DLC {ind}	147
8.1.6	Connection release: MAC_DIS {req;ind}	147
8.1.7	MAC bandwidth: MAC_BW {ind;res}	148
8.1.8	Encryption.....	148
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}	148
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm}	148
8.1.9	C-plane switching procedure.....	149
8.1.9.1	C-plane switching procedure: MAC_C _S _C _F {req, cfm, ind, res}.....	149
8.1.9.2	C-plane switching procedure: MAC_C _S _C _F _END {ind}.....	149
8.2	Connectionless and broadcast service primitives	150
8.2.1	Paging: MAC_PAGE {req;ind}	150
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind}	150
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm}	151
8.2.4	"no-emission" mode.....	151
8.3	Management primitives	151
8.3.1	Connection control.....	151
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	151
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req}	151
8.3.1.3	Bearer release: MAC_ME_REL {req}	151
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind}	152
8.3.2	System information and identities	152
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req}	152
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req}	152
8.3.2.3	System information output: MAC_ME_INFO {ind;res}	152
8.3.2.4	Extended system info: MAC_ME_EXT.{req;ind;res;cfm}	152
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	152
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm}	153
8.3.5	Error reports: MAC_ME_ERROR {ind;res}	153
8.4	Flow control	153
8.4.1	MA SAP flow control.....	153
8.4.2	MB SAP flow control	153
8.4.3	MC SAP flow control	153
9	Broadcast and connectionless procedures	155
9.1	Downlink broadcast and connectionless procedures	155
9.1.1	Downlink broadcast procedure	156
9.1.1.1	Broadcast information.....	156
9.1.1.2	Channel selection for downlink broadcast services.....	156
9.1.1.3	Downlink broadcast procedure description.....	157

9.1.2	Downlink connectionless procedure	158
9.1.2.1	Channel selection at the RFP	158
9.1.2.2	Downlink connectionless procedure description	158
9.1.3	Paging broadcast procedure	158
9.1.3.1	RFP paging broadcasts	158
9.1.3.2	PP paging procedures	161
9.1.3.2.1	PP paging detection	161
9.1.3.2.2	PP paging processing	161
9.2	Uplink connectionless procedures	161
9.2.1	General	161
9.2.2	Bearer selection for the connectionless uplink	162
9.2.3	Procedure for the connectionless uplink	162
9.2.3.1	Predicates	162
9.2.3.2	PT D-field construction	162
9.2.3.3	PT transmission sequence	163
9.2.3.4	FT procedure	163
9.3	Non-continuous broadcast procedure	164
9.3.1	Request for specific Q channel information	164
9.3.1.1	A-field procedure	164
9.3.1.2	B-field procedure	164
9.3.2	Request for a new dummy bearer	165
9.4	"No-emission" mode procedures	165
9.4.1	Initiation of the "no-emission" mode	165
9.4.1.1	Successful activation (countdown to zero)	165
9.4.1.2	Multiframe countdown stopped by FT	166
9.4.1.3	Multiframe countdown stopped by PT	166
9.4.1.4	PT does not receive multiframe countdown "zero"	167
9.4.2	Behaviour during power-down mode	167
9.4.3	Waking up, FT initiated	167
9.4.4	Waking up, PT initiated	171
10	Connection oriented service procedures	172
10.1	Overview	172
10.2	C/O connection setup	173
10.2.1	General	173
10.2.2	Initiation of a basic and a normal connection setup	173
10.2.3	Initiation of a fast connection setup	173
10.2.4	Connection setup procedure description	174
10.2.4.1	Creation of MBCs	174
10.2.4.2	Establishment of a single bearer duplex connection of a known service type	176
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation	177
10.2.4.3.1	Symmetric connection	179
10.2.4.3.2	Asymmetric uplink connection	179
10.2.4.3.3	Asymmetric downlink connection	179
10.2.4.3.4	Connection established	179
10.3	C/O connection modification	180
10.3.1	Advanced connection: bandwidth modification	180
10.3.1.1	Suspend and resume	182
10.3.1.2	MAC resume paging	182
10.3.2	Advanced connection: service type or slot type modification	182
10.3.2.1	Procedure for service type modification	182
10.3.2.2	Procedures for slot type modification	183
10.3.2.2.1	Procedure for slot type modification full to double	183
10.3.2.2.2	Procedure for slot type modification double to full	184
10.3.2.2.3	Procedures for slot type modification to/from long	184
10.3.2.2.4	Procedure for slot type modification in multibearer connections	185
10.3.2.3	Procedure for ECN number modification in an advanced connection	185
10.3.3	Connection type modification	185
10.3.3.1	Procedure for connection type modification basic to advanced	186
10.3.3.1.1	General procedure	186
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double	186

10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	187
10.3.3.2	Procedure for connection type modification advanced to basic	187
10.3.4	Modulation type modification.....	187
10.3.4.1	Adaptive code rate.....	189
10.4	C/O connection release.....	189
10.4.1	General.....	189
10.4.2	Procedure description	190
10.5	C/O bearer setup.....	190
10.5.1	Single bearer setup procedures	190
10.5.1.1	Basic bearer setup procedure.....	190
10.5.1.2	A-field advanced single bearer setup procedure	192
10.5.1.2.1	PT initiated	193
10.5.1.2.2	FT initiated	195
10.5.1.3	B-field single bearer setup procedure.....	196
10.5.1.3.1	PT initiated	197
10.5.1.3.2	FT initiated	199
10.5.1.4	Double simplex setup procedure	199
10.5.1.4.1	Terminology and Predicates	199
10.5.1.4.2	General description.....	200
10.5.1.4.3	Channel selection procedure for circuit mode connections	200
10.5.1.4.4	Channel selection procedure for packet mode connections	201
10.5.1.4.5	Indirect setup procedure	202
10.5.1.4.6	Direct setup procedure.....	202
10.5.1.4.7	Handling of encrypted connections	205
10.5.1.5	Complementary connection bearer setup	207
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	207
10.5.1.7	Usage of TA special code "111" and M _T message "B-field setup, first PT transmission"	208
10.5.1.7.1	Default rules for TA code "111"	209
10.5.1.7.2	Default rules for M _T message "B-field setup, first transmission"	209
10.5.2	Channel list procedures.....	210
10.5.2.1	General	210
10.5.2.2	Description of the channel list messages.....	210
10.5.2.3	Usage of the channel list messages.....	211
10.6	C/O bearer handover	212
10.6.1	General.....	212
10.6.2	Duplex bearer handover procedure.....	213
10.6.3	Double simplex bearer handover	214
10.6.4	Bearer replacement	214
10.6.4.1	General bearer replacement.....	214
10.6.4.2	Frequency replacement	215
10.7	C/O bearer release	216
10.7.1	General.....	216
10.7.2	Bearer release procedure description	216
10.7.2.1	Unacknowledged release procedure.....	216
10.7.2.1.1	Crossed bearer release procedure	217
10.7.2.2	Acknowledged release procedure.....	217
10.7.2.3	Fast release procedure	217
10.7.2.4	REP relayed bearer release.....	218
10.8	C/O data transfer	218
10.8.1	Higher layer associated signalling (C)	218
10.8.1.1	C _S channel data	218
10.8.1.1.1	Transmission principle	219
10.8.1.1.2	Numbering principle.....	219
10.8.1.2	C _F channel data	219
10.8.1.2.1	Transmission principle	219
10.8.1.2.2	Numbering principle.....	220
10.8.1.3	Q1 and Q2 bit settings for I _N and I _{P_error_detection} services	220
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I _N	220
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I _{P_error_detect}	220
10.8.1.3.3	Q2 bit settings.....	221
10.8.1.3.4	Q1 bit settings.....	222

10.8.2	MOD-2 protected I channel operation (I_P).....	223
10.8.2.1	General.....	223
10.8.2.2	Limiting the lifetime of packets.....	223
10.8.2.3	A-field shall always be correct.....	223
10.8.2.4	Use of the acknowledge bits.....	223
10.8.2.4.1	Q2 and BCK bit setting for I_P _error_correction services.....	224
10.8.2.4.2	BCK bit setting.....	224
10.8.2.5	Data jump procedures.....	224
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement.....	225
10.8.2.5.2	Unilateral jump.....	225
10.8.2.5.3	MAC I_P bearer reset.....	226
10.8.2.6	Bearer handover and bearer replacement procedures.....	227
10.8.2.6.1	General.....	227
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	227
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel.....	227
10.8.2.7	Exchange of data from/to higher layers.....	228
10.8.2.7.1	Operation if I_{PF} channel is supported.....	228
10.8.3	Higher layer unprotected information (I_N) and MAC_error_detection services (I_P).....	229
10.8.3.1	I_N _minimum_delay service.....	229
10.8.3.2	I_N _normal_delay service.....	229
10.8.3.3	I_P _error_detection service.....	229
10.8.3.3.1	Operation if I_{PF} channel is supported.....	230
10.8.3.4	I_P _encodec_protected service (I_{PX}).....	230
10.8.4	Higher layer U-plane channel (I_{PF}) in E+U type mux.....	230
10.8.4.1	Purpose of the I_{PF} channel.....	230
10.8.4.2	Activation of the E+U type mux mode.....	230
10.8.4.3	I_{PF} procedures.....	231
10.8.4.3.1	I_{PF} basic procedures.....	231
10.8.4.3.2	I_{PF} advanced procedures.....	232
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	232
10.8.4.4	I_{PF} Mod-2 protected operation.....	232
10.8.4.5	I_{PF} _error_detect operation.....	233
10.8.4.6	I_{PF} _operation with I_N service.....	233
10.8.4.7	Backcompatibility rule.....	233
10.9	C/O procedures for FT connections with CRFP.....	233
10.9.1	Dual C/O bearer setup.....	233
10.9.2	C/O connection release of connection with CRFP.....	234
10.9.3	C/O connection suspend and resume.....	234
11	Medium access layer management procedures.....	234
11.1	Broadcasting.....	234
11.1.1	RFP transmission.....	234
11.1.2	PP reception.....	234
11.2	Extended system information.....	235
11.2.1	PP requests.....	235
11.2.2	RFP response.....	235
11.3	PP states and state transitions.....	235
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	235
11.3.2	Entry into the Idle_Locked state.....	235
11.3.3	Actions in the Idle_Locked state.....	236
11.3.3.1	Page detection in Idle_Locked state.....	236
11.3.3.2	Setup detection in Idle_Locked state.....	236
11.3.4	Idle_Locked and Active_Locked state transitions.....	237
11.4	Physical channel selection.....	237
11.4.1	The channel selection lists.....	237
11.4.2	Physical channel and RFP selection at the PP.....	239
11.4.3	Physical channel selection at the RFP.....	241
11.4.4	Hand over criteria due to in-connection base identification.....	242
11.4.5	Handover criteria due to interference.....	243
11.5	In-connection quality control.....	243
11.5.1	RFPI handshake.....	243
11.5.2	Frequency control.....	243

11.5.2.1	RFP measurement of frequency error	243
11.5.2.2	PT frequency correction	243
11.6	Maximum allowed system load at RFPs	244
11.7	PMID and FMID definitions	244
11.7.1	FMID definition	244
11.7.2	PMID definition	244
11.8	RFP idle receiver scan sequence	244
11.9	PT receiver scan sequence	245
11.10	Management of connections associated with Broadband data links	245
11.11	Management procedures for "no-emission" mode	246
11.11.1	Behaviour during "no-emission" mode	246
12	Medium access layer test message procedure	246
12.1	Introduction	246
12.2	General	246
12.2.1	Portable part testing	248
12.2.2	Fixed part testing	248
12.2.3	Applicability of test messages	248
12.3	FORCE_TRANSMIT	248
12.3.1	Portable part	248
12.3.2	Fixed part	249
12.4	LOOPBACK_DATA	249
12.4.1	Portable part	250
12.4.2	Fixed Part	250
12.4.2.1	IUTs implementing the DECT scrambler	250
12.4.2.2	IUTs implementing a proprietary scrambler	250
12.5	DEFEAT_ANTENNA_DIVERSITY	250
12.6	NETWORK_TEST	250
12.7	ESCAPE	250
12.8	CLEAR_TEST_MODES	250
12.9	CHANGE_MODULATION_SCHEME	250
Annex A (normative):	MAC layer timers and constants	251
A.1	Timers and Time Windows	251
A.2	Constants	251
Annex B (informative):	Construction of the CRC polynomial and error detecting performance	253
Annex C (informative):	MAC relationship to other layers	254
Annex D (informative):	Synchronization	255
Annex E (normative):	Scrambling patterns	256
Annex F (informative):	Seamless handover operation	257
F.1	I channel data flow for I _N _minimum_delay service	257
Annex G (normative):	Requirements for PPs with direct PP to PP communication mode	258
G.1	Description of operation in direct PP to PP communication mode	258
G.2	Requirements	258
G.2.1	Setting the PP in direct communications mode	259
G.2.2	Specific Alternative 1 requirements	259
G.2.2.1	When the PP has not initiated a call	259
G.2.2.2	When the PP initiates a call	259
G.2.3	Specific Alternative 2 Requirements	260
Annex H (normative):	Requirements for FPs with Wireless FT to FT (W-FT2FT) communication mode	261

H.1	Introduction	261
H.2	Description of operation in W-FT2FT communication mode	262
Annex I (normative):	Channel coding and Modulation	263
I.1	Channel coding	263
I.1.1	The parallel Turbo Code Principle	264
I.1.2	The FOCTC implementation	264
I.1.2.1	The FOCTC concept	264
I.1.2.2	The FOCTC structure and the component code	265
I.1.2.3	The FOCTC Inner interleaving algorithm	267
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats	268
I.2	Adaptive coding and Modulation Embodiment	270
I.2.1	Adaptive code rates	270
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80)	271
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32)	272
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80)	272
I.2.2	Puncturing patterns	273
I.2.3	Channel Capacity for the B-field map configurations	274
I.2.3.1	Double Slot Structure	274
I.2.3.2	Full Slot Structure	275
I.2.3.3	Half Slot Structure	276
I.3	Change Modulation Scheme	276
Annex J (informative):	Channel decoding	277
Annex K (informative):	Additional information on MAC messages	278
K.1	Historic use of some MAC service codes	278
Annex L (informative):	Bibliography	279
Annex M (informative):	Change history	280
History		281

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [i.1] and ETR 043 [i.2].

National transposition dates	
Date of adoption of this EN:	17 October 2008
Date of latest announcement of this EN (doa):	31 January 2009
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2009
Date of withdrawal of any conflicting National Standard (dow):	31 July 2009