

**Digital Enhanced Cordless Telecommunications (DECT);  
Common Interface (CI);  
Part 3: Medium Access Control (MAC) layer**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/7198600c-43ff-4080-9146-0613c2807515/etsi-en-300-175-3-v2.2.1-2008-11>



---

**Reference**REN/DECT-000248-3

---

---

**Keywords**DECT, IMT-2000, MAC, mobility, radio, TDD,  
TDMA**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.  
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	13
Foreword.....	13
1 Scope .....	14
2 References .....	14
2.1 Normative references .....	15
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations .....	16
3.1 Definitions.....	16
3.2 Symbols and abbreviations.....	16
4 Description of the MAC layer .....	18
4.1 MAC layer reference model .....	18
4.1.1 General.....	19
4.1.2 Cluster Control Function (CCF) .....	19
4.1.3 Cell Site Functions (CSF).....	19
4.1.4 Relationship to physical layer elements.....	19
4.2 Frame and multiframe structures.....	20
4.2.1 General.....	20
4.2.2 Frame structure .....	20
4.2.3 Multiframe structure .....	22
4.3 State definitions.....	22
4.3.1 PP states.....	22
4.3.2 RFP states .....	23
5 Overview of MAC layer services.....	24
5.1 General .....	24
5.1.1 Broadcast Message Control (BMC).....	24
5.1.2 Connectionless Message Control (CMC).....	24
5.1.3 Multi-Bearer Control .....	24
5.2 Service descriptions.....	24
5.2.1 Common functions.....	24
5.2.2 BMC service .....	25
5.2.3 CMC service .....	25
5.2.4 MBC services.....	25
5.3 Logical channels.....	26
5.3.1 MBC connection endpoints (MC-SAP logical channels) .....	26
5.3.1.1 The higher layer C-plane channels, C .....	26
5.3.1.2 The higher layer U-Plane channels, I .....	26
5.3.1.3 The higher layer U-Plane control channel, G <sub>F</sub> .....	27
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I <sub>PF</sub> .....	27
5.3.2 CMC endpoints (MB-SAP logical channels).....	27
5.3.2.1 The connectionless C-Plane channels, CL .....	27
5.3.2.2 The connectionless U-Plane channels, SI <sub>N</sub> and SI <sub>P</sub> .....	28
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI <sub>PF</sub> .....	28
5.3.3 BMC endpoint (MA-SAP logical channel).....	28
5.3.3.1 The slow broadcast channel, B <sub>S</sub> .....	28
5.3.4 Internal MAC control channels.....	28
5.3.4.1 The system information channel, Q .....	28
5.3.4.2 Identities channel, N.....	29
5.3.4.3 The MAC control channel, M .....	29
5.3.4.4 MAC paging channel, P .....	29
5.4 SAP definitions .....	29
5.4.1 MA SAP .....	29
5.4.2 MB SAP.....	30
5.4.3 MC SAP.....	30

5.4.4	ME SAP .....	31
5.4.5	Order of transmission.....	31
5.5	Bearer.....	31
5.5.1	Bearer types .....	31
5.5.2	Bearer operation.....	32
5.6	Connection oriented services.....	32
5.6.1	Connection types .....	32
5.6.1.1	Basic connections.....	32
5.6.1.2	Advanced connections .....	33
5.6.1.2.1	Rules for ECN selection in advanced connections .....	33
5.6.1.3	Connection identifiers .....	33
5.6.1.4	Complementary connections .....	34
5.6.2	Symmetric and asymmetric connections.....	34
5.6.2.1	Symmetric connections .....	34
5.6.2.2	Asymmetric connections .....	39
5.7	Broadcast and connectionless services .....	47
5.7.1	The broadcast services .....	48
5.7.1.1	The continuous broadcast service .....	48
5.7.1.2	The non-continuous broadcast service .....	48
5.7.2	The connectionless services .....	49
5.7.2.1	Connectionless downlink services .....	49
5.7.2.2	Connectionless uplink services .....	49
6	Multiplexing .....	50
6.1	CCF multiplexing functions .....	50
6.2	CSF multiplexing functions.....	50
6.2.1	Bit Mappings (MAP) .....	55
6.2.1.1	D-field mapping (D-MAP).....	55
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80) .....	56
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32).....	56
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00) .....	57
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j) .....	57
6.2.1.2	A-field Mapping (A-MAP) .....	58
6.2.1.3	B-field Mapping (B-MAP).....	59
6.2.1.3.1	Unprotected format.....	59
6.2.1.3.2	Encoded protected format.....	61
6.2.1.3.3	Multisubfield protected format.....	61
6.2.1.3.4	Singlesubfield protected format.....	63
6.2.2	Time multiplexers .....	65
6.2.2.1	Tail MULTipleXer (T-MUX) .....	65
6.2.2.1.1	T-MUX algorithm for RFP transmissions .....	65
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	66
6.2.2.2	B-field control multiplexer (E/U-MUX) .....	67
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes .....	69
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield .....	69
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation .....	82
6.2.2.4	Priority scheme in E or E+U mode .....	82
6.2.3	Encryption.....	83
6.2.4	Scrambling.....	84
6.2.5	Error control.....	85
6.2.5.1	R-CRC overview .....	85
6.2.5.2	R-CRC generation and checking.....	86
6.2.5.3	X-CRC overview.....	87
6.2.5.4	X-CRC generation and checking.....	87
6.2.5.5	B-CRC generation and checking.....	89
6.2.6	Broadcast controller .....	89
7	Medium access layer messages .....	90
7.1	Header field .....	90
7.1.1	Overview/formatting.....	90
7.1.2	Tail identification, TA, bits $a_0$ to $a_2$ .....	91
7.1.3	The "Q1/BCK" bit, bit $a_3$ .....	91

7.1.4	B-field identification, BA, bits $a_4$ to $a_6$ .....	92
7.1.5	The "Q2" bit, bit $a_7$ .....	93
7.2	Messages in the tail field .....	93
7.2.1	Overview .....	93
7.2.2	Identities information ( $N_T$ ).....	93
7.2.3	System information and multiframe marker ( $Q_T$ ) .....	94
7.2.3.1	General .....	94
7.2.3.2	Static system information.....	95
7.2.3.2.1	General, $Q_H = 0, 1$ (hex) .....	95
7.2.3.2.2	$Q_H$ and Normal-Reverse (NR) .....	95
7.2.3.2.3	Slot Number (SN).....	95
7.2.3.2.4	Start Position (SP) .....	96
7.2.3.2.5	ESCAPE bit (ESC).....	96
7.2.3.2.6	Number of transceivers.....	96
7.2.3.2.7	Extended RF carrier information available ( $M_c$ ).....	96
7.2.3.2.8	RF carriers available (RF-cars).....	97
7.2.3.2.9	Spare bits (SPR) .....	97
7.2.3.2.10	Carrier number.....	97
7.2.3.2.11	Spare bits (SPR) .....	97
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	98
7.2.3.3	Extended RF carrier information part 1 .....	98
7.2.3.3.1	General, $Q_H = 2$ (hex).....	98
7.2.3.3.2	Further RF carrier extensions .....	99
7.2.3.3.3	Number of RF carriers.....	99
7.2.3.4	Fixed part capabilities .....	99
7.2.3.4.1	General, $Q_H = 3$ (hex) .....	99
7.2.3.4.2	Standard capabilities.....	99
7.2.3.5	Extended fixed part capabilities .....	100
7.2.3.5.1	General, $Q_H = 4$ (hex).....	100
7.2.3.5.2	Extended Physical and MAC layer capabilities.....	101
7.2.3.5.3	Extended higher layer capabilities.....	102
7.2.3.6	Secondary access rights identities .....	102
7.2.3.6.1	General, $Q_H = 5$ (hex).....	102
7.2.3.6.2	SARI message .....	102
7.2.3.7	Multiframe number .....	102
7.2.3.7.1	General, $Q_H = 6$ (hex).....	102
7.2.3.7.2	Multiframe number.....	102
7.2.3.8	Escape .....	103
7.2.3.8.1	General, $Q_H = 7$ (hex).....	103
7.2.3.8.2	Escape information.....	103
7.2.3.9	Extended RF carrier information part 2 .....	103
7.2.3.9.1	General, $Q_H = 9$ (hex).....	103
7.2.3.10	Transmit information .....	103
7.2.3.10.1	General, $Q_H = B$ (hex) .....	103
7.2.3.11	Extended fixed part capabilities (part 2) .....	104
7.2.3.11.1	General, $Q_H = C$ (hex) .....	104
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2).....	104
7.2.3.11.3	Extended higher layer capabilities (part 2).....	105
7.2.4	Paging Tail ( $P_T$ ) .....	105
7.2.4.1	General format .....	105
7.2.4.1.1	$P_T$ format for full and long page messages .....	105
7.2.4.1.2	$P_T$ format for short page messages .....	106
7.2.4.1.3	$P_T$ format for zero length page messages.....	106
7.2.4.1.4	$P_T$ format for MAC_Resume_and_Control_page message .....	106
7.2.4.2	$P_T$ header format.....	107
7.2.4.2.1	General format.....	107
7.2.4.2.2	Bit $a_8$ is the extend flag.....	107
7.2.4.2.3	$B_S$ SDU length indication .....	107
7.2.4.3	MAC layer information for PT.....	108
7.2.4.3.1	Information type .....	108
7.2.4.3.2	Fill bits / Blind long slot ( $j=640$ / $j=672$ ) information .....	108
7.2.4.3.3	Blind full slot information .....	109

7.2.4.3.4	Bearer description.....	109
7.2.4.3.5	Escape.....	110
7.2.4.3.6	Dummy or connectionless downlink bearer marker .....	110
7.2.4.3.7	Bearer handover/replacement information .....	110
7.2.4.3.8	RFP status and modulation types.....	111
7.2.4.3.9	Active carriers .....	112
7.2.4.3.10	RFP power level .....	112
7.2.4.3.11	Blind double slot/RFP-FP interface resource information.....	113
7.2.4.3.12	Extended modulation types .....	113
7.2.5	MAC control ( $M_T$ ) .....	114
7.2.5.1	General format and contents .....	114
7.2.5.2	Basic connection control .....	114
7.2.5.2.1	General .....	114
7.2.5.2.2	Format for most messages .....	115
7.2.5.2.3	WAIT .....	115
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm} .....	115
7.2.5.3	Advanced connection control.....	116
7.2.5.3.1	General .....	116
7.2.5.3.2	ACCESS_REQUEST .....	116
7.2.5.3.3	BEARER_HANDOVER_REQUEST .....	116
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST .....	116
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST .....	117
7.2.5.3.6	BEARER_CONFIRM .....	117
7.2.5.3.7	WAIT .....	117
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm} .....	117
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm} .....	120
7.2.5.3.10	Channel_list.....	120
7.2.5.3.11	Unconfirmed_dummy.....	121
7.2.5.3.12	Unconfirmed_handover.....	121
7.2.5.3.13	RELEASE .....	121
7.2.5.4	MAC layer test messages .....	122
7.2.5.4.1	Basic format .....	122
7.2.5.4.2	FORCE_TRANSMIT .....	123
7.2.5.4.3	LOOPBACK_DATA .....	123
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY.....	124
7.2.5.4.5	ESCAPE .....	125
7.2.5.4.6	NETWORK_TEST.....	125
7.2.5.4.7	CLEAR_TEST_MODES.....	125
7.2.5.4.8	CHANGE_MODULATION_SCHEME .....	125
7.2.5.5	Quality control .....	126
7.2.5.5.1	Prolonged preamble diversity .....	127
7.2.5.6	Broadcast and connectionless services.....	128
7.2.5.7	Encryption control.....	128
7.2.5.8	B-field setup, first PT transmission.....	129
7.2.5.9	Escape .....	129
7.2.5.10	TARI message.....	129
7.2.5.11	REP connection control.....	129
7.2.5.11.1	General .....	129
7.2.5.11.2	Format for most messages .....	130
7.2.5.11.3	REP CHANNEL MAP REQUEST .....	130
7.2.5.11.4	REP CHANNEL MAP CONFIRM.....	130
7.3	Messages in the B-field .....	130
7.3.1	Overview .....	130
7.3.2	Advanced connection control .....	132
7.3.2.1	General format .....	132
7.3.2.2	BEARER_REQUEST .....	132
7.3.2.3	BEARER_CONFIRM.....	133
7.3.2.4	WAIT .....	133
7.3.2.5	ATTRIBUTES_B_{Req;Cfm} .....	133
7.3.2.6	BANDWIDTH_B_{Req;Cfm} .....	134
7.3.2.7	CHANNEL_LIST .....	135
7.3.2.8	UNCONFIRMED_DUMMY.....	135

7.3.2.9	UNCONFIRMED_HANDOVER .....	135
7.3.2.10	RELEASE .....	135
7.3.3	Null or I <sub>PF</sub> segmentation info .....	137
7.3.3.1	Spare or I <sub>PF</sub> segmentation info .....	138
7.3.3.2	Extended NCF bits .....	138
7.3.4	Quality control .....	139
7.3.4.1	General format .....	139
7.3.4.2	Bearer and connection control.....	139
7.3.4.3	RESET .....	141
7.3.4.4	Bearer quality in an asymmetric connection .....	141
7.3.5	Extended system information .....	142
7.3.5.1	General format .....	142
7.3.5.2	TARI messages .....	142
7.3.5.3	"no-emission" mode sync information .....	142
7.3.6	G <sub>F</sub> channel data packet.....	143
7.3.7	Escape.....	143
8	Medium access layer primitives .....	143
8.1	Connection oriented service primitives .....	144
8.1.1	Connection setup: MAC_CON {req;ind;cfm} .....	144
8.1.2	Connection modification: MAC_MOD {req;ind;cfm} .....	145
8.1.3	CO data transmit ready: MAC_CO_DTR {ind} .....	146
8.1.4	CO data transfer: MAC_CO_DATA {req;ind} .....	147
8.1.5	Restart DLC: MAC_RES_DLC {ind} .....	147
8.1.6	Connection release: MAC_DIS {req;ind} .....	147
8.1.7	MAC bandwidth: MAC_BW {ind;res} .....	148
8.1.8	Encryption.....	148
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}.....	148
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm} .....	148
8.1.9	C-plane switching procedure .....	149
8.1.9.1	C-plane switching procedure: MAC_C <sub>S</sub> C <sub>F</sub> {req, cfm, ind, res}.....	149
8.1.9.2	C-plane switching procedure: MAC_C <sub>S</sub> C <sub>F</sub> _END {ind} .....	149
8.2	Connectionless and broadcast service primitives.....	150
8.2.1	Paging: MAC_PAGE {req;ind}.....	150
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind} .....	150
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm} .....	151
8.2.4	"no-emission" mode.....	151
8.3	Management primitives .....	151
8.3.1	Connection control.....	151
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	151
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req} .....	151
8.3.1.3	Bearer release: MAC_ME_REL {req} .....	151
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind} .....	152
8.3.2	System information and identities .....	152
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req} .....	152
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req} .....	152
8.3.2.3	System information output: MAC_ME_INFO {ind;res} .....	152
8.3.2.4	Extended system info: MAC_ME_EXT.{req;ind;res;cfm} .....	152
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	152
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm} .....	153
8.3.5	Error reports: MAC_ME_ERROR {ind;res} .....	153
8.4	Flow control .....	153
8.4.1	MA SAP flow control.....	153
8.4.2	MB SAP flow control .....	153
8.4.3	MC SAP flow control .....	153
9	Broadcast and connectionless procedures .....	155
9.1	Downlink broadcast and connectionless procedures .....	155
9.1.1	Downlink broadcast procedure .....	156
9.1.1.1	Broadcast information.....	156
9.1.1.2	Channel selection for downlink broadcast services.....	156
9.1.1.3	Downlink broadcast procedure description.....	157

9.1.2	Downlink connectionless procedure .....	158
9.1.2.1	Channel selection at the RFP .....	158
9.1.2.2	Downlink connectionless procedure description .....	158
9.1.3	Paging broadcast procedure .....	158
9.1.3.1	RFP paging broadcasts .....	158
9.1.3.2	PP paging procedures .....	161
9.1.3.2.1	PP paging detection .....	161
9.1.3.2.2	PP paging processing .....	161
9.2	Uplink connectionless procedures .....	161
9.2.1	General .....	161
9.2.2	Bearer selection for the connectionless uplink .....	162
9.2.3	Procedure for the connectionless uplink .....	162
9.2.3.1	Predicates .....	162
9.2.3.2	PT D-field construction .....	162
9.2.3.3	PT transmission sequence .....	163
9.2.3.4	FT procedure .....	163
9.3	Non-continuous broadcast procedure .....	164
9.3.1	Request for specific Q channel information .....	164
9.3.1.1	A-field procedure .....	164
9.3.1.2	B-field procedure .....	164
9.3.2	Request for a new dummy bearer .....	165
9.4	"No-emission" mode procedures .....	165
9.4.1	Initiation of the "no-emission" mode .....	165
9.4.1.1	Successful activation (countdown to zero) .....	165
9.4.1.2	Multiframe countdown stopped by FT .....	166
9.4.1.3	Multiframe countdown stopped by PT .....	166
9.4.1.4	PT does not receive multiframe countdown "zero" .....	167
9.4.2	Behaviour during power-down-mode .....	167
9.4.3	Waking up, FT initiated .....	167
9.4.4	Waking up, PT initiated .....	171
10	Connection oriented service procedures .....	172
10.1	Overview .....	172
10.2	C/O connection setup .....	173
10.2.1	General .....	173
10.2.2	Initiation of a basic and a normal connection setup .....	173
10.2.3	Initiation of a fast connection setup .....	173
10.2.4	Connection setup procedure description .....	174
10.2.4.1	Creation of MBCs .....	174
10.2.4.2	Establishment of a single bearer duplex connection of a known service type .....	176
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation .....	177
10.2.4.3.1	Symmetric connection .....	179
10.2.4.3.2	Asymmetric uplink connection .....	179
10.2.4.3.3	Asymmetric downlink connection .....	179
10.2.4.3.4	Connection established .....	179
10.3	C/O connection modification .....	180
10.3.1	Advanced connection: bandwidth modification .....	180
10.3.1.1	Suspend and resume .....	182
10.3.1.2	MAC resume paging .....	182
10.3.2	Advanced connection: service type or slot type modification .....	182
10.3.2.1	Procedure for service type modification .....	182
10.3.2.2	Procedures for slot type modification .....	183
10.3.2.2.1	Procedure for slot type modification full to double .....	183
10.3.2.2.2	Procedure for slot type modification double to full .....	184
10.3.2.2.3	Procedures for slot type modification to/from long .....	184
10.3.2.2.4	Procedure for slot type modification in multibearer connections .....	185
10.3.2.3	Procedure for ECN number modification in an advanced connection .....	185
10.3.3	Connection type modification .....	185
10.3.3.1	Procedure for connection type modification basic to advanced .....	186
10.3.3.1.1	General procedure .....	186
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double .....	186



10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long.....	187
10.3.3.2	Procedure for connection type modification advanced to basic .....	187
10.3.4	Modulation type modification.....	187
10.3.4.1	Adaptive code rate.....	189
10.4	C/O connection release.....	189
10.4.1	General.....	189
10.4.2	Procedure description .....	190
10.5	C/O bearer setup.....	190
10.5.1	Single bearer setup procedures .....	190
10.5.1.1	Basic bearer setup procedure.....	190
10.5.1.2	A-field advanced single bearer setup procedure .....	192
10.5.1.2.1	PT initiated .....	193
10.5.1.2.2	FT initiated .....	195
10.5.1.3	B-field single bearer setup procedure.....	196
10.5.1.3.1	PT initiated .....	197
10.5.1.3.2	FT initiated .....	199
10.5.1.4	Double simplex setup procedure .....	199
10.5.1.4.1	Terminology and Predicates .....	199
10.5.1.4.2	General description.....	200
10.5.1.4.3	Channel selection procedure for circuit mode connections .....	200
10.5.1.4.4	Channel selection procedure for packet mode connections .....	201
10.5.1.4.5	Indirect setup procedure .....	202
10.5.1.4.6	Direct setup procedure.....	202
10.5.1.4.7	Handling of encrypted connections .....	205
10.5.1.5	Complementary connection bearer setup .....	207
10.5.1.6	Double duplex bearer setup procedure: Mapping procedure.....	207
10.5.1.7	Usage of TA special code "111" and M <sub>T</sub> message "B-field setup, first PT transmission" .....	208
10.5.1.7.1	Default rules for TA code "111" .....	209
10.5.1.7.2	Default rules for M <sub>T</sub> message "B-field setup, first transmission" .....	209
10.5.2	Channel list procedures.....	210
10.5.2.1	General .....	210
10.5.2.2	Description of the channel list messages.....	210
10.5.2.3	Usage of the channel list messages .....	211
10.6	C/O bearer handover .....	212
10.6.1	General.....	212
10.6.2	Duplex bearer handover procedure.....	213
10.6.3	Double simplex bearer handover .....	214
10.6.4	Bearer replacement .....	214
10.6.4.1	General bearer replacement.....	214
10.6.4.2	Frequency replacement .....	215
10.7	C/O bearer release .....	216
10.7.1	General.....	216
10.7.2	Bearer release procedure description .....	216
10.7.2.1	Unacknowledged release procedure.....	216
10.7.2.1.1	Crossed bearer release procedure .....	217
10.7.2.2	Acknowledged release procedure.....	217
10.7.2.3	Fast release procedure .....	217
10.7.2.4	REP relayed bearer release.....	218
10.8	C/O data transfer .....	218
10.8.1	Higher layer associated signalling (C) .....	218
10.8.1.1	C <sub>S</sub> channel data .....	218
10.8.1.1.1	Transmission principle .....	219
10.8.1.1.2	Numbering principle.....	219
10.8.1.2	C <sub>F</sub> channel data .....	219
10.8.1.2.1	Transmission principle .....	219
10.8.1.2.2	Numbering principle.....	220
10.8.1.3	Q1 and Q2 bit settings for I <sub>N</sub> and I <sub>P_error_detection</sub> services .....	220
10.8.1.3.1	Q1 and Q2 bit settings for MAC service I <sub>N</sub> .....	220
10.8.1.3.2	Q1 and Q2 bit settings for MAC service I <sub>P_error_detect</sub> .....	220
10.8.1.3.3	Q2 bit settings.....	221
10.8.1.3.4	Q1 bit settings.....	222

10.8.2	MOD-2 protected I channel operation ( $I_P$ ).....	223
10.8.2.1	General.....	223
10.8.2.2	Limiting the lifetime of packets.....	223
10.8.2.3	A-field shall always be correct.....	223
10.8.2.4	Use of the acknowledge bits.....	223
10.8.2.4.1	Q2 and BCK bit setting for $I_P$ _error_correction services.....	224
10.8.2.4.2	BCK bit setting.....	224
10.8.2.5	Data jump procedures.....	224
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement.....	225
10.8.2.5.2	Unilateral jump.....	225
10.8.2.5.3	MAC $I_P$ bearer reset.....	226
10.8.2.6	Bearer handover and bearer replacement procedures.....	227
10.8.2.6.1	General.....	227
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	227
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel.....	227
10.8.2.7	Exchange of data from/to higher layers.....	228
10.8.2.7.1	Operation if $I_{PF}$ channel is supported.....	228
10.8.3	Higher layer unprotected information ( $I_N$ ) and MAC_error_detection services ( $I_P$ ).....	229
10.8.3.1	$I_N$ _minimum_delay service.....	229
10.8.3.2	$I_N$ _normal_delay service.....	229
10.8.3.3	$I_P$ _error_detection service.....	229
10.8.3.3.1	Operation if $I_{PF}$ channel is supported.....	230
10.8.3.4	$I_P$ _encodec_protected service ( $I_{PX}$ ).....	230
10.8.4	Higher layer U-plane channel ( $I_{PF}$ ) in E+U type mux.....	230
10.8.4.1	Purpose of the $I_{PF}$ channel.....	230
10.8.4.2	Activation of the E+U type mux mode.....	230
10.8.4.3	$I_{PF}$ procedures.....	231
10.8.4.3.1	$I_{PF}$ basic procedures.....	231
10.8.4.3.2	$I_{PF}$ advanced procedures.....	232
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	232
10.8.4.4	$I_{PF}$ Mod-2 protected operation.....	232
10.8.4.5	$I_{PF}$ _error_detect operation.....	233
10.8.4.6	$I_{PF}$ _operation with $I_N$ service.....	233
10.8.4.7	Backcompatibility rule.....	233
10.9	C/O procedures for FT connections with CRFP.....	233
10.9.1	Dual C/O bearer setup.....	233
10.9.2	C/O connection release of connection with CRFP.....	234
10.9.3	C/O connection suspend and resume.....	234
11	Medium access layer management procedures.....	234
11.1	Broadcasting.....	234
11.1.1	RFP transmission.....	234
11.1.2	PP reception.....	234
11.2	Extended system information.....	235
11.2.1	PP requests.....	235
11.2.2	RFP response.....	235
11.3	PP states and state transitions.....	235
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	235
11.3.2	Entry into the Idle_Locked state.....	235
11.3.3	Actions in the Idle_Locked state.....	236
11.3.3.1	Page detection in Idle_Locked state.....	236
11.3.3.2	Setup detection in Idle_Locked state.....	236
11.3.4	Idle_Locked and Active_Locked state transitions.....	237
11.4	Physical channel selection.....	237
11.4.1	The channel selection lists.....	237
11.4.2	Physical channel and RFP selection at the PP.....	239
11.4.3	Physical channel selection at the RFP.....	241
11.4.4	Hand over criteria due to in-connection base identification.....	242
11.4.5	Handover criteria due to interference.....	243
11.5	In-connection quality control.....	243
11.5.1	RFPI handshake.....	243
11.5.2	Frequency control.....	243

11.5.2.1	RFP measurement of frequency error .....	243
11.5.2.2	PT frequency correction .....	243
11.6	Maximum allowed system load at RFPs .....	244
11.7	PMID and FMID definitions .....	244
11.7.1	FMID definition .....	244
11.7.2	PMID definition .....	244
11.8	RFP idle receiver scan sequence .....	244
11.9	PT receiver scan sequence .....	245
11.10	Management of connections associated with Broadband data links .....	245
11.11	Management procedures for "no-emission" mode .....	246
11.11.1	Behaviour during "no-emission" mode .....	246
12	Medium access layer test message procedure .....	246
12.1	Introduction .....	246
12.2	General .....	246
12.2.1	Portable part testing .....	248
12.2.2	Fixed part testing .....	248
12.2.3	Applicability of test messages .....	248
12.3	FORCE_TRANSMIT .....	248
12.3.1	Portable part .....	248
12.3.2	Fixed part .....	249
12.4	LOOPBACK_DATA .....	249
12.4.1	Portable part .....	250
12.4.2	Fixed Part .....	250
12.4.2.1	IUTs implementing the DECT scrambler .....	250
12.4.2.2	IUTs implementing a proprietary scrambler .....	250
12.5	DEFEAT_ANTENNA_DIVERSITY .....	250
12.6	NETWORK_TEST .....	250
12.7	ESCAPE .....	250
12.8	CLEAR_TEST_MODES .....	250
12.9	CHANGE_MODULATION_SCHEME .....	250
<b>Annex A (normative):</b>	<b>MAC layer timers and constants .....</b>	<b>251</b>
A.1	Timers and Time Windows .....	251
A.2	Constants .....	251
<b>Annex B (informative):</b>	<b>Construction of the CRC polynomial and error detecting performance .....</b>	<b>253</b>
<b>Annex C (informative):</b>	<b>MAC relationship to other layers .....</b>	<b>254</b>
<b>Annex D (informative):</b>	<b>Synchronization .....</b>	<b>255</b>
<b>Annex E (normative):</b>	<b>Scrambling patterns .....</b>	<b>256</b>
<b>Annex F (informative):</b>	<b>Seamless handover operation .....</b>	<b>257</b>
F.1	I channel data flow for I <sub>N</sub> _minimum_delay service .....	257
<b>Annex G (normative):</b>	<b>Requirements for PPs with direct PP to PP communication mode .....</b>	<b>258</b>
G.1	Description of operation in direct PP to PP communication mode .....	258
G.2	Requirements .....	258
G.2.1	Setting the PP in direct communications mode .....	259
G.2.2	Specific Alternative 1 requirements .....	259
G.2.2.1	When the PP has not initiated a call .....	259
G.2.2.2	When the PP initiates a call .....	259
G.2.3	Specific Alternative 2 Requirements .....	260
<b>Annex H (normative):</b>	<b>Requirements for PPs with Wireless FT to FT (W-FT2FT) communication mode .....</b>	<b>261</b>

H.1	Introduction .....	261
H.2	Description of operation in W-FT2FT communication mode .....	262
<b>Annex I (normative):</b>	<b>Channel coding and Modulation .....</b>	<b>263</b>
I.1	Channel coding .....	263
I.1.1	The parallel Turbo Code Principle .....	264
I.1.2	The FOCTC implementation .....	264
I.1.2.1	The FOCTC concept .....	264
I.1.2.2	The FOCTC structure and the component code .....	265
I.1.2.3	The FOCTC Inner interleaving algorithm .....	267
I.1.2.4	FOCTC Inner interleaving size adaptation to all Physical Packet Formats .....	268
I.2	Adaptive coding and Modulation Embodiment .....	270
I.2.1	Adaptive code rates .....	270
I.2.1.1	Adaptive code rates for the double slot structure (physical packet P80) .....	271
I.2.1.2	Adaptive code rates for the full slot structure (physical packet P32) .....	272
I.2.1.3	Adaptive code rates for the half slot structure (physical packet P00j with j=80) .....	272
I.2.2	Puncturing patterns .....	273
I.2.3	Channel Capacity for the B-field map configurations .....	274
I.2.3.1	Double Slot Structure .....	274
I.2.3.2	Full Slot Structure .....	275
I.2.3.3	Half Slot Structure .....	276
I.3	Change Modulation Scheme .....	276
<b>Annex J (informative):</b>	<b>Channel decoding .....</b>	<b>277</b>
<b>Annex K (informative):</b>	<b>Additional information on MAC messages .....</b>	<b>278</b>
K.1	Historic use of some MAC service codes .....	278
<b>Annex L (informative):</b>	<b>Bibliography .....</b>	<b>279</b>
<b>Annex M (informative):</b>	<b>Change history .....</b>	<b>280</b>
History .....		281

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in TR 101 178 [11] and ETR 043 [12].

<b>Proposed national transposition dates</b>	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa