

---

---

**Gas cylinders — Parallel threads for  
connection of valves to gas cylinders —**

**Part 1:  
Specification**

*Bouteilles à gaz — Filetages parallèles pour le raccordement des robinets  
sur les bouteilles à gaz —*  
*(Partie 1: Spécifications)*

[ISO 15245-1:2001](https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15245-1:2001

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

© ISO 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Contents

Page

Foreword.....	iv
Introduction .....	v
1     Scope .....	1
2     Normative references .....	1
3     Terms and definitions.....	2
4     Requirements .....	3
4.1   Thread rotation.....	3
4.2   Thread profile .....	4
4.3   Pitch .....	4
4.4   Thread dimensions .....	6
5     Thread end finish .....	6
6     Identification.....	6
Bibliography .....	8

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 15245-1:2001

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 15245 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 15245-1 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

ISO 15245 consists of the following parts, under the general title *Gas cylinders – Parallel threads for connection of valves to gas cylinders*:

— *Part 1: Specification*

— *Part 2: Gauge inspection*

TC1 STANDARD PREVIEW  
(standards.iteh.ai)  
<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

## Introduction

Cylinders intended to contain compressed, liquefied or dissolved gas under pressure are fitted with accessories (valves, straight or angle fittings) to allow release of and refilling with gas. Hereinafter, the term “valve” applies to such accessories.

The connection between cylinder and valve is obtained by the assembly of two parallel threads with the same nominal pitch and thread profile – an external one on the valve stem and an internal one in the cylinder neck – and an “O” ring seal.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15245-1:2001](https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15245-1:2001

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

# Gas cylinders — Parallel threads for connection of valves to gas cylinders —

## Part 1: Specification

### 1 Scope

This part of ISO 15245 specifies definitions, dimensions and tolerances of parallel screw threads of nominal diameter 30 mm (designated 30P), 25 mm (designated 25P) and 18 mm (designated 18P), for the connection of valves to medical and industrial gas cylinders.

This part of ISO 15245 does not cover the connection requirements for:

- mechanical strength;
- gas tightness;
- capability of repeated assembly and dismounting operations<sup>1)</sup>.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO 15245-1:2001](https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001)

### 2 Normative references

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 15245. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 15245 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 68-1, *ISO general purpose screw threads — Basic profile — Part 1: Metric screw threads*

ISO 261, *ISO general-purpose metric screw threads — General plan*

ISO 724, *ISO general-purpose metric screw threads — Basic dimensions*

ISO 965-1, *ISO general-purpose metric screw threads — Tolerances — Part 1: Principles and basic data*

ISO 965-2, *ISO general purpose metric screw threads — Tolerances — Part 2: Limits of sizes for general purpose external and internal screw threads — Medium quality*

ISO 11114-2, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 2: Non-metallic materials*

1) This aspect is covered in ISO 13341.

### 3 Terms and definitions

General definitions for parallel threads can be found in ISO 5408.

For the purposes of this part of ISO 15245, the following terms and definitions apply.

#### 3.1

##### **valve stem**

parallel sided end of valve body, with a thread formed on the external surface with a plain machined section close to the flange on the valve body for “O” ring seating

See Figure 1, thread X.

#### 3.2

##### **cylinder neck thread**

A

parallel sided axial hole in the cylinder neck

See Figure 2.

NOTE This includes a thread formed on the internal surface including a sealing recess for the “O” ring and thread relief.

#### 3.3

##### **sealing recess diameter**

B

diameter of tapered recess machined in the top face of the cylinder neck, concentric with the cylinder neck thread, to provide a surface on which the “O” ring can seal

See Figure 2.

#### 3.4

##### **sealing recess depth**

F

depth of tapered recess machined in the top face of the cylinder neck, concentric with the cylinder neck thread, to provide a surface on which the “O” ring can seal

See Figure 2.

#### 3.5

##### **thread relief**

C

diameter of plain machined parallel sided section, concentric with the cylinder neck thread, between the cylinder neck thread and the sealing recess

See Figure 2.

#### 3.6

##### **distance to start of thread**

E

distance from the top face of the cylinder neck to the start of the thread, including recess depth and thread relief

See Figure 2.

#### 3.7

##### **thread relief**

V

minimum length of plain machined parallel sided section on the valve stem, between the valve stem thread and the flange on the valve body, on to which the “O” ring can seal

See Figure 1.



### 3.8 minimum full thread length

*D*

minimum distance from the top face of the cylinder neck to the bottom of the cylinder neck thread

See Figure 2.

### 3.9 “O” ring diameter

*R*

internal diameter of seal used to prevent unintentional escape of gas from the cylinder

See Figure 3.

### 3.10 “O” ring thickness

*W*

width of cross section of seal used to prevent unintentional escape of gas from the cylinder

See Figure 3.

### 3.11 flange

*Y*

minimum diameter of the flange on the valve body which seals on to the “O” ring and the top face of the cylinder neck

See Figure 1.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO 15245-1:2001](https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001)

<https://standards.iteh.ai/catalog/standards/sist/df45fc4b-9816-4eae-b307-1020b802b722/iso-15245-1-2001>

### 3.12 length of valve stem

*Z*

distance from the flange on the valve body to the bottom of the valve stem thread

See Figure 1.

### 3.13 vent groove (optional)

*G*

groove(s) which are machined in the valve stem thread such that any residual pressure within the cylinder will be vented when the valve is unscrewed

See Figure 4.

NOTE Such grooves need to have smooth edges in order to ensure that they do not damage the cylinder threads during insertion or removal of valves.

## 4 Requirements

### 4.1 Thread rotation

The thread shall be a right hand thread such that it moves away from an observer when rotated clockwise.