



Designation: D 803 – 03

## Standard Test Methods for Testing Tall Oil<sup>1</sup>

This standard is issued under the fixed designation D 803; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last approval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 These test methods cover the test procedures to be applied to whole tall oils or refined tall oils. Previous editions of these test methods have described test procedures that are used to test tall oil fatty acid, rosin, and other tall oil-derived products as well as test crude and refined tall oil. Consequently, these test methods are widely cited in reference books and industry literature for the testing of tall oil-derived products.

1.1.1 In this current revision, procedural details of some of the often-cited test methods have been removed and the test methods consolidated with other existing test methods. In such cases the consolidated methods, applicable to all tall oil-derived products, are referenced.

1.2 The procedures appear in the following order:

	Physical Tests	Sections
Viscosity:		
Brookfield Method (Preferred Method)		7
Bubble Time Method		8
Flash Point		9
Color		10
Moisture:		11
Insoluble Matter		12
Ash		13
	Chemical Analysis	
Acid Number		16
Saponification Number		17
Rosin Acids		18
Unsaponifiable Matter		19
Fatty Acids		20

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

#### 2.1 ASTM Standards:

D 92 Test Method for Flash and Fire Points by Cleveland Open Cup<sup>2</sup>

<sup>1</sup> These test methods are under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and are the direct responsibility of Subcommittee D01.34 on Naval Stores.

Current edition approved May 10, 2003. Published June 2003. Originally approved in 1944. Last previous edition approved in 2002 as D 803 – 02.

<sup>2</sup> *Annual Book of ASTM Standards*, Vol 05.01.

- D 93 Test Methods for Flash Point by Pensky-Martens Closed Tester<sup>2</sup>
- D 269 Test Method for Insoluble Matter in Rosin and Rosin Derivatives<sup>3</sup>
- D 464 Test Methods for Saponification Number of Naval Store Products Including Tall Oil and Other Related Products<sup>3</sup>
- D 465 Test Methods for Acid Number of Naval Store Products Including Tall Oil and Other Related Products<sup>3</sup>
- D 890 Test Method for Water in Liquid Naval Stores<sup>3</sup>
- D 1065 Test Method for Unsaponifiable Matter in Naval Stores, Including Rosin, Tall Oil, and Related Products<sup>3</sup>
- D 1240 Test Methods for Rosin Acids Content of Naval Stores, Including Rosin, Tall Oil, and Related Products<sup>3</sup>
- D 1466 Test Method for Sampling Liquid Oils and Fatty Acids Commonly Used in Paints, Varnishes, and Related Materials<sup>3</sup>
- D 1544 Test Method for Color of Transparent Liquids (Gardner Color Scale)<sup>4</sup>
- D 1545 Test Method for Viscosity of Transparent Liquids by Bubble Time Method<sup>3</sup>
- D 1585 Test Methods for Fatty Acids Content of Naval Stores Including Rosin, Tall Oil, and Related Products<sup>3</sup>
- D 2196 Test Methods for Rheological Properties of Non-Newtonian Materials by Rotational (Brookfield type) Viscometer<sup>4</sup>
- D 3278 Test Methods for Flash Point of Liquids by Small Scale Closed-Cup Apparatus<sup>4</sup>
- D 5974 Test Methods for Fatty and Rosin Acids in Tall Oil Fractionation Products By Capillary Gas Chromatography<sup>3</sup>
- D 6166 Test Method for Color of Naval Stores and Related Products (Instrumental Determination of Gardner Color)<sup>3</sup>
- E 300 Practice for Sampling Industrial Chemicals<sup>5</sup>

### 3. Significance and Use

3.1 Tall oil, both crude and refined, is an important by-product of the alkaline (kraft) pulping of pine wood. It consists primarily of fatty acids, resin acids, and neutral materials; the

<sup>3</sup> *Annual Book of ASTM Standards*, Vol 06.03.

<sup>4</sup> *Annual Book of ASTM Standards*, Vol 06.01.

<sup>5</sup> *Annual Book of ASTM Standards*, Vol 15.05.