
**Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) -
Naprave kratkega dosega (SRD) - Radijska oprema, ki se uporablja v frekvenčnem
območju od 25 MHz do 1000 MHz z močnostnimi nivoji do največ 500 mW - 1. del:
Tehnične karakteristike in preskusne metode**

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Short Range Devices (SRD) - Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW - Part 1: Technical characteristics and test methods

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 220-1 V2.3.1:2010](https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010>

Ta slovenski standard je istoveten z: EN 300 220-1 Version 2.3.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

SIST EN 300 220-1 V2.3.1:2010 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 220-1 V2.3.1:2010

<https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010>

ETSI EN 300 220-1 V2.3.1 (2010-02)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Radio equipment to be used in the 25 MHz to 1 000 MHz
frequency range with power levels ranging up to 500 mW;
Part 1: Technical characteristics and test methods**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 220-1 V2.3.1:2010](https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010>



Reference

REN/ERM-TG28-0420-1

Keywords

radio, SRD, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 220-1 V2.3.1:2010

<https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/ETSI-ERM-TG28-0420-1-v2-3-1-2010>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	9
2 References	10
2.1 Normative references	10
2.2 Informative references.....	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	14
3.3 Abbreviations	14
4 Technical requirement specifications	15
4.1 General requirements	15
4.1.1 Receiver category	15
4.1.2 General performance criteria	15
4.2 Presentation of equipment for testing purposes.....	16
4.2.1 Choice of model for testing	16
4.2.2 Testing of equipment with alternative power levels	16
4.2.3 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment)	16
4.2.3.1 Equipment with an internal permanent or temporary antenna connector or using a dedicated test fixture	16
4.2.3.2 Equipment with a temporary antenna connector.....	17
4.3 Mechanical and electrical design.....	17
4.3.1 General.....	17
4.3.2 Controls	17
4.3.3 Transmitter shut-off facility.....	17
4.3.4 Receiver mute or squelch.....	17
4.3.5 Marking (equipment identification).....	17
4.4 Auxiliary test equipment	17
5 Test conditions, power sources and ambient temperatures	18
5.1 Normal and extreme test conditions	18
5.2 Test power source.....	18
5.2.1 External test power source	18
5.2.2 Internal test power source	18
5.3 Normal test conditions.....	18
5.3.1 Normal temperature and humidity	18
5.3.2 Normal test power source	19
5.3.2.1 Mains voltage	19
5.3.2.2 Regulated lead-acid battery power sources	19
5.3.2.3 Other power sources.....	19
5.4 Extreme test conditions	19
5.4.1 Extreme temperatures	19
5.4.1.1 Procedure for tests at extreme temperatures.....	19
5.4.1.1.1 Procedure for equipment designed for continuous operation	19
5.4.1.1.2 Procedure for equipment designed for intermittent operation	20
5.4.1.2 Extreme temperature ranges.....	20
5.4.2 Extreme test source voltages.....	20
5.4.2.1 Mains voltage.....	20
5.4.2.2 Regulated lead-acid battery power sources	20
5.4.2.3 Power sources using other types of batteries.....	21
5.4.2.4 Other power sources.....	21

6	General conditions.....	21
6.1	Normal test signals and test modulation.....	21
6.1.1	Normal test signals for analogue speech.....	21
6.1.2	Normal test signals for data.....	22
6.1.3	Testing of frequency agile or hopping equipment.....	22
6.2	Artificial antenna.....	22
6.3	Test fixture.....	22
6.3.1	Validation of the test-fixture in the temperature chamber.....	23
6.3.2	Mode of use.....	25
6.4	Test sites and general arrangements for radiated measurements.....	26
6.5	Modes of operation of the transmitter.....	26
6.6	Measuring receiver.....	26
7	Methods of measurement and limits for transmitter parameters.....	27
7.1	Frequency error.....	27
7.1.1	Definition.....	27
7.1.2	Method of measurement.....	27
7.1.3	Limits.....	27
7.2	Average power (conducted).....	28
7.2.1	Definition.....	28
7.2.2	Method of measurement.....	28
7.2.3	Limits.....	29
7.3	Effective radiated power.....	31
7.3.1	Definition.....	31
7.3.2	Methods of measurement.....	31
7.3.3	Limits.....	32
7.4	Spread spectrum modulation.....	32
7.4.1	Frequency Hopping Spread Spectrum devices (FHSS).....	32
7.4.1.1	FHSS definitions.....	32
7.4.1.2	FHSS declarations.....	32
7.4.1.3	Limits.....	33
7.4.2	Direct sequence or spread spectrum other than FHSS.....	33
7.4.2.1	Definition.....	33
7.4.2.2	Limits.....	33
7.5	Transient power.....	34
7.5.1	Definition.....	34
7.5.2	Method of measurement.....	34
7.5.3	Limits.....	35
7.6	Adjacent channel power.....	35
7.6.1	Definition.....	35
7.6.2	Method of measurement.....	35
7.6.3	Limits.....	36
7.7	Modulation bandwidth.....	36
7.7.1	Measurement applicability.....	36
7.7.2	Method of measurement.....	37
7.7.3	Limits.....	38
7.8	Unwanted emissions in the spurious domain.....	38
7.8.1	Definition.....	38
7.8.2	Method of measurement.....	39
7.8.2.1	Method of measuring the power level in a specified load, clause 7.8.1 a) i).....	39
7.8.2.2	Method of measuring the effective radiated power, clause 7.8.1 a) ii).....	40
7.8.2.3	Method of measuring the effective radiated power, clause 7.8.1 b).....	41
7.8.3	Limits.....	41
7.9	Frequency stability under low voltage conditions.....	41
7.9.1	Definition.....	41
7.9.2	Method of measurement.....	41
7.9.3	Limits.....	41
7.10	Duty Cycle.....	41
7.10.1	Definitions.....	42
7.10.2	Declaration.....	42
7.10.3	Duty cycle limits.....	42
7.11	Time-out-timer.....	42

7.11.1	Definition.....	42
7.11.2	Declaration.....	42
7.11.3	Limit	42
8	Receiver parameters	43
8.1	Receiver sensitivity	43
8.1.1	Definition.....	43
8.1.2	Method of measurement with continuous bit streams.....	43
8.1.3	Method of measurement with messages	44
8.1.4	Limits.....	44
8.2	Receiver LBT threshold	45
8.2.1	Definitions	45
8.2.2	Method of measurements.....	45
8.2.3	Limits.....	46
8.3	Adjacent channel selectivity.....	46
8.3.1	Definition.....	46
8.3.2	Method of measurement	47
8.3.3	Limits.....	48
8.3.4	Receiver saturation at adjacent channel.....	48
8.3.4.1	Definition	48
8.3.4.2	Method of measurements	48
8.3.4.3	Limits	48
8.4	Blocking	48
8.4.1	Definition.....	48
8.4.2	Method of measurement	49
8.4.3	Limit for blocking.....	50
8.5	Spurious response rejection.....	50
8.5.1	Definition.....	50
8.5.2	Introduction to the method of measurement	50
8.5.2.1	Method of measurement.....	51
8.5.3	Limits for spurious response rejection.....	51
8.6	Receiver spurious radiation	52
8.6.1	Definition.....	52
8.6.2	Method of measuring the power level in a specified load, clause 8.6.1 a) i)	52
8.6.3	Method of measuring the effective radiated power, clause 8.6.1 a) ii)	52
8.6.4	Method of measuring the effective radiated power, clause 8.6.1 b)	53
8.6.5	Limits.....	53
9	Spectrum access techniques	54
9.1	Principle for Listen Before Talk (LBT).....	54
9.2	LBT timing parameters	54
9.2.1	Minimum transmitter off-time	54
9.2.1.1	Definition	54
9.2.1.2	Limit.....	54
9.2.2	LBT minimum listening time.....	55
9.2.2.1	Definition	55
9.2.2.2	Limit for minimum listening time	55
9.2.3	Dead Time	55
9.2.3.1	Definition	55
9.2.3.2	Limit.....	55
9.2.4	Acknowledge transmissions.....	55
9.2.5	Maximum transmitter on-time	56
9.2.5.1	Definition	56
9.2.5.2	Limit.....	56
9.2.5.2.1	Tx on-time for a single transmission	56
9.2.5.2.2	Tx on-time for a transmission dialogue	56
9.2.5.2.3	Maximum Tx on-time within a period of 1 hour for devices using LBT + AFA	56
9.2.6	Declaration of LBT parameters	56
9.2.7	Equipment with or without LBT using transmitter time-out-timer	56
10	Measurement uncertainty	57
Annex A (normative):	Radiated measurement.....	58

A.1	Test sites and general arrangements for measurements involving the use of radiated fields	58
A.1.1	Anechoic Chamber	58
A.1.2	Anechoic Chamber with a conductive ground plane	59
A.1.3	Open Area Test Site (OATS)	60
A.1.4	Test antenna.....	61
A.1.5	Substitution antenna	61
A.1.6	Measuring antenna	62
A.2	Guidance on the use of radiation test sites	62
A.2.1	Verification of the test site	62
A.2.2	Preparation of the EUT.....	62
A.2.3	Power supplies to the EUT	62
A.2.4	Volume control setting for analogue speech tests	62
A.2.5	Range length.....	63
A.2.6	Site preparation	63
A.3	Coupling of signals.....	64
A.3.1	General	64
A.3.2	Data Signals.....	64
A.3.3	Speech and analogue signals	64
A.3.3.1	Acoustic coupler description.....	64
A.3.3.2	Calibration	65
A.4	Standard test position	65
Annex B (normative):	Specification for measurement filter	66
Annex C (normative):	Technical performance of the spectrum analyser	68
Annex D (normative):	Application: Social alarm systems.....	69
D.1	General	69
D.2	Classification of effective radiated power levels.....	69
D.3	Receiver parameters and limits	69
Annex E (normative):	Supplementary parameters for receivers	70
E.1	Receiver sensitivity (conducted)	70
E.2	Average usable sensitivity (field strength).....	70
E.2.1	Definition	70
E.2.2	Limits	71
Annex F (informative):	Bibliography.....	72
History	73

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

For non EU countries the present document may be used for regulatory (Type Approval) purposes.

The present document includes improvements to the previous version of the standard that take advantage of technical developments within the SRD industry. It also serves the purpose of providing the requirements and associated measurement methods to improve the intra- SRD co-existence and promote efficient spectrum use.

The present document is part 1 of a multi-part deliverable covering the Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive".

[https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-](https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010)

[7b750c436290/sist-en-300-220-1-v2-3-1-2010](https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010)

National transposition dates

Date of adoption of this EN:	15 February 2010
Date of latest announcement of this EN (doa):	31 May 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2010
Date of withdrawal of any conflicting National Standard (dow):	30 November 2010

Introduction

Clauses 1 and 3 provide a general description on the types of equipment covered by the present document and the definitions and abbreviations used.

Clause 4 provides a guide as to the number of samples required in order that tests may be carried out, and any markings on the equipment which the provider should provide.

The present document describes a generic categorization of receiver performance in clause 4.1.1.

Clauses 5 and 6 give guidance on the test and general conditions for testing of the device.

Clause 7 specifies the spectrum utilization parameters which are required to be measured. The clauses provide details on how the equipment should be tested and the conditions which should be applied.

Clause 8 specifies receiver parameters.

Clause 9 specifies spectrum access techniques in case of Listen Before Talk (LBT) protocol is used to control the transmitter.

Clause 10 gives the maximum measurement uncertainty values.

Annex A (normative) provides specifications concerning radiated measurements.

Annex B (normative) contains specifications for a filter for transmitter measurement arrangements.

Annex C (normative) provides the spectrum analyser specification.

Annex D (normative) covers normative requirements for social alarms.

Annex E (normative) covers supplementary requirements for receivers.

Annex F (informative) Bibliography covers other supplementary information.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 220-1 V2.3.1:2010](https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010)

<https://standards.iteh.ai/catalog/standards/sist/cd071e8c-283f-439d-b28b-7b750c436290/sist-en-300-220-1-v2-3-1-2010>

1 Scope

The present document applies to the following Short Range Device major equipment types:

- 1) Non-specific Short Range Devices.
- 2) Alarms, identification systems, radio-determination, telecommand, telemetry, etc.
- 3) Radio Frequency Identification (RFID).
- 4) Detection, movement and alert applications.

These radio equipment types are capable of operating in the frequency bands within the 25 MHz to 1 000 MHz range as specified in table 1:

- either with a Radio Frequency (RF) output connection and dedicated antenna or with an integral antenna;
- for all types of modulation;
- with or without speech.

Table 1 shows a list of the frequency bands as designated to Short Range Devices by some European Commission Decisions [i.4] and [i.5] and the CEPT/ERC/REC 70-03 [i.1] as known at the date of publication of the present document.

Table 1: Frequency bands commonly designated to Short Range Devices within 25 MHz to 1 000 MHz

	Frequency Bands/frequencies	Applications
Transmit and Receive	26,995 MHz, 27,045 MHz, 27,095 MHz, 27,145 MHz, 27,195 MHz, 34,995 MHz to 35,225 MHz, 40,665 MHz, 40,675 MHz, 40,685 MHz, 40,695 MHz	Model control
Transmit and Receive	26,957 MHz to 27,283 MHz	Non-specific use
Transmit and Receive	40,660 MHz to 40,700 MHz	Non-specific use
Transmit and Receive	138,200 MHz to 138,450 MHz	Non-specific use
Transmit and Receive	169,400 MHz to 169,475 MHz	Tracking, tracing and data acquisition and meter reading
Transmit and Receive	169,475 MHz to 169,4875 MHz	Social alarms
Transmit and Receive	169,5875 MHz to 169,6000 MHz	Social alarms
Transmit and Receive	433,050 MHz to 434,790 MHz	Non-specific use
Transmit and Receive	863,000 MHz to 870,000 MHz	Non-specific use
Transmit and Receive	864,800 MHz to 865,000 MHz	Wireless audio applications
Transmit and Receive	868,000 MHz to 868,600 MHz	Non-specific use
Transmit and Receive	868,600 MHz to 868,700 MHz	Alarms
Transmit and Receive	868,700 MHz to 869,200 MHz	Non-specific use
Transmit and Receive	869,200 MHz to 869,250 MHz	Social alarms
Transmit and Receive	869,250 MHz to 869,300 MHz	Alarms (0,1 % duty cycle)
Transmit and Receive	869,300 MHz to 869,400 MHz	Alarms (1 % duty cycle)
Transmit and Receive	869,400 MHz to 869,650 MHz	Non-specific use
Transmit and Receive	869,650 MHz to 869,700 MHz	Alarms
Transmit and Receive	869,700 MHz to 870,000 MHz	Non-specific use

NOTE 1: It should be noted that table 1 represents the most widely implemented position within the European Union and the CEPT countries, but it should not be assumed that all designated bands are available in all countries.

NOTE 2: In addition, it should be noted that other frequency bands may be available for short range devices in a country within the frequency range 25 MHz to 1 000 MHz covered by the present document. See European Commission Decisions on Short Range Devices [i.4] and [i.5] and CEPT/ERC/REC 70-03 [i.1] as implemented through National Radio Interfaces (NRI) or additional NRI as relevant.

NOTE 3: On non-harmonized parameters, national administrations may impose certain conditions such as the type of modulation, frequency, channel/frequency separations, maximum transmitter radiated power, duty cycle, and the inclusion of an automatic transmitter shut-off facility, as a condition for the issue of Individual Rights for use of spectrum or General Authorization, or as a condition for use under "licence exemption" as it is in most cases for Short Range Devices.

The present document covers fixed stations, mobile stations and portable stations.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ITU-T Recommendation O.153: "Basic parameters for the measurement of error performance at bit rates below the primary rate".
- [2] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] CISPR 16 (2006) (parts 1-1, 1-4 and 1-5): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [4] ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".
- [5] ETSI TR 102 273 (all parts) (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [6] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] CEPT/ERC/REC 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.2] ITU-R Radio Regulations.
- [i.3] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.4] Commission Decision 2006/771/EC on harmonization of the radio spectrum for use by short-range devices as amended by subsequent Commission Decisions.
- [i.5] Commission Decision 2005/928/EC on the harmonization of the 169,4-169,8125 MHz frequency band in the Community as amended by Commission Decision of 13 August 2008.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

adaptive frequency agility: capability of an equipment to dynamically change the temporary operational channel within its available frequencies for proper operation. For the purpose of the present document, non-overlapping channels are used

NOTE: Dynamic change of a channel can be triggered by sensing an occupied channel (e.g. LBT), reaching the maximum channel occupancy time, evaluating the radio link quality.

adjacent channels: channels on either side of the nominal channel separated by the nominal channel bandwidth

alarm: use of radio communication for indicating an alert condition at a distant location

alternate adjacent channels: those two channels offset from the nominal channel by double the channel bandwidth

NOTE 1: The wanted channel is described by the occupied bandwidth (see definition below) of the wanted emissions, i.e. the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0,5 % of the total mean power of a given emission. In addition, the necessary bandwidth of the emissions as defined by the ITU-R Radio Regulations [i.2] is not to exceed the wanted channel.




Figure 1: Adjacent and alternate adjacent channel definitions

NOTE 2: For equipment to be used in a frequency band where channelization is not defined by regulation, the channel spacing of the equipment is defined by the provider.

assigned frequency band: frequency band or sub-band within which the device is authorized to operate and to perform the intended function of the equipment

audio: wideband application where the activity factor is high (e.g. music)

channelized equipment: equipment to be used at a frequency where a channel spacing is defined by regulation or is defined by the provider

conducted measurements: measurements which are made using a direct 50Ω connection to the equipment under test

continuous transmission: modulated transmission without interruption for the period of the test

dedicated antenna: removable antenna supplied and tested with the radio equipment, designed as an indispensable part of the equipment

fixed station: equipment intended for use in a fixed location

frequency agility: ability to change sub-band or channel of operation

Frequency Hopping Spread Spectrum (FHSS): technique in which the transmitter signal occupies a number of frequencies in time, each for some period of time, referred to as the dwell time

NOTE: Transmitter and receiver follow the same frequency hop pattern. The frequency range is determined by the lowest and highest hop positions and the bandwidth per hop position (see clause 6.1.3).

identification system: equipment consisting of a transmitter(s), receiver(s) (or a combination of the two) and an antenna(s) to identify objects by means of a transponder

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

Listen Before Talk (LBT): combination of the listen mode followed by the talk mode

listen mode: action taken by an interrogator to detect an unoccupied sub-band or channel prior to transmitting

meter reading: devices which allow remote status monitoring, measuring and service commands using radio communication

mobile station: equipment normally fixed in a vehicle

model control: devices used to control models (principally miniature representations of vehicles) in the air, on land or over or under the water surface

narrowband: equipment to be used in a non-channelized continuous frequency band with a channel bandwidth of equal or less than 25 kHz, or equipment to be used in a channelized frequency band with a channel spacing of equal or less than 25 kHz

NOTE: For equipment to be used in a non-channelized frequency band by the regulation the channel spacing of the equipment is defined by the provider.

necessary bandwidth: width of the emitted frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

NOTE: The necessary bandwidth including the frequency tolerances is to be accommodated within the assigned frequency band.

non overlapping channels: hopping positions separated by channel bandwidth of 90 % or more below the maximum power as measured with a spectrum analyser

non-specific use: any type of application.

occupied bandwidth: width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to 0,5 % of the total mean power of a given emission

operating frequency: nominal frequency at which equipment is operated; this is also referred to as the operating centre frequency

NOTE: Equipment may be able to operate at more than one operating frequency.

portable station: equipment intended to be carried, attached or implanted

provider: means the manufacturer, or his authorized representative or the person responsible for placing on the market

radiated measurements: measurements which involve the absolute measurement of a radiated field

social alarm devices: devices that allow reliable communication for a person in distress in a limited area to initiate a call for assistance by a simple manipulation

spurious emissions: emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include harmonic emissions, parasitic emissions, intermodulation products and frequency conversion products, but exclude out-of-band emissions.

talk mode: transmission of intentional radiation by a transmitter

telecommand: use of radio communication for the transmission of signals to initiate, modify or terminate functions of equipment at a distance

telemetry: use of radio communication for indicating or recording data at a distance

tracking and tracing: devices which allow the tracing and tracking of goods, leading to their recovery, consisting in general of a radio transmitter placed on the item to be protected and a receiver and may also include an alarm

transponder: device that responds to an interrogation signal

voice (speech): audio communications that are considered to be inherently low activity factor devices where there are frequent interruptions to the communications transmitted

wanted channel: occupied bandwidth of the wanted emissions

wideband: any equipment not falling under the definition of narrowband

wireless audio applications: cordless audio devices for portable use

NOTE: Possible applications include cordless loudspeakers, cordless headphones for portable use, babyphones, ring bells, etc.