INTERNATIONAL STANDARD

ISO 603-2

Second edition 1999-07-15

Bonded abrasive products — Dimensions —

Part 2:

Grinding wheels for centreless external cylindrical grinding

Partie 2: Meules pour rectification cylindrique extérieure sans centres



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 603-2 was prepared by Technical Committee ISO/TC 29, *Small tools*, subcommittee SC 5, *Grinding wheels and abrasives*.

This second edition, together with ISO 603-1:1999 and ISO 603-3:1999 to ISO 603-16:1999, cancels and replaces ISO/R 603:1967, ISO 603-2:1981, ISO 1117:1975, ISO 2220:1972, ISO 2933:1974, ISO 3290:1976 and ISO 3921:1976 as a technical revision of these standards.

ISO 603 consists of the following parts, under the general title Bonded abrasive products — Dimensions:

- Part 1: Grinding wheels for external cylindrical grinding between centres
- Part 2: Grinding wheels for centreless external cylindrical grinding

https://standards.iteh.ai/catalog/standards/sist/04fd5b19-a89f-4bb7-b049-

- Part 3: Grinding wheels for internal cylindrical grinding/iso-603-2-1999
- Part 4: Grinding wheels for surface grinding/peripheral grinding
- Part 5: Grinding wheels for surface grinding/face grinding
- Part 6: Grinding wheels for tool and tool room grinding
- Part 7: Grinding wheels for manually guided grinding
- Part 8: Grinding wheels for deburring and fettling/snagging
- Part 9: Grinding wheels for high-pressure grinding
- Part 10: Stones for honing and superfinishings
- Part 11: Hand finishing sticks
- Part 12: Grinding wheels for deburring and fettling on a straight grinder

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland Internet iso@iso.ch

Printed in Switzerland

- Part 13: Grinding wheels for deburring and fettling on a vertical grinder
- Part 14: Grinding wheels for deburring and fettling/snagging on an angle grinder
- Part 15: Grinding wheels for cutting-off on stationary or mobile cutting-off machines
- Part 16: Grinding wheels for cutting-off on hand held power tools

iTeh STANDARD PREVIEW (standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Bonded abrasive products — Dimensions —

Part 2:

Grinding wheels for centreless external cylindrical grinding

1 Scope

This part of ISO 603 specifies the nominal dimensions, in millimeters, of:

- Type 1: Straight grinding wheel
- Type 5: Wheel recessed on one side
- Type 7: Wheel recessed on both sides

These bonded abrasive products are intended to be used for the grinding of the external peripheral surface of a rotating workpiece. The workpiece is rotated and mechanically guided with reference to the grinding wheel by means of a control-wheel and rests on a straight-edge placed between the two wheels.

ISO 603-2:1999

2 Normative references standards.iteh.ai/catalog/standards/sist/04fd5b19-a89f-4bb7-b049-33454031a58a/iso-603-2-1999

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 603. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 603 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the lates edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 525:1999, Bonded abrasive products — General requirements.

ISO 6103:1999, Bonded abrasive products — Static balancing of grinding wheels — Testing.

ISO 13942:—1), Bonded abrasive products — Limit deviations and run-out tolerances.

¹⁾ To be published.

ISO 603-2:1999(E) © ISO

3 Dimensions

3.1 Grinding wheels for centreless grinding


See Figures 1, 2 and 3 and Table 1.

Type 1: Straight grinding wheel

on one side

Type 5: Wheel recessed

Type 7: Wheel recessed on both sides



The recess depth F is taken as less than or equal to half thickness T.

 ϕH

ΦD

The recess depth F or F + G are taken as less than or equal to half thickness T.

(standards.iteh.ai)

Figure 1 — Type 1

 ϕH

ΦD

Figure 2 — Type 5 ISO 603-2:1999 Figure 3 — Type 7

Table 1 — Dimensions of Type 1, Type 5 and Type 7


D	Ta												Н	P	R _{max}
	25	40	63	100	125	160	200	250	315	400	500	600			
300	Х	Χ	Х	Х	Χ		_	-		1	ı		127	190	- 5
400/406	Х	Χ	Х	Х	Х	Х	Х	Х	1	1	1	1	203,2	280	
500/508	Xp	X	Х	Х	X	X	Х	X	X	X	X	X			
600/610	Xp	Xp	Xp	Х	Х	Х	Х	Х	Х	Х	Х	Х	304,8	400	8
750/762	-	-	-	Х	Х	Х	Х	Х	Х	Х	Х	Х			

^a For wheels with thicknesses of 200 mm and greater wheels may be supplied in more than one piece.

b Only camshaft grinding.

3.2 Type 5 Control wheels

See Figure 4 and Table 2.



The recess depth F is taken as less than or equal to half thickness T.

Figure 4 — Control wheel

D $R_{\sf max}$ H25t 2160 200 315 63 100 500 25 40 600 200 Χ Χ Χ Χ Χ 76,2 114 3,2 34540 1ax8a **sox**60 250 Χ Χ Χ Χ Χ 127 160 Χ 250 Χ Χ Χ Χ Χ 152,4 160 Χ Χ 127 300 Χ Χ Χ Χ Χ Χ Χ 190 5 300 Χ Χ Χ Χ Χ Χ Χ 152,4 190 350/356 Χ Χ Χ Χ Χ Χ Χ Χ Χ 127 203 Χ 350/356 Χ Χ Χ Χ Χ Χ Χ Χ 152,4 203

Table 2 — Dimensions of control wheels

For wheels with thicknesses of 200 mm and greater wheels may be supplied in more than one piece.

ISO 603-2:1999(E) © ISO

4 Designation

A complete designation of a bonded abrasive product in accordance with this part of ISO 603 consist of the following information:

- a) designation of the bonded abrasives, e.g. "Grinding wheel";
- b) reference of this part of ISO 603;
- c) type (shape);
- d) dimensions;
- e) specifications of an internal nature;
- f) the maximum operating speed.

In accordance with ISO 525 and this part of ISO 603

EXAMPLE

A grinding wheel for centreless external cylindrical grinding, Type 5, D = 500 mm, T = 200 mm, H = 304.8 mm, P = 400 mm, F = 70 mm, nature of abrasive A, grain size 60, grade L, structure 5, nature of bond V and a maximum operating speed of 50 m/s is designated as follows:

Grinding wheel ISO 603-2 - 5 - 500 imes 200 imes 304,8 - 400/70 A 60 L5V - 50 m/s

iTeh STANDARD PREVIEW

5 Specifications

(standards.iteh.ai)

The specifications are left to the manufacture's discretion, see ISO 525.

5.1 Tolerances

ISO 603-2:1999 https://standards.iteh.ai/catalog/standards/sist/04fid5b19-a89f-4bb7-b049-

33454031a58a/iso-603-2-1999

Limit deviations and run-out tolerances in accordance with ISO 13942.

5.2 Balancing

Balancing is in accordance with ISO 6103.

5.3 Marking

Marking of bonded abrasive products is in accordance with ISO 525.

Bibliography

- [1] ISO 8486-1, Bonded abrasives Determination and designation of grain size distribution Part 1: Macrogrits F4 to F220.
- [2] ISO 8486-2, Bonded abrasives Determination and designation of grain size distribution Part 2: Microgrits F230 to F1200.

iTeh STANDARD PREVIEW (standards.iteh.ai)