



SLOVENSKI STANDARD

SIST EN 301 068-1:2000

01-januar-2000

ü]fc_cdUgcj bc`X][]HJbc`ca fYy`Y`n`]bhY[f]fUbj]a]`glcf]hj Ua]`f6 !=G8 BŁ!`Dfcltc_c`
X][]HJbY`bUfc b]y_Y`g][bU]nUWY`Y`y`h`r`&`f8 GG&Ł!`? UfU_hyf]gh_Y`nj YnY`!`DfYbcgbU
na cýbcgh]b`]bX]_UWY`Udfca YlbY[UdfUa YfU5 HA `!`%`r`XY.`GdYWZ]_UWY`Udfcltc_c`U

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM transfer capability and traffic parameter indication; Part 1: Protocol specification [ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997), Q.2961.4 (1997), modified]

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 068-1:2000](https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000)

<https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000>

Ta slovenski standard je istoveten z: EN 301 068-1 Version 1.2.4

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 301 068-1:2000

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 068-1:2000

<https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000>

EN 301 068-1 V1.2.4 (1998-11)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Connection characteristics;
ATM transfer capability and traffic parameter indication;
Part 1: Protocol specification**

[ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997),
Q.2961.4 (1997), modified]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 068-1:2000](https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000)

<https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000>



Reference

DEN/SPS-05081-1 (9w090iqo.PDF)

Keywords

B-ISDN, DSS2, UNI, layer 3, ATM

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la

Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable

can be downloaded from

<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 1 of a multi-part standard covering the Digital Subscriber Signalling System No. two (DSS2) protocol specification for the Broadband Integrated Services Digital Network (B-ISDN) ATM transfer capability and traffic parameter indication, as described below:

- Part 1:** "**Protocol specification [ITU-T Recommendation Q.2961 Part 1 (1995), Part 2 (1997), Part 3 (1997), Part 4 (1997), modified]**";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "TSS&TP specification for the network";
- Part 6: "ATS and partial PIXIT proforma specification for the network".

The present document details the access signalling system protocol aspects and switching functions required to support the ATM transfer capability and the related traffic parameter indication at call and/or connection establishment time.

National transposition dates	
Date of adoption of this EN:	6 November 1998
Date of latest announcement of this EN (doa):	28 February 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 1999
Date of withdrawal of any conflicting National Standard (dow):	31 August 1999

Endorsement notice

The text of ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997) and Q.2961.4 (1997) was approved by ETSI as an EN with agreed modifications as given below.

NOTE: New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

Global modifications to ITU-T Recommendations Q.2961.1 to Q.2961.4

Insert the following clause (Scope).

Scope

This first part of EN 301 068 covers the support of additional traffic parameters for the Broadband Integrated Services Digital Network (B-ISDN) at the T_B reference point or coincident S_B and T_B reference point as defined in ITU-T Recommendation I.413 by means of the Digital Subscriber Signalling System No. two (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN) as provided by European public telecommunication operators.

It defines the DSS2 protocol procedures, formats and functions needed to support the identified ATM transfer capabilities and the ATM traffic related additional capabilities.

The specifications provided by the present document allow for the signalling of the ATM transfer capabilities and of the additional traffic parameters beyond the ones already specified by EN 300 443-1 for B-ISDN basic call/connection control at the UNI. The additional traffic parameters support a Broadband Connection-Oriented Bearer Service (BCOB) as specified in ITU-T Recommendation F.811.

The present document forms part of the DSS2 family of standards; it specifies extensions to EN 300 443-1 which specifies the control protocol for point-to-point call/bearer connection, and does not repeat states, information elements, messages and procedures contained therein, but only specifies extensions related to additional traffic parameter indications.

This present document does not cover procedures for the negotiation and modification/re-negotiation of the ATM traffic parameters.

iTech STANDARD PREVIEW
(standards.itch.ai)

SIST EN 301 068-1:2000

Throughout the text of ITU-T Recommendations Q.2961.1 to Q.2961.4

f997eb5391e9/sist-en-301-068-1-2000

Replace references as shown in the following table.

Reference in ITU-T Recommendations Q.2961.1 to Q.2961.4	Modified reference
ITU-T Recommendation Q.2931	ITU-T Recommendation Q.2931 as modified by EN 300 443-1
ITU-T Recommendation Q.2933	ITU-T Recommendation Q.2933 as modified by EN 301 174-1
ITU-T Recommendation I.371	ITU-T Recommendation I.371 as modified by ETS 300 301 edition 2
ITU-T Recommendation I.356	ITU-T Recommendation I.356 as modified by ETS 300 xxx
ITU-T Recommendation Q.2951, clause 1	ITU-T Recommendation Q.2951 as modified by ETS 300 661-1
ITU-T Recommendation Q.2951, clause 2	ITU-T Recommendation Q.2951 as modified by ETS 300 662-1
ITU-T Recommendation Q.2951, clause 3	ITU-T Recommendation Q.2951 as modified by ETS 300 663-1
ITU-T Recommendation Q.2951, clause 4	ITU-T Recommendation Q.2951 as modified by ETS 300 664-1
ITU-T Recommendation Q.2951, clause 5	ITU-T Recommendation Q.2951 as modified by ETS 300 665-1
ITU-T Recommendation Q.2951, clause 6	ITU-T Recommendation Q.2951 as modified by ETS 300 666-1
ITU-T Recommendation Q.2951, clause 8	ITU-T Recommendation Q.2951 as modified by ETS 300 667-1
ITU-T Recommendation Q.2955.1	ITU-T Recommendation Q.2955 as modified by ETS 300 770-1
ITU-T Recommendation Q.2957	ITU-T Recommendation Q.2957 as modified by ETS 300 668-1
ITU-T Recommendation Q.2962	ITU-T Recommendation Q.2962 as modified by EN 301 067-1
ITU-T Recommendation Q.2963.1	ITU-T Recommendation Q.2963.1 as modified by EN 301 003-1
ITU-T Recommendation F.811 (1992)	ITU-T Recommendation F.811 (1996)

Modifications to ITU-T Recommendation Q.2961.1

Replace VBR (Variable Bit Rate) by SBR (Statistical Bit rate) ATM Transfer Capability.

Appendix I

Appendix I is informative.

Appendix II

Appendix II is informative.

Appendix III

Appendix III is informative.

Appendix IV

Appendix IV is not applicable.

Modifications to ITU-T Recommendation Q.2961.2

Reference [6] (ITU-T Recommendation Q.2933) is not applicable.

NOTE: The use of the Frame Relay Bearer Class codepoint in octet 5 (bits 1 to 5) of the Broadband bearer capability information element (Figure 1/Q.2961.2) will be the subject of a separate standard defining the application of ITU-T Recommendation Q.2933.

[SIST EN 301 068-1:2000](https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000)

Annex A

<https://standards.iteh.ai/catalog/standards/sist/be90bf3f-147a-4300-8e27-f997eb5391e9/sist-en-301-068-1-2000>

Annex A is normative.

Replace TABLE A-1/Q.2961.2 by the following new one:

Table A-1 (Part 1/3)/Q.2961.2

Valid combinations of Traffic related parameters in the SETUP message

<i>Broadband bearer capability</i>											
Bearer class	A	A	A	C	C	C	C		C	C	
BTC (value) (NOTE 1)	absent	absent	7	absent	absent	absent	absent		11	19	
<i>Traffic descriptor for a given direction</i>											
PCR (CLP=0)		S			S						
PCR (CLP=0+1)	S	S	S	S	S	S	S		S	S	
{SCR, MBS} (CLP=0)							S				
{SCR, MBS} (CLP=0+1)						S			S	S	
Tagging (NOTE 13)	N	Y/N	N	N	Y/N	N	Y/N		N	N	
End-to-end timing required	Y	Y	Y	N	N	N	N		N	Y	
<i>For the given direction:</i>											
<i>Requested I.371 ATC</i>	NOTE 2	NOTE 2	DBR	NOTE 2	NOTE 6, 14	NOTE 7	NOTE 14		SBR1	SBR1	
<i>Implicitly requested QoS when the QoS class is 0</i>	NOTE 3	NOTE 3	Class 1	NOTE 5	Class 3	NOTE 5	Class 3		Class 2	NOTE 10	
<i>For the given direction:</i>											
<i>I.371 ATC that supports the requested ATC</i>	DBR	DBR NOTE 4	DBR	DBR	NOTE 6, 14	SBR1	NOTE14		SBR1	SBR1	
<i>I.356 QoS class that supports the implicitly requested QoS</i>	Class 1	Class 1	Class 1	Class 2	Class 3	Class 2	Class 3		Class 2	Class 1	
	NOTE 1	NOTE 11	NOTE 12	NOTE 11	NOTE 11	NOTE 11	NOTE 11		NOTE 12	NOTE 12	

Table A-1 (Part 2/3)/Q.2961.2

Valid combinations of Traffic related parameters in the SETUP message

<i>Broadband bearer capability</i>												
Bearer class	C	C	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR	X or FR
BTC (value) (NOTE 1)	9	9	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	absent, 0, 2, 8 or 10	7	11	19	4, 5 or 6	4, 5 or 6	1 or 9
<i>Traffic descriptor for a given direction</i>												
PCR (CLP=0)				S							S	
PCR (CLP=0+1)	S	S	S	S	S	S	S	S	S	S	S	S
SCR , MBS (CLP=0)	S					S						
SCR , MBS (CLP=0+1)		S			S			S	S			
Tagging (NOTE 13)	Y/N	N	N	Y/N	N	Y/N	N	N	N	N	Y/N	N
End-to-end timing required	Y	Y	N	N	N	N	Y	N	Y	Y	Y	Y
<i>For the given direction:</i>												
Requested I.371 ATC	NOTE 14	NOTE 7	NOTE 2	NOTE 6, 14	NOTE 7	NOTE 14	DBR	SBR1	SBR1	NOTE 2	NOTE 2	NOTE 2
Implicitly requested QoS when the QoS class is 0	NOTE 8	NOTE 8	NOTE 5	Class 3	NOTE 5	Class 3	Class 1	Class 2	NOTE 10	NOTE 3	NOTE 3	NOTE 8
<i>For the given direction:</i>												
I.371 ATC that supports the requested ATC	NOTE 9	SBR1	DBR	NOTE 6, 14	SBR1	NOTE 14	DBR	SBR1	SBR1	DBR	DBR NOTE 4	DBR
I.356 QoS class that supports the implicitly requested QoS		Class 1	Class 2	Class 3	Class 2	Class 3	Class 1	Class 2	Class 1	Class 1	Class 1	Class 1
			NOTE 11	NOTE 11	NOTE 11	NOTE 11	NOTE 12	NOTE 12	NOTE 12	NOTE 11	NOTE 11	NOTE 11