INTERNATIONAL STANDARD

ISO 14951-1

First edition 1999-10-01

Space systems — Fluid characteristics —

Part 1: Oxygen

iTeh Systèmes spatiaux — Caractéristiques des fluides — Partie 1: Oxygène (standards.iteh.ai)

ISO 14951-1:1999 https://standards.iteh.ai/catalog/standards/sist/92bd0a5e-8914-4951-ba00-549efe33c4a7/iso-14951-1-1999



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 14951-1 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

ISO 14951 consists of the following parts, under the general title Space systems — Fluid characteristics:

- Part 1: Oxygen
- Part 2: Hydrogen propellant Teh STANDARD PREVIEW
- Part 3: Nitrogen

(standards.iteh.ai)

— Part 4: Helium

ISO 14951-1:1999

- Part 5: Nitrogen tetroxide propellant is.itch.ai/catalog/standards/sist/92bd0a5e-8914-4951-ba00-549efe33c4a7/iso-14951-1-1999
- Part 6: Monomethylhydrazine propellant
- Part 7: Hydrazine propellant
- Part 8: Kerosene propellant
- Part 9: Argon
- Part 10: Water
- Part 11: Ammonia
- Part 12: Carbon dioxide
- Part 13: Breathing air

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland Internet iso@iso.ch

Printed in Switzerland

Space systems — Fluid characteristics —

Part 1:

Oxygen

1 Scope

This part of ISO 14951 specifies limits for the composition of oxygen and test methods for verification of oxygen composition. This part of ISO 14951 is applicable to oxygen of the following types and grades, intended for use as an oxidizer and for purging and pressurization of propellant systems of space systems:

- type I: gaseous
- iTeh STANDARD PREVIEW
- grade A: standard, purging/pressurization; (standards.iteh.ai)
- grade CB: crew breathing;
- ISO 14951-1:1999
- grade F: fuel-cell: https://standards.iteh.ai/catalog/standards/sist/92bd0a5e-8914-4951-ba00-
- 549efe33c4a7/iso-14951-1-1999 type II: liquid
 - grade A: oxidizer, 99,6 % pure;
 - grade B: oxidizer, 99,5 % pure;
 - grade F: fuel-cell.

This part of ISO 14951 is applicable to oxygen used in both flight hardware and ground facilities, systems, and equipment. It is applicable to influents only to the extent specified herein.

2 Term and definition

For the purposes of this part of ISO 14951, the following term and definition apply.

2.1

particulate

undissolved solids retained on a filter paper with a 10 µm absolute rating

3 Composition

The composition of oxygen delivered to the flight vehicle interface shall be in accordance with the limits given in Table 1 when tested in accordance with the applicable test methods.

4 Test methods

4.1 Sampling

Oxygen should be selected in accordance with a sampling plan that will produce results with sensitivities and accuracies equivalent to or better than those required to meet the programme or project requirements.

4.2 Composition tests

The composition of the oxygen shall be tested by such methods, apparatus, or analyzers as may be required to produce results with the sensitivities and accuracies necessary to meet programme or project requirements.

Table 1 — Composition limits

Composition			Limits					
			Type I (gaseous)			Type II (liquid)		
			Grade A	Grade CB	Grade F	Grade A	Grade B	Grade F
Purity	Oxygen (O ₂)	volume fraction, %, min.	99,6	99,5	99,989	99,2	99,5	99,989
Impurities	Total hydrocarbons, as methane	μl/l, max.	50	50	23 /	75 7	67,7	23
	Alkynes, as acetylene	μl/l, max.			0,05	1,55	0,5	0,05
	Moisture	μl/l, max.	8	40	3	26,3	26,3	3
	Particulate	[mg/l4max.]	:19 99	_	_	_	1,0	_
	https://standards.iteh.a	ai/catalog/standards/ ul/l_max 49efe33c4a7/iso-14	sist/92bd 1951-1-1	0a5 <u>e-</u> 89 999	14-4951-b 16	a00 <u>-</u>	_	16
	Ethane	μl/l, max.	_	_	2	_		2
	Propane and higher hydrocarbons, as propane	μl/l, max.	1		1	_		1
	Nitrous oxide	μl/l, max.		4	1	_		1
	Halogenated hydrocarbons	μl/l, max.	I	2	1	_	1	1
	Chlorinated hydrocarbons	μl/l, max.	1	0,2	0,01	_	1	0,01
	Odour		_	None	None	_	_	None
	Carbon monoxide (CO) and carbon dioxide (CO ₂)	μl/l, max.	_	а	1	b	b	1
	Other [nitrogen (N ₂), argon (Ar), krypton (Kr), etc.]	μl/l, max.	_	С	75	_		75

^a 10 for CO and 10 for CO_2 .

b 0,1 for CO and 3 for CO₂ when required to meet hardware needs.

Control of the con

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14951-1:1999 https://standards.iteh.ai/catalog/standards/sist/92bd0a5e-8914-4951-ba00-549efe33c4a7/iso-14951-1-1999

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14951-1:1999</u> https://standards.iteh.ai/catalog/standards/sist/92bd0a5e-8914-4951-ba00-549efe33c4a7/iso-14951-1-1999