INTERNATIONAL STANDARD

ISO 14951-4

First edition 1999-10-01

Space systems — Fluid characteristics — Part 4:

Helium

Systèmes spatiaux — Caractéristiques des fluides —

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14951-4:1999</u> https://standards.iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-8ce4df9e594b/iso-14951-4-1999



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 14951-4 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

ISO 14951 consists of the following parts, under the general title Space systems — Fluid characteristics:

- Part 1: Oxygen
- Part 2: Hydrogen propellant Teh STANDARD PREVIEW
- Part 3: Nitrogen

(standards.iteh.ai)

— Part 4: Helium

ISO 14951-4:1999

- Part 5: Nitrogen tetroxide propellant ls. iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-8ce4df9e594b/iso-14951-4-1999
- Part 6: Monomethylhydrazine propellant
- Part 7: Hydrazine propellant
- Part 8: Kerosene propellant
- Part 9: Argon
- Part 10: Water
- Part 11: Ammonia
- Part 12: Carbon dioxide
- Part 13: Breathing air

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case postale 56 • CH-1211 Genève 20 • Switzerland Internet iso@iso.ch

Printed in Switzerland

Space systems — Fluid characteristics —

Part 4:

Helium

1 Scope

This part of ISO 14951 specifies limits for the composition of helium and test methods for verification of helium composition. This part of ISO 14951 is applicable to helium of the following types and grades, intended for purging and pressurization of propellant systems of space systems:

- type I: gaseous iTeh STANDARD PREVIEW
 - grade A: purging and pressurizing helium: (Standards.iteh.ai)
 - grade F: purging and pressurizing helium;

ISO 14951-4:1999

- type II: liquid https://standards.iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-
 - 8ce4df9e594b/iso-14951-4-1999
 - grade A: purging and pressurizing helium;
 - grade F: purging and pressurizing helium.

This part of ISO 14951 is applicable to helium used in both flight hardware and ground facilities, systems, and equipment. It is applicable to influents only to the extent specified herein.

2 Composition

The composition of helium delivered to the flight vehicle interface shall be in accordance with the limits given in Table 1 when tested in accordance with the applicable test methods.

3 Test methods

3.1 Sampling

Helium should be selected in accordance with a sampling plan that will produce results with sensitivities and accuracies equivalent to or better than those required to meet the programme or project requirements.

3.2 Composition tests

The composition of the helium shall be tested by such methods, apparatus, or analyzers as may be required to produce results with the sensitivities and accuracies necessary to meet programme or project requirements.

Table 1 — Composition limits

		Limits				
Composition			Type I (gaseous)		Type II (liquid)	
			Grade A	Grade F	Grade A	Grade F
Purity	Helium volume fraction	, %, min.	99,99	99,995	99,99	99,995
Impurities	Water	μl/l, max.	9	5	9	3
	Hydrocarbons (as methane) μl/l, max.		5	10	5	1
	Oxygen	μl/l, max.	10	5	10	3
	Nitrogen	μl/l, max.	50	20	50	5
	Neon	μl/l, max.		23		23
	Argon	μl/l, max.				1
	Hydrogen	μl/l, max.	_	_		5
	Gaseous helium	μl/l, max.				5
	Carbon monoxide plus carbon dioxide	μl/l, max.	_	1	_	1
	Total allowable impurities	μl/l, max.	100	D IF T/II	100	_

(standards.iteh.ai)

ISO 14951-4:1999 https://standards.iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-8ce4df9e594b/iso-14951-4-1999

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 14951-4:1999</u> https://standards.iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-8ce4df9e594b/iso-14951-4-1999

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14951-4:1999 https://standards.iteh.ai/catalog/standards/sist/419a283d-c9ee-4f3a-8db8-8ce4df9e594b/iso-14951-4-1999