

SLOVENSKI STANDARD

SIST EN 3114-001:2009

01-junij-2009

5 YfcbUj H_U! DfYg_i gbY a YhXY! A_fcghfi _h fU[bYhYb]]nXY_cj]nHjHbcj Y
n]HbYf! Z£!\$\$%XY. Gd`c ybYnU HjY Y

Š Ÿ Å Æ æ { æ@œœ|>ç|! æ@^} Å Å ã |[*^>* ^Å{ } ^c|: ^v * } ã•^Å[} Á ãœ |^* ã|` } *
Ç Å Å Æœœ^ÅœœFœœ* ^{ ^Å{ ^Å{ [i`^v] *^ }

Ú..la Áe..[•] aææ^ÆAT ..c@ å^Áo•• aæÆA æ[•c` &c` |^Å^•Á|[å` ã Á[||[^..Á} Áææ^Á^æ
cææ^ÁC ÁEÁ DÜÜÁææcæ ÁEEFÁKcæ ^} &•Á} ..la^•
S. 1001-2009

<https://standards.iteh.ai/catalog/standards/sist/87ecda63-cbe5-4ee2-a561->

e1c071023afb/sist-en-3114-001-2009

Ta slovenski standard je istoveten z: **EN 3114-001:2006**

ICS:

49.025.10 Jekla

Steels

SIST EN 3114-001:2009

en,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 3114-001:2009

<https://standards.iteh.ai/catalog/standards/sist/87ecda63-cbe5-4ee2-a561-e1c071023afb/sist-en-3114-001-2009>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 3114-001

December 2006

ICS 49.025.10

English Version

Aerospace series - Test method - Microstructure of ($\alpha + \beta$)
titanium alloy wrought products - Part 001: General
requirements

Série aérospatiale - Méthode d'essai - Microstructure des
produits corroyés en alliage de titane ($\alpha + \beta$) - Partie 001 :
Exigences générales

Luft- und Raumfahrt - Prüfverfahren - Mikrogefüge
Kneterzeugnisse von Titanlegierung ($\alpha + \beta$) - Teil 001:
Allgemeine Anforderungen

This European Standard was approved by CEN on 18 October 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

iTeh STANDARD PREVIEW
This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom. <http://standardsite.cen.eu.org/standard/87ecda63-cbe5-4ee2-a561-e1c071023afb/sist-en-3114-001-2009>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword.....	3
Introduction	4
1 Scope	4
2 Normative references	4
3 Sampling	4
4 Preparation of the microsections.....	5
5 Assessment.....	7
6 Description of microstructures	7

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 3114-001:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/87ecda63-cbe5-4ee2-a561-e1c071023afb/sist-en-3114-001-2009>

Foreword

This document (EN 3114-001:2006) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2007, and conflicting national standards shall be withdrawn at the latest by June 2007.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

THE STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 3114-001:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/87ecda63-cbe5-4ee2-a561-e1c071023afb/sist-en-3114-001-2009>

Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

1 Scope

This standard specifies the conditions for micrographic examination of $(\alpha + \beta)$ titanium alloy wrought products and description of terms used.

Specific microstructures applicable to each type of product are defined in EN 3114-002 to EN 3114-004.

This standard shall be applied in conjunction with EN material standards, which define the acceptance criteria unless otherwise specified on the order.

It is applicable to:

- bars, sections, forging stock and forgings (EN 3114-002);
- plate (EN 3114-003);
- sheet for superplastic forming (EN 3114-004).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2 Normative references

SIST EN 3114-001:2009

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 3114-002, *Aerospace series — Microstructure of $(\alpha + \beta)$ titanium alloy wrought products — Part 002: Microstructure of bars, sections, forging stock and forgings*.

EN 3114-003, *Aerospace series — Microstructure of $(\alpha + \beta)$ titanium alloy wrought products — Part 003: Microstructure of plate*.

EN 3114-004, *Aerospace series — Microstructure of $(\alpha + \beta)$ titanium alloy wrought products — Part 004: Microstructure of sheet for superplastic forming*.

EN 4258, *Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use*.

3 Sampling

The sampling and its frequency shall be as defined in the relevant technical specification and/or order.

The sampling sections shall be at least 10 mm, in thickness or length.

Samples shall preferably be taken by sawing. Cold work hardened zones shall be avoided or removed. If the sampling material is taken by abrasive cut off or flame cutting, the resulting heat affected zone shall be completely removed in the course of sample preparation.

4 Preparation of the microsections

4.1 General

The surface of the sample sections to be examined shall be prepared by machining and grinding and polishing to ensure that the microstructure is clearly defined after etching.

In the case of electrolytic polishing, grinding may be omitted.

The method of preparation shall not change, contaminate or deform the surface microstructure.

4.2 Grinding

Resin bonded alumina, zirconia or silicon carbide paper shall be used for grinding. The pressure shall be as low as possible in order to avoid any cold work hardening of the surface of the microsection.

4.3 Polishing

Polishing may be accomplished mechanically and/or electrolytically.

The following solution is recommended for electrolytic polishing:

- 700 ml methanol;
- 200 ml butylglycol;
- 60 ml perchloric acid.

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

4.4 Etching

[SIST EN 3114-001:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/87ecda63-cbe5-4ee2-a561-1b070274f/sist-3114-001-2009>

The etchants and their typical composition indicated in Table 1 may be used for development of microstructure.

Table 1 — Etching of titanium alloys

	Reagent	Vol. %	Remarks	Use
1	Hydrofluoric acid (40 %) Nitric acid (65 %) Water up to	8 40 100	Swab or immerse	Micro etch Macro etch (Etching time up to several minutes)
2	Hydrofluoric acid (40 %) Nitric acid (65 %) Water up to	2 10 100	Swab or immerse	Bright grain boundary etch
3	Hydrofluoric acid (40 %) Benzalkonium chloride Methyl alcohol Glycerol	2 to 6 19 35 40	Swab Avoid overetching Avoid water in etch solution	Stain etch Stain α or β depending on the heat treatment condition
4	Hydrofluoric acid (40 %) Water up to	0,5 100	Swab or immerse	Stain etch
5	Hydrofluoric acid (40 %) Nitric acid (65 %) Glycerol up to	2 to 20 5 to 25 100	Swab Glycerol acts as inhibitor	Bright etch Slower etch than 1
6	Potassium hydroxide Hydrogen peroxide (30 %) Water up to	10 15 100	Immerse (70-80) °C SIST EN 3114-001:2009	Grain boundaries, subgrain boundaries. Stains α and transformed β , retained β not stained. Orientation sensitive, develops - contrast between grains.
7	Hydrofluoric acid (40 %) Nitric acid (65 %) Lactic acid	20 20 60	Swab rigorously	Chemical polish and etch
8	Hydrochloric acid (40 %) Nitric acid (65 %) Lactic acid	10 25 65	Swab	General etch
9	Hydrofluoric acid (40 %) Nitric acid (65 %) Water up to	10 15 100	Swab or immersion + 1 min in ammonium bifluoride 20 g/l	Etch for segregation
10	Nitric acid (65 %) Water up to	25 100	Swab or immersion	Removal of copper surface layer
11	Hydrofluoric acid (40 %) Nitric acid (65 %) Hydrogen peroxide (30 %) Water up to	1 2 50 100	Spray wash	Removal of tin surface layer

5 Assessment

The prepared surface shall be examined at the same magnification as that of the reference photomicrograph.

6 Description of microstructures

6.1 Acicular α

A transformation product arising, during cooling, by nucleation and growth on preferred planes of the primary β phase, or by martensitic transformation and growth. It appears in acicular form, as pointed lamellae, or plates.

6.2 α enriched zone (Blocky α)

A coarse area of α by comparison with the primary α grain of the matrix. Such α areas are frequently accompanied by grain boundary α . Microhardness is not significantly different from that of the matrix.

6.3 α phase (α)

The stable sub- β transus α phase with close packed hexagonal crystal structure.

6.4 $\alpha + \beta$ structure

iTeh STANDARD PREVIEW

Microstructure containing α and β phases in various forms.

(standards.iteh.ai)

6.5 α stabilized hard zone High Interstitial Defect (HID)

SIST EN 3114-001:2009

Zone of higher α stabilized content, significantly harder than the surrounding structure. Normally caused through local oxygen and/or nitrogen enrichment.

6.6 α stabilized surface (α case)

A surface zone enriched mainly by oxygen or less often by nitrogen or carbon, in which the α phase is stabilized. The α case result from elevated temperature exposure to environments containing these elements. α case is hard, brittle and considered detrimental.

6.7 α stabilizer

Element preferentially dissolving in the α phase, and which increases the α and β transus temperatures.

6.8 α stringer

In comparison with the fine $\alpha + \beta$ matrix, clearly defined coarse elongated α phase.

6.9 α transus

The temperature which determines the boundary between α and $\alpha + \beta$ fields - also known as $\alpha/\alpha + \beta$ transition temperature.