

SLOVENSKI STANDARD SIST EN 3668:2009

01-maj-2009

5 YfcbUj hj_U'!N`]hjbU'B d D < & \$%fB]7 f &% Y%, A c- ½ c XdcfbU'dfchj'j fc]b]'!'Hcd`chbcbYcVXYUbU!'A UhYf]U'nU_cj Ub^Y'!'UU]'8 '® &) \$`a a

 $\begin{array}{l} \text{CP}^{\perp}[\bullet] \approx & \hat{A} \wedge \hat{A} \wedge \hat{A} & \hat{A} \wedge \hat{A} \wedge$

Š`-dĒÁ}åÁÜæ`{ -æ@oÁEÁP[&@, æd{ -^•c^ÁŠ^*ā^¦`}*ÁÞOËÚPCH-√EFÁQÞãÔ¦CFØ^FÌT[JDÁEÁÞ&&@c ;ê¦{ ^à^@a)å^|oÁEÁÙ&@;ā^å^ç[ᢗ¦{ æg^¦æðdÁå^¦EÁÐÁ;á^!ÁÖÁMÁCÍ €Á;√/ [[]]

https://standards.iteh.ai/catalog/standards/sist/36c2ab75-902b-4679-95fl-

Ta slovenski standard je istoveten z: b6eeab9e0fcc/sist-en-3668-2009 EN 3668:2006

ICS:

49.025.15 Neželezove zlitine na

splošno

Non-ferrous alloys in general

SIST EN 3668:2009

en,de

SIST EN 3668:2009

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 3668:2009

https://standards.iteh.ai/catalog/standards/sist/36c2ab75-902b-4679-95fl-b6eeab9e0fcc/sist-en-3668-2009

EUROPEAN STANDARD

EN 3668

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2006

ICS 49.025.15

English Version

Aerospace series - Heat resisting alloy NI-PH2301 (NiCr21Fe18Mo9) - Non heat treated - Forging stock - a or D ≤ 250 mm

Série aérospatiale - Alliage résistant à chaud NI-PH2301 (NiCr21Fe18Mo9) - Non traité - Produits destinés à la forge - a ou D ≤ 250 mm Luft- und Raumfahrt - Hochwarmfeste Legierung NI-PH2301 (NiCr21Fe18Mo9) - Nicht wärmebehandelt -Schmiedevormaterial - a oder D ≤ 250 mm

This European Standard was approved by CEN on 18 October 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia; Lithuania; Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdomst/36c2ab75-902b-4679-95fl-

b6eeab9e0fcc/sist-en-3668-2009



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

This document (EN 3668:2006) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2007, and conflicting national standards shall be withdrawn at the latest by June 2007.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom. STANDARD PREVIEW

(standards.iteh.ai)

SIST EN 3668:2009 https://standards.iteh.ai/catalog/standards/sist/36c2ab75-902b-4679-95fl-b6eeab9e0fcc/sist-en-3668-2009

Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-3.

1 Scope

This standard specifies the requirements relating to:

Heat resisting alloy NI-PH2301 (NiCr21Fe18Mo9) Non heat treated Forging stock a or $D \le 250$ mm

for aerospace applications.

2 Normative references STANDARD PREVIEW

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies EN 3668:2009

https://standards.iteh.ai/catalog/standards/sist/36c2ab75-902b-4679-95fl-

EN 2043, Aerospace series — Metallical materials en 36 General requirements for semi-finished product qualification (excluding forgings and castings). 1)

EN 2860-2, Aerospace series — Heat resisting alloys — Forging stock and forgings — Technical specification — Part 2: Forging stock. 1)

EN 4258, Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use.

EN 4500-3, Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 3: Specific rules for heat resisting alloys. 1)

3

¹⁾ Published as ASD Prestandard at the date of publication of this standard.

| 1 | Material designati | | Heat resisting alloy NI-PH2301 (NiCr21Fe18Mo9) | | | | | | | | |
|-----|--------------------|---------|--|---------------|------|------|-------|-------|------------------|-----------------|------|
| 2 | Chemical | Element | | С | Si | Mn | Р | S | Al | Co | Cr |
| | composition min. | | | 0,05 | - | - | - | - | - | 0,50 | 20,5 |
| | % | max. | | 0,15 | 1,00 | 1,00 | 0,040 | 0,030 | 0,50 | 2,50 | 23,0 |
| | | Element | | Cu | Fe | Мо | Ti | W | В | Pb | Ni |
| | | min. | | _ | 17,0 | 8,00 | - | 0,20 | _ | - | Base |
| | | | | 0,50 | 20,0 | 10,0 | 0,15 | 1,00 | 100 ^a | 20 ^a | Dase |
| 3 | Method of melting | | Consumable electrode remelted | | | | | | | | |
| 4.1 | Form | | | Forging stock | | | | | | | |
| 4.2 | Method of produc | tion | | - | | | | | | | |
| 4.3 | Limit dimension(s | (s) mm | | a or D ≤ 250 | | | | | | | |
| 5 | Technical specific | | EN 2860-2 | | | | | | | | |

| 6.1 | Delivery condition | Non heat treated |
|-----|-------------------------|------------------------|
| | Heat treatment | _ |
| 6.2 | Delivery condition code | U |
| 7 | Use condition | Delivery condition |
| | Heat treatment | iTob STANDADD DD EVIEW |

(standards.iten.ai)

| 8.1 | 1 Test sample(s) | | | | See EN 2860-2. |
|-----|--------------------------------------|-----------------------|---------------------|-----|---|
| 8.2 | 2 Test piece(s) | | | htt | SIST EN 3668:2009 See EN 2860-2 ps://standards.iteh.ai/catalog/standards/sist/36c2ab 75-902b-4679-95fl- |
| 8.3 | | | | | b6eeab9e0fcc/sist-en-366&eelline 29. |
| 9 | Dimensions concerned mm | | | mm | a or D ≤ 250 |
| 10 | Thickness of cladding on each face % | | | % | - |
| 11 | 11 Direction of test piece | | | | Т |
| 12 | | Temperature | θ | °C | Ambient |
| 13 | | Proof stress | R _{p0,2} | MPa | ≥ 270 |
| 14 | Т | Strength | R _m | MPa | ≥ 690 |
| 15 | | Elongation | Α | % | ≥ 30 |
| 16 | | Reduction of area | Z | % | _ |
| 17 | 17 Hardness | | | | ≤ 255 HB |
| 18 | Shear strength R _c MPa | | MPa | _ | |
| 19 | 19 Bending k – | | - | _ | |
| 20 | 20 Impact strength | | | _ | |
| 21 | | Temperature | θ | °C | 815 b |
| 22 | | Time h | | h | t _R ≥ 23 |
| 23 | С | Stress | σ_{a} | MPa | _ |
| 24 | | Elongation | а | % | - |
| 25 | | Rupture stress | σ_{R} | MPa | 110 |
| 26 | | Elongation at rupture | Α | % | ≥ 8 |
| 27 | 27 Notes (see line 98) | | | | a, b |

| 29 | Reference heat treatment | | Solution treated θ = 1 175 °C \pm 10 °C / t \geq 20 min / AC or faster |
|----|--------------------------|--------|--|
| 44 | External defects | | See EN 2860-2. |
| 51 | i1 Macrostructure | | See EN 2860-2. |
| | | 7 | No harmful defects |
| 61 | Internal defects | _ | See EN 2860-2. |
| | | 7 | Class 3 |
| 95 | https://star | ndard. | STANDARD PREVIEW (standards.iteh.ai) SISTEN 3668:2009 sifeh.ai/catalog/standards/sist/36c2ab75-902b-4679-95fl-b6ceab9e0fcc/sist-en-3668-2009 |
| 95 | Marking inspection | _ | See EN 2860-2. |
| 96 | · | | See EN 2860-2. |
| 98 | 3 Notes | | a p.p.m.b Proportional test piece. |
| 99 | 9 Typical use | | - |

| 100 | 100 – Product qualification | | - | See EN 2043. | | | |
|-----|-----------------------------|----|----------|--|--|--|--|
| | | | | Qualification programme to be agreed between manufacturer and purchaser. | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | iΊ | Teh STANDARD PREVIEW | | | |
| | | | | (standards.iteh.ai) | | | |
| | | | | | | | |
| | | ht | tps://s | <u>SIST EN 3668:2009</u> tandards.iteh.ai/catalog/standards/sist/36c2ab75-902b-4679-95f1- | | | |
| | | | | b6eeab9e0fcc/sist-en-3668-2009 | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| L | | l | <u> </u> | | | | |