



# SLOVENSKI STANDARD

## SIST EN 3972:2009

01-maj-2009

5 YfcbUj H\_U!>Y\_c: 9!D@) \$+ f( \$7fAcJ%&L! DfYHJ Mybc gHJ]bc YY\_HcXc!  
I H Mybc ]b'a Y\_c ýUf Mybc ! DU]WnUcVXYUj c !'8Y®) \$ a a !%& \$ ADU®Fa ®  
% \$\$ ADU

ÓA|[•] æ^Á^|a•ÆÜc^|ÁÖEÜŠFÍ ēí Áç ÉÓIT [ XFGDEÄ[ } • { æ]^Á|^&d[ å^Á^{ ^|çåÆ  
Pæå^} å^æ å^A{ ] ^!^åÆÖæÁ[ Á æ@ a \* ÆÖ^Ám ēá { ÄFÁG €ÁT Úæmñ{ ÁmFÁ €€  
T Úæ

Š^ æÃ } åÜæ { -æ@ÆÜc^|ÁÖEÜŠFÍ ēí Áç ÉÓIT [ XFGDEÄ[ å^|æ^ç^{: ^@^} å^|Å|^d[ å^  
^ { \*^&@ [ ;^ } ÆÖ^@!c^A{ } å^æ \*^æ• } ÆÜc^|A] æ^} å^} Å^æ^æ^æ } \* ÆÖ^  
m ēá { ÄFÁG €ÁT Úæmñ{ ÁmFÁ €€ÁT Úæ

[SIST EN 3972:2009](#)

Ü..la Áe..|[•] æ^Á^|ÆÜc^|ÁÖEÜŠFÍ ēí Áç ÉÓIT [ XFGDEÄ[ } å^|æ^ç^{: ^@^} å^|Å|^d[ å^  
& } • { { æ]^Á^æ^æ^æ } ^ÆÖæ^æ^æ[ ^!A•æ^æ^æ^æ } å^æ^æ^æ } ^ÆÖ^Ám ēá { ÄFÁG €ÁT Úæm  
Ü{ ÁmFÁ €€ÁT Úæ

Ta slovenski standard je istoveten z: **EN 3972:2006**

### ICS:

49.025.10 Jekla

Steels

**SIST EN 3972:2009**

[en.de](#)

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

SIST EN 3972:2009

<https://standards.iteh.ai/catalog/standards/sist/805d8d10-e0f8-4bda-bcf0-c639816695c0/sist-en-3972-2009>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

EN 3972

December 2006

ICS 49.025.10

English Version

Aerospace series - Steel FE-PL1507 (40CrMoV12) -  
Consumable electrode remelted - Hardened and tempered - Bar  
for machining - De  $\leq$  50 mm - 1 250 MPa  $\leq$  Rm  $\leq$  1 400 MPa

Série aérospatiale - Acier FE-PL1507 (40CrMoV12) -  
Refondu à l'électrode consommable - Trempé et revenu -  
Barres pour usinage - De  $\leq$  50 mm - 1 250 MPa  $\leq$  Rm  $\leq$  1  
400 MPa

Luft- und Raumfahrt - Stahl FE-PL1507 (40CrMoV12) - Mit  
selbstverzehrender Elektrode umgeschmolzen - Gehärtet  
und angelassen - Stangen zur spanenden Bearbeitung - De  
 $\leq$  50 mm - 1 250 MPa  $\leq$  Rm  $\leq$  1 400 MPa

This European Standard was approved by CEN on 18 October 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

**THE STANDARD PREVIEW**

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.  
<https://standards.jeclic.cen.eu/sist-en-3972-2006-c639816695c0/sist-en-3972-2009>



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

## Foreword

This document (EN 3972:2006) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2007, and conflicting national standards shall be withdrawn at the latest by June 2007.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## ITEh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 3972:2009

<https://standards.iteh.ai/catalog/standards/sist/805d8d10-e0f8-4bda-bcf0-c639816695c0/sist-en-3972-2009>

## Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-5.

### 1 Scope

This standard specifies the requirements relating to:

Steel FE-PL1507 (40CrMoV12)  
Consumable electrode remelted  
Hardened and tempered  
Bar for machining  
 $D_e \leq 50$  mm  
 $1\ 250\ MPa \leq R_m \leq 1\ 400\ MPa$

for aerospace applications.

## iTeh STANDARD PREVIEW

### 2 Normative references ([standards.iteh.ai](https://standards.iteh.ai/catalog/standards/sist-en-3972-2009))

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2043, Aerospace series — Metallic materials — General requirements for semi-finished product qualification (excluding forgings and castings).<sup>1)</sup>

EN 4258, Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use.

EN 4500-5, Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 5: Specific rules for steels.<sup>1)</sup>

EN 4700-2, Aerospace series — Steel and heat resisting alloys — Wrought products — Technical specification — Part 2: Bar and section.<sup>1)</sup>

---

1) Published as ASD Prestandard at the date of publication of this standard.

## EN 3972:2006 (E)

1	Material designation			Steel FE-PL1507 (40CrMoV12)											
2	Chemical composition %	Element		C	Si	Mn	P <sup>a</sup>	S	Cr	Mo	Ni	Sn <sup>a</sup>	V	Fe	
		min.		0,35	0,10	0,40	–	–	3,00	0,80	–	–	0,15	Base	
		max.		0,43	0,35	0,70	0,015	0,010	3,50	1,10	0,30	0,025	0,25		
3	Method of melting			Consumable electrode remelted											
4.1	Form			Bar for machining											
4.2	Method of production			–											
4.3	Limit dimension(s)		mm	$D_e \leq 50$ <sup>b</sup>											
5	Technical specification			EN 4700-2											

6.1	Delivery condition			Annealed <sup>b</sup>			Hardened and tempered						
	Heat treatment			–			$910 \text{ }^{\circ}\text{C} \leq \theta \leq 950 \text{ }^{\circ}\text{C} / t \geq 1 \text{ h} / \text{OQ}$ $+ \theta \geq 600 \text{ }^{\circ}\text{C} / t \geq 1 \text{ h} / \text{OQ or AC}$						
6.2	Delivery condition code			A			U						
7	Use condition			Hardened and tempered <sup>c</sup>			Delivery condition						
	Heat treatment			Delivery condition $+ 910 \text{ }^{\circ}\text{C} \leq \theta \leq 950 \text{ }^{\circ}\text{C} / t \geq 1 \text{ h} / \text{OQ}$ $+ \theta \geq 600 \text{ }^{\circ}\text{C} / t \geq 1 \text{ h} / \text{OQ or AC}$			–						

## iTeh STANDARD PREVIEW

Characteristics

(standards.iteh.ai)

8.1	Test sample(s)			See EN 4700-2.			See EN 4700-2.			$D = 16 \text{ mm}$ Cut from bar delivered in the annealed condition				
8.2	Test piece(s)			See EN 4700-2. <a href="https://standards.iteh.ai/catalog/standards/sist/805sd8d10-edf8-4bda-bcf0">https://standards.iteh.ai/catalog/standards/sist/805sd8d10-edf8-4bda-bcf0</a>			See EN 4700-2.			Heat treated before machining				
8.3	Heat treatment			Annealed <sup>d</sup>			Hardened and tempered <sup>e</sup>			See line 29.				
9	Dimensions concerned		mm	$a$ or $D \leq 100$			$D_e \leq 50$			$a$ or $D \leq 100$				
10	Thickness of cladding on each face		%	–			–			–				
11	Direction of test piece			L			L			L				
12	T	Temperature	$\theta$	$^{\circ}\text{C}$	Ambient			Ambient			Ambient			
13		Proof stress	$R_{p0,2}$	MPa	–			$\geq 1\ 030$			$\geq 1\ 030$			
14		Strength	$R_m$	MPa	–			$1\ 250 \leq R_m \leq 1\ 400$			$1\ 250 \leq R_m \leq 1\ 400$			
15		Elongation	A	%	–			$\geq 10$			$\geq 10$			
16		Reduction of area	Z	%	–			$\geq 35$			$\geq 35$			
17	Hardness			$\leq 277 \text{ HB}$			$375 \leq \text{HB} \leq 401$			$375 \leq \text{HB} \leq 401$				
18	Shear strength		$R_c$	MPa	–			–			–			
19	Bending		k	–	–			–			–			
20	Impact strength			–			$KV \geq 25 \text{ J}$ ; Notch direction T <sup>d, e</sup>			$KV \geq 25 \text{ J}$ ; Notch direction T <sup>d, e</sup>				
21	C	Temperature	$\theta$	$^{\circ}\text{C}$	–			–			–			
22		Time		h	–			–			–			
23		Stress		$\sigma_a$	MPa	–			–			–		
24		Elongation		a	%	–			–			–		
25		Rupture stress		$\sigma_R$	MPa	–			–			–		
26		Elongation at rupture		A	%	–			–			–		
27	Notes (see line 98)			a, b, c, d, e										

29	Reference heat treatment	-	Hardened and tempered $910^{\circ}\text{C} \leq \theta \leq 950^{\circ}\text{C}$ / $t \geq 30\text{ min}$ / OQ + temper $\theta \geq 600^{\circ}\text{C}$ / $t \geq 1\text{ h}$ / OQ or AC <sup>f</sup>
34	Grain size	-	See EN 4700-2.
		5	Use condition
		7	$G \geq 7$
44	External defects	-	See EN 4700-2.
50	Cleanliness/Inclusion content (micro-cleanliness)	-	See EN 4700-2.
		7	Category 3
51	Macrostructure	-	See EN 4700-2.
		5	Delivery condition
		7	Class 1
			Freckles: severity A
			Class 2
			White spots: severity A
			Class 3
			Radial segregation: severity A
			Class 4
			Ring pattern: severity B
59	Decarburization	-	See EN 4700-2.
61	Internal defects	-	See EN 4700-2.
		7	Class 4
			<p style="text-align: center;"><b>iTeh STANDARD PREVIEW</b> <b>(standards.iteh.ai)</b></p> <p style="text-align: center;">SIST EN 3972:2009  <a href="https://standards.iteh.ai/catalog/standards/sist/805d8d10-e0f8-4bda-bcf0-c639816695c0/sist-en-3972-2009">https://standards.iteh.ai/catalog/standards/sist/805d8d10-e0f8-4bda-bcf0-c639816695c0/sist-en-3972-2009</a></p>
95	Marking inspection	-	See EN 4700-2.
96	Dimensional inspection	-	See EN 4700-2.
98	Notes	-	<sup>a</sup> P + Sn ≤ 0,025 <sup>b</sup> Material with a a or D > 50 mm may be delivered in the annealed condition. <sup>c</sup> Only to be heat treated when $D_e \leq 50\text{ mm}$ <sup>d</sup> Value after blank nitriding: $500^{\circ}\text{C} \pm 10^{\circ}\text{C}$ / $t = 24\text{ h}$ . The "capability clause" applies. <sup>e</sup> IZOD is optional test and shall achieve 20ft.lbf minimum. <sup>f</sup> Actual heat treatment temperature and time shall be reported on the inspection and test report.
99	Typical use	-	Low alloy general purpose steel; suitable for nitriding.

**EN 3972:2006 (E)**

100	-	Product qualification	-	See EN 2043.
				Qualification programme to be agreed between manufacturer and purchaser.

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[SIST EN 3972:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/805d8d10-e0f8-4bda-bcf0-c639816695c0/sist-en-3972-2009>