



DRAFT INTERNATIONAL STANDARD ISO/DIS 5163

ISO/TC 28

Secretariat: **ANSI**

Voting begins on
2002-08-01

Voting terminates on
2003-01-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Petroleum products — Determination of knock characteristics of motor and aviation fuels — Motor method

[Revision of second edition (ISO 5163:1990)]

Produits pétroliers — Détermination des caractéristiques antidétonantes des carburants pour moteur automobile et aviation — Méthode «Moteur»

ICS 75.160.20

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/DIS 5163](#)

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

ISO/CEN PARALLEL ENQUIRY

The CEN Secretary-General has advised the ISO Secretary-General that this ISO/DIS covers a subject of interest to European standardization. **In accordance with the ISO-lead mode of collaboration as defined in the Vienna Agreement, consultation on this ISO/DIS has the same effect for CEN members as would a CEN enquiry on a draft European Standard.** Should this draft be accepted, a final draft, established on the basis of comments received, will be submitted to a parallel two-month FDIS vote in ISO and formal vote in CEN.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to ISO at the address below or ISO's member body in the country of the requester.

Copyright Manager
ISO Central Secretariat
1 rue de Varembé
1211 Geneva 20 Switzerland
tel. + 41 22 749 0111
fax + 41 22 734 1079
internet: iso@iso.ch

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/DIS 5163

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

Contents

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Principle	3
5 Reagents and reference materials	3
6 Apparatus	4
7 Sampling and sample preparation	5
8 Basic engine and instrument settings and standard operating conditions	5
8.1 Installation of engine equipment and instrumentation	5
8.2 Engine speed	6
8.3 Valve timing	6
8.4 Valve lift	6
8.5 Intake valve shroud	6
8.6 Direction of engine rotation	6
8.7 Carburettor venturi	6
8.8 Valve clearances	7
8.9 Oil pressure	7
8.10 Oil temperature	7
8.11 Cylinder jacket coolant temperature	7
8.12 Intake air temperature	7
8.13 Intake mixture temperature	7
8.14 Intake air humidity	7
8.15 Cylinder jacket coolant level	7
8.16 Engine crankcase lubricating oil level	8
8.17 Crankcase internal pressure	8
8.18 Exhaust back pressure	8
8.19 Exhaust and crankcase breather system resonance	8
8.20 Belt tension	8
8.21 Rocker arm carrier support basic setting	8
8.22 Rocker arm carrier basic setting	8
8.23 Rocker arm and push rod length basic settings	8
8.24 Basic spark setting	8
8.25 Basic ignition timer transducer to rotor vane gap setting	9
8.26 Basic ignition timer control arm setting	9
8.27 Spark plug gap	9
8.28 Basic cylinder height setting	9
8.29 Fuel-air ratio	9
8.30 Carburettor cooling	9
8.31 Knockmeter reading limits	9
8.32 Detonation meter spread and time constant settings	10
9 Engine calibration and qualification	10
9.1 General	10
9.2 Engine fit-for-use qualification	10
9.3 Fit-for-use procedure in the 79,8 MON to 94,5 MON range	11
9.4 Fit-for-use procedure below 79,8 MON and above 94,5 MON	11

9.5	Checking performance on check fuels	12
10	Procedure.....	12
10.1	General	12
10.2	Start-up.....	12
10.3	Calibration.....	13
10.4	Sample fuel	13
10.5	Primary reference fuel No. 1	13
10.6	Primary reference fuel No. 2	13
10.7	Additional measurement readings	14
11	Calculation	14
12	Expression of results.....	15
13	Precision	15
13.1	General	15
13.2	Repeatability (<i>r</i>) for ratings at barometric pressures of 94,6 kPa (28,0 in of Hg) and higher	15
13.3	Reproducibility (<i>R</i>) for ratings at barometric pressures of 94,6 kPa (28,0 in of Hg) and higher.....	16
13.4	Precision at lower barometric pressure	16
14	Test report.....	16

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 5163

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 5163 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*.

This third edition cancels and replaces the second edition (1990), which has been technically revised.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 5163

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

Introduction

The purpose of this International Standard is to accord ISO status to a test procedure that is already used in a standardized form all over the world. The procedure in question is published by ASTM International as Standard Test Method D 2700-01a.

By publishing this International Standard, ISO recognizes that this method is used in its original text in many member countries and that the standard equipment and many of the accessories and materials required for the method are obtainable only from specific manufacturers or suppliers. To carry out the procedure requires reference to six annexes and three appendices to ASTM D 2700-01a, contained in the Annual Book of ASTM Standards, Section 5¹⁾. The annexes detail the specific equipment and instrumentation required, the critical component settings and adjustments, and include the working tables of referenced settings. The appendices provide background and additional insight about auxiliary equipment, operational techniques and the concepts relative to proper maintenance of the engine and instrumentation items.

The accumulated motor and aviation-type fuel data relating to knock characteristics determined in many countries has, for many years, been based on the use of the CFR engine²⁾ and the ASTM octane test methods. Accepted worldwide petroleum industry octane number requirements for motor and aviation-type fuels are defined by the motor method and associated CFR F-2 Octane Rating Unit, which emphasizes the need for this method and test equipment to be standardized. The initiation of studies to use a different engine for ISO purposes has therefore been considered an unnecessary duplication of effort.

It is further recognized that this method for rating motor and aviation-type fuels, which does include metric operating conditions, is never-the-less an exceptional case in that the CFR engine is manufactured to inch dimensions and requires numerous settings and adjustments to inch dimensions. Application of metrication to these dimensions and tolerances can only be accomplished by strict numerical conversion which would not reflect proper metric engineering practice. Attempts to utilize metric measurement instruments for checking component dimensions to the numerically converted metric values would only introduce an additional source of test variability.

For these reasons, it has been considered desirable by ISO Technical Committee 28, *Petroleum products and lubricants*, to adopt the ASTM D 2700 standard rewritten to comply with ISO Directives, Part 2, *Rules for the structure and drafting of International Standards*. However, this International Standard refers to annexes and appendices of ASTM D 2700 without change because of their extensive detail. These annexes and appendices are not included in this International Standard because they are published in the Annual Book of ASTM Standards, Section 5.

1) Copies may be purchased directly from the publisher, ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, USA. A new edition of each ASTM standard is issued annually incorporating all revisions authorized by letter ballot action within the previous year. Users of this International Standard should ensure that they have the most recent issue of the Standard Test Method ASTM D 2700.

2) The sole manufacturer of the Model CFR F-2 Octane Rating Unit is Waukesha Engine, Dresser, Inc., 1000 West St. Paul Avenue, Waukesha, WI 53188, USA.

Petroleum products — Determination of knock characteristics of motor and aviation fuels — Motor method

WARNING — The use of this International Standard may involve hazardous materials, operations and equipment. This International Standard does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this International Standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

1 Scope

This International Standard establishes the rating of liquid spark-ignition engine fuel in terms of an arbitrary scale of octane numbers using a standard single cylinder, four-stroke cycle, variable compression ratio, carburetted, CFR engine operated at constant speed. Motor octane number (MON) provides a measure of the knock characteristics of motor fuels in automotive engines under severe conditions of operation. Motor octane number provides a measure of the knock characteristics of aviation fuels in aviation piston engines, by using an equation to correlate to aviation method octane number or performance number (lean mixture aviation rating).

This International Standard is applicable for the entire scale range from zero MON to 120 MON, but the working range is 40 MON to 120 MON. Typical motor fuel testing is in the range of 80 MON to 90 MON. Typical aviation fuel testing is in the range of 98 MON to 102 MON.

This International Standard can be used for oxygenate-containing fuels containing up to 4,0 % (m/m) oxygen.

Certain gases and fumes, such as halogenated refrigerants used in air-conditioning equipment, that can be present in the area where the CFR engine is located, may have a measurable effect on the MON rating. Electrical power transient voltage or frequency surges or distortion can affect MON ratings.

NOTE 1 This International Standard specifies operating conditions in SI units but engine measurements are specified in inch-pound units because these are the units used in the manufacture of the equipment, and thus some references in this International Standard include these units in parenthesis.

NOTE 2 For the purposes of this International Standard, the expressions "% (m/m)" and "% (V/V)" are used to represent the mass and volume fractions of a material respectively.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3170:1988, *Petroleum liquids — Manual sampling*

ISO 3171:1988, *Petroleum liquids — Automatic pipeline sampling*

ISO 3696: 1987, *Water for analytical laboratory use — Specification and test methods*

ISO 4787:1984, *Laboratory glassware — Volumetric glassware — Methods for use and testing of capacity*

ASTM D 2700-01a, *Standard test method for motor octane number of spark-ignition engine fuel*

3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

3.1

check fuels

fuels of selected characteristics that have MON assigned reference values determined by round robin testing by multiple engines in different locations

3.2

cylinder height

relative vertical position of the CFR engine cylinder with respect to the piston at top dead centre (t.d.c.) or the top machined surface of the crankcase

3.3

dial indicator reading

numerical indication of cylinder height, in thousandths of an inch, indexed to a basic setting when the engine is motored with the compression ratio set to produce a specified compression pressure

3.4

digital counter reading

numerical indication of cylinder height, indexed to a basic setting when the engine is motored with the compression ratio set to produce a specified compression pressure

3.5

detonation meter

knock signal conditioning instrumentation that accepts the electrical signal from the detonation pickup and produces an output signal for display

3.6

detonation pickup

magnetostrictive-type transducer that threads into the engine cylinder to sense combustion chamber pressure and provide an electrical signal proportional to the rate-of-change of that cylinder pressure

3.7

firing

engine operation with fuel and ignition

3.8

fuel-air ratio for maximum knock intensity

proportion of fuel to air that produces the highest knock intensity for each fuel

3.9

guide tables

tabulations of the specific relationship between cylinder height and octane number for the CFR engine operated at standard knock intensity and a specified barometric pressure

3.10

knock

abnormal combustion, often producing audible sound, caused by autoignition of the air/fuel mixture

3.11

knock intensity

measure of engine knock

3.12

knockmeter

indicating meter with a 0 to 100 division scale that displays the knock intensity signal from the detonation meter

3.13**lean mixture aviation rating**

indication of the knock resistance for a fuel operating in an aviation piston engine under lean fuel-air ratio conditions

3.14**motoring**

engine operation without fuel and with the ignition off

3.15**motor octane number (MON)**

numerical rating of knock resistance for a fuel obtained by comparing its knock intensity with that of primary reference fuels of known motor octane number when tested in a standardized CFR engine operating under conditions specified in this International Standard

3.16**oxygenate**

oxygen-containing organic compound, such as various alcohols or ethers, used as a fuel or fuel supplement

3.17**primary reference fuels (PRF)**

2,2,4-trimethylpentane (*isooctane*), heptane, volumetrically proportioned mixtures of *isooctane* with heptane, or blends of tetraethyllead in *isooctane*, which define the octane number scale

3.18**spread**

sensitivity of the detonation meter expressed in knockmeter divisions per octane number

3.19**toluene standardization fuel blends (TSF blends)**

volumetrically proportioned blends of two or more of the following; reference fuel grade toluene, heptane, and *isooctane*, that have MON accepted reference values and specified rating tolerances

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

4 Principle

A sample fuel, operating in a CFR engine at the fuel-air ratio that maximizes its knock, is compared to primary reference fuel blends to determine that blend which, when operated at the fuel-air ratio that maximizes its knock, would result in both fuels producing the same standard knock intensity when tested at the same engine compression ratio. The volumetric composition of the primary reference fuel blend defines both its octane number and that of the sample fuel.

5 Reagents and reference materials

5.1 Cylinder jacket coolant, consisting of water conforming to grade 3 of ISO 3696. Water shall be used in the cylinder jacket for laboratory locations where the resultant boiling temperature is $100\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$. Water with commercial glycol-based antifreeze added in sufficient quantity to meet the boiling temperature requirement shall be used when laboratory altitude dictates.

NOTE A commercial multi-functional water treatment material should be used in the coolant to minimize corrosion and mineral scale that can alter heat transfer and rating results.

5.2 Carburettor coolant, if required (see 8.30), comprising water or a water/antifreeze mixture, chilled sufficiently to prevent fuel bubbling, but not colder than $0,6\text{ }^{\circ}\text{C}$ or warmer than $10\text{ }^{\circ}\text{C}$.

5.3 Engine crankcase-lubricating oil, comprising an SAE 30 viscosity grade oil meeting service classification SF/CD or SG/CE. It shall contain a detergent additive and have a kinematic viscosity of $9,3\text{ mm}^2/\text{s}$ to $12,5\text{ mm}^2/\text{s}$ at $100\text{ }^{\circ}\text{C}$ and a viscosity index of not less than 85. Oils containing viscosity index improvers shall not be used. Multigrade lubricating oils shall not be used.

5.4 2,2,4-trimethylpentane (isooctane) primary reference fuel, of minimum purity 99,75 % (V/V), containing no more than 0,10 % (V/V) heptane and no more than 0,50 mg/l lead. This material shall be designated as 100 MON.

5.5 Heptane primary reference fuel, of minimum purity 99,75 % (V/V), containing no more than 0,10 % (V/V) isooctane and no more than 0,5 mg/l lead. This material shall be designated as 0 MON.

5.6 80 octane primary reference fuel blend, prepared using reference fuel grade isooctane (5.4) and heptane (5.5), this blend shall contain 80 % (V/V) \pm 0,1 % (V/V) isooctane.

NOTE ASTM D 2700, Annex A5 (Reference Fuel Blending Tables), provides information for preparation of primary reference fuel blends to specific MON values.

5.7 Tetraethyllead, dilute, (TEL dilute volume basis), comprising a solution of aviation mix tetraethyllead antiknock compound in a hydrocarbon diluent of 70 % (V/V) xylene and 30 % (V/V) heptane. The antiknock compound shall contain 18,23 % (m/m) \pm 0,05 % (m/m) tetraethyllead and have a relative density at 15,6/15,6 °C of 0,957 to 0,967.

NOTE The typical composition of the compound, excluding the tetraethyllead, is as follows:

Ethylene dibromide (scavenger):	10,6 % (m/m)
Diluent:	
xylene	52,5 % (m/m)
heptane	17,8 % (m/m)
dye, antioxidant and inerts	0,87 % (m/m)

5.8 Primary reference fuel blends for ratings over 100 MON, prepared by adding dilute tetraethyllead (5.7), in specified millilitre quantities, to a 400 ml volume of isooctane (5.4). These blends define the MON scale above 100.

NOTE ASTM D 2700, Annex A5 (Reference Fuel Blending Tables), provides the MON values for blends of tetraethyllead in isooctane.

<https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-49e3a9bfb2e/iso-dis-5163>

5.9 Methylbenzene (toluene), reference fuel grade, with a minimum purity of 99,5 % (V/V) as determined by chromatographic analysis, a peroxide number not exceeding 5 mg/kg, and a water content not exceeding 200 mg/kg.

NOTE Antioxidant treatment should be added by the supplier at a rate suitable for long term stability as empirically determined with the assistance of the antioxidant supplier.

5.10 Check fuels, comprising in-house typical spark-ignition engine fuels having MON accepted reference values, low volatility and good long term stability.

6 Apparatus

6.1 Test engine assembly, a CFR F-2 octane rating unit comprising a single cylinder engine consisting of a standard crankcase, a variable compression ratio cylinder/clamping sleeve assembly, thermal siphon recirculating jacket cooling system, multiple fuel bowl system with selector valving to deliver fuel through a single jet passage and carburettor venturi, an intake mixture manifold with mixture heater, an intake air system with controlled temperature and humidity equipment, electrical controls, and a suitable exhaust pipe. The engine shall be connected by a belt to a special electric power-absorption motor which acts as a motor driver to start the engine and as a means to absorb power at constant speed when combustion is occurring (engine firing). See ASTM D 2700, Annex A2 (Engine Equipment Description and Specifications), for all critical, non-critical and equivalent engine equipment, which shall apply for this International Standard.

6.2 Instrumentation, comprising electronic detonation metering instrumentation, including a detonation pickup and knockmeter to measure and display the intensity of combustion knock, as well as conventional thermometry, gauges and general purpose meters. See ASTM D 2700, Annex A3 (Instrumentation Description and

Specifications), for all critical, non-critical and equivalent instrumentation, which shall apply for this International Standard.

NOTE Engine equipment and instrumentation are available from the single source manufacturer, Waukesha Engine, Dresser, Inc., 1000 West St. Paul Avenue, Waukesha, WI 53188, USA. Waukesha Engine also has authorized sales and service organizations in selected geographic areas. This information is given for the convenience of users of this International Standard but does not constitute an endorsement by ISO of this product.

6.3 Reference and standardization fuel dispensing equipment, comprising calibrated burettes or volumetric ware having a capacity of 200 ml to 500 ml and a maximum volumetric tolerance of $\pm 0,2$ %. Calibration shall be verified in accordance with ISO 4787. Burettes shall be outfitted with a delivery valve and delivery tip to accurately control dispensed volumes. The delivery tip shall be of such size and design that shut-off tip discharge does not exceed 0,5 ml. The rate of delivery from the dispensing system shall not exceed 400 ml/min.

6.4 Tetraethyllead (TEL) dispensing equipment, comprising a calibrated burette, pipette assembly, or other liquid dispensing apparatus, having a capacity not exceeding 4,0 ml, and a critically controlled tolerance for dispensing dilute TEL into 400 ml batches of *isooctane*. Calibration shall be verified in accordance with ISO 4787.

NOTE ASTM D 2700, Appendix X1 (Reference Fuel Blending Apparatus and Procedures), provides additional information for application of this International Standard.

6.5 Special maintenance tools. A number of specialty tools and measuring instruments are available for easy, convenient and effective maintenance of the engine and testing equipment.

NOTE Lists and descriptions of these tools and instruments are available from the manufacturers of the engine equipment and those organizations offering engineering and service support for this International Standard.

iTech STANDARD PREVIEW
(standards.iteh.ai)

7 Sampling and sample preparation

7.1 Samples shall be obtained in accordance with ISO 3170, ISO 3171 or an equivalent national standard.

[https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-](https://standards.iteh.ai/catalog/standards/sist/55a4c1e1-656e-4a21-8ed0-4e1e1e1e1e1e)

7.2 Samples shall be cooled to 2 °C to 10 °C in the container in which they are received and before the container is opened.

7.3 Minimize the sample's exposure to light before pouring it into the engine carburettor fuel bowl, because of possible sensitivity to light that can affect fuel characteristics.

8 Basic engine and instrument settings and standard operating conditions

8.1 Installation of engine equipment and instrumentation

Locate the octane test engine in an area where it will not be affected by certain gases and fumes that may have a measurable effect on the MON test result (see clause 1).

Installation of the engine and instrumentation requires placement of the engine on a suitable foundation and hook-up of all utilities. Engineering and technical support for this function is required, and the user shall be responsible for complying with all local and national codes and installation requirements. Proper operation of the test engine requires assembly of a number of engine components and adjustment of a series of engine variables to prescribed specifications. Some of these settings are established by component specifications, others are established at the time of engine assembly or after overhaul, and still others are engine running conditions that shall be observed and/or determined by operator adjustment during the testing process.