
**Pneumatic fluid power — Five-port
directional control valves, sizes 18 mm
and 26 mm —**

**Part 2:
Mounting interface surfaces with optional
electrical connector**

*Transmissions pneumatiques — Distributeurs de commande
directionnels à cinq orifices, tailles 18 mm et 26 mm —*

*Partie 2: Surfaces d'interface de montage avec connecteur électrique
facultatif*

ISO 15407-2:2003

<https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 15407-2:2003

<https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003>

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15407-2 was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 5, *Control products and components*.

ISO 15407 consists of the following parts, under the general title *Pneumatic fluid power — Five-port directional control valves, sizes 18 mm and 26 mm*:

- *Part 1: Mounting interface surfaces without electrical connector*
- *Part 2: Mounting interface surfaces with optional electrical connector*

[ISO 15407-2:2003](https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003)

<https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003>

Introduction

In pneumatic fluid power systems, power is transmitted and controlled through gas under pressure within a circuit.

The various devices for gas distribution and control can be either mounted directly on to the piping, or mounted on interface surfaces, allowing quicker dismantling and promoting equipment interchangeability.

Pneumatic directional control valves of the five-port type, as used on mounting interface surfaces complying with the requirements of this part of ISO 15407, control the flow of compressed gas. When the valve is electrically operated, it may be desirable to use an electrical connector at the interface of the valve body and base. Users of pneumatic valves benefit when this electrical connector is standardized, allowing easy electrical connection interchangeability between valves produced by different manufacturers.

Standardization of port and orifice identification, the result of control-mechanism actuation and a system of dimensional tolerances are provided to enhance mounting interchangeability of pneumatic control valves used on the mounting surfaces complying with the requirements of this part of ISO 15407.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 15407-2:2003](https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003)

<https://standards.iteh.ai/catalog/standards/iso/83172d0c-1d75-4a90-af2b-e422dabc1550/iso-15407-2-2003>

Pneumatic fluid power — Five-port directional control valves, sizes 18 mm and 26 mm —

Part 2: Mounting interface surfaces with optional electrical connector

1 Scope

This part of ISO 15407 specifies the following requirements for a mounting interface and electrical connector for five-port pneumatic directional control valves, sizes 18 mm and 26 mm, for use at a maximum rated pressure of 1,6 MPa [16 bar¹⁾]:

- dimensions and tolerances of the interface features;
- port identification;
- identification of the result of control-mechanism actuation;
- dimensions, tolerances and specifications for optional interface electrical connector mateability.

It is not applicable to the functional characteristics of interfaces.

NOTE The requirements for mounting interfaces of five-port directional control valves, sizes 18 mm and 26 mm, without electrical connector are specified in ISO 15407-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1101:—²⁾, *Geometrical Product Specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 1302, *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*

ISO 4287, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

ISO 4288, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 Pa = 1 N/m²

2) To be published. (Revision of ISO 1101:1983)

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 11727, *Pneumatic fluid power — Identification of ports and control mechanisms of control valves and other components*

3 Terms and definitions

For the purposes of this part of ISO 15407, the terms and definitions given in ISO 5598 and the following apply.

3.1 electrical connector
device consisting of two parts (contact and housing) that, when they are joined, provide electrical and mechanical continuity

3.2 contact
current-carrying component used at a removable junction of an electric circuit

3.3 socket
contact with an opening or hollow designed to be the mechanical holder of a pin-type contact

3.4 pin
pointed contact designed to mate with a socket contact

3.5 housing
device designed to orient, secure and insulate contacts

4 Dimensional requirements and tolerances


4.1 Dimensional requirements for sizes 18 mm and 26 mm are shown in Figure 1 and given in Table 1.

4.2 The tolerances of form and location of the interface features, and position tolerance are shown in Figure 2.

4.3 Tolerances on surface condition, within the continuous wide outer boundary lines in Figure 1, shall be as follows:

- surface roughness: $R_a = 1,6 \mu\text{m}$ (see ISO 1302, ISO 4287 and ISO 4288);
- surface flatness: 0,1 mm over a distance of 100 mm (see ISO 1101).

EXAMPLE



4.4 The mounting surface shall not include any orifices other than those shown in the figures. All passages shown in the interface shall be included, and connected to open ports in the base.