
**Information technology — Automatic
identification and data capture
techniques — Data Carrier Identifiers
(including Symbology Identifiers)**

*Technologies de l'information — Techniques d'identification automatique et
de capture de données — Identificateurs de porteuses de données
(comprenant les identificateurs de symboles)*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

ISO/IEC 15424:2000

[https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-
b4c06ec33024/iso-iec-15424-2000](https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 15424:2000

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	2
4.1 Structure	2
4.2 Code characters	2
4.3 Modifier characters	3
Annex A (normative) Maintenance	11
Annex B (normative) Symbology emulation	12
Annex C (informative) Reference documents	14

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15424:2000](https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000)

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 15424 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*, in collaboration with CEN Technical Committee TC 225, *Bar coding*, and AIM International, Inc. It was based in part on the corresponding European Standard EN 796, *Bar Coding — Symbolology Identifiers*, which is fully compatible with this International Standard.

Annexes A and B form a normative part of this International Standard. Annex C is for information only.

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

Introduction

The need exists to identify the data carrier a reader detects in autodiscrimination environments. The Symbology Identifier concept provides a standardized way for a device receiving data from a reader to differentiate between the data carriers. This specification deals mostly with bar code symbologies, therefore the terms Symbology Identifier, symbology, and bar code are used throughout the document but they are intended to apply to other data carriers as well.

This identification is achieved by the addition of an optional feature to readers enabling the reader to prefix a standard string of characters to data messages. This preamble contains information about the decoded symbol (or other data carrier) and any processing the reader has done. The information is not encoded or otherwise explicitly or implicitly represented in the symbol, except that the presence of some optional features may be detected by the reading equipment, whereas others require the reader to be expressly configured to implement them.

This International Standard should be read in conjunction with the relevant symbology specifications.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO/IEC 15424:2000](https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000)

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 15424:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

Information technology — Automatic identification and data capture techniques — Data Carrier Identifiers (including Symbology Identifiers)

1 Scope

This International Standard applies to automatic identification device communication conventions and standardizes the reporting of data carriers from bar code readers and other automatic identification equipment. It specifies a preamble message generated by the reader and interpretable by the receiving system, which indicates the bar code symbology or other origin of transmitted data, together with details of certain specified optional processing features associated with the data message.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-1e0137213721/iso-646-1991>

ISO/IEC 646:1991, *Information technology — ISO 7-bit Character Set for information interchange*.

EN 1556, *Bar coding — Terminology*.

3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in EN 1556 and the following apply.

3.1

code character

second character in the symbology identifier string, which usually indicates to the host the bar code symbology of the symbol which has been read

3.2

flag character

first character in the symbology identifier string, which indicates to the host that it and the characters following are the symbology identifier characters

3.3

modifier characters

remaining characters following the code character in the symbology identifier string

3.4

FNC1

special function character used for specific purposes in certain symbologies

**3.5
FNC2**

special function character used for specific purposes in certain symbologies

4 Requirements

This International Standard identifies symbologies for which a symbology specification has been published by ISO/IEC JTC 1, AIM International, or another recognized international standards body. In addition there is a fixed number of symbologies which do not have a full standard but do have a reference document available from AIM International, Inc. These symbologies are included in this International Standard because of their historical usage.

4.1 Structure

The symbology identifier shall be an ASCII character string prefixed by the reading equipment to the data contained in a bar code symbol.

The structure of the symbology identifier string shall be as follows:

]cm...

where] (ASCII value 93 in accordance with ISO 646) represents the symbology identifier flag character;

c represents the code character as defined in Table 1;

m... represents the modifier character(s) as defined for the symbology in question.

NOTE The sign] is the character assigned to ASCII value 93 in the United States ASCII character set in accordance with ISO 646.

[ISO/IEC 15424:2000](#)

If a reader is enabled to transmit symbology identifiers, it shall always transmit a symbology identifier at the beginning of each message. The application must know whether or not the reader has symbology identifiers enabled. Therefore, the symbol data may start with a] and still be interpreted unambiguously.

When these ASCII characters are transmitted in a 16-bit (double byte) system, an 8-bit byte of all zeros shall be transmitted before each of the above ASCII characters (bytes).

4.2 Code characters

Code characters shall be drawn from the set of upper- and lower-case alphabetic letters A through Z (ASCII values 65 through 90) and a through z (ASCII values 97 through 122). The currently assigned code characters are listed in Table 1. These code characters are case sensitive, i.e. a capital "A" is a different code character from a lower case "a".

The code character Y is not assigned to a specific symbology but will be used for system expansion. The first modifier character following Y will be a digit from 1 to 9 defining the number of remaining modifier characters in the symbology identifier prefix string.

All code characters not given here are reserved for future use. Maintenance of the list of code characters (and of options given in 4.3) shall be in accordance with annex A of this International Standard.

Certain symbologies emulate the data content of other symbologies, using their assigned symbology identifier. See annex B.

Table 1 — Code characters

Code char.	Symbology	Code char.	Symbology
A	Code 39	a	reserved
B	Telepen	b	reserved
C	Code 128	c	Channel Code
D	Code one	d	Data matrix
E	EAN/UPC	e	reserved
F	Codabar	f	reserved
G	Code 93	g	reserved
H	Code 11	h	reserved
I	Interleaved 2 of 5	i	reserved
J	reserved	j	reserved
K	Code 16K	k	reserved
L	PDF417 and MicroPDF417	l	reserved
M	MSI	m	reserved
N	Anker	n	reserved
O	Codablock	o	reserved
P	Plessey Code	p	reserved
Q	QR Code	q	reserved
R	Straight 2 of 5 (with two bar start/stop codes)	r	reserved
S	Straight 2 of 5 (with three bar start/stop codes)	s	reserved
T	Code 49	t	reserved
U	MaxiCode	u	reserved
V	reserved	v	reserved
W	reserved	w	reserved
X	Other bar code	x	reserved
Y	System expansion	y	reserved
Z	Non-bar code	z	Aztec code

4.3 Modifier characters

Some symbologies covered by this International Standard contain optional features which need to be indicated to the receiving equipment to enable them to be correctly processed. This optional processing is indicated by the modifier character(s).

Each symbology has a different set of optional features. These are listed in the following subclauses.

To determine the modifier character(s) for an application, refer to the subclause corresponding to the symbology concerned. Listed in this subclause may be one or more processing options, each of which has an assigned option value. The precise interpretation of the option should be obtained by reference to the relevant symbology specification. The modifier characters define the options available for the code character. The number of modifier characters and their meaning is defined for each of the code characters. The first modifier character shall be from the set {0 to 9, A to Z, a to z}; in some instances the character may represent a hexadecimal value (0 to F) corresponding to the sum of active processing options.

Where no options are indicated in the subclauses, the modifier character to be transmitted is 0. Values which are not included in the modifier values of a subclause are reserved for future use.

Check character options listed in the subclauses below indicate the basis of calculation of the check character, where a check character algorithm has been defined in the symbology specification or reference document.

4.3.1 Code 39

Code character: **A**

<i>Modifier character value</i>	<i>Option</i>
0	No check character validation nor full ASCII processing; all data transmitted as decoded
1	Modulo 43 check character validated and transmitted
3	Modulo 43 check character validated but not transmitted
4	Full ASCII character conversion performed; no check character validation
5	Full ASCII character conversion performed; modulo 43 check character validated and transmitted
7	Full ASCII character conversion performed; modulo 43 check character validated but not transmitted

4.3.2 Telepen

Code character: **B**

<i>Modifier character value</i>	<i>Option</i>
0	Full ASCII mode
1	Double density numeric only mode
2	Double density numeric followed by full ASCII
4	Full ASCII followed by double density numeric

4.3.3 Code 128

Code character: **C**

[ISO/IEC 15424:2000](https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000)
<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

<i>Modifier character value</i>	<i>Option</i>
0	Standard data packet. No FNC1 in first or second symbol character position after start character
1	EAN/UCC-128 data packet - FNC1 in first symbol character position after start character
2	FNC1 in second symbol character position after start character
4	Concatenation according to International Society for Blood Transfusion specifications has been performed; concatenated data follows

4.3.4 Channel Code

Code character: **c**

<i>Modifier character value</i>	<i>Option</i>
3	Channel 3 decoded
4	Channel 4 decoded
5	Channel 5 decoded
6	Channel 6 decoded
7	Channel 7 decoded
8	Channel 8 decoded
9	Composite format

4.3.5 Code One

Code character: **D**

<i>Modifier character value</i>	<i>Option</i>
0	No special characters in first or second symbol character position
1	FNC1 implied in first symbol character position
2	FNC1 in second symbol character position
4	Pad character in first symbol character position. The first data character in the symbol will define the escape character. When this character is a \ it indicates that the symbol contains ECI escape sequences.

4.3.6 Data Matrix

Code character: **d**

<i>Modifier character value</i>	<i>Option</i>
0	ECC 000 to ECC 140
1	ECC 200
2	ECC 200, FNC1 in first or fifth position
3	ECC 200, FNC1 in second or sixth position
4	ECC 200, ECI protocol implemented
5	ECC 200, FNC1 in first or fifth position, ECI protocol implemented
6	ECC 200, FNC1 in second or sixth position, ECI protocol implemented

4.3.7 EAN/UPC

[ISO/IEC 15424:2000](https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000)

<https://standards.iteh.ai/catalog/standards/sist/060ad8e8-9a26-4c51-80db-b4c06ec33024/iso-iec-15424-2000>

Code character: **E**

EAN/UPC symbols with supplements should be considered as two separate symbols. The first symbol is the main data packet, and the second symbol is the 2 or 5 digit supplement. These two symbols should be transmitted separately, each with its own symbology identifier. Provision is, however, made for the option of transmission of both symbols as a single data packet.

<i>Modifier character value</i>	<i>Option</i>
0	Standard data packet in full EAN format, i.e. 13 digits for EAN-13, UPC-A and UPC-E (does not include add-on data)
1	Two digit add-on data only
2	Five digit add-on data only
3	Combined data packet comprising 13 digits from EAN-13, UPC-A or UPC-E symbol and 2 or 5 digits from add-on symbol
4	EAN-8 data packet