

# ETSI EN 302 502 V1.2.1 (2008-07)

---

*Harmonized European Standard (Telecommunications series)*

**Broadband Radio Access Networks (BRAN);  
5,8 GHz fixed broadband data transmitting systems;  
Harmonized EN covering the essential requirements  
of article 3.2 of the R&TTE Directive**

---

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/52919cd3-d598-4699-93e4-523fab06cd1b/etsi-en-302-502-v1.2.1-2008-07>



---

**Reference**REN/BRAN-0060001

---

---

**Keywords**broadband, digital, HIPERMAN, multipoint

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations .....	8
3.1 Definitions.....	8
3.2 Symbols.....	9
3.3 Abbreviations .....	10
4 Technical requirements specification.....	10
4.1 Designation of centre frequencies and frequency error.....	10
4.1.1 Definition.....	10
4.1.2 Limits.....	10
4.1.3 Conformance.....	10
4.2 Transmitter RF output power, EIRP and EIRP spectral density.....	11
4.2.1 Definition.....	11
4.2.2 Limits.....	11
4.2.3 Conformance.....	11
4.3 Transmitter unwanted emissions .....	11
4.3.1 Transmitter unwanted emissions outside the 5 725 MHz to 5 875 MHz band .....	11
4.3.1.1 Definition .....	11
4.3.1.2 Limits .....	12
4.3.1.3 Conformance .....	12
4.3.2 Transmitter unwanted emissions within the 5 725 MHz to 5 875 MHz band.....	12
4.3.2.1 Definition .....	12
4.3.2.2 Limits .....	13
4.3.2.3 Conformance.....	13
4.4 Transmitter Power Control (TPC).....	13
4.4.1 Definition.....	13
4.4.2 Limit .....	13
4.4.3 Conformance.....	13
4.5 Receiver spurious emissions.....	14
4.5.1 Definition.....	14
4.5.2 Limit .....	14
4.5.3 Conformance.....	14
4.6 Dynamic Frequency Selection (DFS).....	14
4.6.1 Introduction.....	14
4.6.2 DFS Technical requirements specifications.....	15
4.6.2.1 Channel availability check and channel revalidation period .....	15
4.6.2.1.1 Definition.....	15
4.6.2.1.2 Limit .....	15
4.6.2.1.3 Conformance .....	15
4.6.2.2 In-Service Monitoring.....	15
4.6.2.2.1 Definition.....	15
4.6.2.2.2 Limit .....	15
4.6.2.2.3 Conformance .....	15
4.6.2.3 Channel Shutdown .....	16
4.6.2.3.1 Definition.....	16
4.6.2.3.2 Limit .....	16
4.6.2.3.3 Conformance .....	16
4.6.2.4 Non-Occupancy Period .....	16

4.6.2.4.1	Definition.....	16
4.6.2.4.2	Limit .....	16
4.6.2.4.3	Conformance .....	16
5	Testing for compliance with technical requirements.....	16
5.1	Conditions of Testing .....	16
5.1.1	Environmental specifications.....	16
5.1.2	Test sequences and Traffic load.....	17
5.1.2.1	General test transmission sequences .....	17
5.1.2.2	Test transmission sequences for DFS tests.....	17
5.1.3	Test frequencies .....	17
5.1.4	Presentation of Equipment.....	17
5.1.4.1	Integrated and Dedicated antennas.....	17
5.1.4.2	Testing of host connected equipment and plug-in radio devices.....	17
5.1.4.2.1	The use of a host or test jig for testing Plug-In radio devices.....	18
5.1.4.2.2	Testing of combinations .....	18
5.2	Interpretation of the measurement results .....	19
5.3	Essential radio test suites.....	19
5.3.1	Product information .....	19
5.3.2	Frequency error.....	20
5.3.2.1	Test conditions .....	20
5.3.2.2	Test methods .....	20
5.3.2.2.1	Conducted measurement.....	20
5.3.2.2.2	Radiated measurement.....	20
5.3.3	Transmitter RF Output Power, EIRP, TPC and EIRP Spectral Density .....	21
5.3.3.1	Test conditions .....	21
5.3.3.2	Test method.....	21
5.3.3.2.1	Conducted measurement.....	21
5.3.3.2.2	Radiated measurement.....	23
5.3.4	Transmitter unwanted emissions.....	23
5.3.4.1	Transmitter unwanted emissions outside the 5 725 MHz to 5 875 MHz band.....	23
5.3.4.1.1	Test conditions .....	23
5.3.4.1.2	Test method .....	24
5.3.4.2	Transmitter unwanted emissions within the 5 725 MHz to 5 875 MHz band.....	25
5.3.4.2.1	Test conditions .....	25
5.3.4.2.2	Test method .....	25
5.3.5	Receiver spurious emissions .....	26
5.3.5.1	Test conditions .....	26
5.3.5.2	Test method.....	26
5.3.5.2.1	Conducted tests.....	26
5.3.5.2.2	Radiated tests.....	26
5.3.6	Dynamic Frequency Selection (DFS) .....	27
5.3.6.1	Test conditions .....	27
5.3.6.1.1	Selection of Radar Test Signals.....	27
5.3.6.1.2	Test Set-Up.....	27
5.3.6.2	Test Method .....	28
5.3.6.2.1	Conducted measurement.....	28
5.3.6.2.2	Radiated measurement.....	32
<b>Annex A (normative):</b>	<b>HS Requirements and conformance Test specifications Table (HS-RTT).....</b>	<b>33</b>
<b>Annex B (normative):</b>	<b>Test sites and arrangements for radiated measurements.....</b>	<b>35</b>
B.1	Test sites .....	35
B.1.1	Open air test sites .....	35
B.1.2	Anechoic chamber.....	36
B.1.2.1	General.....	36
B.1.2.2	Description.....	36
B.1.2.3	Influence of parasitic reflections.....	36
B.1.2.4	Calibration and mode of use .....	37
B.2	Test antenna.....	38

B.3	Substitution antenna .....	39
<b>Annex C (normative):</b>	<b>General description of measurement .....</b>	<b>40</b>
C.1	Conducted measurements .....	40
C.2	Radiated measurements .....	40
C.3	Substitution measurement .....	41
<b>Annex D (normative):</b>	<b>DFS parameters .....</b>	<b>42</b>
<b>Annex E (informative):</b>	<b>The EN title in the official languages .....</b>	<b>45</b>
History .....		46

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/52919cd3-d598-4699-93e4-523fab06cd1b/etsi-en-302-502-v1.2.1-2008-07>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Broadband Radio Access Networks (BRAN).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [1] are given in annex A.

### National transposition dates

Date of adoption of this EN:	20 June 2008
Date of latest announcement of this EN (doa):	30 September 2008
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2009
Date of withdrawal of any conflicting National Standard (dow):	31 March 2010

---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [9].

---

# 1 Scope

The present document is applicable to radio equipment for Fixed Broadband Data Transmitting Systems intended to operate in the 5,8 GHz band (5 725 MHz to 5 875 MHz). The document is equally applicable to systems utilizing integral or dedicated antennas.

The present document is intended to cover the provisions of Directive 1999/5/EC [1] (R&TTE Directive) article 3.2, which states that: "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

---

# 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
  - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
  - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

## 2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [2] ETSI EN 300 019-1-0 (V2.1.2): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [3] ETSI TR 100 028-1 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [4] ETSI TR 100 028-2 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [5] CISPR 16-1-1 (second edition 2006-03): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus".

- [6] CISPR 16-2-1 (edition 1.1 2005-09): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 2-1: Methods of measurement of disturbances and immunity - Conducted disturbance measurements".
- [7] CISPR/TR 16-3 (second edition 2003-11): "Specification for radio disturbance and immunity measuring apparatus and methods - Part 3: CISPR technical reports".
- [8] CEPT/ECC Report 68 (Riga, June 2005): "Compatibility studies in the band 5725-5875 MHz between Fixed Wireless Access (FWA) systems and other systems".
- [9] ETSI EG 201 399 (V2.1.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [10] CEPT/ERC Recommendation 74-01: "Unwanted Emissions in the Spurious Domain" (Siófok 98, Nice 99, Sesimbra 02, Hradec Kralove 05).

## 2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Not applicable.

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [1] and the following apply:

**antenna assembly:** combination of the antenna (integral or dedicated), its coaxial cable and if applicable, its antenna connector and associated switching components

**available channel:** channel identified as usable as an *Operating Channel*

**burst:** period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

**dedicated antenna:** antenna external to the equipment, using an antenna connector with a cable or a wave-guide

NOTE: The antenna has been designed or developed for one or more specific types of equipment. It is the combination of dedicated antenna and radio equipment that is expected to be compliant with the regulations.

**environmental profile:** declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant

**in-service monitoring:** mechanism to check a channel in use by the device for the presence of a radar signal with a level above the Interference Detection Threshold

**integral antenna:** antenna designed as a fixed part of the equipment, without the use of an external connector and as such which can not be disconnected from the equipment by a user with the intend to connect another antenna

NOTE 1: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable or wave-guide can be used.

NOTE 2: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of the present document may be done separately.



**manufacturer:** manufacturer or his authorized representative established in the Community

NOTE 1: See R&TTE Directive [1], annex II.

NOTE 2: Or the person responsible for placing the apparatus on the market (R&TTE Directive [1], article 6.3).

**operating channel:** *Available Channel* on which the FWA device has started transmissions

NOTE: An *Operating Channel* becomes again an *Available Channel* if the FWA device stopped all transmissions on that channel and no radar signal was detected by the *In-Service Monitoring*.

**operating nominal RF channel width:** nominal amount of spectrum used by a single device operating on an identified centre frequency

**Transmit Power Control (TPC):** technique in which the transmitter output power is controlled resulting in reduced interference to other systems

**Transmit Power Control Range:** power range over which the TPC is able to control the transmitter output power

**Unavailable Channel:** channel which can not be considered by the FWA device for a certain period of time (*Non-Occupancy Period*) after a radar signal was detected on that channel

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

A	Measured power output (dBm)
B	Radar burst period
$Ch_f$	Channel free from radars
$Ch_r$	Channel occupied by a radar
$Ch_S$	Nominal occupied channel bandwidth
D	Measured power density
E	Field strength
$E_o$	Reference field strength
$f_c$	Carrier frequency
G	Antenna gain (dBi)
L	Radar burst length
n	Number of channels
$P_{cond}$	The conducted power level of the equipment
$P_{cond\_1}$	The maximum useable conducted power level from the equipment
$P_{cond\_2}$	The maximum conducted power level from the power range associated with the highest useable antenna assembly gain
$P_{cond\_3}$	The minimum conducted power level from the equipment
$P_{EIRP}$	The EIRP of the equipment
R	Distance
$R_o$	Reference distance
S0	Signal power
T0	Time instant
T1	Time instant
T2	Time instant
T3	Time instant
W	Radar pulse width
x	Observed duty cycle

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CW	Continuous Wave
DFS	Dynamic Frequency Selection
EIRP	Equivalent Isotropically Radiated Power
EMC	Electro-Magnetic Compatibility
ERP	Effective Radiated Power
FWA	Fixed Wireless Access
IF	Intermediate Frequencies
PD	mean Power Density EIRP
ppm	parts per million
pps	pulses per second
PRF	Pulse Repetition Frequency
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
TPC	Transmit Power Control
Tx	Transmit, Transmitter
UUT	Unit Under Test

---

## 4 Technical requirements specification

With reference to article 3.2 of Directive 1999/5/EC [1] the technical requirements in this clause have been identified as relevant to presume compliance with the essential requirements:

### 4.1 Designation of centre frequencies and frequency error

#### 4.1.1 Definition

The nominal channel centre frequencies  $f_c$ , identified by the following expression:

$$5\,725 + (n \times 2,5) \text{ MHz, where } n = 2 \text{ to } 58 \text{ for ChS} = 10 \text{ MHz;}$$

$$\text{where } n = 4 \text{ to } 56 \text{ for ChS} = 20 \text{ MHz.}$$

Frequency error is the difference between the nominal channel centre frequency and the actual channel centre frequency.

#### 4.1.2 Limits

The manufacturer shall declare the centre frequencies on which the equipment can operate. The equipment shall only operate in channels centred on any of those frequencies identified in clause 4.1.1.

The actual carrier centre frequency shall be maintained within the range  $f_c \pm 20$  ppm of the nominal channel centre frequency.

#### 4.1.3 Conformance

Conformance tests as defined in clause 5.3.2 shall be carried out.

## 4.2 Transmitter RF output power, EIRP and EIRP spectral density

### 4.2.1 Definition

The RF output power is the mean conducted power applied to the antenna assembly, during a transmission burst.

The EIRP is the maximum radiated power of the equipment relative to an isotropic antenna.

The EIRP spectral density is the mean EIRP evaluated within a specified measurement bandwidth during a transmission burst.

### 4.2.2 Limits

The mean EIRP, RF power and EIRP spectral density when configured to operate at the highest stated power level ( $P_{\text{cond}_1}$ ) shall not exceed the limits in table 1.

**Table 1: Mean RF output power, EIRP and power density limits at the highest power level**

Channel Width (MHz) ChS	Mean RF power into antenna (dBm)	mean EIRP (dBm)	Mean EIRP spectral density (dBm/MHz)
10	27	33	23
20	30	36	23

### 4.2.3 Conformance

Conformance tests as defined in clause 5.3.3 shall be carried out.

## 4.3 Transmitter unwanted emissions

Equipment that, in addition to a transmit mode, has also a standby or idle mode, shall in this mode meet the requirements defined in clause 4.5.

### 4.3.1 Transmitter unwanted emissions outside the 5 725 MHz to 5 875 MHz band

#### 4.3.1.1 Definition

These are radio frequency emissions outside the band 5 725 MHz to 5 875 MHz.

### 4.3.1.2 Limits

The level of unwanted emission shall not exceed the limits given in table 2.

**Table 2: Transmitter unwanted emission limits**

Frequency range (MHz)	Limit (dBm)	Bandwidth (kHz) (see note)
30 to 1 000	-36	100
1 000 to 5 725	-30	1 000
5 875 to 26 500	-30	1 000

NOTE: At frequencies just below 5 725 MHz or just above 5 875 MHz, account shall be taken of the spacing between the emission centre frequency and the measurement centre frequency to evaluate the appropriate reference bandwidth given in annex 2 of CEPT/ERC Recommendation 74-01 [10].

### 4.3.1.3 Conformance

Conformance tests as defined in clause 5.3.4.1 shall be carried out.

## 4.3.2 Transmitter unwanted emissions within the 5 725 MHz to 5 875 MHz band

### 4.3.2.1 Definition

These are radio frequency emissions within the band 5 725 MHz to 5 875 MHz.