

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 1: General network design**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ede64d6a-ab79-4058-bd74-3eabf784fa52/etsi-en-300-392-1-v1.4.1-2009-01>



Reference

REN/TETRA-03190

Keywords

air interface, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	12
Foreword.....	12
1 Scope	14
2 References	14
2.1 Normative references	15
2.2 Informative references.....	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions	16
3.2 Symbols.....	21
3.3 Abbreviations	22
4 Circuit mode reference points	24
5 Packet mode reference points.....	24
6 Protocol architecture for V+D	24
7 Addressing and identities	24
7.1 Introduction	24
7.2 Subscriber identities	26
7.2.1 General.....	26
7.2.2 TSI	27
7.2.3 SSI	28
7.2.4 Composition of subscriber identities	28
7.2.5 Allocation principles for subscriber identities	29
7.2.6 Use of subscriber identities.....	29
7.2.7 NSAP addresses.....	30
7.2.8 Installation of TSIs.....	30
7.3 TETRA Management Identity (TMI).....	30
7.3.1 General.....	30
7.3.2 Composition of management identities.....	31
7.3.3 Use of management identities.....	31
7.4 Network layer SAP (NSAP) addresses.....	31
7.4.1 General.....	31
7.4.2 Static binding	31
7.4.3 Dynamic binding	32
7.4.3.1 General	32
7.4.3.2 Structure and contents of NSAP addresses	32
7.4.3.3 Use of NSAP addresses.....	32
7.4.3.4 Binding of NSAP addresses	32
7.5 TETRA Equipment Identity (TEI)	32
7.5.1 General.....	32
7.5.2 Contents of TEI.....	33
7.5.3 Allocation principles for TEI.....	33
7.5.4 Use of TEI.....	33
7.6 Mobile Network Identity (MNI).....	34
7.6.1 Contents of MNI	34
7.7 Layer 2 addresses and labels	34
7.7.1 Overview	34
7.7.2 Event labelling	34
7.7.3 Scrambling labelling	34
7.7.4 Use and implementation of layer 2 addresses	35
7.7.4.1 General requirement.....	35
7.7.4.2 Implementation of event labels	35
7.7.4.3 Implementation of scrambling labels	35
7.7.5 Use of identities for V+D control channels	35

7.7.6	Labelling of packet channels	36
7.7.6.1	Use of identities for uplink data transfers	36
7.7.6.2	Use of identities for downlink data transfers.....	36
7.7.7	System information broadcast.....	37
7.7.8	Reserved value of group address for user information broadcast	37
7.8	Use of individual addresses.....	37
7.8.1	Air interface addressing functions	37
7.8.2	Address placement in primitives and PDUs	37
7.8.2.1	Use of ISSI at layer 2	37
7.8.2.2	Use of ITSI/ISSI at layer 3	39
7.8.2.2.1	Void.....	39
7.8.2.2.2	Use of ITSI/ISSI by CMCE.....	39
7.8.3	Routing principles.....	40
7.8.3.1	Routing of intra-TETRA calls (within one TETRA network)	40
7.8.3.2	Routing of inter-TETRA calls (between two TETRA networks).....	40
7.8.3.3	Routing of external calls (to/from non-TETRA networks)	41
7.8.4	Address and identity comparison.....	41
7.9	Addressing in interworking and roaming with other telecommunication networks	41
8	Circuit mode basic services.....	41
9	Mobility Management (MM) in MS	42
10	MLE mobility scenarios and functionalities.....	42
11	Technical realization of SDS.....	42
12	Void.....	42
13	Void.....	42
14	General on supplementary services	42
Annex A (informative):	Circuit mode reference points.....	43
A.1	Introduction	43
A.2	Reference configuration	43
A.2.1	Configuration examples of TETRA LMNs	44
A.3	TETRA LMN access	45
A.3.1	MS access	45
A.3.1.1	MS functional groups.....	45
A.3.1.2	MS access points and reference points	45
A.3.2	Void.....	46
A.3.3	Inter System Interface (ISI) access	46
A.3.4	Location of TETRA functionality	46
A.3.5	TETRA terminals	46
Annex B (informative):	Protocol architecture for V+D	47
B.1	Introduction	47
B.2	Mobile/base protocol architecture	47
B.2.1	Overview	47
B.2.2	Air interface layer 1.....	47
B.2.3	Air interface layer 2.....	48
B.2.3.1	Medium Access Control (MAC).....	48
B.2.3.2	Logical Link Control (LLC)	50
B.2.4	Air interface layer 3.....	50
B.2.4.1	Mobile/Base Link control Entity (MLE/BLE).....	50
B.2.4.2	Sub-Network Access Functions (SNAF)	51
B.2.4.2.1	Mobility Management (MM)	51
B.2.4.2.2	Circuit Mode Control Entity (CMCE).....	51
B.2.4.2.3	Packet data handling	52
B.2.4.2.4	TETRA packet data protocol (PDP).....	52

B.2.4.2.5	Void.....	52
B.2.5	Mobile/base protocol stack.....	52
B.3	Lower Layer Management Entity (LLME) and other layers interaction.....	53
B.3.1	General description.....	53

Annex C (informative): Overview of circuit mode basic services54

C.1	Introduction	54
C.2	Functional groupings in circuit switched mode calls	54
C.2.1	Circuit switched call control, C-plane	54
C.2.2	Circuit switched call, user data, U-plane	54
C.3	Protocols.....	54
C.3.1	TNP1	54
C.3.2	Void.....	54
C.3.3	TNP3	54
C.3.4	TNP4	55
C.3.5	AI1.....	55
C.3.6	AI2.....	55
C.3.7	TLC1	55
C.3.8	V.24T	55
C.4	Example configuration	55
C.4.1	MS to MS	55
C.4.2	Void.....	56
C.4.3	Void.....	56
C.4.4	MS to MS over ISI	56

Annex D (informative): Individual circuit mode call scenarios.....58

D.1	Introduction	58
D.2	Procedures - message trunked systems.....	58
D.2.1	Call set-up - on/off hook signalling.....	58
D.2.1.1	Call set-up - on/off hook signalling flow.....	58
D.2.1.2	Traffic channel assignment.....	59
D.2.2	Call set-up - direct set-up signalling.....	59
D.2.2.1	Call set-up - direct set-up signalling flow.....	59
D.2.2.2	Traffic channel assignment.....	60
D.2.3	Request-to-transmit	61
D.2.4	Response to request-to-transmit	62
D.2.5	Permission to transmit withdrawn	62
D.2.6	Permission to continue with withdrawn call.....	62
D.2.7	End of transmission	62
D.2.8	Stop-transmission order.....	62
D.2.9	Call clearing	63
D.2.9.1	Mobile originated.....	63
D.2.9.2	SwMI originated	64
D.3	Procedures - transmission trunked systems.....	64
D.3.1	Call set-up - on/off hook signalling.....	64
D.3.1.1	Call set-up - on/off hook signalling flow	64
D.3.1.2	Traffic assignment	65
D.3.2	Call set-up - direct set-up signalling.....	65
D.3.2.1	Call set-up - direct set-up signalling flow	65
D.3.2.2	Traffic channel assignment	66
D.3.3	Request-to-transmit	66
D.3.4	Response to request-to-transmit	67
D.3.5	Permission to transmit withdrawn	68
D.3.6	Permission to continue with withdrawn call.....	68
D.3.7	End of transmission	68
D.3.8	Stop-transmission order.....	68
D.3.9	Call clearing	68

D.3.9.1	Mobile originated.....	68
D.3.9.2	SwMI originated	69
D.4	Procedures - quasi-transmission trunked systems	70
D.4.1	Call set-up - on/off hook signalling.....	70
D.4.1.1	Call set-up - on/off hook signalling flow	70
D.4.1.2	Traffic assignment	71
D.4.2	Call set-up - direct set-up signalling.....	71
D.4.2.1	Call set-up - direct set-up signalling flow	71
D.4.2.2	Traffic assignment	72
D.4.3	Request-to-transmit	73
D.4.4	Response to request-to-transmit	74
D.4.5	Permission to transmit withdrawn	74
D.4.6	Permission to continue with withdrawn call.....	75
D.4.7	End of transmission request.....	75
D.4.8	Stop-transmission order.....	75
D.4.9	Call clearing	75
D.4.9.1	Mobile originated.....	75
D.4.9.2	SwMI originated	76

Annex E (informative): Group voice call scenarios..... **77**

E.1	Procedures for message trunked systems	77
E.1.1	General	77
E.1.2	Call set-up	78
E.1.2.1	Call set-up flow.....	78
E.1.2.2	Traffic channel assignment	79
E.1.3	Request-to-transmit	79
E.1.4	Response to request-to-transmit	80
E.1.5	Permission to transmit withdrawn	81
E.1.6	Permission to continue with withdrawn call.....	81
E.1.7	End of transmission	81
E.1.8	Stop-transmission order.....	81
E.1.9	Call clearing	82
E.1.9.1	Mobile originated.....	82
E.1.9.2	SwMI originated	82
E.2	Procedures for transmission trunked systems.....	82
E.2.1	General	82
E.2.2	Call set-up	83
E.2.2.1	Call set-up flow.....	83
E.2.2.2	Traffic channel assignment	84
E.2.3	Request-to-transmit	84
E.2.4	Response to request-to-transmit	85
E.2.5	Permission to transmit withdrawn	86
E.2.6	Permission to continue with withdrawn call.....	86
E.2.7	End of transmission	86
E.2.8	Stop-transmission order.....	86
E.2.9	Call clearing	86
E.2.9.1	Mobile originated.....	86
E.2.9.2	SwMI originated	87
E.3	Procedures for quasi-transmission trunked systems.....	87
E.3.1	General	87
E.3.2	Call set-up	88
E.3.2.1	Call set-up flow.....	88
E.3.2.2	Traffic channel assignment	89
E.3.3	Request-to-transmit	89
E.3.4	Response to request-to-transmit	90
E.3.5	Permission to transmit withdrawn	90
E.3.6	Permission to continue with withdrawn call.....	90
E.3.7	End of transmission	91
E.3.8	Stop-transmission order.....	91

E.3.9	Call clearing	91
E.3.9.1	Mobile originated.....	91
E.3.9.2	SwMI originated	92

Annex F (informative): Priority functions for circuit mode services93

F.1	Introduction	93
F.2	Priority requirements.....	93
F.2.1	Access priority.....	93
F.2.2	Call type priority	94
F.2.3	Queue priority	94
F.2.4	Pre-emptive priority	94
F.2.5	Call retention priority	94
F.2.6	Subscriber priority.....	94
F.3	Mechanisms for supporting priority	94
F.4	Supplementary service activation and invocation	95

Annex G (informative): Mobility Management (MM) in MS.....96

G.1	Introduction	96
G.2	Overview of MM relations and procedures.....	96
G.3	Stimuli of MM.....	97
G.3.1	Stimulation through TNMM-SAP	97
G.3.2	Stimulation through LMM-SAP	98
G.3.3	Stimulation through peer MM	98
G.3.4	Other stimulation.....	98
G.4	Outputs from MM	98
G.4.1	Output through TNMM-SAP	98
G.4.2	Outputs through LMM-SAP	99
G.4.3	Output to peer MM.....	99
G.5	Database requirement	99
G.6	MM procedures	99
G.6.1	Registration	99
G.6.1.1	Registration at roaming	99
G.6.1.1.1	Implicit registration	99
G.6.1.1.2	Registration area	100
G.6.1.1.3	Registration procedure	100
G.6.1.1.4	Registration with authentication.....	101
G.6.1.1.5	Registration with identity exchange	102
G.6.1.2	Registration at migration	103
G.6.1.2.1	Registration with identity exchange	103
G.6.1.2.2	Registration with authentication.....	105
G.6.1.3	Network initiated registration	106
G.6.1.4	TEI request.....	106
G.6.2	Authentication	106
G.6.2.1	Network initiated authentication.....	106
G.6.2.2	MS initiated authentication	107
G.6.3	De-registration.....	108
G.6.4	Periodic registration	108
G.6.5	Disable/enable	108
G.6.5.1	Temporary disable	108
G.6.5.2	Enable	108
G.6.5.3	Permanently disable	109
G.6.6	Energy economy mode change.....	109
G.7	Downloading of group identities	109
G.7.1	Add group identity.....	109
G.7.2	Delete group identity	110

G.7.3	Delete all group identities.....	110
G.7.4	Report group identities	111

Annex H (informative): MLE mobility scenarios and functionalities.....112

H.1	Introduction	112
H.2	Overview	112
H.3	MLE responsibilities	112
H.4	MS-MLE model	113
H.5	MLE functionalities.....	114
H.5.1	Monitoring of neighbour cells (scenario 1)	115
H.5.2	Scanning of neighbour cells (scenario 2)	115
H.5.3	MM activation of the MS-MLE (scenario 3).....	116
H.5.4	Open up MLE service (scenario 4).....	117
H.5.5	Close of MLE service (scenario 5).....	118
H.5.6	Changing to serving cell (scenario 6).....	118
H.5.7	Surveillance of the serving cell (scenario 7)	118
H.5.8	Inviting MM intervention.....	119
H.5.8.1	No service can be found (scenario 8).....	119
H.5.8.2	LA found outside RA (scenario 9).....	120
H.5.9	Set-up of MAC broadcast (SYNC + SYSINFO) (scenario 10).....	121
H.5.10	Set-up of MLE broadcast (NETWORK) (scenario 11).....	121
H.5.11	MM registering (scenario 12).....	122
H.5.12	Announce old cell and go-to-channel (scenario 13).....	122
H.5.13	Announce old cell (scenario 14).....	122
H.5.14	Announce new cell and successful restoration (scenario 15).....	123
H.5.15	Announce new cell and restoration failure (scenario 16).....	124
H.5.16	Path lost to the serving cell (scenario 17).....	124
H.6	Initial cell selection	125
H.6.1	MLE functions as viewed at the LMM SAP	125
H.6.2	MLE functions.....	125
H.7	Cell re-selection by roaming	126
H.7.1	Announced cell re-selection	126
H.7.1.1	Announced cell re-selection (type-1).....	127
H.7.1.1.1	MLE functions as viewed at the LMM SAP	127
H.7.1.1.2	MLE functions as viewed at the LCMC SAP	128
H.7.1.1.3	MLE functions	128
H.7.1.2	Announced cell re-selection (type-2).....	129
H.7.1.3	Announced cell re-selection (type-3).....	130
H.7.1.3.1	MLE functions as viewed at the LCMC SAP	130
H.7.1.3.2	MLE functions	131
H.7.2	Unannounced cell re-selection	131
H.7.3	Undeclared cell re-selection	132
H.7.3.1	MLE functions as viewed at the LMM SAP.....	132
H.8	MLE service requests during cell re-selection	132
H.8.1	Undeclared cell re-selection	133
H.9	No MLE recovery.....	133
H.10	Use of LLC.....	133
H.10.1	MS-MLE using the LLC basic link	134
H.10.1.1	Basic link and connectionless MLE service	134
H.10.1.2	Basic link and MLE connections	134
H.10.2	MS-MLE using the LLC advanced link	135
H.10.2.1	Advanced link and connectionless MLE service	135
H.10.2.2	Advanced link and MLE connection	136
Annex I (informative): Void	137	

Annex J (informative):	Technical realization of SDS and SDS-TL.....	138
J.1	Introduction	138
J.2	General	138
J.3	Internal organization of the network layer	138
J.3.1	Service model	138
J.3.2	Network model	139
J.3.2.1	Description of the functional entities	139
J.3.2.2	Description of the relationships between functional entities	142
J.3.3	Allocation of functional entities	142
J.3.3.1	Point-to-point message transfer within one SwMI.....	142
J.3.3.2	Point-to-multipoint message transfer within one SwMI	143
J.3.3.3	Point-to-point message transfer within two SwMI	143
J.3.3.4	Point-to-multipoint message transfer within two SwMI	143
J.3.3.5	Point-to-point message transfer via an outgoing gateway	144
J.3.3.6	Point-to-point message transfer via an incoming gateway.....	144
J.3.3.7	Point-to-multipoint message transfer via an outgoing gateway	144
J.3.3.8	Point-to-multipoint message transfer via an incoming gateway	144
J.4	Protocol architecture.....	145
J.4.1	MS protocol stack.....	145
J.4.2	BS protocol stack	146
J.5	Addressing.....	146
J.5.1	Uplink addressing on the air interface.....	146
J.5.2	Downlink addressing on the air interface	147
J.6	Services provided by the air interface protocol.....	147
J.7	Lower layer services used	148
J.7.1	MLE primitives used in the MS and the LS	148
Annex K (informative):	General on supplementary services.....	149
K.1	Introduction	149
K.2	General	149
K.2.1	Framework for the description of supplementary services	149
K.2.2	Alignment with the European Computer Manufacturers Association (ECMA)	149
K.2.3	Methodology	150
K.3	Supplementary service concepts	150
K.3.1	Concepts associated with supplementary services	150
K.3.1.1	Provision	150
K.3.1.2	Withdrawal	151
K.3.1.3	Activation	151
K.3.1.4	Deactivation	151
K.3.1.5	Definition	151
K.3.1.6	Registration	151
K.3.1.7	Interrogation	151
K.3.1.8	Cancellation	152
K.3.1.9	Invocation	152
K.3.1.10	Operation	152
K.3.1.11	Exceptional procedures	152
K.3.1.12	Interworking considerations.....	152
K.3.2	Supplementary service invocation order	152
K.3.3	Use of a password option in relation to supplementary services	153
K.3.3.1	Description.....	153
K.3.3.2	Management - normal procedures	153
K.3.3.2.1	Provision of password option.....	153
K.3.3.2.2	Withdrawal of the password option.....	153
K.3.3.2.3	Registration of password.....	153
K.3.3.2.4	Erasure of password	153

K.3.3.2.5	Password checking	153
K.3.3.3	Management - exceptional procedures	153
K.4	Supported supplementary services	154
K.4.1	Format of description	156

Annex L (informative): Packet mode reference points.....157

L.1	Introduction	157
L.2	Physical interfaces.....	157
L.3	Configurations.....	157
L.3.1	Basic configurations	157
L.3.2	Void.....	157
L.3.3	Interworking	157
L.4	Reference points.....	157
L.4.1	MS reference points.....	157
L.4.2	Void.....	158
L.4.3	Void.....	158
L.4.4	TETRA to TETRA reference point	158
L.4.5	TETRA to non-TETRA reference point	159
L.5	Protocol stacks.....	159
L.5.1	Protocol stacks at R1 reference point	159
L.5.2	Protocol stacks at R2 reference point	159
L.5.3	Protocol stacks at R4 reference point	160

Annex M (informative): Quality of Service (QoS).....161

M.1	Introduction	161
M.2	Quality of network service	161
M.2.1	Determination of quality of network service	161
M.2.1.1	Connection oriented quality of network service	162
M.2.1.2	Connectionless quality of network service	162
M.2.2	QoS negotiation and non-negotiation	162
M.2.3	QoS parameter set for connection oriented services.....	162
M.2.3.1	Summary.....	162
M.2.3.2	NC establishment delay	163
M.2.3.3	NC establishment failure probability	163
M.2.4	Throughput (User information transfer rate)	163
M.2.4.1	Throughput for constant delay services	163
M.2.4.2	Throughput for variable delay services.....	164
M.2.5	Transit delay	164
M.2.5.1	Transit delay for constant delay services	164
M.2.5.2	Transit delay for voice services	164
M.2.5.3	Transit delay for variable delay services.....	164
M.2.6	Residual error rate	165
M.2.7	Transfer failure probability.....	165
M.2.8	NC resilience	165
M.2.8.1	NC release delay	166
M.2.8.1.1	NC release delay at the peer user	166
M.2.8.1.2	NC release delay at the invoking user	166
M.2.8.2	NC release failure probability	166
M.2.8.3	NC protection.....	166
M.2.8.4	NC priority.....	167
M.2.9	Maximum acceptable cost	167
M.2.10	Air interface parameters	167
M.2.10.1	Duration of interruption of user traffic due to call restoration	167
M.2.10.2	Call restoration success rate.....	167
M.2.10.3	Interruption of user traffic due to slot stealing	167
M.2.11	Supplementary service parameters	168
M.2.11.1	Maximum time to activate a supplementary service	168

M.2.12	Connection oriented QoS negotiation.....	168
M.2.13	QoS parameter set for connectionless services.....	168
M.2.13.1	Summary.....	168
M.2.13.2	Transit delay	169
M.2.13.3	Protection from unauthorized access	169
M.2.13.4	Cost determinants	169
M.2.13.5	Residual error probability	169
M.2.13.6	Priority	170
M.2.13.7	Connectionless QoS negotiation.....	170
M.3	Applicability of QoS parameters to TETRA services	170
Annex N (normative):	TETRA type approval code information element.....	172
N.1	Encoding of the TAC information element	172
N.2	Application for the TAC value	172
Annex O (normative):	TETRA final assembly code information element.....	175
O.1	Encoding of the FAC information element	175
O.2	Application for the FAC value	175
O.3	WEB page contents for FAC data base	175
Annex P (normative):	TETRA electronic serial number information element.....	178
P.1	Encoding of the ESN information element	178
P.2	Usage of the ESN	178
P.3	Usage of check sum of the equipment identity.....	178
Annex Q (informative):	Change requests.....	179
History	180	

*It is a STANDARD PREVIEW
Full standard:
<https://standards.iteh.ai/catalog/4058-bd74-3eabf784fa52/etsi-en-300-392-1-v1.4.1-2009-01>*

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 1 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

EN 300 392-1: "General network design";

EN 300 392-2: "Air Interface (AI)";

EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";

ETS 300 392-4: "Gateways basic operation";

EN 300 392-5: "Peripheral Equipment Interface (PEI)";

EN 300 392-7: "Security";

EN 300 392-9: "General requirements for supplementary services";

EN 300 392-10: "Supplementary services stage 1";

EN 300 392-11: "Supplementary services stage 2";

EN 300 392-12: "Supplementary services stage 3";

ETS 300 392-13: "SDL Model of the Air Interface (AI)";

ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";

TS 100 392-16: "Network Performance Metrics";

TR 100 392-17: "TETRA V+D and DMO specifications";

TS 100 392-18: "Air interface optimized applications".

NOTE: Part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

Teh STANDART REVIEW
Full standard:
<https://standards.etsi.org/catalog/standards/sist/ede64d6a-ab79-408-be2a-3eab784fa2/etsi-en-300-392-1-v1.4.1-2009-01>

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ede64d6a-ab79-4058-bd74-3eabf784fa52/etsi-en-300-392-1-v1.4.1-2009-01>