



SLOVENSKI STANDARD

SIST EN 300 396-5 V1.3.1:2012

01-februar-2012

Prizemni snopovni radio (TETRA) - Tehnične zahteve za neposredni način delovanja (DMO) - 5. del: Radijski vmesnik prehoda

Terrestrial Trunked Radio (TETRA) - Technical requirements for Direct Mode Operation (DMO) - Part 5: Gateway air interface

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 396-5 Version 1.3.1**

SIST EN 300 396-5 V1.3.1:2012
<https://standards.iteh.ai/catalog/standards/sist/52a96dc6-2571-45de-8a14-b34ae8932de2/sist-en-300-396-5-v1-3-1-2012>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 396-5 V1.3.1:2012	en
--------------------------------------	-----------

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 396-5 V1.3.1:2012](https://standards.iteh.ai/catalog/standards/sist/32a96de8-257f-43de-8a14-b34ae8932de2/sist-en-300-396-5-v1-3-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/32a96de8-257f-43de-8a14-b34ae8932de2/sist-en-300-396-5-v1-3-1-2012>

ETSI EN 300 396-5 V1.3.1 (2011-12)



Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 5: Gateway air interface

[SIST EN 300 396-5 V1.3.1:2012](https://standards.iteh.ai/catalog/standards/sist/32a96de8-257f-43de-8a14-b34ae8932de2/sist-en-300-396-5-v1-3-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/32a96de8-257f-43de-8a14-b34ae8932de2/sist-en-300-396-5-v1-3-1-2012>

Reference

REN/TETRA-08195

Keywords

air interface, gateway, protocol, radio, TETRA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 396-5 V1.3.1:2012<https://standards.iteh.ai/catalog/standards/sist/32a96de8-257f-43de-8a14-b34ae8932022/etsi-en-300-396-v1-3-1-2012>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	15
Foreword.....	15
1 Scope	16
2 References	16
2.1 Normative references	16
2.2 Informative references.....	17
3 Definitions and abbreviations.....	17
3.1 Definitions.....	17
3.2 Abbreviations	21
4 Overview of protocol.....	22
4.1 General	22
4.2 The DM channel.....	24
4.3 DM call procedures for operation with a gateway.....	25
4.3.1 Constraints on the frame structure	26
4.3.2 Setting up a call through a DM-GATE	27
4.3.2.1 Group call from TMO to DM-MS via a DM-GATE.....	27
4.3.2.2 Group call from DM-MS via a DM-GATE.....	29
4.3.2.3 Individual call from TM-MS to DM-MS via a DM-GATE	31
4.3.2.4 Individual call from DM-MS to TM-MS via a DM-GATE	34
4.3.3 Changeover in a call via a DM-GATE.....	36
4.3.4 Pre-emption of a direct mode call through a DM-GATE.....	38
4.3.5 Short Data Service through a gateway.....	39
4.3.6 Group call from DM-MS via DM-REP/GATE.....	40
5 DM-MS layer 3 service description (for operation with a gateway).....	41
5.1 Introduction	41
5.2 Services offered at the DMCC-SAP.....	41
5.3 Description of primitives at the DMCC-SAP.....	41
5.4 Description of parameters at the DMCC-SAP.....	42
5.5 States for DMCC-SAP	43
5.6 Services offered at the DMMM-SAP	43
5.7 Description of primitives at the DMMM-SAP	43
5.7.1 DMMM-REGISTRATION primitive	44
5.7.2 DMMM-REPORT primitive.....	44
5.8 Description of parameters at the DMMM-SAP.....	44
6 DM-MS layer 3 protocol (for operation with a gateway).....	45
6.1 Introduction	45
6.1.1 DMCC protocol states	45
6.1.2 DMMM protocol states.....	45
6.1.2.1 NOT-REGISTERED.....	45
6.1.2.2 WAIT-REGISTRATION.....	46
6.1.2.3 REGISTRATION-ACCEPTED.....	46
6.1.2.4 REGISTRATION-REJECTED.....	46
6.2 Circuit mode calls.....	46
6.2.1 Procedures for outgoing call set-up through a gateway	47
6.2.1.1 Outgoing call set-up	47
6.2.1.2 Temporary group address.....	49
6.2.1.3 Layer 3 addressing in DM-GSETUP PDU.....	49
6.2.1.3.1 Called party address	49
6.2.1.3.2 Area selection.....	49
6.2.1.3.3 Calls to external subscribers.....	49
6.2.1.3.4 Calling party address	49
6.2.2 Procedures for incoming call set-up.....	49
6.2.2.1 Incoming call set-up without presence check.....	49

6.2.2.2	Incoming call set-up with presence check.....	50
6.2.2.3	Transmitting Party Number Identification (TPNI) during incoming call set-up	50
6.2.3	Usage of DM-OCCUPIED PDU	50
6.2.3.1	Sending of DM-OCCUPIED PDU by master DM-MS.....	50
6.2.3.2	Late entry by slave DM-MS.....	50
6.2.4	Procedures during occupation.....	51
6.2.4.1	Master DM-MS	51
6.2.4.2	Slave DM-MS	51
6.2.4.3	Transmitting Party Number Identification (TPNI) during occupation	53
6.2.4.3.1	Master DM-MS	53
6.2.4.3.2	Slave DM-MS.....	53
6.2.5	Procedures during reservation.....	53
6.2.5.1	Master DM-MS	53
6.2.5.2	Slave DM-MS	54
6.2.5.3	Pre-emption of short data sent as a transaction within a circuit mode call.....	54
6.2.6	Procedures to set up a new call by pre-emption.....	55
6.3	Short Data Service (SDS) procedures	55
6.3.1	Sending short data.....	56
6.3.1.1	Sending short data on a free channel.....	56
6.3.1.1.1	Sending unacknowledged short data on a free channel	56
6.3.1.1.2	Sending acknowledged short data on a free channel	56
6.3.1.2	Sending short data by pre-emption.....	56
6.3.1.3	Sending short data during circuit mode transmission.....	56
6.3.1.4	Sending short data as a transaction within a circuit mode call.....	57
6.3.1.4.1	Pre-emption to send short data as a transaction within a circuit mode call	57
6.3.1.4.2	Changeover to send short data as a transaction within a circuit mode call.....	57
6.3.1.4.3	Sending the short data as master of the circuit mode call.....	57
6.3.2	Receiving short data.....	57
6.3.2.1	Receiving unacknowledged short data.....	57
6.3.2.2	Receiving acknowledged short data.....	58
6.3.3	Additional addressing	58
6.3.3.1	DM-MS sending short data.....	58
6.3.3.2	DM-MS receiving short data.....	58
6.3.4	Extended error protection.....	58
6.3.5	SDS-TL service in DMO	58
6.3.5.1	Service primitives at the DMTL-SAP	58
6.3.5.2	DMTL-SDS primitives' parameters	59
6.3.5.3	DMTL-SDS PDUs	59
6.3.5.4	DMTL-SDS procedures	59
6.4	Procedures for mobility management.....	59
6.4.1	Solicited registration	59
6.4.2	Unsolicited registration.....	60
6.4.3	Cancellation of registration by gateway.....	60
6.4.4	Other criteria for DMMM state change	60
6.4.5	Action on entering state REGISTRATION-REJECTED.....	61
6.4.6	Layer 3 addressing in DM-GREGISTER REQUEST PDU.....	61
6.5	Usage of DMA-UNITDATA primitive.....	61
6.5.1	Sending a DMCC PDU.....	61
6.5.2	Sending a DMMM PDU	61
6.5.3	Protocol control function for delivery of received message	61
6.6	General procedures.....	62
6.6.1	Usage restriction type and validity time	62
7	DM-MS layer 2 service description (for operation with a gateway).....	62
7.1	Introduction	62
7.2	Layer 2 architecture.....	63
7.3	Service descriptions.....	63
7.3.1	Services at the DMA-SAP	63
7.3.1.1	Services provided to layer 3	63
7.3.1.2	Service primitives at the DMA-SAP	63
7.3.1.2.1	DMA-REPORT primitive.....	63
7.3.1.2.2	DMA-UNITDATA primitive	63

7.3.2	Services at the DMC-SAP	64
7.3.2.1	Services provided to layer 3	64
7.3.2.2	Service primitives at the DMC-SAP	64
7.3.2.2.1	DMC-CONFIGURE primitive	64
7.3.2.2.2	DMC-REPORT primitive	64
7.3.3	Services at the DMD-SAP	64
7.3.3.1	Services provided to the U-plane application	64
7.3.3.2	Service primitives at the DMD-SAP	64
7.4	Parameter listing	65
8	DM-MS layer 2 protocol (for operation with a gateway)	66
8.1	Introduction	66
8.1.1	Functions of lower MAC	66
8.1.2	Functions of upper MAC	66
8.2	Interface between lower and upper MAC	66
8.2.1	Logical channels defined at the DMV-SAP	66
8.2.2	Service primitives at the DMV-SAP	66
8.2.3	PDU mapping of the logical channels at the DMV-SAP	66
8.2.4	Scrambling mechanism	67
8.2.5	PDU error detection	67
8.2.6	Modes of operation	67
8.3	Basic capabilities of the physical layer	68
8.3.1	DM-MS capabilities	68
8.3.1.1	DM only and dual mode capable MS operation	68
8.3.1.2	Dual watch capable MS operation	68
8.4	Usage of DM channel with gateway	68
8.4.1	Definition of DM channel	69
8.4.1.1	DM channel arrangement	69
8.4.1.1.1	DM channel arrangement for operation with a DM-GATE	69
8.4.1.1.2	DM channel arrangement for operation with a type 1A DM-REP/GATE	69
8.4.1.1.3	DM channel arrangement for operation with a type 1B DM-REP/GATE	69
8.4.1.2	DM channel operation	70
8.4.2	DM-MAC states	70
8.4.2.1	DM-MAC state definitions	71
8.4.2.2	DM-MS channel surveillance procedures	72
8.4.2.2.1	Initial determination of DM channel state	72
8.4.2.2.1.1	Initial determination of state of carrier	72
8.4.2.2.1.2	Determination of state of one DM channel when other DM channel is busy	73
8.4.2.2.2	Fast call set-up surveillance in idle mode	73
8.4.2.2.2.1	Fast call set-up surveillance when idle on a free carrier	73
8.4.2.2.2.2	Fast call set-up surveillance when idle on a carrier that is not free	74
8.4.2.2.3	DM-MS channel surveillance at call set-up (circuit mode call or short data message)	74
8.4.2.2.4	DM-MS channel surveillance for registration outside the registration phase	74
8.4.2.3	Master DM-MS channel maintenance procedures during a call transaction	75
8.4.2.4	Slave DM-MS channel maintenance procedures during a call	76
8.4.2.4.1	Slave MS channel maintenance during call transaction	76
8.4.2.4.2	Slave MS signal quality measurement during call transaction	76
8.4.2.4.3	Slave MS channel maintenance during reservation	76
8.4.3	Criteria for changing DM-MAC states	76
8.4.3.1	Criteria for changing DM-MAC state for master DM-MS	76
8.4.3.2	Criteria for changing DM-MAC state for slave DM-MS	76
8.4.3.3	Criteria for changing DM-MAC state for idle DM-MS	77
8.4.4	DM-MS channel monitoring procedures	78
8.4.4.1	DM channel when setting up a circuit mode call through a gateway	78
8.4.4.2	DM channel when receiving a circuit mode call set-up from a gateway	79
8.4.4.3	DM channel in occupation during a circuit mode call	79
8.4.4.4	DM channel in reservation during a circuit mode call	79
8.4.4.5	DM channel in occupation during an SDS call	79
8.4.4.6	DM channel during pre-emption signalling	80
8.4.4.7	DM channel during registration phase	80
8.4.4.8	DM channel in occupation for an unsolicited registration	80
8.4.5	Transmission of layer 3 messages by DM-MAC	81

8.4.5.1	Transmission of C-plane messages by DM-MAC.....	81
8.4.5.1.1	Transmitting DM-SETUP.....	81
8.4.5.1.2	Transmitting DM-SETUP PRES.....	81
8.4.5.1.3	Transmitting DM-CONNECT.....	81
8.4.5.1.4	Transmitting DM-DISCONNECT.....	81
8.4.5.1.5	Transmitting DM-CONNECT ACK.....	81
8.4.5.1.6	Transmitting DM-RELEASE.....	82
8.4.5.1.7	Transmitting DM-OCCUPIED.....	82
8.4.5.1.8	Transmitting DM-TX CEASED.....	82
8.4.5.1.9	Transmitting DM-TX REQUEST.....	82
8.4.5.1.10	Transmitting response to DM-TX REQUEST.....	82
8.4.5.1.11	Transmitting DM-PREEMPT.....	83
8.4.5.1.12	Transmitting response to DM-PREEMPT.....	83
8.4.5.1.13	Transmitting DM-SDS UDATA and DM-SDS DATA.....	83
8.4.5.1.14	Transmitting response to DM-SDS DATA.....	83
8.4.5.1.15	Transmitting DM-INFO.....	83
8.4.5.1.16	Transmitting DM-GSETUP.....	84
8.4.5.1.17	Transmitting DM-GTX REQUEST.....	84
8.4.5.1.18	Transmitting DM-GPREEMPT.....	85
8.4.5.1.19	Transmitting DM-GREGISTER REQUEST.....	85
8.4.5.1.20	Transmitting DM-GCANCEL ACK.....	86
8.4.5.2	Transmission of U-plane messages by DM-MAC.....	86
8.4.6	Transmission of layer 2 messages generated by DM-MAC.....	86
8.4.6.1	Transmitting DM-RESERVED.....	86
8.4.6.2	Transmitting DM-SDS OCCUPIED.....	86
8.4.6.3	Transmitting DM-TIMING REQUEST.....	86
8.4.6.4	Transmitting DM-TIMING ACK.....	86
8.4.7	General DM-MAC procedures.....	87
8.4.7.1	DM-MAC repeat transmissions.....	87
8.4.7.2	DM-MAC frame countdown procedure.....	87
8.4.7.3	Use of timers.....	87
8.4.7.4	Linearization.....	87
8.4.7.5	Fragmentation.....	88
8.4.7.6	Fill bit indication.....	88
8.4.7.7	Selection of pseudo address.....	88
8.4.7.8	Slot flag indication.....	88
8.4.7.9	Requests bitmap.....	88
8.4.7.10	Dual watch operation.....	88
8.4.7.11	Air interface encryption.....	88
8.4.7.12	Channel A or B operation.....	89
8.4.7.13	Sending short data as a transaction within a circuit mode call.....	89
8.4.7.14	SDS and registration transaction time remaining.....	89
8.4.7.14.1	SDS time remaining.....	89
8.4.7.14.2	Registration transaction time remaining.....	89
8.4.7.15	Timing change procedure.....	89
8.4.7.16	Timing change at changeover or pre-emption.....	89
8.4.7.17	Modification of slot/frame numbering by gateway.....	90
8.4.7.18	Modification of channel timing by gateway.....	90
8.5	MAC procedures for transfer of signalling messages.....	90
8.5.1	Formation of MAC PDU.....	90
8.5.2	Addressing.....	91
8.5.2.1	Transmission of message.....	91
8.5.2.1.1	Addressing in synchronization burst carrying gateway-specific message.....	91
8.5.2.1.2	Addressing in synchronization burst carrying non-gateway-specific message.....	91
8.5.2.1.3	Lifetime of pseudo SSI.....	92
8.5.2.1.4	Additional elements in synchronization burst.....	93
8.5.2.1.5	Addressing in normal burst.....	93
8.5.2.2	Reception of message.....	93
8.5.2.3	Usage of MNI.....	94
8.5.3	Use of air interface encryption.....	94
8.5.4	Fragmentation and reconstruction.....	95
8.5.4.1	Fragmentation by a DM-MS.....	95

8.5.4.2	Reconstruction by a DM-MS	96
8.5.5	Fill bit addition and deletion	97
8.5.6	Transmission and reception of messages by layer 2 unacknowledged service	97
8.5.6.1	Transmission of message	98
8.5.6.2	Reception of message	99
8.5.7	Random access protocol during occupation and reservation periods	101
8.5.7.1	Introduction	101
8.5.7.2	Procedures for master DM-MS	101
8.5.7.2.1	Indicating frames available for requests	102
8.5.7.2.2	Monitoring frames available for requests	102
8.5.7.2.3	Response to pre-emption request	102
8.5.7.2.4	Response to timing change request	103
8.5.7.2.5	Response to DM-GRELEASE message	103
8.5.7.3	Procedures for requesting DM-MS	103
8.5.8	Procedures for sending messages during registration phase	105
8.5.8.1	Procedures for registering DM-MS during registration phase	105
8.5.8.1.1	Preparing for registration access	105
8.5.8.1.2	First transmission of solicited registration request	105
8.5.8.1.3	Valid access slots	105
8.5.8.1.4	Waiting for response	105
8.5.8.1.5	Subsequent transmission of request	105
8.5.8.1.6	Abandoning registration access attempt	106
8.5.8.2	Procedures for pre-empting DM-MS during registration phase	106
8.5.8.2.1	Preparing for random access	106
8.5.8.2.2	First transmission of pre-emption request	106
8.5.8.2.3	Valid slots for pre-emption	106
8.5.8.2.4	Waiting for response	106
8.5.8.2.5	Subsequent transmission of request	107
8.5.8.2.6	Abandoning random access attempt	107
8.6	MAC procedures in traffic mode	107
8.6.1	Introduction	107
8.6.2	Criteria for transmission and reception of traffic	108
8.6.3	Change of U-plane mode	108
8.6.3.1	Call set-up by DM-MS	108
8.6.3.2	Incoming call set-up	108
8.6.3.2.1	Incoming call set-up without presence check	108
8.6.3.2.2	Incoming call set-up with presence check	109
8.6.3.3	Late entry	109
8.6.3.4	End of traffic transmission	109
8.6.3.4.1	Master DM-MS	109
8.6.3.4.2	Slave DM-MS	109
8.6.4	Exchange of information at the DMD-SAP	109
8.6.5	Stealing from circuit mode capacity	109
9	Gateway layer 3 call control procedures	110
9.1	Introduction	110
9.2	Gateway call control states	110
9.2.1	Gateway TMO call control states	110
9.2.1.1	IDLE	110
9.2.1.2	MO-CALL-SETUP	110
9.2.1.3	MT-CALL-SETUP	110
9.2.1.4	CALL ACTIVE	110
9.2.1.5	CALL DISCONNECT	110
9.2.1.6	WAIT	111
9.2.2	Gateway DM call control states	111
9.2.2.1	IDLE	111
9.2.2.2	CALL SETUP NORMAL ORIGINATING	111
9.2.2.3	CALL SETUP PRES_CHECK ORIGINATING	111
9.2.2.4	CALL SETUP TERMINATING	111
9.2.2.5	PRE-EMPTION	111
9.2.2.6	CALL ACTIVE TX OCCUPATION	111
9.2.2.7	CALL ACTIVE TX RESERVATION	111

9.2.2.8	CALL ACTIVE RX OCCUPATION.....	111
9.2.2.9	WAIT RSP OCCUPATION	111
9.2.2.10	ACK'D SHORT DATA INITIATED.....	111
9.2.2.11	UNACK'D SHORT DATA INITIATED.....	111
9.3	Layer 3 circuit mode call control procedures	112
9.3.1	Incoming call set-up from TMO	112
9.3.1.1	Incoming individual call set-up from TMO	112
9.3.1.2	Incoming group call set-up from TMO	115
9.3.1.3	Sending of DM-OCCUPIED PDU by master gateway	116
9.3.2	Outgoing call set-up to TMO.....	116
9.3.2.1	Outgoing call to TMO set-up procedures.....	116
9.3.2.2	Colliding call set-up signalling over the TMO air interface (Um).....	119
9.3.2.3	Unsuccessful call set-up to TMO	119
9.3.3	Call maintenance procedures	119
9.3.3.1	End of transmission.....	119
9.3.3.1.1	Reception of DM-TX CEASED PDU from current master DM-MS	119
9.3.3.1.2	Reception of D-TX CEASED PDU from TMO	120
9.3.3.1.3	Gateway initiated DM-TX CEASED	120
9.3.3.2	Reception of D-TX INTERRUPT from TMO	120
9.3.3.3	Incoming TMO transmission during DM channel reservation.....	121
9.3.3.4	Reception of a DM request to transmit during DM channel reservation.....	121
9.3.3.4.1	Response to valid DM-GTX REQUEST (or DM-GPREEMPT) PDU.....	121
9.3.3.4.2	Response to valid DM-TX REQUEST (or DM-PREEMPT) PDU	123
9.3.3.5	TMO permission to transmit withdrawn during a call	124
9.3.3.6	TMO permission to continue with withdrawn call.....	124
9.3.3.7	SwMI initiated call continuation.....	125
9.3.3.8	Call modification.....	125
9.3.3.8.1	DM-MS initiated call modification	125
9.3.3.8.2	SwMI initiated call modification	125
9.3.3.9	Call disconnection.....	126
9.3.3.9.1	Reception of DM-RELEASE from current master DM-MS (or call lost).....	126
9.3.3.9.2	Call disconnection by SwMI.....	126
9.3.3.9.3	Expiry of call length timer.....	127
9.3.3.10	TMO call restoration.....	127
9.3.3.11	Unsolicited D-TX GRANTED PDU.....	127
9.3.3.12	Extension and end of reservation period	128
9.3.4	Gateway pre-emption procedures	128
9.3.4.1	DM-MS pre-emption of a gateway operating as master.....	128
9.3.4.1.1	New call pre-emption during call set-up	129
9.3.4.1.2	New call pre-emption during DM channel occupation.....	129
9.3.4.1.3	New call pre-emption during DM channel reservation.....	129
9.3.4.1.4	DM-MS pre-emption during DM channel occupation to continue existing call.....	130
9.3.4.1.5	DM-MS pre-emption during DM channel occupation to send short data within ongoing call	131
9.3.4.2	Pre-emption procedures during gateway slave operation.....	132
9.3.4.2.1	Transmission interrupt from TMO	132
9.3.4.2.2	Pre-emption initiated by gateway during an ongoing call	133
9.3.4.2.3	New call pre-emption by gateway	134
9.3.4.2.4	Pre-emption by another DM-MS	134
9.3.4.3	Pre-emption procedure when gateway idle	135
9.4	Layer 3 short data service procedures	135
9.4.1	Incoming SDS message from TMO.....	135
9.4.1.1	Transmission of short data message from TMO using DM unacknowledged service	135
9.4.1.2	Transmission of short data message from TMO using DM acknowledged service	136
9.4.1.3	Pre-emption of DM unacknowledged or acknowledged SDS transaction	137
9.4.1.4	Transmission of short data message from TMO during DM channel occupation.....	137
9.4.1.5	Transmission of short data message from TMO during DM channel reservation.....	138
9.4.2	Outgoing DM SDS message to TMO	138
9.4.2.1	Reception of outgoing SDS message on DM channel.....	138
9.4.2.1.1	Reception of outgoing unacknowledged SDS message on DM channel	138
9.4.2.1.2	Reception of outgoing acknowledged SDS message on DM channel	138
9.4.2.2	Reception of DM short data sent within ongoing call	139
9.4.3	SDS-TL Service.....	139

9.5	Addressing methods on TMO air interface	140
9.5.1	Receiving group call from TMO.....	140
9.5.2	Receiving individual call from TMO.....	140
9.5.3	Call set-up to TMO.....	140
9.6	Information element mapping between TM and DM PDUs.....	141
9.6.1	TMO communication type – DMO call type flag mapping	141
9.6.2	TMO call priority – DMO priority mapping.....	141
9.6.3	TMO short data type identifier – DMO short data type identifier mapping	141
9.6.4	TMO TX demand priority – DMO priority level mapping	142
10	Gateway layer 3 mobility management procedures	142
10.1	Introduction	142
10.2	Gateway MM states	142
10.2.1	MM protocol states – TMO	142
10.2.2	MM protocol states – DM.....	142
10.2.2.1	REGISTRATIONS SOLICITED.....	142
10.2.2.2	REGISTRATIONS NOT PERMITTED	142
10.2.2.3	REGISTRATIONS PERMITTED	142
10.3	Gateway MM procedures	142
10.3.1	Gateway registration to SwMI.....	142
10.3.2	Gateway MM procedures on DM	143
10.3.3	Receiving DM registration requests.....	144
10.3.3.1	Solicited registration requests	144
10.3.3.2	Unsolicited registration requests	144
10.3.4	Registration cancellation.....	145
10.3.5	Procedures for U-MM STATUS and D-MM STATUS.....	145
10.3.5.1	Procedures for sending U-MM STATUS.....	145
10.3.5.2	Procedures for receiving D-MM STATUS.....	146
11	Gateway U-plane converter..... (standards.iteh.ai)	146
11.1	Introduction	146
11.2	Start of call transaction.....	147
11.2.1	Call transaction from DMO to TMO	147
11.2.2	Call transaction from TMO to DMO	147
11.3	U-plane conversion during call transaction.....	147
11.3.1	U-plane conversion from DMO to TMO	147
11.3.2	U-plane conversion from TMO to DM.....	148
11.4	Stopping transmission/reception	149
11.4.1	Call transaction from DMO to TMO	149
11.4.2	Call transaction from TMO to DMO	149
12	Gateway DM layer 2 service description	149
12.1	Introduction	149
12.2	Gateway DM layer 2 architecture.....	149
12.2.1	Lower layer management in layer 2.....	150
12.3	Service descriptions.....	150
12.3.1	Services at the GMA-SAP	150
12.3.1.1	Services provided to layer 3.....	150
12.3.1.1.1	Protocol control function for delivery of received message	150
12.3.1.2	Service primitives at the GMA-SAP	150
12.3.1.2.1	GMA-REPORT primitive.....	150
12.3.1.2.2	GMA-UNITDATA primitive	150
12.3.2	Services at the GMC-SAP	151
12.3.2.1	Services provided to layer 3.....	151
12.3.2.2	Service primitives at the GMC-SAP	151
12.3.2.2.1	GMC-CONFIGURE primitive	151
12.3.2.2.2	GMC-REPORT primitive.....	151
12.3.3	Services at the GMD-SAP	151
12.3.3.1	Services provided to the U-plane converter	151
12.3.3.2	Service primitives at the GMD-SAP.....	151
12.3.3.2.1	GMD-REPORT primitive.....	151
12.3.3.2.2	GMD-UNITDATA primitive	152
12.4	Parameter listing.....	152

13	Gateway DM layer 2 protocol.....	153
13.1	Introduction.....	153
13.1.1	Functions of lower MAC.....	153
13.1.2	Functions of upper MAC.....	153
13.2	Interface between lower and upper MAC.....	154
13.3	Basic capabilities of the gateway physical layer.....	155
13.3.1	DM-GATE capabilities.....	155
13.3.2	Type 1A DM-REP/GATE capabilities.....	155
13.3.2.1	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM downlink carrier.....	156
13.3.2.2	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM uplink carrier.....	156
13.3.2.3	Type 1A DM-REP/GATE: DM RF carrier not in either TMO sub-band.....	156
13.3.3	Type 1B DM-REP/GATE capabilities.....	157
13.3.3.1	Type 1B DM-REP/GATE: frequency usage method 1.....	157
13.3.3.2	Type 1B DM-REP/GATE: frequency usage method 2.....	158
13.4	Usage of DM channel.....	158
13.4.1	Gateway operation.....	158
13.4.1.1	DM-GATE operation.....	159
13.4.1.2	DM-REP/GATE operation.....	159
13.4.1.2.1	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM downlink carrier.....	160
13.4.1.2.2	Type 1A DM-REP/GATE: DM RF carrier in same sub-band as TM uplink carrier.....	160
13.4.1.2.3	Type 1A DM-REP/GATE (if DM RF carrier not in TMO sub-band) or type 1B DM-REP/GATE with frequency usage method 1.....	161
13.4.1.2.4	Type 1B DM-REP/GATE with frequency usage method 2.....	161
13.4.2	Gateway DM-MAC states.....	162
13.4.2.1	Gateway DM-MAC state definitions.....	162
13.4.2.2	Gateway channel surveillance procedures.....	164
13.4.2.2.1	Channel surveillance when idle on a channel in unknown or free state (i.e. in state 0 or 1).....	164
13.4.2.2.2	Channel surveillance when idle on a busy channel (i.e. in state 2, 3 or 4).....	165
13.4.2.2.3	Channel surveillance when idle at DM-MS call set-up.....	165
13.4.2.2.4	Channel surveillance before call set-up by gateway (circuit mode call or short data).....	166
13.4.2.2.5	Channel surveillance before registration phase.....	167
13.4.2.2.6	Channel surveillance before registration cancellation.....	168
13.4.2.3	Master gateway channel maintenance during a call.....	168
13.4.2.4	Slave gateway channel maintenance during a call.....	168
13.4.3	Criteria for changing gateway state.....	169
13.4.3.1	Criteria for changing DM-MAC state for master gateway.....	169
13.4.3.2	Criteria for changing DM-MAC state for slave gateway.....	169
13.4.3.3	Criteria for changing DM-MAC state for idle gateway.....	170
13.4.4	Gateway channel monitoring procedures.....	172
13.4.4.1	DM channel during reception of fragmented DM-GSETUP message.....	172
13.4.4.2	DM channel during call set-up with presence check.....	172
13.4.4.3	DM channel in reservation during circuit mode call set-up.....	172
13.4.4.4	DM channel following circuit mode connection by gateway.....	173
13.4.4.5	Gateway as master in circuit mode occupation.....	173
13.4.4.6	Gateway as slave in circuit mode occupation.....	173
13.4.4.7	DM channel in reservation during a circuit mode call.....	173
13.4.4.8	Gateway as master in SDS occupation.....	173
13.4.4.9	Gateway as slave in SDS occupation.....	174
13.4.4.10	DM channel following pre-emption or changeover acceptance by gateway.....	174
13.4.4.11	DM channel following pre-emption acceptance by a master DM-MS.....	175
13.4.4.12	DM channel following pre-emption request generated by gateway.....	175
13.4.4.13	Gateway as master in registration phase.....	175
13.4.4.14	Gateway as master during registration cancellation.....	175
13.4.5	Transmission of layer 3 messages by layer 2.....	176
13.4.5.1	Transmission of C-plane messages by layer 2.....	176
13.4.5.1.1	Transmitting DM-SETUP and DM-SETUP PRES.....	176
13.4.5.1.2	Transmitting DM-CONNECT ACK.....	177
13.4.5.1.3	Transmitting DM-RELEASE.....	177
13.4.5.1.4	Transmitting DM-OCCUPIED.....	177
13.4.5.1.5	Transmitting DM-TX CEASED.....	178
13.4.5.1.6	Transmitting response to DM-TX REQUEST.....	179
13.4.5.1.7	Transmitting DM-PREEMPT.....	179

13.4.5.1.8	Transmitting response to DM-PREEMPT	180
13.4.5.1.9	Transmitting DM-SDS UDATA and DM-SDS DATA	180
13.4.5.1.10	Transmitting response to DM-SDS DATA	181
13.4.5.1.11	Transmitting DM-INFO	181
13.4.5.1.12	Transmitting response to DM-GSETUP	182
13.4.5.1.13	Transmitting response to DM-GTX REQUEST	182
13.4.5.1.14	Transmitting response to DM-GPREEMPT	183
13.4.5.1.15	Transmitting DM-GRELEASE	183
13.4.5.1.16	Transmitting response to registration request	184
13.4.5.1.17	Transmitting registration cancellation	184
13.4.5.2	Transmission of U-plane messages by layer 2	184
13.4.6	Transmission of layer 2 messages	184
13.4.6.1	Layer 2 messages sent in DMAC-SYNC PDU	184
13.4.6.1.1	Transmitting DM-RESERVED	185
13.4.6.1.2	Transmitting DM-SDS OCCUPIED	185
13.4.6.1.3	Transmitting DM-TIMING ACK	186
13.4.6.2	Gateway presence signal	186
13.4.6.2.1	Channel free	186
13.4.6.2.2	Channel in occupation	187
13.4.6.2.3	Channel in reservation	188
13.4.6.2.4	Channel in registration phase	188
13.4.7	General layer 2 procedures	188
13.4.7.1	Repeat transmissions	188
13.4.7.2	Frame countdown procedure	188
13.4.7.3	Use of timers	188
13.4.7.4	Linearization	188
13.4.7.5	Fragmentation	189
13.4.7.6	Fill bit indication	189
13.4.7.7	Use of pseudo address	189
13.4.7.8	Slot flag indication	189
13.4.7.9	Requests bitmap	190
13.4.7.10	Receiving the TM channel	190
13.4.7.11	Air interface encryption	190
13.4.7.12	Channel A or B operation	190
13.4.7.13	Sending short data as a transaction within a circuit mode call	190
13.4.7.14	SDS and registration transaction time remaining	190
13.4.7.14.1	SDS time remaining	190
13.4.7.14.2	Registration transaction time remaining	191
13.4.7.15	Modification of slot/frame numbering by gateway	191
13.4.7.16	Modification of channel timing by gateway	191
13.4.8	DM-REP/GATE procedures for DM re-transmission of DM signalling messages	192
13.4.8.1	DM re-transmission of master DM-MS signalling messages received in a DSB	192
13.4.8.1.1	General procedures	192
13.4.8.1.2	Re-transmission of DM-SETUP message	193
13.4.8.1.3	Re-transmission of DM-SDS DATA or DM-SDS UDATA message	194
13.4.8.1.4	Re-transmission of unsolicited DM-GREGISTER REQUEST	194
13.4.8.1.5	Re-transmission of other messages in a DSB when not using multi-slot regeneration	195
13.4.8.1.6	Re-transmission of other messages in a DSB during traffic transmission with multi-slot regeneration	195
13.4.8.2	DM re-transmission of master DM-MS signalling messages received in a DNB	195
13.4.8.2.1	Call transaction without multi-slot regeneration	195
13.4.8.2.2	Call transaction with multi-slot regeneration	196
13.4.8.3	Regeneration of missing repetitions on the slave link	196
13.4.8.4	DM re-transmission of messages received from a slave DM-MS	197
13.5	Layer 2 procedures for transfer of signalling messages	197
13.5.1	Formation of MAC PDU	197
13.5.2	Addressing	198
13.5.2.1	Transmission of message	198
13.5.2.1.1	Addressing in synchronization burst carrying gateway-specific message	198
13.5.2.1.2	Addressing in synchronization burst carrying non-gateway-specific message	198
13.5.2.1.3	Gateway pseudo SSI	199
13.5.2.1.4	Additional elements in synchronization burst	199

13.5.2.1.5	Addressing in normal burst.....	199
13.5.2.2	Reception of message.....	200
13.5.2.3	Usage of MNI.....	200
13.5.3	Use of air interface encryption.....	200
13.5.4	Fragmentation and reconstruction.....	201
13.5.4.1	Fragmentation by a gateway	201
13.5.4.2	Reconstruction by a gateway.....	201
13.5.4.2.1	Reconstruction by a DM-GATE.....	201
13.5.4.2.2	Reconstruction of master link message by DM-REP/GATE.....	201
13.5.4.2.3	Reconstruction of slave link message by DM-REP/GATE	202
13.5.5	Fill bit addition and deletion	202
13.5.6	Transmission and reception of messages by layer 2 unacknowledged service	202
13.5.6.1	Transmission of message	203
13.5.6.2	Reception of message.....	203
13.5.7	Random access protocol during occupation and reservation periods.....	205
13.5.7.1	Introduction.....	205
13.5.7.2	Procedures for master gateway	205
13.5.7.2.1	Indicating frames available for requests	205
13.5.7.2.2	Monitoring frames available for requests	206
13.5.7.2.3	Response to pre-emption or changeover request	206
13.5.7.3	Procedures for requesting slave gateway	208
13.5.7.3.1	Transmission of message by requesting slave gateway	208
13.5.7.3.2	Looking for response	208
13.5.7.3.3	Abandoning transmission attempt	209
13.5.8	Procedures in registration phase	209
13.5.8.1	Start of registration phase.....	209
13.5.8.2	Receiving registration requests	209
13.5.8.3	Sending response.....	209
13.5.8.4	Maintenance of registration phase	210
13.5.8.5	Termination of registration phase	210
13.6	Gateway procedures in traffic mode.....	210
13.6.1	Introduction.....	210
13.6.2	Criteria for transmission and reception of traffic.....	211
13.6.3	Change of U-plane mode.....	211
13.6.3.1	Call transaction from DMO to TMO.....	211
13.6.3.2	Call transaction from TMO to DMO.....	212
13.6.3.2.1	Call set-up without presence check	212
13.6.3.2.2	Call set-up with presence check	212
13.6.3.3	End of traffic transmission	212
13.6.3.3.1	Call transaction from DMO to TMO.....	212
13.6.3.3.2	Call transaction from TMO to DMO.....	212
13.6.4	Exchange of information at the GMD-SAP.....	213
13.6.4.1	Interface at gateway transmitting traffic on DMO side.....	214
13.6.4.2	Interface at gateway receiving traffic on DMO side	214
13.6.5	Stealing from circuit mode capacity	215
13.6.5.1	Transmission on STCH	215
13.6.5.2	Criteria for C-plane stealing.....	215
13.6.5.3	Reception on STCH	216
13.6.6	DM-REP/GATE procedures for DM re-transmission of DM U-plane traffic	216
13.6.6.1	Call transaction without multi-slot regeneration	216
13.6.6.2	Call transaction with multi-slot regeneration	216
14	DM PDU descriptions	217
14.1	Layer 2 PDUs sent in DSB.....	217
14.1.1	DMAC-SYNC PDU	217
14.1.2	DPRES-SYNC PDU	218
14.2	Layer 2 PDUs sent in DNB	220
14.3	Layer 2 information element coding	221
14.3.1	Addressing for URT = 0010 ₂ or 1000 ₂	221
14.3.2	Addressing for URT = 0011 ₂ or 1001 ₂	221
14.3.3	Addressing for URT = 0100 ₂ or 0101 ₂	221
14.3.4	Addressing for URT = 0110 ₂	221

14.3.4A	Addressing for URT = 1010 ₂	222
14.3.4B	Addressing for URT = 1011 ₂	222
14.3.5	Channel state	222
14.3.6	Channel usage	222
14.3.7	DM-REP function flag	222
14.3.8	Not used	223
14.3.9	Maximum DM-MS power class	223
14.3.10	M-DMO flag	224
14.3.11	MNI of SwMI	224
14.3.12	Number of validity time units	224
14.3.13	Registration access parameter	224
14.3.14	Registration label	225
14.3.14A	Registration phase terminated flag	225
14.3.15	Registration phase time remaining	225
14.3.16	Registrations forwarded flag	226
14.3.17	Registrations permitted	226
14.3.18	Repeater operating modes	226
14.3.19	Spacing of uplink	226
14.3.19A	System wide services not available	227
14.3.20	SwMI availability flag	227
14.3.21	Timing for DM-REP function	228
14.3.22	Two-frequency repeater flag	228
14.3.23	Usage restriction type (URT)	228
14.3.24	Validity time unit	229
14.3.25	Value of DT264	229
14.3.26	Values of DN232 and DN233	229
14.4	Messages generated by layer 2	230
14.5	Layer 3 PDUs	230
14.5.1	DM-GSETUP	231
14.5.2	DM-GCONNECT	231
14.5.3	DM-GACK	232
14.5.4	DM-GRELEASE	232
14.5.5	DM-GTX REQUEST	233
14.5.6	DM-GTX ACCEPT	233
14.5.7	DM-GPREEMPT	234
14.5.8	DM-GPRE ACCEPT	234
14.5.9	DM-GREJECT	235
14.5.10	DM-GREGISTER REQUEST	235
14.5.11	DM-GREGISTER ACCEPT	236
14.5.12	DM-GREGISTER REJECT	236
14.5.13	DM-GREGISTER CANCEL	237
14.5.14	DM-GCANCEL ACK	237
14.6	Message dependent elements coding	238
14.6.1	Gateway message subtype	239
14.6.2	Registration transaction time remaining	239
14.6.3	Reservation announced	239
14.6.4	Type of DM-GTX REQUEST	240
14.6.5	Type of registration request	240
14.7	DM-SDU elements coding	240
14.7.1	Area selection	242
14.7.2	Called party address type flag	242
14.7.3	Called party MNI	242
14.7.4	Called party SSI	242
14.7.5	Calling party TSI flag	242
14.7.6	External subscriber number	243
14.7.7	Gateway reject cause	243
14.7.8	Gateway release cause	243
14.7.9	Registration label	244
14.7.10	Registration reject cause	244
14.7.11	Request label	244
14.7.12	Serviced GSSI	244
14.7.13	Serviced GSSI flag	244