

INTERNATIONAL STANDARD

IEC
60335-2-31

1995

AMENDMENT 1

1998-10

Amendment 1

**Safety of household and similar electrical
appliances**

**Part 2-31:
Particular requirements for range hoods**

Amendment 1

Sécurité des appareils électrodomestiques et analogues

Partie 2-31: 60335-2-31:1995/AMD1:1998

Règles particulières pour les hottes de cuisine 0335-2-31-1995-amd1-1998

© IEC 1998 Droits de reproduction réservés — Copyright - all rights reserved

International Electrotechnical Commission
Telefax: +41 22 919 0300

3, rue de Varembé Geneva, Switzerland
e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CODE PRIX
PRICE CODE

B

*Pour prix, voir catalogue en vigueur
For price, see current catalogue*

FOREWORD

This amendment has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61/1464/FDIS	61/1517/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

7 Marking and instructions

7.12.1 Replace the second dashed item by the following:

- the minimum distance between the supporting surface for the cooking vessels on the hob and the lowest part of the range hood. When the range hood is located above a gas appliance, this distance shall be at least 65 cm. If the instructions for installation for the gas hob specify a greater distance, this has to be taken into account.

30 Resistance to heat, fire and tracking

<https://standards.iteh.ai/catalog/standards/iec60335-2-31-1995-amd1-1998>

Add:

30.1 Addition:

The ball pressure test is carried out on the exposed parts of the underside of the range hood at a temperature of at least 105 °C.