

SLOVENSKI STANDARD SIST TBR 012 E1:2004/A1:2004

01-oktober-2004

Dcg`cjbY`hY`Y_caib]_UW]YY`f6H7½!'HY\b]bY`nU\hYjY`nU'nU[chUj`1Ub^Y`cXdfhcgh] cafYÿ]^!'8][]hUb]`nU_id`^Yb]`jcX]`nU'dfYbcgbc`\]hfcgh'&`\$(,`_V]h#g`]b`nU bYghfi_hif]fUbY`g][bUY`f8&\$(,I½!`Df]_`1]hjYbY`nU\hYjY`nU`jaYgb]_`hYfa]bU`g_Y cdfYaY

Business TeleCommunications (BTC); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U); Attachment requirements for terminal equipment interface

(standards.iteh.ai)

SIST TBR 012 E1:2004/A1:2004 https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-204d76abdct3/sist-tbr-012-e1-2004-a1-2004

Ta slovenski standard je istoveten z: TBR 012/A1 Edition 1

ICS:

33.040.50 Vodi, zveze in tokokrogi

Lines, connections and circuits

SIST TBR 012 E1:2004/A1:2004

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 012 E1:2004/A1:2004 https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-204d76abdcf3/sist-tbr-012-e1-2004-a1-2004 SIST TBR 012 E1:2004/A1:2004



Amendment

TBR 12

A1

January 1996

Source: ETSI TC-BTC

Reference: RTBR/BTC-02065

ICS: 33.120

*

Key words: ONP, leased lines, D2048U

This amendment A1 modifies the Technical Basis for Regulation TBR 12 (1993)

iTeh STANDARD PREVIEW

Business TeleCommunications (BTC); Open Network Provision (ONP) technical requirements; 2 048 kbit/s digital unstructured leased line (D2048U); Attachment requirements for terminal equipment interface

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE **Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE **X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

Page 2 TBR 012: December 1993/A1: January 1996

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST TBR 012 E1:2004/A1:2004</u> https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-204d76abdcf3/sist-tbr-012-e1-2004-a1-2004

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

Foreword

This amendment to TBR 12 (1993) has been produced by the Business TeleCommunications (BTC) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This amendment changes TBR 12 (1993) as described below:

The connector type specified, conforming to ISO/IEC 10173 (1991), cannot be manufactured. Since a standardized connector is not available, the terminal equipment is required to provide either a point for connection of solid conductors, or solid conductors themselves. In order to allow connection to be made using other methods, the TE is permitted to be supplied with other connection schemes (e.g. connectors).

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST TBR 012 E1:2004/A1:2004</u> https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-204d76abdcf3/sist-tbr-012-e1-2004-a1-2004

Page 4 TBR 012: December 1993/A1: January 1996

Amendments

Page 7, amendment to clause 2

Delete reference [3].

Page 8, amendment to subclause 5.1

Replace subclause 5.1 with subclauses 5.1, 5.1.1 and 5.1.2 as given below:

"5.1 Physical characteristics


Justification: Without a connection method defined, it is impossible for the terminal equipment to connect to the network, therefore this is required for the terminal equipment to interwork with the network (article 4f).

Currently no standardized connector is readily available. Consequently, the only method of connection that can be specified in this TBR is the use of solid conductors of 0,4 to 0,6 mm. This TBR requires the TE to be capable of presenting either a point for the attachment of unterminated solid conductors, or solid conductors themselves (see subclause 5.1.1). It is a requirement that such a connection method be available to be provided for use with the TE if necessary.

In order to allow connection to be made using other methods (e.g. connectors), the TE is permitted to be supplied with a connection method suitable for use with those methods (see subclause 5.1.2).

- NOTE 1: The following are examples of arrangements that comply with the requirements. The list below should not be regarded as an exhaustive list of all permitted arrangements:
 - a) a cord, permanently connected to the terminal equipment at one end and unterminated at the other end, with wires that are solid conductors with diameters in the range 0,4 to 0,6 mm;
 - b) a cord, connected via a plug and socket to the terminal equipment at one end and unterminated at the other end, with wires that are solid conductors with diameters in the range 0,4 to 0,6 mm;
 - c) an insulation displacement connector, designed to accept wires with solid conductors with diameters in the range 0,4 to 0,6 mm, but with no cord;
 - d) a screw connector, designed to accept wires with solid conductors with diameters in the range 0,4 to 0,6 mm, but with no cord;
 - e) the arrangement in b) plus one or more additional alternative cords with the same plug or socket arrangement at the terminal end and any plug or socket at the other end;
 - f) the arrangement in c) or d) plus one or more cords suitable for connection to the terminal equipment at one end and any plug or socket at the other end.

The transmit pair is the output from the terminal equipment interface. The receive pair is the input to the terminal equipment interface, as shown in figure 1. Where the terms "output" and "input" are used without qualification in this TBR, they refer to the terminal equipment interface.





NOTE 2: The use of a shielded cord or cable may be necessary to meet radiation and immunity requirements defined in Electro-Magnetic Compatibility (EMC) standards.

5.1.1 Hardwired connection

Requirement: The terminal equipment shall provide:

- a) a set of connection contacts (e.g. an insulation displacement connector or a screw terminal block) to which solid wire conductors with diameters in the range 0,4 to 0,6 mm may be connected; or
- b) a wiring arrangement connected by any means to the terminal equipment, with unterminated solid wire conductors with diameters in the range 0,4 to 0,6 mm at the end distant from the terminal equipment.

Test: There is no test. All subsequent tests are carried out via the specified connection method.

5.1.2 Alternative means of connection

Any alternative means of connection may be provided in addition to the connection arrangements under subclause 5.1.1.

Page 14, amendment to subclause A.1.1, first paragraph

Delete the first sentence:

"The tests shall normally be applied at the plug for connection to the NTP."

and replace with: iTeh STANDARD PREVIEW

"The tests in this TBR shall be carried out using the connection method suitable for use with unterminated solid conductors as defined in subclause 5.1.1.".

Page 14, amendment to subclause A 1.1, note 1/2004/A1:2004

https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-

Delete "the normal plug and cord" and replace with "additional wiring".

Delete "5.1" and replace with "5.1.2".

Page 6 TBR 012: December 1993/A1: January 1996

History

Document history			
December 1993	First Edition		
June 1995	Unified Approval Procedure	UAP 30:	1995-06-05 to 1995-09-29
January 1996	Amendment 1 to 1st Edition		

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST TBR 012 E1:2004/A1:2004 https://standards.iteh.ai/catalog/standards/sist/c6fcf709-6e83-4ca2-bb85-204d76abdcf3/sist-tbr-012-e1-2004-a1-2004

ISBN 2-7437-0306-7 - Amendement 1 Dépôt légal : Janvier 1996