INTERNATIONAL STANDARD

ISO 13715

Second edition
2000-06-15

Technical drawings — Edges of undefined shape — Vocabulary and indications

Dessins techniques — Arêtes de forme non définie — Vocabulaire et indications sur les dessins

Reference number
ISO 13715:2000(E)

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 13715 was prepared by Technical Committee ISO/TC 10, *Technical drawings, product definition and related documentation*, Subcommittee SC 6, *Mechanical engineering documentation*.

This second edition cancels and replaces the first edition (ISO 13715:1994), which has been technically revised.

Annex A forms a normative part of this International Standard. Annexes B and C are for information only.

Introduction

In technical drawings, the ideal geometric shape is represented without any deviation and, in general, without consideration of the states of the edges. Nevertheless, for many purposes (the functioning of a part, or out of safety considerations, for example) particular states of edges need to be indicated. Such states include those of external edges free from burr, sharp edges or those with a burr of limited size, and internal edges with a passing. In principle, all the edges of a part should be produced in their requisite states. In practice, unless those states are specified in the technical drawing or related documentation, the part will be delivered direct from the machine without the required treatment.

This International Standard is aimed at enabling this situation to be avoided, through specification of guidelines for the indication and graphic representation of the states of edges in technical drawings.

Technical drawings — Edges of undefined shape — Vocabulary and indications

1 Scope

This International Standard defines the terms defining the states of edges and specifies rules for representing states of edges of undefined shape in technical drawings.

The proportions and dimensions of the graphical symbols to be used are also specified.

In cases where the geometrically defined shape of an edge ($1 \times 45°$, for example) is required, the general dimensioning principles given in ISO 129-1 apply.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 128-20, *Technical drawings — General principles of presentation — Part 20: Basic conventions for lines.*

ISO 128-22, *Technical drawings — General principles of presentation — Part 22: Basic conventions and applications for leader lines and reference lines.*

ISO 129-1—[1)], *Technical drawings — Indication of dimensions and tolerances — Part 1: General principles.*

ISO 3098-0:1997, *Technical product documentation — Lettering — Part 0: General requirements.*

ISO 81714-1:1999, *Design of graphical symbols for use in the technical documentation of products — Part 1: Basic rules*.

3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

3.1
edge
intersection of two surfaces

NOTE See annex C for further information.

1) To be published. (Partial revision of ISO 129:1985)

3.2
state of an edge
geometrical shape and size of an edge

3.3
edge of undefined shape
edge with a shape that is not specified precisely

3.4
sharp edge
external or internal edge of a part with almost zero deviation from the ideal geometrical shape

NOTE Examples are presented in Figures 1 and 2.

3.5
burr
rough remainder of material outside the ideal geometrical shape of an external edge, residue of machining or of a forming process

NOTE Examples are presented in Figures 1 and 3.

3.6
undercut
deviation inside the ideal geometrical shape of an internal edge

NOTE Examples are presented in Figures 1, 2, 4 and 5.

3.7
passing
deviation outside the ideal geometrical shape of an internal edge

NOTE Examples are presented in Figures 2 and 6.



Key

1 Size of undercut
2 Size of sharp edge
3 Size of burr

Figure 1 — States of an external edge



Key

1 Size of undercut
2 Size of sharp edge
3 Size of passing

Figure 2 — States of an internal edge



a is the size of the burr

Figure 3 — Examples of burr



a is the size of the undercut

Figure 4 — Examples of undercut at an external edge



a is the size of the undercut

Figure 5 — Examples of undercut at an internal edge



a is the size of the passing

Figure 6 — Examples of passing

4 Indications on drawings

4.1 Basic symbol

The state of the edges of a part shall be indicated by the basic graphical symbol shown in Figure 7. Complementary indications shall be placed in the areas a_1, a_2 or a_3 defined in Figure A.1. The length and direction of the leader line may be adapted to suit the characteristics of the drawing (see, for example, Figure 14).

NOTE Rules for drafting the basic symbol are given in annex A.

Figure 7 — Basic symbol

4.2 Location of the basic symbol

The indications concerning edges of undefined shape shall be given as:

— an individual indication for a single edge;

— individual indications for all edges around the represented profile of a part;

— collective indications common to all or the majority of a part's edges.

Individual indications are immediately assigned to a line (e.g. visible outlines, areas with specific treatment or extension lines), or to a point representing an edge parallel with, or vertical to, the projection plane (see Figures 14 to 16).

Collective indications are indicated only once for all the common edges and are located near the representation of the part or near the title block (see Figures 17 to 21).

4.3 Shape of edges

The shape of an edge shall be indicated in the area a_1 (defined in Figure A.1), beside the basic symbol, by the element + (plus), – (minus) or ± (plus or minus), in accordance with Table 1 (see Figures 8 to 10).

The symbol element + (plus) indicates permitted excess material in relation to the ideal shape of the edge: i.e. burr on external and passing on internal edges. The element – (minus) indicates required material removal in relation to the ideal shape of the edge: i.e. undercut of external and internal edges. Neither a burr's or undercut's direction nor its size is specified by a single symbol element.

The deviation from ideal shape can be controlled by indicating the direction of burr and undercut (see 4.4) and the size (see 4.5).



Figure 8 — Symbol element ±

Figure 9 — Symbol element +

Figure 10 — Symbol element –

Table 1 — Symbol elements for the shapes of edges

Symbol element	Meaning	
	External edge	Internal edge
+	Burr permitted; undercut not permitted	Passing permitted; undercut not permitted
–	Undercut required; burr not permitted	Undercut required; passing not permitted
± [a]	Burr or undercut permitted	Undercut or passing permitted

[a] To be used only with an indication of size.

4.4 Direction of burr or undercut

Wherever indication of the permitted direction of burr on an external edge or undercut on an internal edge is needed, the indication of size shall be given in the area a_2 or a_3 (as defined in Figure A.1), accordingly (see Figures 11 and 12). Indication of the direction of the undercut on an external, or passing on an internal, edge is not permitted.



Figure 11 — Direction of the burr on an external edge