

ETSI EN 301 908-2 V4.2.1 (2010-03)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Base Stations (BS), Repeaters and User Equipment (UE)
for IMT-2000 Third-Generation cellular networks;
Part 2: Harmonized EN for IMT-2000,
CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (UE)
covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/2568efa-1fa1-4240-9613-0b7d3b9cb337/etsi-en-301-908-2-v4.2.1-2010-03>



Reference

REN/ERM-TFES-004-2

Keywords3G, 3GPP, cellular, digital, IMT-2000, mobile,
radio, regulation, UMTS, WCDMA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88*iTeh STANDARD REVIEW*
*Full standard:
http://standards.etsi.org/tb/908-2-v4.2.1-2010-03*

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered
for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|--|----|
| Intellectual Property Rights | 6 |
| Foreword..... | 6 |
| Introduction | 7 |
| 1 Scope | 8 |
| 2 References | 8 |
| 2.1 Normative references | 9 |
| 2.2 Informative references..... | 9 |
| 3 Definitions, symbols and abbreviations | 10 |
| 3.1 Definitions | 10 |
| 3.2 Symbols..... | 11 |
| 3.3 Abbreviations | 11 |
| 4 Technical requirements specifications | 12 |
| 4.1 Environmental profile..... | 12 |
| 4.2 Conformance requirements | 12 |
| 4.2.1 Introduction..... | 12 |
| 4.2.2 Transmitter maximum output power..... | 13 |
| 4.2.2.1 Definition | 13 |
| 4.2.2.2 Limits | 13 |
| 4.2.2.3 Conformance | 13 |
| 4.2.3 Transmitter spectrum emission mask..... | 13 |
| 4.2.3.1 Definition | 13 |
| 4.2.3.2 Limits | 14 |
| 4.2.3.3 Conformance | 14 |
| 4.2.4 Transmitter spurious emissions..... | 14 |
| 4.2.4.1 Definition | 14 |
| 4.2.4.2 Limits | 14 |
| 4.2.4.3 Conformance | 15 |
| 4.2.5 Transmitter minimum output power..... | 16 |
| 4.2.5.1 Definition | 16 |
| 4.2.5.2 Limits | 16 |
| 4.2.5.3 Conformance | 16 |
| 4.2.6 Receiver Adjacent Channel Selectivity (ACS) | 16 |
| 4.2.6.1 Definition | 16 |
| 4.2.6.2 Limits | 16 |
| 4.2.6.3 Conformance | 16 |
| 4.2.7 Receiver blocking characteristics | 17 |
| 4.2.7.1 Definition | 17 |
| 4.2.7.2 Limits | 17 |
| 4.2.7.3 Conformance | 18 |
| 4.2.8 Receiver spurious response..... | 18 |
| 4.2.8.1 Definition | 18 |
| 4.2.8.2 Limits | 18 |
| 4.2.8.3 Conformance | 18 |
| 4.2.9 Receiver intermodulation characteristics | 19 |
| 4.2.9.1 Definition | 19 |
| 4.2.9.2 Limits | 19 |
| 4.2.9.3 Conformance | 19 |
| 4.2.10 Receiver spurious emissions | 19 |
| 4.2.10.1 Definition | 19 |
| 4.2.10.2 Limits | 20 |
| 4.2.10.3 Conformance | 21 |
| 4.2.11 Out-of-synchronization handling of output power..... | 21 |
| 4.2.11.1 Definition | 21 |

| | | |
|------------|--|----|
| 4.2.11.2 | Limits | 21 |
| 4.2.11.3 | Conformance | 22 |
| 4.2.12 | Transmitter Adjacent Channel Leakage power Ratio (ACLR) | 22 |
| 4.2.12.1 | Definition | 22 |
| 4.2.12.2 | Limits | 22 |
| 4.2.12.3 | Conformance | 23 |
| 5 | Testing for compliance with technical requirements..... | 23 |
| 5.1 | Environmental conditions for testing | 23 |
| 5.2 | Interpretation of the measurement results | 23 |
| 5.3 | Essential radio test suites..... | 24 |
| 5.3.1 | Transmitter maximum output power..... | 24 |
| 5.3.1.1 | Method of test | 24 |
| 5.3.1.1.1 | Initial conditions..... | 24 |
| 5.3.1.1.2 | Procedure | 24 |
| 5.3.1.2 | Test requirements | 25 |
| 5.3.2 | Transmitter spectrum emission mask..... | 25 |
| 5.3.2.1 | Method of test | 25 |
| 5.3.2.1.1 | Initial conditions for UEs not supporting HSDPA and/or E-DCH | 25 |
| 5.3.2.1.1A | Initial conditions for UEs supporting HSDPA and/or E-DCH | 25 |
| 5.3.2.1.2 | Procedure for UEs not supporting HSDPA and/or E-DCH | 25 |
| 5.3.2.1.2A | Procedure for UEs supporting HSDPA and/or E-DCH | 25 |
| 5.3.2.2 | Test requirements | 25 |
| 5.3.3 | Transmitter spurious emissions..... | 26 |
| 5.3.3.1 | Method of test | 26 |
| 5.3.3.1.1 | Initial conditions..... | 26 |
| 5.3.3.1.2 | Procedure | 26 |
| 5.3.3.2 | Test requirements | 26 |
| 5.3.4 | Transmitter minimum output power | 26 |
| 5.3.4.1 | Method of test | 26 |
| 5.3.4.1.1 | Initial conditions..... | 26 |
| 5.3.4.1.2 | Procedure | 26 |
| 5.3.4.2 | Test requirements | 26 |
| 5.3.5 | Receiver Adjacent Channel Selectivity (ACS) | 27 |
| 5.3.5.1 | Method of test | 27 |
| 5.3.5.1.1 | Initial conditions..... | 27 |
| 5.3.5.1.2 | Procedure | 27 |
| 5.3.5.2 | Test requirements | 27 |
| 5.3.6 | Receiver blocking characteristics | 27 |
| 5.3.6.1 | Method of test | 27 |
| 5.3.6.1.1 | Initial requirements..... | 27 |
| 5.3.6.1.2 | Procedure | 28 |
| 5.3.6.2 | Test requirements | 28 |
| 5.3.7 | Receiver spurious response | 28 |
| 5.3.7.1 | Method of test | 28 |
| 5.3.7.1.1 | Initial conditions..... | 28 |
| 5.3.7.1.2 | Procedure | 28 |
| 5.3.7.2 | Test requirements | 28 |
| 5.3.8 | Receiver Intermodulation characteristics | 28 |
| 5.3.8.1 | Method of test | 28 |
| 5.3.8.1.1 | Initial conditions..... | 28 |
| 5.3.8.1.2 | Procedure | 29 |
| 5.3.8.2 | Test requirements | 29 |
| 5.3.9 | Receiver spurious emissions | 29 |
| 5.3.9.1 | Method of test | 29 |
| 5.3.9.1.1 | Initial conditions..... | 29 |
| 5.3.9.1.2 | Procedure | 29 |
| 5.3.9.2 | Test requirements | 29 |
| 5.3.10 | Out-of-synchronization handling of output power..... | 29 |
| 5.3.10.1 | Method of test | 29 |
| 5.3.10.1.1 | Initial conditions..... | 29 |
| 5.3.10.1.2 | Procedure | 30 |

| | | |
|-------------------------------|--|-----------|
| 5.3.10.2 | Test requirements | 30 |
| 5.3.11 | Transmitter adjacent channel leakage power ratio | 30 |
| 5.3.11.1 | Method of test | 30 |
| 5.3.11.1.1 | Initial conditions for UEs not supporting HSDPA and/or E-DCH | 30 |
| 5.3.11.1A | Initial conditions for UEs supporting HSDPA and/or E-DCH | 31 |
| 5.3.11.1.2 | Procedure for UEs not supporting HSDPA and/or E-DCH | 31 |
| 5.3.11.1.2A | Procedure for UEs supporting HSDPA and/or E-DCH | 31 |
| 5.3.11.2 | Test requirements | 31 |
| Annex A (normative): | HS Requirements and conformance Test specifications Table (HS-RTT)..... | 32 |
| Annex B (normative): | Environmental profile | 34 |
| B.1 | General | 34 |
| B.1.1 | Introduction | 34 |
| B.1.2 | Temperature | 34 |
| B.1.3 | Voltage | 34 |
| B.1.4 | Test environment..... | 35 |
| Annex C (informative): | The EN title in the official languages | 36 |
| Annex D (informative): | Bibliography..... | 37 |
| History | | 38 |

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/2568efa-1#I-4240-9613-0b7d3b9cb337/etsi-en-301-908-2-v4.2.1-2010-03>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.2] are given in annex A.

The present document is part 2 of a multi-part deliverable covering the Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks, as identified below:

- Part 1: "Harmonized EN for IMT-2000, introduction and common requirements, covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 2: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";**
- Part 3: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 4: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 5: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) and Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 6: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD and E-UTRA TDD) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 7: "Harmonized EN for IMT-2000, CDMA TDD (UTRA TDD and E-UTRA TDD) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";

- Part 10: "Harmonized EN for IMT-2000, FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 11: "Harmonized EN for IMT-2000, CDMA Direct Spread (UTRA FDD and E-UTRA FDD) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 12: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 13: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 14: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 15: "Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (FDD Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 16: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 17: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive".

| National transposition dates | |
|--|------------------|
| Date of adoption of this EN: | 19 February 2010 |
| Date of latest announcement of this EN (doa): | 31 May 2010 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 30 November 2010 |
| Date of withdrawal of any conflicting National Standard (dow): | 30 November 2011 |

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- User Equipment for IMT-2000 CDMA Direct Spread (UTRA FDD and E-UTRA FDD).

These radio equipment types are capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: UTRA FDD operating bands

| UTRA FDD Band | Direction of transmission | UTRA FDD operating bands |
|---------------|---------------------------|--------------------------|
| I | Transmit | 1 920 MHz to 1 980 MHz |
| | Receive | 2 110 MHz to 2 170 MHz |
| III | Transmit | 1 710 MHz to 1 785 MHz |
| | Receive | 1 805 MHz to 1 880 MHz |
| VII | Transmit | 2 500 MHz to 2 570 MHz |
| | Receive | 2 620 MHz to 2 690 MHz |
| VIII | Transmit | 880 MHz to 915 MHz |
| | Receive | 925 MHz to 960 MHz |
| XV | Transmit | 1 900 MHz to 1 920 MHz |
| | Receive | 2 600 MHz to 2 620 MHz |
| XVI | Transmit | 2 010 MHz to 2 025 MHz |
| | Receive | 2 585 MHz to 2 600 MHz |

The present document covers requirements for UTRA FDD User Equipments from 3GPP Release 99, 4, 5, 6, 7 and 8 and E-UTRA FDD User Equipment Release 8. In addition, the present document covers requirements for UTRA FDD User Equipment in the operating bands specified in TS 102 735 [i.4].

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org/>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] Void.
- [2] ETSI TS 134 121-1 (V8.8.0): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) conformance specification; Radio transmission and reception (FDD); Part 1: Conformance specification (3GPP TS 34.121-1 version 8.8.0 Release 8)".
- [3] ETSI TS 134 108 (V8.8.0): "Universal Mobile Telecommunications System (UMTS); LTE; Common test environments for User Equipment (UE); Conformance testing (3GPP TS 34.108 version 8.8.0 Release 8)".
- [4] ETSI TS 134 109 (V8.0.0): "Universal Mobile Telecommunications System (UMTS); LTE; Terminal logical test interface; Special conformance testing functions (3GPP TS 34.109 version 8.0.0 Release 8)".
- [5] ETSI TS 125 101 (V8.8.0): "Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 8.8.0 Release 8)".
- [6] IEC 60068-2-1 (2007): "Environmental testing - Part 2-1: Tests. Test A: Cold".
- [7] IEC 60068-2-2 (2007): "Environmental testing - Part 2-2: Tests. Test B: Dry heat".
- [8] ETSI TS 125 214 (V8.6.0): "Universal Mobile Telecommunications System (UMTS); Physical layer procedures (FDD) (3GPP TS 25.214 version 8.6.0 Release 8)".
- [9] ETSI TS 145 004 (V8.0.0): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 8.0.0 Release 8)".
- [10] ETSI EN 301 908-1 (V4.1.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 1: Harmonized EN for IMT-2000, introduction and common requirements, covering the essential requirements of article 3.2 of the R&TTE Directive".
- [11] ETSI EN 301 908-13 (V4.1.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 13: Harmonized EN for IMT-2000, Evolved Universal Terrestrial Radio Access (E-UTRA) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".

- [i.4] ETSI TS 102 735 (V7.0.1): "Universal Mobile Telecommunications System (UMTS); Band-specific requirements for UMTS Frequency Division Duplex (FDD) operation in the bands 1 900 MHz to 1 920 MHz paired with 2 600 MHz to 2 620 MHz and 2 010 MHz to 2 025 MHz paired with 2 585 MHz to 2 600 MHz".
- [i.5] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

chip rate: rate of "chips" (modulated symbols after spreading) per second

NOTE: The UTRA FDD chip rate is 3,84 Mchip/s.

data rate: rate of the user information, which must be transmitted over the Air Interface

EXAMPLE: Output rate of the voice codec.

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

maximum output power: measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode

NOTE: The period of measurement is assumed to be at least one timeslot.

mean power: power (transmitted or received) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode, when applied to a WCDMA modulated signal

NOTE: The period of measurement is assumed to be at least one timeslot unless otherwise stated.

node B: logical node responsible for radio transmission/reception in one or more cells to/from the User Equipment

nominal maximum output power: nominal power defined by the UE power class

power spectral density: function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth

NOTE 1: When the mean power is normalized to (divided by) the chip-rate it represents the mean energy per chip. Some signals are directly defined in terms of energy per chip, (DPCH_Ec, Ec, OCNS_Ec and S-CCPCH_Ec) and others defined in terms of PSD (I_o , I_{oc} , I_{or} and \hat{I}_{or}). There also exist quantities that are a ratio of energy per chip to PSD (DPCH_Ec/ I_{or} , E_c/I_{or} etc.). This is the common practice of relating energy magnitudes in communication systems.

NOTE 2: It can be seen that if both energy magnitudes in the ratio are divided by time, the ratio is converted from an energy ratio to a power ratio, which is more useful from a measurement point of view. It follows that an energy per chip of X dBm/3,84 MHz can be expressed as a mean power per chip of X dBm. Similarly, a signal PSD of Y dBm/3,84 MHz can be expressed as a signal power of Y dBm.

NOTE 3: The units of Power Spectral Density (PSD) are extensively used in the present document.

RRC filtered mean power: mean power as measured through a root raised cosine filter with roll-off factor α and a bandwidth equal to the chip rate of the radio access mode

NOTE: The RRC filtered mean power of a perfectly modulated WCDMA signal is 0,246 dB lower than the mean power of the same signal.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

| | |
|----------|---|
| α | Roll-off factor of the root raised cosine filter, $\alpha = 0,22$ |
| DPCH_Ec | Average energy per PN chip for DPCH |
| E_c | Average energy per PN chip |
| F_{uw} | Frequency of unwanted signal |

NOTE: This is specified in bracket in terms of an absolute frequency(s) or a frequency offset from the assigned channel frequency.

| | |
|----------------|--|
| I_o | The total received power spectral density, including signal and interference, as measured at the UE antenna connector |
| I_{oc} | Power spectral density (integrated in a noise bandwidth equal to the chip rate and normalized to the chip rate) of a band limited white noise source (simulating interference from cells, which are not defined in a test procedure) as measured at the UE antenna connector |
| I_{or} | Total transmit power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal at the Node B antenna connector |
| \hat{I}_{or} | Received power spectral density (integrated in a bandwidth of $(1 + \alpha)$ times the chip rate and normalized to the chip rate) of the downlink signal as measured at the UE antenna connector |
| β_c | Gain factor for DPCCH |
| β_d | Gain factor for DPDCH |
| β_{hs} | Gain factor for HS-DPCCH |
| β_{ec} | Gain factor for E-DPCCH |
| β_{ed} | Gain factor for E-DPDCH |

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|------|--------------------------------------|
| ACLR | Adjacent Channel Leakage power Ratio |
| ACS | Adjacent Channel Selectivity |
| BER | Bit Error Ratio |
| CW | Continuous Wave |

NOTE: Unmodulated signal.

| | |
|----------|--|
| DCH | Dedicated Channel, which is mapped into Dedicated Physical Channel |
| DPCCH | Dedicated Physical Control CHannel |
| DPDCH | Dedicated Physical Data CHannel |
| E-DCH | Enhanced Dedicated CHannel |
| E-UTRA | Evolved Universal Terrestrial Radio Access |
| EMC | ElectroMagnetic Compatibility |
| FDD | Frequency Division Duplex |
| HSDPA | High Speed Downlink Packet Access |
| IMT-2000 | International Mobile Telecommunications 2000 |
| OCNS | Orthogonal Channel Noise Simulator |

NOTE: A mechanism used to simulate the users or control signals on the other orthogonal channels of a downlink.