

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 7: Security**

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/3bc1b660-557f-45e5-9b16-9d60843e2e58/etsi-en-300-392-7-v3.2.1-2010-06>



Reference

REN/TETRA-06179

Keywords

security, TETRA, V+D

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
1 Scope	12
2 References	12
2.1 Normative references	13
2.2 Informative references.....	13
3 Definitions and abbreviations.....	14
3.1 Definitions	14
3.2 Abbreviations	16
4 Air Interface authentication and key management mechanisms	18
4.0 Security classes	18
4.1 Air interface authentication mechanisms	19
4.1.1 Overview	19
4.1.2 Authentication of an MS	19
4.1.3 Authentication of the infrastructure	20
4.1.4 Mutual authentication of MS and infrastructure	21
4.1.5 The authentication key.....	23
4.1.6 Equipment authentication	23
4.1.7 Authentication of an MS when migrated	24
4.1.8 Authentication of the home SwMI when migrated.....	24
4.1.9 Mutual Authentication of MS and infrastructure when migrated	25
4.2 Air Interface key management mechanisms.....	26
4.2.1 The DCK.....	26
4.2.2 The GCK.....	27
4.2.2.1 Session key modifier GCK0	28
4.2.3 The CCK	28
4.2.4 The SCK	29
4.2.4.1 SCK association for DMO use	31
4.2.4.1.1 DMO SCK subset grouping.....	31
4.2.5 The GSKO	34
4.2.5.1 SCK distribution to groups with OTAR.....	35
4.2.5.2 GCK distribution to groups with OTAR	35
4.2.5.3 Rules for MS response to group key distribution	36
4.2.6 Encrypted Short Identity (ESI) mechanism	36
4.2.7 Encryption Cipher Key	37
4.2.8 Summary of AI key management mechanisms.....	37
4.3 Service description and primitives	39
4.3.1 Authentication primitives	39
4.3.2 SCK transfer primitives	39
4.3.3 GCK transfer primitives.....	40
4.3.4 GSKO transfer primitives	41
4.4 Authentication protocol.....	42
4.4.1 Authentication state transitions.....	42
4.4.2 Authentication protocol sequences and operations	45
4.4.2.1 MSCs for authentication	46
4.4.2.2 MSCs for authentication Type-3 element	52
4.4.2.3 Control of authentication timer T354 at MS	55
4.5 OTAR protocols	56
4.5.1 CCK delivery - protocol functions.....	56
4.5.1.1 SwMI-initiated CCK provision	56
4.5.1.2 MS-initiated CCK provision with U-OTAR CCK demand.....	58
4.5.1.3 MS-initiated CCK provision with announced cell reselection	59
4.5.2 OTAR protocol functions - SCK	59
4.5.2.1 MS requests provision of SCK(s).....	60
4.5.2.2 SwMI provides SCK(s) to individual MS	61

4.5.2.3	SwMI provides SCK(s) to group of MSs	64
4.5.2.4	SwMI rejects provision of SCK	66
4.5.3	OTAR protocol functions - GCK	66
4.5.3.1	MS requests provision of GCK	66
4.5.3.2	SwMI provides GCK to an individual MS	69
4.5.3.3	SwMI provides GCK to a group of MSs	71
4.5.3.4	SwMI rejects provision of GCK	73
4.5.4	Cipher key association to group address	73
4.5.4.1	SCK association for DMO	74
4.5.4.2	GCK association	78
4.5.5	Notification of key change over the air	80
4.5.5.1	Change of DCK	82
4.5.5.2	Change of CCK	82
4.5.5.3	Change of GCK	82
4.5.5.4	Change of SCK for TMO	82
4.5.5.5	Change of SCK for DMO	83
4.5.5.6	Synchronization of Cipher Key Change	83
4.5.6	Security class change	83
4.5.6.1	Change of security class to security class 1	84
4.5.6.2	Change of security class to security class 2	84
4.5.6.3	Change of security class to security class 3	84
4.5.6.4	Change of security class to security class 3 with GCK	85
4.5.7	Notification of key in use	85
4.5.8	Notification of GCK Activation/Deactivation	85
4.5.9	Deletion of SCK, GCK and GSKO	85
4.5.10	Air Interface Key Status Enquiry	87
4.5.11	Crypto management group	90
4.5.12	OTAR retry mechanism	90
4.5.13	OTAR protocol functions - GSKO	91
4.5.13.1	MS requests provision of GSKO	91
4.5.13.2	SwMI provides GSKO to an MS	92
4.5.13.3	SwMI rejects provision of GSKO	93
4.5.14	OTAR protocol functions - interaction and queuing	93
4.5.15	KSOv for OTAR operations in visited SwMI	93
4.5.16	Transfer of AI cipher keys across the ISI	97
5	Enable and disable mechanism	97
5.1	General relationships	98
5.2	Enable/disable state transitions	98
5.3	Mechanisms	99
5.3.1	Disable of MS equipment	100
5.3.2	Disable of an subscription	100
5.3.3	Disable of subscription and equipment	100
5.3.4	Enable an MS equipment	100
5.3.5	Enable an MS subscription	100
5.3.6	Enable an MS equipment and subscription	100
5.4	Enable/disable protocol	101
5.4.1	General case	101
5.4.2	Status of cipher key material	102
5.4.2.1	Permanently disabled state	102
5.4.2.2	Temporarily disabled state	102
5.4.3	Specific protocol exchanges	103
5.4.3.1	Disabling an MS with mutual authentication	103
5.4.3.2	Enabling an MS with mutual authentication	105
5.4.3.3	Enabling an MS with non-mutual authentication	106
5.4.3.4	Disabling an MS with non-mutual authentication	107
5.4.4	Enabling an MS without authentication	108
5.4.5	Disabling an MS without authentication	109
5.4.6	Rejection of enable or disable command	109
5.4.6a	Expiry of Enable/Disable protocol timer	110
5.4.7	MM service primitives	111
5.4.7.1	TNMM-DISABLING primitive	111

5.4.7.2	TNMM-ENABLING primitive	111
6	Air Interface (AI) encryption	111
6.1	General principles.....	111
6.2	Security class.....	112
6.2.0	Notification of security class	113
6.2.0.1	Security Class of Neighbouring Cells	113
6.2.0.2	Identification of MS security capabilities	113
6.2.1	Constraints on LA arising from cell class	114
6.3	Key Stream Generator (KSG)	114
6.3.1	KSG numbering and selection	114
6.3.2	Interface parameters.....	115
6.3.2.1	Initial Value (IV).....	115
6.3.2.2	Cipher Key	115
6.4	Encryption mechanism	116
6.4.1	Allocation of KSS to logical channels	116
6.4.2	Allocation of KSS to logical channels with PDU association	118
6.4.2.1	General.....	118
6.4.2.2	KSS allocation on phase modulation channels.....	118
6.4.2.3	KSS allocation on QAM channels	120
6.4.2.3.1	Fixed mapping	120
6.4.2.3.2	Offset mapping	121
6.4.3	Synchronization of data calls where data is multi-slot interleaved	122
6.4.4	Recovery of stolen frames from interleaved data	123
6.5	Use of cipher keys	123
6.5.1	Identification of encryption state of downlink MAC PDUs	124
6.5.1.1	Class 1 cells.....	124
6.5.1.2	Class 2 cells.....	125
6.5.1.3	Class 3 cells.....	125
6.5.2	Identification of encryption state of uplink MAC PDUs	125
6.6	Mobility procedures	126
6.6.1	General requirements	126
6.6.1.1	Additional requirements for class 3 systems	126
6.6.2	Protocol description	126
6.6.2.1	Negotiation of ciphering parameters.....	126
6.6.2.1.1	Class 1 cells	126
6.6.2.1.2	Class 2 cells	127
6.6.2.1.3	Class 3 cells	127
6.6.2.2	Initial and undeclared cell re-selection.....	127
6.6.2.3	Unannounced cell re-selection	128
6.6.2.4	Announced cell re-selection type-3.....	129
6.6.2.5	Announced cell re-selection type-2.....	129
6.6.2.6	Announced cell re-selection type-1	129
6.6.2.7	Key forwarding	129
6.7	Encryption control.....	131
6.7.1	Data to be encrypted	131
6.7.1.1	Downlink control channel requirements	131
6.7.1.2	Encryption of MAC header elements	131
6.7.1.3	Traffic channel encryption control.....	131
6.7.1.4	Handling of PDUs that do not conform to negotiated ciphering mode	132
6.7.2	Service description and primitives	132
6.7.2.1	Mobility Management (MM)	133
6.7.2.2	Mobile Link Entity (MLE).....	133
6.7.2.3	Layer 2	135
6.7.3	Protocol functions	135
6.7.3.1	MM	135
6.7.3.2	MLE	135
6.7.3.3	LLC	135
6.7.3.4	MAC	136
6.7.4	PDUs for cipher negotiation	136
Annex A (normative):	PDU and element definitions	137

A.1	Authentication PDUs.....	137
A.1.1	D-AUTHENTICATION demand.....	137
A.1.2	D-AUTHENTICATION reject.....	137
A.1.3	D-AUTHENTICATION response.....	138
A.1.4	D-AUTHENTICATION result.....	138
A.1.5	U-AUTHENTICATION demand.....	138
A.1.6	U-AUTHENTICATION reject.....	139
A.1.7	U-AUTHENTICATION response.....	139
A.1.8	U-AUTHENTICATION result.....	140
A.2	OTAR PDUs	140
A.2.1	D-OTAR CCK Provide	140
A.2.2	U-OTAR CCK Demand	140
A.2.3	U-OTAR CCK Result	141
A.2.4	D-OTAR GCK Provide	141
A.2.5	U-OTAR GCK Demand	142
A.2.6	U-OTAR GCK Result	143
A.2.6a	D-OTAR GCK Reject	143
A.2.7	D-OTAR SCK Provide.....	144
A.2.8	U-OTAR SCK Demand.....	145
A.2.9	U-OTAR SCK Result.....	145
A.2.9a	D-OTAR SCK Reject.....	146
A.2.10	D-OTAR GSKO Provide.....	146
A.2.11	U-OTAR GSKO Demand	147
A.2.12	U-OTAR GSKO Result.....	147
A.2.12a	D-OTAR GSKO Reject.....	147
A.3	PDUs for key association to GTSI	148
A.3.1	D-OTAR KEY ASSOCIATE demand	148
A.3.2	U-OTAR KEY ASSOCIATE status.....	149
A.4	PDUs to synchronize key or security class change	149
A.4.1	D-CK CHANGE demand.....	149
A.4.2	U-CK CHANGE result.....	150
A.4.2a	U-OTAR KEY DELETE result.....	151
A.4.2b	U-OTAR KEY STATUS response.....	152
A.4.3	D-DM-SCK ACTIVATE DEMAND.....	153
A.4.4	U-DM-SCK ACTIVATE RESULT	154
A.4a	PDUs to delete air interface keys in MS	155
A.4a.1	D-OTAR KEY DELETE demand.....	155
A.4a.2	U-OTAR KEY DELETE result.....	155
A.4b	PDUs to obtain Air Interface Key Status	156
A.4b.1	D-OTAR KEY STATUS demand.....	156
A.4b.2	U-OTAR KEY STATUS response.....	157
A.5	Other security domain PDUs.....	158
A.5.1	U-TEI PROVIDE	158
A.5.2	U-OTAR PREPARE	159
A.5.3	D-OTAR NEWCELL.....	159
A.5.4	D-OTAR CMG GTSI PROVIDE.....	159
A.5.5	U-OTAR CMG GTSI RESULT	160
A.6	PDUs for Enable and Disable.....	160
A.6.1	D-DISABLE.....	160
A.6.2	D-ENABLE.....	161
A.6.3	U-DISABLE STATUS.....	161
A.7	MM PDU type 3 information elements coding	162
A.7.1	Authentication downlink	162
A.7.2	Authentication uplink	162
A.8	PDU Information elements coding.....	163
A.8.1	Acknowledgement flag.....	163

A.8.2	Address extension.....	163
A.8.3	Authentication challenge.....	163
A.8.4	Authentication reject reason.....	163
A.8.5	Authentication result.....	164
A.8.6	Authentication sub-type.....	164
A.8.7	CCK identifier.....	164
A.8.8	CCK information.....	164
A.8.9	CCK Location area information.....	165
A.8.10	CCK request flag.....	165
A.8.11	Change of security class.....	165
A.8.12	Ciphering parameters.....	166
A.8.13	CK provision flag.....	166
A.8.14	CK provisioning information.....	166
A.8.15	CK request flag.....	167
A.8.16	Class Change flag.....	167
A.8.17	DCK forwarding result.....	167
A.8.18	Disabling type.....	167
A.8.19	Enable/Disable result.....	168
A.8.20	Encryption mode.....	168
A.8.20.1	Class 1 cells.....	168
A.8.20.2	Class 2 cells.....	168
A.8.20.3	Class 3 cells.....	169
A.8.21	Equipment disable.....	169
A.8.22	Equipment enable.....	169
A.8.23	Equipment status.....	169
A.8.23a	Explicit response.....	170
A.8.24	Frame number.....	170
A.8.25	Future key flag.....	170
A.8.26	GCK data.....	170
A.8.27	GCK key and identifier.....	170
A.8.28	GCK Number (GCKN).....	171
A.8.28a	GCK Provision result.....	171
A.8.28b	GCK rejected.....	171
A.8.29	GCK select number.....	171
A.8.29a	GCK Supported.....	172
A.8.30	GCK Version Number (GCK-VN).....	172
A.8.31	Group association.....	172
A.8.31a	Group Identity Security Related Information.....	173
A.8.32	GSKO Version Number (GSKO-VN).....	173
A.8.33	GSSI.....	173
A.8.34	Hyperframe number.....	173
A.8.35	Intent/confirm.....	173
A.8.36	Void.....	174
A.8.37	Key association status.....	174
A.8.38	Key association type.....	174
A.8.39	Key change type.....	174
A.8.39a	Key delete type.....	175
A.8.39b	Key status type.....	175
A.8.39c	Key delete extension.....	175
A.8.40	Key type flag.....	176
A.8.41	KSG-number.....	176
A.8.42	Location area.....	176
A.8.43	Location area bit mask.....	176
A.8.44	Location area selector.....	176
A.8.45	Location area list.....	177
A.8.46	Location area range.....	177
A.8.46a	Max response timer value.....	177
A.8.47	Mobile country code.....	177
A.8.48	Mobile network code.....	177
A.8.49	Multiframe number.....	177
A.8.50	Mutual authentication flag.....	178
A.8.51	Network time.....	178

A.8.52	Number of GCKs changed	178
A.8.52a	Number of GCKs deleted	178
A.8.52b	Number of GCK status	178
A.8.52c	Number of GCKs provided	179
A.8.52d	Number of GCKs rejected	179
A.8.52e	Number of GCKs requested by GCKN	179
A.8.52f	Number of GCKs requested by GSSI	180
A.8.53	Number of groups	180
A.8.53a	Number of GSKO status	180
A.8.54	Number of location areas	180
A.8.55	Number of SCKs changed	181
A.8.55a	Number of SCKs deleted	181
A.8.56	Number of SCKs provided	181
A.8.56a	Number of SCKs rejected	181
A.8.57	Number of SCKs requested	182
A.8.57a	Number of SCK status	182
A.8.57b	OTAR reject reason	182
A.8.57c	OTAR retry interval	183
A.8.58	OTAR sub-type	183
A.8.59	PDU type	184
A.8.60	Proprietary	185
A.8.61	Provision result	185
A.8.62	Random challenge	185
A.8.63	Random seed	185
A.8.64	Random seed for OTAR	185
A.8.65	Void	186
A.8.65a	Reject reason	186
A.8.66	Response value	186
A.8.67	SCK data	186
A.8.68	SCK information	186
A.8.69	SCK key and identifier	187
A.8.70	SCK Number (SCKN)	187
A.8.71	SCK number and result	187
A.8.72	SCK provision flag	187
A.8.72a	Void	188
A.8.72b	SCK rejected	188
A.8.73	SCK select number	188
A.8.73a	SCK subset grouping type	188
A.8.73b	SCK subset number	189
A.8.74	SCK use	189
A.8.75	SCK version number	189
A.8.76	Sealed Key (Sealed CCK, Sealed SCK, Sealed GCK, Sealed GSKO)	189
A.8.77	Security information element	190
A.8.77a	Security related information element	191
A.8.78	Session key	191
A.8.79	Slot Number	191
A.8.80	SSI	191
A.8.81	Subscription disable	192
A.8.82	Subscription enable	192
A.8.83	Subscription status	192
A.8.84	TEI	193
A.8.85	TEI request flag	193
A.8.85a	Timeshare cell and AI encryption information	193
A.8.86	Time type	194
A.8.87	Type 3 element identifier	194

Annex B (normative): Boundary conditions for the cryptographic algorithms and procedures195

B.1	Dimensioning of the cryptographic parameters	200
B.2	Summary of the cryptographic processes	201

Annex C (normative):	Timers	206
C.1	T354, authorization protocol timer	206
C.2	T371, Delay timer for group addressed delivery of SCK and GCK.....	206
C.3	T372, Key forwarding timer.....	206
C.4	T355, disable control timer	206
Annex D (informative):	Bibliography.....	207
Annex E (informative):	Change request history.....	208
History		209

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/3bc1b660-557f-45e5-9b16-9d60843e2e58/etsi-en-300-392-7-v3.2.1-2010-06>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA), and is now submitted for the ETSI standards One-step Approval Procedure.

The present document is part 7 of a multi-part deliverable covering the Voice plus Data (V+D), as identified below:

- EN 300 392-1: "General network design";
- EN 300 392-2: "Air Interface (AI)";
- EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";
- ETS 300 392-4: "Gateways basic operation";
- EN 300 392-5: "Peripheral Equipment Interface (PEI)";
- EN 300 392-7: "Security";**
- EN 300 392-9: "General requirements for supplementary services";
- EN 300 392-10: "Supplementary services stage 1";
- EN 300 392-11: "Supplementary services stage 2";
- EN 300 392-12: "Supplementary services stage 3";
- ETS 300 392-13: "SDL model of the Air Interface (AI)";
- ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";
- TS 100 392-16: "Network Performance Metrics";
- TR 100 392-17: "TETRA V+D and DMO specifications";
- TS 100 392-18: "Air interface optimized applications".

NOTE: Part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/3bc1b660-557f-45e5-9b16-9d60843e2e58/etsi-en-300-392-7-v3.2.1-2010-06>

1 Scope

The present document defines the Terrestrial Trunked Radio system (TETRA) supporting Voice plus Data (V+D). It specifies the air interface, the inter-working between TETRA systems and to other systems via gateways, the terminal equipment interface on the mobile station, the connection of line stations to the infrastructure, the security aspects in TETRA networks, the management services offered to the operator, the performance objectives, and the supplementary services that come in addition to the basic and teleservices.

The present part describes the security mechanisms in TETRA V+D. It provides mechanisms for confidentiality of control signalling and user speech and data at the air interface, authentication and key management mechanisms for the air interface and for the Inter-System Interface (ISI).

Clause 4 describes the authentication and key management mechanisms for the TETRA air interface. The following two authentication services have been specified for the air-interface in ETR 086-3 [1.3], based on a threat analysis:

- authentication of an MS by the TETRA infrastructure;
- authentication of the TETRA infrastructure by an MS.

Clause 5 describes the mechanisms and protocol for enable and disable of both the mobile station equipment and the mobile station user's subscription.

Air interface encryption may be provided as an option in TETRA. Where employed, clause 6 describes the confidentiality mechanisms using encryption on the air interface, for circuit mode speech, circuit mode data, packet data and control information. Clause 6 describes both encryption mechanisms and mobility procedures. It also details the protocol concerning control of encryption at the air interface.

The present document does not address the detail handling of protocol errors or any protocol mechanisms when TETRA is operating in a degraded mode. These issues are implementation specific and therefore fall outside the scope of the TETRA standardization effort.

The detail description of the Authentication Centre is outside the scope of the present document.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
- [2] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [3] ISO 7498-2: "Information processing systems - Open Systems Interconnection - Basic Reference Model - Part 2: Security Architecture".
- [4] ETSI EN 300 812: "Terrestrial Trunked Radio (TETRA); Subscriber Identity Module to Mobile Equipment (SIM-ME) interface; Part 3: Integrated Circuit (IC); Physical, logical and TSIM application characteristics".
- [5] ETSI EN 300 396-6: "Terrestrial Trunked Radio (TETRA); Direct Mode Operation (DMO); Part 6: Security".
- [6] ETSI EN 302 109: "Terrestrial Trunked Radio (TETRA); Security; Synchronization mechanism for end-to-end encryption".
- [7] ETSI EN 300 392-12-22: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 12: Supplementary services stage 3; Sub-part 22: Dynamic Group Number Assignment (DGNA)".
- [8] ETSI EN 300 392-3-5: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 5: Additional Network Feature for Mobility Management (ANF-ISIMM)".
- [9] ETSI ETS 300 396-1: "Terrestrial Trunked Radio (TETRA); Technical requirements for Direct Mode Operation (DMO); Part 1: General network design".

2.2 Informative references

The following referenced documents are not essential to the use of the present document but they assist the user with regard to a particular subject area. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- [i.1] ETSI ETS 300 392-2 (1996): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
- [i.2] ETSI ETS 300 392-7: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.3] ETSI ETR 086-3: "Trans European Trunked Radio (TETRA) systems; Technical requirements specification; Part 3: Security aspects".
- [i.4] ETSI EN 300 392-7 (V2.3.1): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.5] ETSI EN 300 392-7 (V2.1.1): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 7: Security".
- [i.6] ETSI TS 100 392-18-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D) and Direct Mode Operation (DMO); Part 18: Air interface optimized applications; Sub-part 1: Location Information Protocol (LIP)".
- [i.7] ETSI EN 300 392-10-21: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 21: Ambience Listening (AL)".