## INTERNATIONAL STANDARD



First edition 1999-01-15

# Information technology — 8-bit single-byte coded graphic character sets —

Part 6: Latin/Arabic alphabet

iTeh Sun seul octet

Partie 6: Alphabet latin/arabea

<u>ISO/IEC 8859-6:1999</u> https://standards.iteh.ai/catalog/standards/sist/36384fa1-c8b8-4b94-bb09-7ff2214f743b/iso-iec-8859-6-1999



#### Contents

		Page					
Fo	Foreword						
Int	Introduction						
1	Scope						
2	Confo	mance 1					
3	Norma	tive references					
4	Definit	ions 2					
5	Notatio	on, code table and names					
6							
7		ication of the character set					
An	inex A:	Coverage of languages by parts/datogloaofards/sist/36384fa1-c8b8-4b94-bb09- ISO/IEC 8859					
An	inex B:	Main differences between ISO 8859-6:1987 and this first edition of this part of ISO/IEC 8859 10					
An	nex C:	Bibliography 11					

© ISO/IEC 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

#### Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and nongovernmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC1. Draft International Standards adopted by the joint technical committee are circulated to iTeh ST Anational bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a (stavote ards.iteh.ai)

International Standard ISO/IEC 8859-6 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information technology, https://standards.iteh.ai/Subcommittee SC 2,4 Coded character sets. 7ft2214f743b/iso-jec-8859-6-1999

This edition cancels and replaces ISO 8859-6:1987 which has been technically revised.

ISO/IEC 8859 consists of the following parts, under the general title *Information technology – 8-bit single-byte coded graphic character sets*:

- Part 1: Latin alphabet No. 1
- Part 2: Latin alphabet No. 2
- Part 3: Latin alphabet No. 3
- Part 4: Latin alphabet No. 4
- Part 5: Latin/Cyrillic alphabet
- Part 6: Latin/Arabic alphabet
- Part 7: Latin/Greek alphabet
- Part 8: Latin/Hebrew alphabet
- Part 9: Latin alphabet No. 5
- Part 10: Latin alphabet No. 6

Annexes A to C of this part of ISO/IEC 8859 are for information only.

#### Introduction

ISO/IEC 8859 consists of several parts. Each part specifies a set of up to 191 graphic characters and the coded representation of these characters by means of a single 8-bit byte. Each set is intended for use for a particular group of languages.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/IEC 8859-6:1999</u> https://standards.iteh.ai/catalog/standards/sist/36384fa1-c8b8-4b94-bb09-7ff2214f743b/iso-iec-8859-6-1999

### Information technology – 8-bit single-byte coded graphic character sets –

Part 6: Latin/Arabic alphabet

#### 1 Scope

This part of ISO/IEC 8859 specifies a set of 146 coded graphic characters identified as Latin/Arabic alphabet.

This set of coded graphic characters is intended for use in data and text processing applications and also for information interchange.

The set contains graphic characters used for general purpose applications in typical office environments in at least the following languages:

Arabic, English and Latin.

Some of the characters in this set are combining characters (see clause 6).

This set of coded graphic characters may be RD regarded as a version of an 8-bit code according to ISO/IEC 2022 or ISO/IEC 4873 at level and ards.

This part of ISO/IEC 8859 may not be used in conjunction with any other parts of ISO/IEC 8859.50-6:1999 If coded characters from more than one part are to be used together, by means of code extension icc-885A receiving techniques, the equivalent coded character sets from ISO/IEC 10367 should be used instead within a version of ISO/IEC 4873 at level 2 or level 3.

The coded characters in this set may be used in conjunction with coded control functions selected from ISO/IEC 6429. However, control functions are not used to create composite graphic symbols from two or more graphic characters (see clause 6).

**NOTE** – ISO/IEC 8859 is not intended for use with Telematic services defined by ITU-T. If information coded according to ISO/IEC 8859 is to be transferred to such services, it will have to conform to the requirements of those services at the access-point.

#### 2 Conformance

#### 2.1 Conformance of information interchange

A coded-character-data-element (CC-data-element) within coded information for interchange is in conformance with this part of ISO/IEC 8859 if all the coded representations of graphic characters within that CC-data-element conform to the requirements of clause 6.

#### 2.2 Conformance of devices

A device is in conformance with this part of ISO/IEC 8859 if it conforms to the requirements of 2.2.1, and either or both of 2.2.2 and 2.2.3. A claim of conformance shall identify the document which contains the description specified in 2.2.1.

#### 2.2.1 Device description

A device that conforms to this part of ISO/IEC 8859 shall be the subject of a description that identifies the means by which the user may supply characters to the device, or may recognize them when they are made available to him, as specified respectively in 2.2.2 and 2.2.3.

#### 2.2.2 Originating devices

An originating device shall allow its user to supply any sequence of characters from those specified in clause 6, and shall be capable of transmitting their coded representations within a CC-data-element.

#### 2.2.3 Receiving devices

885A feceiving device shall be capable of receiving and interpreting any coded representations of characters that are within a CC-data-element, and that conform to clause 6, and shall make the corresponding characters available to its user in such a way that the user can identify them from among those specified there, and can distinguish them from each other.

#### **3** Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 8859. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 8859 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards. ISO/IEC 2022:1994, Information technology -Character code structure and extension techniques.

ISO/IEC 4873:1991. Information technology -ISO 8-bit code for information interchange -Structure and rules for implementation.

ISO/IEC 8824-1:1995, Information technology -Abstract Syntax Notation One (ASN.1): Specification of basic notation.

#### 4 Definitions

For the purposes of this part of ISO/IEC 8859 the following definitions apply:

4.1 bit combination: An ordered set of bits used for the representation of characters.

**4.2 byte:** A bit string that is operated upon as a unit.

4.3 character: A member of a set of elements used for the organization, control, or representation of data.

4.4 code table: A table showing the characters allocated to each bit combination in a code.

4.5 coded character set; code: A set of DA unambiguous rules that establishes a character set and the one-to-one relationship between the ar characters of the set and their bit combinations.

4.6 coded-character-data-element (CC-data-)/IEC 8An\_68 bit code table consists of 256 positions element): An element of interchanged information standarranged in 16 columns and 16 rows. The columns that is specified to consist of a sequence of coded 3b/iso and the rows are numbered 00 to 15. In hexarepresentations of characters, in accordance with decimal notation the columns and the rows are one or more identified standards for coded numbered 0 to F. character sets.

4.7 graphic character: A character, other than a control function, that has a visual representation normally handwritten, printed or displayed, and that has a coded representation consisting of one or more bit combinations.

**NOTE** – In ISO/IEC 8859 a single bit combination is used to represent each character.

4.8 graphic symbol: A visual representation of a graphic character or of a control function.

4.9 position: That part of a code table identified by its column and row coordinates.

#### 5 Notation, code table and names

#### 5.1 Notation

The bits of the bit combinations of the 8-bit code are identified by  $b_8$ ,  $b_7$ ,  $b_6$ ,  $b_5$ ,  $b_4$ ,  $b_3$ ,  $b_2$ 1, where b<sub>8</sub> is the highest-order, or most-significant bit and b<sub>1</sub> is the lowest-order, or least-significant bit.

The bit combinations may be interpreted to represent numbers in binary notation by attributing the following weights to the individual bits:

Bit	b <sub>8</sub>	b <sub>7</sub>	b <sub>6</sub>	b <sub>5</sub>	b <sub>4</sub>	b <sub>3</sub>	b <sub>2</sub>	b <sub>1</sub>
Weight	128	64	32	16	8	4	2	1

Using these weights, the bit combinations are identified by notations of the form xx/yy, where xx and yy are numbers in the range 00 to 15. The correspondence between the notations of the form xx/yy and the bit combinations consisting of the bits b<sub>8</sub> to b<sub>1</sub> is as follows:

 xx is the number represented by b<sub>8</sub>, b<sub>7</sub>, b<sub>6</sub> and  $b_5$  where these bits are given the weights 8, 4, 2, and 1 respectively.

yy is the number represented by b<sub>4</sub>, b<sub>3</sub>, b<sub>2</sub> and  $b_1$  where these bits are given the weights 8, 4, 2, and 1 respectively.

The bit combinations are also identified by notations of the form hk, where h and k are numbers in the range 0 to F in hexadecimal notation. The number h is the same as the number xx described above, and the number k the same as the number yy described above.

#### 5.2 Layout of the code table

The code table positions are identified by notations of the form xx/yy, where xx is the column number and yy is the row number. The column and row numbers are shown at the top and left edges of the table respectively. The code table positions are also identified by notations of the form hk, where h is the column number and k is the row number in hexadecimal notation. The column and row numbers are shown at the bottom and right edges of the table respectively.

The positions of the code table are in one-to-one correspondence with the bit combinations of the code. The notation of a code table position, of the form xx/yy, or of the form hk, is the same as that of the corresponding bit combination.

#### 5.3 Names and meanings

also specifies an acronym for each of the characters SPACE, NO-BREAK SPACE and SOFT HYPHEN. For acronyms only Latin capital letters A to Z are used. It is intended that the acronyms be retained in all translations of the text.

Except for SPACE (SP), NO-BREAK SPACE (NBSP) and SOFT HYPHEN (SHY), this part of ISO/IEC 8859 does not define and does not restrict the meanings of graphic characters.

This part of ISO/IEC 8859 specifies a graphic symbol for each graphic character. This symbol is shown in the corresponding position of the code table. However, this part, or any other part, of ISO/IEC 8859 does not specify a particular style or font design for imaging graphic characters. Annex B of ISO/IEC 10367 gives further information on this subject.

#### 5.3.1 SPACE (SP)

A graphic character the visual representation of which consists of the absence of a graphic symbol.

#### 5.3.2 NO-BREAK SPACE (NBSP)

A graphic character the visual representation of R which consists of the absence of a graphic symbol, for use when a line break is to be prevented in the S. text as presented.

#### 6 Specification of the coded character set

This part of ISO/IEC 8859 specifies 146 characters allocated to the bit combinations of the code table (table 2).

Some of these characters are combining characters. They are identified in table 1 as such.

**NOTE** – Combining characters are described in ISO/IEC 2022:1994 subclause 6.3.3.

The coded representation of a combining character shall follow that of the base character with which it is associated. Any combining character may be associated with any non-combining character in the ranges 12/01 to 13/10 and 14/01 to 14/10 (hexadecimal C1 to DA and E1 to EA).

Control functions, such as BACKSPACE or CARRIAGE RETURN, shall not be used to create composite graphic symbols, which are made up from the graphic representations of two or more characters.

**NOTE** – There is only one set of DIGITS in this part. How these will be imaged, is a matter of local conventions. In the code table, graphic symbols for the most common styles of writing digits are given next to each other. In this way data communication between various Arabic writing countries remains possible without code conversion.

# 6.1 Characters of the set and their coded <u>ISO/IEC 8859-6:1</u> representation

### 5.3.3 SOFT HYPHEN (SHY) https://standards.iteh.ai/catalog/standards/sist/36384fa1-c8b8-4b94-bb09-

A graphic character that is imaged 7by2a1graphiciec-8859-6-1999 symbol identical with, or similar to, that representing HYPHEN, for use when a line break has been established within a word.

#### Table 1 - Character set, coded representation

#### Table 1 (continued)

Bit combi- nation	Hex	Identifier	Name		Bit combi- nation	Hex	Identifier	Name
02/00	20	U+0020	SPACE		05/00	50	U+0050	LATIN CAPITAL LETTER P
02/00	20	U+0020	EXCLAMATION MARK		05/00	51	U+0051	LATIN CAPITAL LETTER Q
02/01	22	U+0022	QUOTATION MARK		05/02	52	U+0052	LATIN CAPITAL LETTER R
02/02	23	U+0023	NUMBER SIGN		05/02	53	U+0053	LATIN CAPITAL LETTER S
02/03	23	U+0023	DOLLAR SIGN		05/03	54	U+0054	LATIN CAPITAL LETTER T
02/04	25	U+0025	PERCENT SIGN		05/05	55	U+0055	LATIN CAPITAL LETTER U
02/06	26	U+0026	AMPERSAND		05/06	56	U+0056	LATIN CAPITAL LETTER V
02/00	27	U+0027	APOSTROPHE		05/07	57	U+0057	LATIN CAPITAL LETTER W
02/08	28	U+0028	LEFT PARENTHESIS		05/08	58	U+0058	LATIN CAPITAL LETTER X
02/00	29	U+0020	RIGHT PARENTHESIS		05/09	59	U+0059	LATIN CAPITAL LETTER Y
02/10	2A	U+002A	ASTERISK		05/10	5A	U+005A	LATIN CAPITAL LETTER Z
02/10	2B	U+002B	PLUS SIGN		05/11	5B	U+005B	LEFT SQUARE BRACKET
02/12	2C	U+002C	СОММА		05/12	5C	U+005C	REVERSE SOLIDUS
02/12	20 2D	U+002D	HYPHEN-MINUS		05/12	5D	U+005D	RIGHT SQUARE BRACKET
02/13	20 2E	U+002D	FULL STOP		05/13	5E	U+005E	CIRCUMFLEX ACCENT
02/14	2E 2F	U+002F	SOLIDUS		05/15	5F	U+005F	LOW LINE
03/00	30	U+0030	DIGIT ZERO		06/00	60	U+0060	GRAVE ACCENT
03/00	31	U+0031	DIGIT ONE		06/01	61	U+0061	LATIN SMALL LETTER A
03/02	32	U+0031 U+0032	DIGIT TWO		06/02	62	U+0001 U+0062	LATIN SMALL LETTER B
03/02	33	U+0033	DIGIT THREE <b>iTeh STANE</b>		06/02	63	U+0063	LATIN SMALL LETTER C
03/03	34	U+0034	DIGIT FOUR		06/04	64	U+0064	LATIN SMALL LETTER D
03/04	35	U+0034 U+0035	DIGIT FIVE (stand			65	U+0065	LATIN SMALL LETTER E
03/06	36	U+0035 U+0036	DIGIT FIVE (standa	ar	06/06	66	U+0066	LATIN SMALL LETTER F
03/07	37	U+0037	DIGIT SEVEN		06/07	67	U+0067	LATIN SMALL LETTER G
03/08	38	U+0038			06/08	. 168	U+0068	LATIN SMALL LETTER H
03/09	39	U+0039			06/00	69	U+0069	LATIN SMALL LETTER I
03/10	3A	U+003A	COLON https://standards.iteh.ai/catalog/s	tan	06/10 <sup>s</sup>	st <sub>6Å</sub> 6	30+006A	LATIN SMALL LETTER J
03/11	3B	U+003B	SEMICOLON 7ff2214f743	b/is	006/418	86B-	604006B	LATIN SMALL LETTER K
03/12	3C	U+003C	LESS-THAN SIGN		06/12	6C	U+006C	LATIN SMALL LETTER L
03/13	3D	U+003D	EQUALS SIGN		06/12	6D	U+006D	LATIN SMALL LETTER M
03/14	3E	U+003E	GREATER-THAN SIGN		06/14	6E	U+006E	LATIN SMALL LETTER N
03/15	3F	U+003F	QUESTION MARK		06/15	6F	U+006F	LATIN SMALL LETTER O
04/00	40	U+0040	COMMERCIAL AT		07/00	70	U+0070	LATIN SMALL LETTER P
04/01	41	U+0041	LATIN CAPITAL LETTER A		07/01	71	U+0071	LATIN SMALL LETTER Q
04/02	42	U+0042	LATIN CAPITAL LETTER B		07/02	72	U+0072	LATIN SMALL LETTER R
04/03	43	U+0043	LATIN CAPITAL LETTER C		07/03	73	U+0073	LATIN SMALL LETTER S
04/04	44	U+0044	LATIN CAPITAL LETTER D		07/04	74	U+0074	LATIN SMALL LETTER T
04/05	45	U+0045	LATIN CAPITAL LETTER E		07/05	75	U+0075	LATIN SMALL LETTER U
04/06	46	U+0046	LATIN CAPITAL LETTER F		07/06	76	U+0076	LATIN SMALL LETTER V
04/07	47	U+0047	LATIN CAPITAL LETTER G		07/07	77	U+0077	LATIN SMALL LETTER W
04/08	48	U+0048	LATIN CAPITAL LETTER H		07/08	78	U+0078	LATIN SMALL LETTER X
04/09	49	U+0049	LATIN CAPITAL LETTER I		07/09	79	U+0079	LATIN SMALL LETTER Y
04/10	4A	U+004A	LATIN CAPITAL LETTER J		07/10	7A	U+007A	LATIN SMALL LETTER Z
04/11	4B	U+004B	LATIN CAPITAL LETTER K		07/11	7B	U+007B	LEFT CURLY BRACKET
04/12	4C	U+004C	LATIN CAPITAL LETTER L		07/12	7C	U+007C	VERTICAL LINE
04/13	4D	U+004D	LATIN CAPITAL LETTER M		07/13	7D	U+007D	RIGHT CURLY BRACKET
04/14	4E	U+004E	LATIN CAPITAL LETTER N		07/14	7E	U+007E	TILDE
04/15	4F	U+004F	LATIN CAPITAL LETTER O					
				l				

 Table 1 (continued)

 Table 1 (concluded)

Bit combi- nation	Hex	Identifier	Name		Bit combi- nation	Hex	Identifier	Name
10/00	A0	U+00A0	NO-BREAK SPACE		13/00	D0	U+0630	ARABIC LETTER THAL
10/01	A1		(This position shall not be used)		13/01	D1	U+0631	ARABIC LETTER REH
10/02	A2		(This position shall not be used)		13/02	D2	U+0632	ARABIC LETTER ZAIN
10/03	A3		(This position shall not be used)		13/03	D3	U+0633	ARABIC LETTER SEEN
10/04	A4	U+00A4	CURRENCY SIGN		13/04	D4	U+0634	ARABIC LETTER SHEEN
10/05	A5		(This position shall not be used)		13/05	D5	U+0635	ARABIC LETTER SAD
10/06	A6		(This position shall not be used)		13/06	D6	U+0636	ARABIC LETTER DAD
10/07	A7		(This position shall not be used)		13/07	D7	U+0637	ARABIC LETTER TAH
10/08	A8		(This position shall not be used)		13/08	D8	U+0638	ARABIC LETTER ZAH
10/09	A9		(This position shall not be used)		13/09	D9	U+0639	ARABIC LETTER AIN
10/10	AA		(This position shall not be used)		13/10	DA	U+063A	ARABIC LETTER GHAIN
10/11	AB		(This position shall not be used)		13/11	DB		(This position shall not be used)
10/12	AC	U+060C	ARABIC COMMA		13/12	DC		(This position shall not be used)
10/13	AD	U+00AD	SOFT HYPHEN		13/13	DD		(This position shall not be used)
10/14	AE		(This position shall not be used)		13/14	DE		(This position shall not be used)
10/15	AF		(This position shall not be used)		13/15	DF		(This position shall not be used)
11/00	B0		(This position shall not be used)		14/00	E0	U+0640	ARABIC TATWEEL
11/01	B1		(This position shall not be used)		14/01	E1	U+0641	ARABIC LETTER FEH
11/02	B2		(This position shall not be used)		14/02	E2	U+0642	ARABIC LETTER QAF
11/03	B3		(This position shall not be used)	Т	14/03	E3	U+0643	ARABIC LETTER KAF
11/04	B4		(This position shall not be used)		14/04	E4	U+0644	ARABIC LETTER LAM
11/05	B5		(This position shall not be used)		14/05	E5	U+0645	ARABIC LETTER MEEM
11/06	B6		(This position shall not be used) tandards	<b>S.</b> ]	14/06	<b>E</b> 6	U+0646	ARABIC LETTER NOON
11/07	B7		(This position shall not be used)		14/07	E7	U+0647	ARABIC LETTER HEH
11/08	B8		(This position shall not be used)		14/08	E8	U+0648	ARABIC LETTER WAW
11/09	B9		(This position shall not be used) ISO/IEC 885		14/09	E9	U+0649	ARABIC LETTER ALEF MAKSURA
11/10	BA		(This position shall not be used) h. ai/catalog/standard	s/si	st/14/108	4êa -	c04064Ab	9ARABIC LETTER YEH
11/11	BB	U+061B	ARABIC SEMICOLON 7ff2214f743b/iso-ie		8519/11-	(EB)	U+064B	ARABIC FATHATAN (combining character)
11/12	BC		(This position shall not be used)		14/12	EC	U+064C	ARABIC DAMMATAN (combining character)
11/13	BD		(This position shall not be used)		14/13	ED	U+064D	ARABIC KASRATAN (combining character)
11/14	BE		(This position shall not be used)		14/14	EE	U+064E	ARABIC FATHA (combining character)
11/15	BF	U+061F	ARABIC QUESTION MARK		14/15	EF	U+064F	ARABIC DAMMA (combining character)
12/00	C0		(This position shall not be used)		15/00	F0	U+0650	ARABIC KASRA (combining character)
12/01	C1	U+0621	ARABIC LETTER HAMZA		15/01	F1	U+0651	ARABIC SHADDA (combining character)
12/02	C2	U+0622	ARABIC LETTER ALEF WITH MADDA ABOVE		15/02	F2	U+0652	ARABIC SUKUN (combining character)
12/03	C3	U+0623	ARABIC LETTER ALEF WITH HAMZA ABOVE		15/03	F3		(This position shall not be used)
12/04	C4	U+0624	ARABIC LETTER WAW WITH HAMZA ABOVE		15/04	F4		(This position shall not be used)
12/05	C5	U+0625	ARABIC LETTER ALEF WITH HAMZA BELOW		15/05	F5		(This position shall not be used)
12/06	C6	U+0626	ARABIC LETTER YEH WITH HAMZA ABOVE		15/06	F6		(This position shall not be used)
12/07	C7	U+0627	ARABIC LETTER ALEF		15/07	F7		(This position shall not be used)
12/08	C8	U+0628	ARABIC LETTER BEH		15/08	F8		(This position shall not be used)
12/09	C9	U+0629	ARABIC LETTER TEH MARBUTA		15/09	F9		This position shall not be used)
12/10	CA	U+062A	ARABIC LETTER TEH		15/10	FA		(This position shall not be used)
12/11	СВ	U+062B	ARABIC LETTER THEH		15/11	FB		(This position shall not be used)
12/12	CC	U+062C	ARABIC LETTER JEEM		15/12	FC		(This position shall not be used)
12/13	CD	U+062D	ARABIC LETTER HAH		15/13	FD		(This position shall not be used)
12/14	CE	U+062E	ARABIC LETTER KHAH		15/14	FE		(This position shall not be used)
12/15	CF	U+062F	ARABIC LETTER DAL		15/15	FF		(This position shall not be used)