



SLOVENSKI STANDARD
oSIST prEN 15681-2:2007
01-julij-2007

**Steklo v gradbeništvu - Osnovni izdelki iz aluminij-silikatnega stekla - 2. del:
Ovrednotenje skladnosti/standard za izdelek**

Glass in building - Basic alumino silicate glass products - Part 2: Evaluation of conformity/Product standard

Glas im Bauwesen - Basiserzeugnisse aus Alumo-Silicatglas - Teil 2:
Konformitätsbewertung/Produktnorm

Verre dans la construction - Produits de base verre alumino silicaté - Partie 2 :
Evaluation de la conformité/Norme de produit

<https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pr-en-15681-2-2007>

Ta slovenski standard je istoveten z: prEN 15681-2

ICS:

81.040.20 Steklo v gradbeništvu Glass in building

oSIST prEN 15681-2:2007 **en;de**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 15681-2:2007](https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007)

<https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007>

May 2007

ICS 81.040.20

English Version

Glass in building - Basic alumino silicate glass products - Part 2: Evaluation of conformity/Product standard

Glas im Bauwesen - Basiserzeugnisse aus Alumo-Silicatglas - Teil 2: Konformitätsbewertung/Produktnorm

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 129.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	4
Scope	5
1 Normative references	5
2 Terms and definitions.....	6
3 Requirements	6
3.1 Conformity with the definition of basic alumino silicate glass products	6
3.2 Determination of the characteristic's performances.....	6
3.2.1 Characteristics of basic alumino silicate glasses	6
3.2.2 Characteristics of basic alumino silicate glass products.....	7
3.3 Durability.....	9
3.4 Characteristics other than listed in 4.2.....	10
3.5 Dangerous substances.....	10
4 Evaluation of conformity.....	10
4.1 General.....	10
4.2 Initial type testing of the product (see 5.1.2).....	10
4.2.1 General.....	10
4.2.2 Initial type testing if the product belongs to the group basic alumino silicate glasses, clear or tinted.....	12
4.2.3 Initial type testing of characteristic's performances.....	12
4.3 Factory production control and inspection of samples in accordance with a prescribed test plan (see 5.1, 1a)	12
4.4 Initial inspection of factory and of factory production control (see 5.1, 1b)	13
4.5 Continuous surveillance and assessment of the factory production control (5.1, 1c)	13
5 Marking and labelling	14
5.1 General.....	14
5.2 Product marking.....	14
5.3 Product characteristics	14
5.4 "Characteristics/performance identification paper"	14
Annex A (normative) Factory Production Control	15
A.1 Factory Production Control Requirements	15
A.1.1 General.....	15
A.1.2 Organisation	15
A.1.3 Control system	15
A.2 Marking	16
A.3 Inspection and testing tables of basic alumino silicate glass products production.....	17
A.3.1 Information to the tables A.1 to A3	17
A.3.2 Use of proxy testing.....	17
Annex B (informative) Provisions for voluntary third party(ies).....	21
B.1 General.....	21
B.2 Voluntary tasks for third parties.....	21
B.3 Marking and labelling	21
Annex ZA (informative) Clauses of this European Standard addressing the provisions of EU Construction Products Directives.....	22

ZA.1	Scope and relevant characteristics	22
ZA.2	Procedure(s) for the attestation of conformity of basic alumino silicate glass products	24
ZA.2.1	System(s) of attestation of conformity	24
ZA.2.2	EC Certificate and Declaration of conformity	26
ZA.3	CE marking and labelling	28
	Bibliography	30

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 15681-2:2007](https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007)

<https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007>

Foreword

This document (prEN 15681-2:2007) has been prepared by Technical Committee CEN/TC 129 “Glass in building”, the secretariat of which is held by NBN.

This document is currently submitted to the CEN Enquiry.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[oSIST prEN 15681-2:2007](https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007)

<https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007>

Scope

This European Standard covers the evaluation of conformity and the factory production control of basic alumino silicate glass products for use in buildings.

Note: For glass products with electrical wiring or connections for, e.g. alarm or heating purposes, other directives, e.g. Low Voltage Directive, may apply.

1 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 356, *Glass in Building - Security glazing - Testing and classification of resistance against manual attack*

EN 410, *Glass in Building - Determination of luminous and solar characteristics of glazing*

EN 673, *Glass in Building - Determination of thermal transmittance (U-value) – Calculation method*

EN 1063, *Glass in Building - Security glazing – Testing and classification of resistance against bullet attack*

EN 12600, *Glass in Building - Pendulum test - Impact test method and classification for flat glass*

EN 12758, *Glass in Building - Glazing and airborne sound insulation – Product descriptions and determination of properties*

EN 12898, *Glass in Building - Determination of the emissivity*

prEN 13474, *Glass in building – Design of glass panes*

EN 13501-1, *Fire classification of construction products and building elements – Part 1: Classification using test data from fire reaction to fire tests*

EN 13501-2, *Fire classification of construction products and building elements - Part 2: Classification using data from fire resistance tests, excluding ventilation services*

EN 13501-5, *Fire classification of construction products and building elements – Part 5: Classification using data from fire exposure roof tests*

EN 13541, *Glass in Building - Security glazing - Testing and classification of resistance against explosion pressure*

prEN 15681-1, *Glass in Building – Basic alumino silicate glass products – Part 1: Definitions and general physical and mechanical properties*

2 Terms and definitions

For the purposes of this document, the terms and definitions given in prEN BA1uS-1 and the following apply.

3.1

initial type testing

determination of the performance of a product (characteristic, durability), on the basis of either actual tests or other procedures (such as conventional, standardised, tabulated or general accepted values; standardised or recognised calculation methods; test reports when made available), in accordance with this document that demonstrates compliance with this document.

3.2

test report

document that covers the results of tests undertaken on a representative sample of the product from production or on a prototype design of the product.

3.3

product description

document that details the relevant parameters, e.g. process conditions, structure, etc., for defining a product that complies with the standard. It includes specific reference(s) to characteristics that are modified by the production process.

3.4

significant change

variation in performance beyond the permitted tolerance for the characteristic.

iteh STANDARD PREVIEW
(standards.iteh.ai)

[oSIST prEN 15681-2:2007](https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007)

<https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007>

3 Requirements

3.1 Conformity with the definition of basic alumino silicate glass products

Products shall conform to the definition and fulfil the requirements of basic alumino silicate glass products as defined in prEN 15681-1.

3.2 Determination of the characteristic's performances

3.2.1 Characteristics of basic alumino silicate glasses

Basic alumino silicate glass products are made in accordance with prEN 15681-1. The characteristics listed in table 1, concern generally accepted values, calculated values or measured values.

Table 1 — Necessary information on characteristics of basic alumino silicate glasses

Characteristic	Symbol	Unit
General accepted values:		
- density	ρ	kg/m ³
- hardness	$HK_{0,1/20}$	GPa
- Young's modulus	E	Pa
- Poisson's ratio	μ	Dimensionless
- characteristic bending strength	$f_{g,k}$	Pa
- resistance against sudden temperature changes and temperature differentials		K
- specific heat capacity	c	J/(kg*K)
- coefficient of linear expansion	α	K ⁻¹
- thermal conductivity	λ	W/(m*K)
- mean refractive index to visible radiation	n	Dimensionless
- emissivity	ε	Dimensionless
Measured values:		
- light transmittance	τ_V	Dimensionless
- solar direct transmittance	τ_e	Dimensionless
Calculated values:		
- total solar energy transmittance	g	Dimensionless

3.2.2 Characteristics of basic alumino silicate glass products

If the basic alumino silicate glass manufacturer wishes to claim that any performance characteristic is independent of the production equipment used then the factory production control system shall be in accordance with this document including his specific process control conditions.

3.2.2.1 Safety in the case of fire - Resistance to fire

Fire resistance shall be determined and classified in accordance with EN 13501-2.

Note: EN 357 may be used as a classification reference specific to fire resistant glazed elements.

3.2.2.2 Safety in the case of fire - Reaction to fire

Reaction to fire shall be determined and classified according to EN 13501-1.

Basic alumino silicate glass products are products/materials that do not require to be tested for reaction to fire (e.g. Products/materials of Classes A1* according to Commission Decision 96/603/EC, as amended 2000/605/EC).

prEN 15681-2:2007 (E)

3.2.2.3 Safety in the case of fire - External fire behaviour

Where the manufacturer wishes to declare external fire performance (e.g. when subject to regulatory requirements), the product shall be tested and classified in accordance with EN 13501-5.

3.2.2.4 Safety in use - Bullet resistance: shatter properties and resistance to attack

Bullet resistance shall be determined and classified in accordance with EN 1063.

3.2.2.5 Safety in use - Explosion resistance: impact behaviour and resistance to impact

Explosion resistance shall be determined and classified in accordance with EN 13541.

3.2.2.6 Safety in use - Burglar resistance: shatter properties and resistance to attack

Burglar resistance shall be determined and classified in accordance with EN 356.

3.2.2.7 Safety in use - Pendulum body impact resistance: shatter properties (safe breakability) and resistance to impact

Pendulum body impact resistance shall be determined and classified in accordance with EN 12600.

3.2.2.8 Safety in use - Mechanical resistance: Resistance against sudden temperature changes and temperature differentials

The resistance against sudden temperature changes and temperature differentials is a generally accepted value that is given in prEN 15681-1 and shall be ensured by compliance with this document.

3.2.2.9 Safety in use - Mechanical resistance: Resistance against wind, snow, permanent load and/or imposed loads of the glass unit

The mechanical resistance of basic alumino silicate glass is a characteristic value that is given in prEN BALuS-1 and shall be ensured by compliance with this document.

As long as on the concerned construction or building site no part of prEN 13474 is applicable then the current method of determining mechanical resistance in the country of destination shall be applied.

The manufactured or supplied thickness of glass shall conform to the ordered thickness.

3.2.2.10 Protection against noise - Direct airborne sound reduction

The sound reduction index shall be determined in accordance with EN 12758.

3.2.2.11 Energy conservation and heat retention - Thermal properties

The thermal transmittance value (U -value) shall be determined by calculation in accordance with EN 673 with:

- emissivity ε : using the value the emissivity as given in prEN 15681-1.
- nominal thickness of the glass panes

3.2.2.12 Energy conservation and heat retention - Radiation properties: Light transmittance and reflectance

The light transmittance and reflectance shall be determined in accordance with EN 410.

3.2.2.13 Energy conservation and heat retention - Radiation properties: Solar energy characteristics

The solar energy transmittance and reflectance shall be determined in accordance with EN 410.

3.3 Durability

When products conform to the definition of basic alumino silicate glass products as 4.1, the characteristic's performances in 4.2 are ensured during an economically reasonable working life.

The durability of glass products, including their characteristics, shall be ensured by the following:

- Compliance with this document <https://standards.iteh.ai/catalog/standards/sist/b8258d87-9c50-4cc0-90da-2c45033a4ce0/osist-pren-15681-2-2007>
- Compliance with instructions from the glass product manufacturer or supplier

The manufacturer shall supply specific installation instructions or make reference to appropriate technical specifications.

Note 1: The durability of glass products depends on:

- building and construction movements due to various actions;
- building and construction vibrations due to various actions;
- deflection and racking of the glass support due to various actions;
- glass support design (e.g. drainage of infiltrated water in the rebate, prevention of direct contact between glass support members and glass);
- accuracy of glass support and glass support member dimensions;
- quality of the assembling of glass support members up to a glass support;
- quality of installation of the glass support into or onto the buildings or constructions;
- glass support expansion due to adsorbed moisture from the air or other sources;
- the quality of installation of the glass product into or onto its support.

prEN 15681-2:2007 (E)

3.4 Characteristics other than listed in 4.2

Optical and visual characteristics shall comply with prEN 15681-1.

Dimensional tolerances: shall comply with prEN 15681-1.

3.5 Dangerous substances

Materials used in products shall not release any dangerous substances in excess of the maximum permitted levels specified in a relevant European Standard for the material or permitted in the national regulations of the member state of destination.

4 Evaluation of conformity

4.1 General

Evaluation of conformity in accordance with this document shall be a result of Factory Production Control and Initial Type Testing in accordance with this document.

- 1) Factory production control;

This shall include the following:

- a) Inspection of samples taken at the factory in accordance with a prescribed test plan;
- b) Initial inspection of the factory and of factory production control;
- c) Continuous surveillance and assessment of the factory production control.

- 2) Initial type testing of the product;

Note: There may be a need to involve a third party with 1b), 1c) and/or 2), for the purpose of regulatory marking (see Annex ZA).

4.2 Initial type testing of the product (see 5.1, 2)

4.2.1 General

All the product's characteristics shall be initial type tested to verify they are in conformity with the requirements of this document. In addition instead of performing any actual testing, initial type testing may make use of:

- generally accepted and/or conventional and/or standardised values, in the Clause 2 referenced standards, or in publications that are referred to in these standards;
- standardised calculation methods and recognised calculation methods in the Clause 2 referenced standards, or in publications that are referred to in these standards;
- test report(s) on the basis of 5.2.1.2 when made available except for the characteristics listed in 5.2.2.
- where components are used whose characteristics have already been determined, by the component manufacturer, on the basis of conformity with other product standards, these