## INTERNATIONAL STANDARD

# IEC 60335-2-41

1996

AMENDMENT 1 2000-02

Amendment 1

Amendement 1

Safety of household and similar electrical appliances –

Part 2-41: Particular requirements for pumps for liquids having a temperature not exceeding 35 °C

Sécurité des appareils électrodomestiques et analogues –

Partie 2-41: Règles particulières pour les pompes pour liquides dont la température ne dépasse pas 35 °C

© IEC 2000 — Copyright - all rights reserved

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site http://www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия

PRICE CODE

For price, see current catalogue

С

## FOREWORD

This amendment has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

The text of this amendment is based on the following documents:

FDIS	Report on voting
61/1752/FDIS	61/1777/RVD

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

A bilingual version of this amendment may be issued at a later date.

## Title

Replace the title by:

#### Part 2: Particular requirements for pumps

## Foreword

In the third paragraph after the table, replace the title of the standard by:

1996/AMD1:2000

346b-4dc0-bce4-47ad40cd7a39/iec-60335-2-41-1996-amd1-2000

#### 1 Scope

In the first paragraph, replace "35 °C" by "90 °C".

## 4 General conditions for the tests

Safety requirements for electric pumps

**4.7** *Replace the addition by:* 

The liquid temperature is maintained within +0, –5 K of the temperature marked on the **pump**.

#### 7 Marking and instructions

#### **7.1** Add the following:

**Pumps** shall be marked with the maximum liquid temperature which shall not be less than 35 °C. If the temperature exceeds 35 °C, they shall be marked with the maximum period of operation, unless they are intended for continuous operation.