

INTERNATIONAL STANDARD

IEC
60335-2-41

Third edition
2002-10

Household and similar electrical appliances – Safety –

Part 2-41: Particular requirements for pumps

*Appareils électrodomestiques et analogues –
Sécurité –*

*Partie 2-41:
Règles particulières pour les pompes*

<https://standards.iteh.ai/en/standards/iec/3c5570f82-2dce-43c0-b275-1f22d2171ad6/iec-60335-2-41-2002>

<https://standards.iteh.ai/en/standards/iec/3c5570f82-2dce-43c0-b275-1f22d2171ad6/iec-60335-2-41-2002>



Reference number
IEC 60335-2-41:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (http://www.iec.ch/online_news/justpub/jp_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre: -43c0-b275-1f22d2171ad6/iec-60335-2-41-2002

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60335-2-41

Third edition
2002-10

Household and similar electrical appliances – Safety –

Part 2-41: Particular requirements for pumps

*Appareils électrodomestiques et analogues –
Sécurité –*

*Partie 2-41:
Règles particulières pour les pompes*

<https://standards.iteh.ai/standards/iec/3c576182-2dce-43c0-b275-1f22d2171ad6/iec-60335-2-41-2002>

<https://standards.iteh.ai/standards/iec/3c576182-2dce-43c0-b275-1f22d2171ad6/iec-60335-2-41-2002>

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

P

For price, see current catalogue

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references.....	6
3 Definitions	7
4 General requirement.....	7
5 General conditions for the tests	7
6 Classification	7
7 Marking and instructions	8
8 Protection against access to live parts	9
9 Starting of motor-operated appliances	9
10 Power input and current.....	9
11 Heating.....	9
12 Void	10
13 Leakage current and electric strength at operating temperature	10
14 Transient overvoltages.....	10
15 Moisture resistance.....	10
16 Leakage current and electric strength	10
17 Overload protection of transformers and associated circuits.....	11
18 Endurance	11
19 Abnormal operation.....	11
20 Stability and mechanical hazards.....	11
21 Mechanical strength.....	11
22 Construction	11
23 Internal wiring.....	13
24 Components	13
25 Supply connection and external flexible cords.....	13
26 Terminals for external conductors	14
27 Provision for earthing.....	14
28 Screws and connections	14
29 Clearances, creepage distances and solid insulation	14
30 Resistance to heat and fire	14
31 Resistance to rusting	14
32 Radiation, toxicity and similar hazards	14
Annexes.....	15
Bibliography.....	15

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES –
SAFETY –****Part 2-41: Particular requirements for pumps**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

This part of International Standard IEC 60335 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

This third edition cancels and replaces the second edition published in 1996 and its amendment 1 (2000). It constitutes a technical revision.

The text of this part of IEC 60335 is based on the following documents:

FDIS	Report on voting
61/2217/FDIS	61/2292/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fourth edition (2001) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for electric pumps.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states “addition”, “modification” or “replacement”, the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of this publication will remain unchanged until 2003. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

The following differences exist in the countries indicated below.

- 6.1: Pumps intended to be used in or close to swimming pools, garden ponds and similar places may be class 0I if their supply circuit incorporates a residual current device. Other pumps may be class 0I (Japan).
- 6.1: Class 0 aquarium pumps are allowed (USA).
- 7.12.1: Stationary pumps not incorporating a protective device are to be marked with the characteristics of the device to be installed in the fixed wiring (USA).
- 15.1.1: The test is different (USA).
- 20.1: This test is only carried out on fountain pumps, the angle being 15° (USA).
- 22.105: The test is different (USA).

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features that impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

<https://standards.iteh.ai/>

<https://standards.iteh.ai/catalog/standards/iec/3c570f82-2dce-43c0-b275-1f22d2171ad6/iec-60335-2-41-2002>

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-41: Particular requirements for pumps

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of electric pumps for liquids having a temperature not exceeding 90 °C, intended for household and similar purposes, their **rated voltage** being not more than 250 V for single-phase appliances and 480 V for other appliances.

NOTE 101 Examples of appliances within the scope of this standard are

- aquarium pumps;
- pumps for garden ponds;
- **sludge pumps**;
- **submersible pumps**;
- table fountain pumps;
- **vertical wet pit pumps**.

Appliances not intended for normal household use, but that nevertheless may be a source of danger to the public, such as appliances intended to be used by laymen in shops, in light industry and on farms, are within the scope of this standard.

As far as is practicable, this standard deals with the common hazards presented by appliances that are encountered by all persons in and around the home. However, in general, it does not take into account

- the use of appliances by young children or infirm persons without supervision;
- playing with the appliance by young children.

NOTE 102 Attention is drawn to the fact that

- for appliances intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries additional requirements are specified by the national health authorities, the national authorities responsible for the protection of labour and similar authorities.

NOTE 103 This standard does not apply to

- **stationary circulation pumps** for heating and service water installations (IEC 60335-2-51);
- pumps for flammable liquids;
- pumps intended exclusively for industrial purposes;
- pumps intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- pumps incorporating chlorinators of the electrolytic type.

NOTE 104 Pumps incorporated in appliances are not covered by this standard unless a specific reference is made.

2 Normative references

This clause of Part 1 is applicable.

3 Definitions

This clause of Part 1 is applicable except as follows.

3.1.9 Replacement:

normal operation

operation of the appliance under the following conditions

Pumps are operated with the inlet in liquid at zero pressure, and between the minimum and maximum total head, so that the highest power input is attained.

NOTE 101 The total head is measured between the inlet and the discharge outlet.

Sludge pumps are operated with water.

3.101

submersible pump

pump having the electrical part completely or partially immersed in liquid during normal use

NOTE The motor windings may be dry, immersed in oil or in the pumped liquid.

3.102

vertical wet pit pump

pump having the electrical part separated from the hydraulic part and not immersed in liquid during normal use

NOTE Controls such as water level switches may be immersed in the liquid.

3.103

sludge pump

pump intended for moving a mixture of water and small solids

NOTE **Sludge pumps** may be **submersible pumps** or **vertical wet pit pumps**.

4 General requirement

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable except as follows.

5.7 Addition:

The liquid temperature is maintained between 0 °C and –5 °C of the temperature marked on the pump.

5.101 Pumps are tested as **portable appliances**, unless they are **fixed appliances**.

5.102 **Stationary pumps** having a three-phase motor that does not incorporate a **protective device** are installed with an appropriate device, in accordance with the instructions.

6 Classification

This clause of Part 1 is applicable except as follows.

6.1 Modification:

Submersible pumps for use in swimming pools, when persons are in the pool, shall be **class III** with a **rated voltage** not exceeding 12 V.

Other **submersible pumps** for use in water and other conducting liquids shall be **class I** or **class III**. However, aquarium pumps may be **class II**.

Portable pumps for cleaning and other maintenance of swimming pools shall be **class I** or **class III**.

Other pumps shall be **class I**, **class II** or **class III**.

6.2 Addition:

Submersible pumps shall be IPX8.

Portable pumps for cleaning and other maintenance of swimming pools shall be at least IPX7.

Other pumps shall be at least IPX4.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 Addition:

Pumps having a **rated power input** exceeding 50 W shall be marked with

- the minimum total head, in metres, if greater than zero;
- the maximum operating depth, in metres with a minimum of 1 m (for **submersible pumps**);
- the direction of rotation (for pumps having three-phase motors).

Pumps shall be marked with the maximum liquid temperature, which shall not be less than 35 °C. If the temperature exceeds 35 °C, pumps shall be marked with the maximum period of operation, unless they are intended for continuous operation.

7.6 Addition:

H_{\min} minimum total head

∇
... m maximum operating depth

7.12 Addition:

The instructions for **class I portable pumps** for cleaning and other maintenance of swimming pools shall include the substance of the following:

- the pump must not be used when people are in the water;
- the pump must be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30 mA.